

```

1  /*<html>
2  <span id="gsh" data-title="GShell" data-author="sato@its-more.jp">
3  <meta charset="UTF-8">
4  <meta name="viewport" content="width=device-width, initial-scale=1.0">
5  <link rel="icon" id="GshFaviconURL" href=""/>
```

```

125 "sort" // <a href="https://golang.org/pkg/sort/">sort</a>
126 "time" // <a href="https://golang.org/pkg/time/">time</a>
127 "bufio" // <a href="https://golang.org/pkg/bufio/">bufio</a>
128 "io/ioutil" // <a href="https://golang.org/pkg/io/ioutil/">ioutil</a>
129 "os" // <a href="https://golang.org/pkg/os/">os</a>
130 "syscall" // <a href="https://golang.org/pkg/syscall/">syscall</a>
131 "plugin" // <a href="https://golang.org/pkg/plugin/">plugin</a>
132 "net" // <a href="https://golang.org/pkg/net/">net</a>
133 "net/http" // <a href="https://golang.org/pkg/net/http/">http</a>
134 // "html" // <a href="https://golang.org/pkg/html/">html</a>
135 "path/filepath" // <a href="https://golang.org/pkg/path/filepath/">filepath</a>
136 "go/types" // <a href="https://golang.org/pkg/go/types/">types</a>
137 "go/token" // <a href="https://golang.org/pkg/go/token/">token</a>
138 "encoding/base64" // <a href="https://golang.org/pkg/encoding/base64/">base64</a>
139 "unicode/utf8" // <a href="https://golang.org/pkg/unicode/utf8/">utf8</a>
140 // "gshdata" // gshell's logo and source code
141 "hash/crc32" // <a href="https://golang.org/pkg/unicode/hash/crc32/">crc32</a>
142 )
143
144 // // 2020-0906 added,
145 // // <a href="https://golang.org/cmd/cgo/">CGO</a>
146 // #include "poll.h" // <poll.h> // </poll.h> to be closed as HTML tag :-p
147 // typedef struct { struct pollfd fdv[8]; } pollFdv;
148 // int pollx(pollFdv *fdv, int nfd, int timeout){
149 //     return poll(fdv->fdv,nfds,timeout);
150 // }
151 import "C"
152
153 // // 2020-0906 added,
154 func CFPollInl(fp*os.File, timeoutUs int)(ready uintptr){
155     var fdv = C.pollFdv{}
156     var nfds = 1
157     var timeout = timeoutUs/1000
158
159     fdv.fdv[0].fd = C.int(fp.Fd())
160     fdv.fdv[0].events = C.POLLIN
161     if( 0 < EventRecvFd ){
162         fdv.fdv[1].fd = C.int(EventRecvFd)
163         fdv.fdv[1].events = C.POLLIN
164         nfds += 1
165     }
166     r := C.pollx(&fdv,C.int(nfds),C.int(timeout))
167     if( r <= 0 ){
168         return 0
169     }
170     if (int(fdv.fdv[1].revents) & int(C.POLLIN)) != 0 {
171         //fprintf(stderr,"--De-- got Event\n");
172         return uintptr(EventFdOffset + fdv.fdv[1].fd)
173     }
174     if (int(fdv.fdv[0].revents) & int(C.POLLIN)) != 0 {
175         return uintptr(NormalFdOffset + fdv.fdv[0].fd)
176     }
177     return 0
178 }
179
180 const (
181     NAME = "gsh"
182     VERSION = "0.4.2"
183     DATE = "2020-09-15"
184     AUTHOR = "SatoxITS(^-^)"
185 )
186 var (
187     GSH_HOME = ".gsh" // under home directory
188     GSH_PORT = 9999
189     MaxStreamSize = int64(128*1024*1024*1024) // 128GiB is too large?
190     PROMPT = ">"
191     LINESIZE = (8*1024)
192     PATHSEP = ":" // should be ";" in Windows
193     DIRSEP = "/" // canbe \ in Windows
194 )
195
196 // -xX logging control
197 // --A-- all
198 // --I-- info.
199 // --D-- debug
200 // --T-- time and resource usage
201 // --W-- warning
202 // --E-- error
203 // --F-- fatal error
204 // --Xn- network
205
206 // <a name="struct">Structures</a>
207 type GCommandHistory struct {
208     StartAt time.Time // command line execution started at
209     EndAt time.Time // command line execution ended at
210     ResCode int // exit code of (external command)
211     CmdError error // error string
212     OutData *os.File // output of the command
213     FoundFile []string // output - result of ufind
214     Rusagev [2]syscall.Rusage // Resource consumption, CPU time or so
215     CmdId int // maybe with identified with arguments or impact
216     // redirection commands should not be the CmdId
217     WorkDir string // working directory at start
218     WorkDirX int // index in ChdirHistory
219     CmdLine string // command line
220 }
221 type GChdirHistory struct {
222     Dir string
223     MovedAt time.Time
224     CmdIndex int
225 }
226 type CmdMode struct {
227     Background bool
228 }
229 type Event struct {
230     when time.Time
231     event int
232     evarg int64
233     CmdIndex int
234 }
235 var CmdIndex int
236 var Events []Event
237 type PluginInfo struct {
238     Spec *plugin.Plugin
239     Addr plugin.Symbol
240     Name string // maybe relative
241     Path string // this is in Plugin but hidden
242 }
243 type GServer struct {
244     host string
245     port string
246 }
247
248 // <a href="https://tools.ietf.org/html/rfc3230">Digest</a>
249 const ( // SumType

```

```

250 SUM_ITEMS = 0x000001 // items count
251 SUM_SIZE = 0x000002 // data length (simply added)
252 SUM_SIZEHASH = 0x000004 // data length (hashed sequence)
253 SUM_DATEHASH = 0x000008 // date of data (hashed sequence)
254 // also envelope attributes like time stamp can be a part of digest
255 // hashed value of sizes or mod-date of files will be useful to detect changes
256
257 SUM_WORDS = 0x000010 // word count is a kind of digest
258 SUM_LINES = 0x000020 // line count is a kind of digest
259 SUM_SUM64 = 0x000040 // simple add of bytes, useful for human too
260
261 SUM_SUM32_BITS = 0x000100 // the number of true bits
262 SUM_SUM32_2BYTE = 0x000200 // 16bits words
263 SUM_SUM32_4BYTE = 0x000400 // 32bits words
264 SUM_SUM32_8BYTE = 0x000800 // 64bits words
265
266 SUM_SUM16_BSD = 0x001000 // UNIXsum -sum -bsd
267 SUM_SUM16_SYSV = 0x002000 // UNIXsum -sum -sysv
268 SUM_UNIXFILE = 0x004000
269 SUM_CRCIEEE = 0x008000
270 )
271 type CheckSum struct {
272     Files int64 // the number of files (or data)
273     Size int64 // content size
274     Words int64 // word count
275     Lines int64 // line count
276     SumType int
277     Sum64 uint64
278     Crc32Table crc32.Table
279     Crc32Val uint32
280     Sum16 int
281     Ctime time.Time
282     Atime time.Time
283     Mtime time.Time
284     Start time.Time
285     Done time.Time
286     RusgAtStart [2]syscall.Rusage
287     RusgAtEnd [2]syscall.Rusage
288 }
289 type ValueStack [][]string
290 type GshContext struct {
291     StartDir string // the current directory at the start
292     GetLine string // gsh-getline command as a input line editor
293     ChdirHistory []GChdirHistory // the 1st entry is wd at the start
294     gshPA syscall.ProcAttr
295     CommandHistory []GCommandHistory
296     CmdCurrent GCommandHistory
297     Background bool
298     BackgroundJobs []int
299     LastRusage syscall.Rusage
300     GshHomeDir string
301     TerminalId int
302     CmdTrace bool // should be [map]
303     CmdTime bool // should be [map]
304     PluginFuncs []PluginInfo
305     iValues []string
306     iDelimiter string // field separator of print out
307     iFormat string // default print format (of integer)
308     iValStack ValueStack
309     LastServer GServer
310     RSERV string // [gsh://]host[port]
311     RWD string // remote (target, there) working directory
312     lastCheckSum CheckSum
313 }
314
315 func nsleep(ns time.Duration){
316     time.Sleep(ns)
317 }
318 func usleep(ns time.Duration){
319     nsleep(ns*1000)
320 }
321 func msleep(ns time.Duration){
322     nsleep(ns*1000000)
323 }
324 func sleep(ns time.Duration){
325     nsleep(ns*1000000000)
326 }
327
328 func strBegins(str, pat string)(bool){
329     if len(pat) <= len(str){
330         yes := str[0:len(pat)] == pat
331         //fmt.Printf("--D-- strBegins(%v,%v)=%v\n",str,pat,yes)
332         return yes
333     }
334     //fmt.Printf("--D-- strBegins(%v,%v)=%v\n",str,pat,false)
335     return false
336 }
337 func isin(what string, list []string) bool {
338     for _, v := range list {
339         if v == what {
340             return true
341         }
342     }
343     return false
344 }
345 func isinX(what string,list[]string)(int){
346     for i,v := range list {
347         if v == what {
348             return i
349         }
350     }
351     return -1
352 }
353
354 func env(opts []string) {
355     env := os.Environ()
356     if isin("-s", opts){
357         sort.Slice(env, func(i,j int) bool {
358             return env[i] < env[j]
359         })
360     }
361     for _, v := range env {
362         fmt.Printf("%v\n",v)
363     }
364 }
365
366 // - rewriting should be context dependent
367 // - should postpone until the real point of evaluation
368 // - should rewrite only known notation of symbol
369 func scanInt(str string)(val int,leng int){
370     leng = -1
371     for i,ch := range str {
372         if '0' <= ch && ch <= '9' {
373             leng = i+1
374         }else{

```

```

375         break
376     }
377 }
378 if 0 < leng {
379     ival, _ := strconv.Atoi(str[0:leng])
380     return ival, leng
381 }else{
382     return 0, 0
383 }
384 }
385 func substHistory(gshCtx *GshContext, str string, i int, rstr string)(leng int, rst string){
386     if len(str[i+1:]) == 0 {
387         return 0, rstr
388     }
389     hi := 0
390     histlen := len(gshCtx.CommandHistory)
391     if str[i+1] == '!' {
392         hi = histlen - 1
393         leng = 1
394     }else{
395         hi, leng = scanInt(str[i+1:])
396         if leng == 0 {
397             return 0, rstr
398         }
399         if hi < 0 {
400             hi = histlen + hi
401         }
402     }
403     if 0 <= hi && hi < histlen {
404         var ext byte
405         if 1 < len(str[i+leng:]) {
406             ext = str[i+leng:][1]
407         }
408         //fmt.Printf("--D-- %v(%c)\n", str[i+leng:], str[i+leng])
409         if ext == 'f' {
410             leng += 1
411             xlist := []string{}
412             list := gshCtx.CommandHistory[hi].FoundFile
413             for _, v := range list {
414                 //list[i] = escapeWhiteSP(v)
415                 xlist = append(xlist, escapeWhiteSP(v))
416             }
417             //rstr += strings.Join(list, " ")
418             rstr += strings.Join(xlist, " ")
419         }else
420         if ext == 'e' || ext == 'd' {
421             // IN0 ... workdir at the start of the command
422             leng += 1
423             rstr += gshCtx.CommandHistory[hi].WorkDir
424         }else{
425             rstr += gshCtx.CommandHistory[hi].CmdLine
426         }
427     }else{
428         leng = 0
429     }
430     return leng, rstr
431 }
432 func escapeWhiteSP(str string)(string){
433     if len(str) == 0 {
434         return "\\z" // empty, to be ignored
435     }
436     rstr := ""
437     for _, ch := range str {
438         switch ch {
439             case '\\': rstr += "\\\\"
440             case ' ': rstr += "\\s"
441             case 't': rstr += "\\t"
442             case 'r': rstr += "\\r"
443             case 'n': rstr += "\\n"
444             default: rstr += string(ch)
445         }
446     }
447     return rstr
448 }
449 func unescapeWhiteSP(str string)(string){ // strip original escapes
450     rstr := ""
451     for i := 0; i < len(str); i++ {
452         ch := str[i]
453         if ch == '\\' {
454             if i+1 < len(str) {
455                 switch str[i+1] {
456                     case 'z':
457                         continue;
458                 }
459             }
460         }
461         rstr += string(ch)
462     }
463     return rstr
464 }
465 func unescapeWhiteSPV(strv []string)([]string){ // strip original escapes
466     ustrv := []string{}
467     for _, v := range strv {
468         ustrv = append(ustrv, unescapeWhiteSP(v))
469     }
470     return ustrv
471 }
472
473 // <a name="comexpansion">str-expansion</a>
474 // - this should be a macro processor
475 func strsubst(gshCtx *GshContext, str string, histonly bool) string {
476     rbuff := []byte{}
477     if false {
478         //@@U Unicode should be cared as a character
479         return str
480     }
481     //rstr := ""
482     inEsc := 0 // escape characer mode
483     for i := 0; i < len(str); i++ {
484         //fmt.Printf("--D--Subst %v:%v\n", i, str[i:])
485         ch := str[i]
486         if inEsc == 0 {
487             if ch == '!' {
488                 //leng, xrstr := substHistory(gshCtx, str, i, rstr)
489                 leng, rs := substHistory(gshCtx, str, i, "")
490                 if 0 < leng {
491                     //_, rs := substHistory(gshCtx, str, i, "")
492                     rbuff = append(rbuff, []byte(rs)...)
493                     i += leng
494                     //rstr = xrstr
495                     continue
496                 }
497             }
498             switch ch {
499                 case '\\': inEsc = '\\'; continue

```

```

500         //case '%': inEsc = '%'; continue
501         case '$':
502     }
503 }
504 switch inEsc {
505 case '\\':
506     switch ch {
507         case '\\': ch = '\\'
508         case 's': ch = ' '
509         case 't': ch = '\t'
510         case 'r': ch = '\r'
511         case 'n': ch = '\n'
512         case 'z': inEsc = 0; continue // empty, to be ignored
513     }
514     inEsc = 0
515 case '%':
516     switch {
517     case ch == '%': ch = '%'
518     case ch == 'T':
519         //rstr = rstr + time.Now().Format(time.Stamp)
520     rs := time.Now().Format(time.Stamp)
521     rbuff = append(rbuff,[]byte(rs)...)
522     inEsc = 0
523     continue;
524     default:
525         // postpone the interpretation
526         //rstr = rstr + "%" + string(ch)
527     rbuff = append(rbuff,ch)
528     inEsc = 0
529     continue;
530     }
531     inEsc = 0
532 }
533 //rstr = rstr + string(ch)
534 rbuff = append(rbuff,ch)
535 }
536 //fmt.Printf("--D--subst(%s)(%s)\n",str,string(rbuff))
537 return string(rbuff)
538 //return rstr
539 }
540 func showFileInfo(path string, opts []string) {
541     if isin("-l",opts) || isin("-ls",opts) {
542         fi, err := os.Stat(path)
543         if err != nil {
544             fmt.Printf("----- ((%v))",err)
545         }else{
546             mod := fi.ModTime()
547             date := mod.Format(time.Stamp)
548             fmt.Printf("%v %v %s ",fi.Mode(),fi.Size(),date)
549         }
550     }
551     fmt.Printf("%s",path)
552     if isin("-sp",opts) {
553         fmt.Printf(" ")
554     }else
555     if ! isin("-n",opts) {
556         fmt.Printf("\n")
557     }
558 }
559 func userHomeDir()(string,bool){
560     /*
561     homedir,_ = os.UserHomeDir() // not implemented in older Golang
562     */
563     homedir,found := os.LookupEnv("HOME")
564     //fmt.Printf("--I-- HOME=%v(%v)\n",homedir,found)
565     if !found {
566         return "/tmp",found
567     }
568     return homedir,found
569 }
570 }
571 func toFullpath(path string) (fullpath string) {
572     if path[0] == '/' {
573         return path
574     }
575     pathv := strings.Split(path,DIRSEP)
576     switch {
577     case pathv[0] == ".":
578         pathv[0],_ = os.Getwd()
579     case pathv[0] == "..": // all ones should be interpreted
580         cwd,_ = os.Getwd()
581         ppathv := strings.Split(cwd,DIRSEP)
582         pathv[0] = strings.Join(ppathv,DIRSEP)
583     case pathv[0] == "-":
584         pathv[0],_ = userHomeDir()
585     default:
586         cwd,_ := os.Getwd()
587         pathv[0] = cwd + DIRSEP + pathv[0]
588     }
589     return strings.Join(pathv,DIRSEP)
590 }
591 }
592 func IsRegFile(path string)(bool){
593     fi, err := os.Stat(path)
594     if err == nil {
595         fm := fi.Mode()
596         return fm.IsRegular();
597     }
598     return false
599 }
600 }
601 // <a name="encode">Encode / Decode</a>
602 // <a href="https://golang.org/pkg/encoding/base64/#example_NewEncoder">Encoder</a>
603 func (gshCtx *GshContext)Enc(argv[]string){
604     file := os.Stdin
605     buff := make([]byte,LINESIZE)
606     li := 0
607     encoder := base64.NewEncoder(base64.StdEncoding,os.Stdout)
608     for li = 0; ; li++ {
609         count, err := file.Read(buff)
610         if count <= 0 {
611             break
612         }
613         if err != nil {
614             break
615         }
616         encoder.Write(buff[0:count])
617     }
618     encoder.Close()
619 }
620 func (gshCtx *GshContext)Dec(argv[]string){
621     decoder := base64.NewDecoder(base64.StdEncoding,os.Stdin)
622     li := 0
623     buff := make([]byte,LINESIZE)
624     for li = 0; ; li++ {

```

```

625     count, err := decoder.Read(buff)
626     if count <= 0 {
627         break
628     }
629     if err != nil {
630         break
631     }
632     os.Stdout.Write(buff[0:count])
633 }
634 }
635 // lnspl [N] [-crflj][-C \\\
636 func (gshCtx *GshContext)SplitLine(argv[]string){
637     strRep := isin("-str",argv) // "..."+
638     reader := bufio.NewReaderSize(os.Stdin,64*1024)
639     ni := 0
640     toi := 0
641     for ni = 0; ; ni++ {
642         line, err := reader.ReadString('\n')
643         if len(line) <= 0 {
644             if err != nil {
645                 fmt.Fprintf(os.Stderr,"--I-- lnspl %d to %d (%v)\n",ni,toi,err)
646                 break
647             }
648         }
649         off := 0
650         ilen := len(line)
651         remlen := len(line)
652         if strRep { os.Stdout.Write([]byte("\n")) }
653         for oi := 0; 0 < remlen; oi++ {
654             olen := remlen
655             addnl := false
656             if 72 < olen {
657                 olen = 72
658                 addnl = true
659             }
660             fmt.Fprintf(os.Stderr,"--D-- write %d [%d.%d] %d %d/%d\n",
661                 toi,ni,oi,off,olen,remlen,ilen)
662             toi += 1
663             os.Stdout.Write([]byte(line[0:olen]))
664             if addnl {
665                 if strRep {
666                     os.Stdout.Write([]byte("\n\n"))
667                 }else{
668                     //os.Stdout.Write([]byte("\r\n"))
669                     os.Stdout.Write([]byte("\n"))
670                     os.Stdout.Write([]byte("\n"))
671                 }
672             }
673             line = line[olen:]
674             off += olen
675             remlen -= olen
676         }
677         if strRep { os.Stdout.Write([]byte("\n")) }
678     }
679     fmt.Fprintf(os.Stderr,"--I-- lnspl %d to %d\n",ni,toi)
680 }
681 }
682 // CRC32 <a href="http://golang.jp/pkg/hash-crc32">crc32</a>
683 // 1 0000 0100 1100 0001 0001 1101 1011 0111
684 var CRC32UNIX uint32 = uint32(0x04C11DB7) // Unix cksum
685 var CRC32IEEE uint32 = uint32(0xEDB88320)
686 func byteCRC32add(crc uint32,str[]byte,len uint64)(uint32){
687     var oi uint64
688     for oi = 0; oi < len; oi++ {
689         var oct = str[oi]
690         for bi := 0; bi < 8; bi++ {
691             //fprintf(stderr,"--CRC32 %d %X (%d.%d)\n",crc,oct,oi,bi)
692             ovf1 := (crc & 0x80000000) != 0
693             ovf2 := (oct & 0x80) != 0
694             ovf := (ovf1 && !ovf2) || (!ovf1 && ovf2)
695             oct <<= 1
696             crc <<= 1
697             if ovf { crc ^= CRC32UNIX }
698         }
699     }
700     //fprintf(stderr,"--CRC32 return %d %d\n",crc,len)
701     return crc;
702 }
703 func byteCRC32end(crc uint32, len uint64)(uint32){
704     var slen = make([]byte,4)
705     var li = 0
706     for li = 0; li < 4; {
707         slen[li] = byte(len)
708         li += 1
709         len >>= 8
710         if( len == 0 ){
711             break
712         }
713     }
714     crc = byteCRC32add(crc,slen,uint64(li))
715     crc ^= 0xFFFFFFFF
716     return crc
717 }
718 func strCRC32(str string,len uint64)(crc uint32){
719     crc = byteCRC32add(0,[]byte(str),len)
720     crc = byteCRC32end(crc,len)
721     //fprintf(stderr,"--CRC32 %d %d\n",crc,len)
722     return crc
723 }
724 func CRC32Finish(crc uint32, table *crc32.Table, len uint64)(uint32){
725     var slen = make([]byte,4)
726     var li = 0
727     for li = 0; li < 4; {
728         slen[li] = byte(len & 0xFF)
729         li += 1
730         len >>= 8
731         if( len == 0 ){
732             break
733         }
734     }
735     crc = crc32.Update(crc,table,slen)
736     crc ^= 0xFFFFFFFF
737     return crc
738 }
739 }
740 func (gsh*GshContext)xChecksum(path string,argv[]string, sum*Checksum)(int64){
741     if isin("-type/f",argv) && !IsRegFile(path){
742         return 0
743     }
744     if isin("-type/d",argv) && IsRegFile(path){
745         return 0
746     }
747     file, err := os.OpenFile(path,os.O_RDONLY,0)
748     if err != nil {
749         fmt.Printf("--E-- cksum %v (%v)\n",path,err)

```

```

750     return -1
751 }
752 defer file.Close()
753 if gsh.CmdTrace { fmt.Printf("--I-- cksum %v %v\n",path,argv) }
754
755 bi := 0
756 var buff = make([]byte,32*1024)
757 var total int64 = 0
758 var initTime = time.Time{}
759 if sum.Start == initTime {
760     sum.Start = time.Now()
761 }
762 for bi = 0; ; bi++ {
763     count,err := file.Read(buff)
764     if count <= 0 || err != nil {
765         break
766     }
767     if (sum.SumType & SUM_SUM64) != 0 {
768         s := sum.Sum64
769         for _,c := range buff[0:count] {
770             s += uint64(c)
771         }
772         sum.Sum64 = s
773     }
774     if (sum.SumType & SUM_UNIXFILE) != 0 {
775         sum.Crc32Val = byteCRC32add(sum.Crc32Val,buff,uint64(count))
776     }
777     if (sum.SumType & SUM_CRCIEEE) != 0 {
778         sum.Crc32Val = crc32.Update(sum.Crc32Val,&sum.Crc32Table,buff[0:count])
779     }
780     // <a href="https://en.wikipedia.org/wiki/BSD_checksum">BSD checksum</a>
781     if (sum.SumType & SUM_SUM16_BSD) != 0 {
782         s := sum.Sum16
783         for _,c := range buff[0:count] {
784             s = (s >> 1) + ((s & 1) << 15)
785             s += int(c)
786             s &= 0xFFFF
787             //fmt.Printf("BSDsum: %d[%d] %d\n",sum.Size+int64(i),i,s)
788         }
789         sum.Sum16 = s
790     }
791     if (sum.SumType & SUM_SUM16_SYSV) != 0 {
792         for bj := 0; bj < count; bj++ {
793             sum.Sum16 += int(buff[bj])
794         }
795     }
796     total += int64(count)
797 }
798 sum.Done = time.Now()
799 sum.Files += 1
800 sum.Size += total
801 if !isin("-s",argv) {
802     fmt.Printf("%v ",total)
803 }
804 return 0
805 }
806
807 // <a name="grep">grep</a>
808 // "lines", "lin" or "lnp" for "(text) line processor" or "scanner"
809 // a*,lab,c,... sequential combination of patterns
810 // what "LINE" is should be definable
811 // generic line-by-line processing
812 // grep [-v]
813 // cat -n -v
814 // uniq [-c]
815 // tail -f
816 // sed s/x/y/ or awk
817 // grep with line count like wc
818 // rewrite contents if specified
819 func (gsh*GshContext)XGrep(path string,rxpv[]string)(int){
820     file, err := os.OpenFile(path,os.O_RDONLY,0)
821     if err != nil {
822         fmt.Printf("--E-- grep %v (%v)\n",path,err)
823         return -1
824     }
825     defer file.Close()
826     if gsh.CmdTrace { fmt.Printf("--I-- grep %v %v\n",path,rxpv) }
827     //reader := bufio.NewReaderSize(file,LINESIZE)
828     reader := bufio.NewReaderSize(file,80)
829     li := 0
830     found := 0
831     for li = 0; ; li++ {
832         line, err := reader.ReadString('\n')
833         if len(line) <= 0 {
834             break
835         }
836         if 150 < len(line) {
837             // maybe binary
838             break;
839         }
840         if err != nil {
841             break
842         }
843         if 0 <= strings.Index(string(line),rxpv[0]) {
844             found += 1
845             fmt.Printf("%s:%d: %s",path,li,line)
846         }
847     }
848     //fmt.Printf("total %d lines %s\n",li,path)
849     //if( 0 < found ){ fmt.Printf("((found %d lines %s))\n",found,path); }
850     return found
851 }
852
853 // <a name="finder">Finder</a>
854 // finding files with it name and contents
855 // file names are ORED
856 // show the content with %x fmt list
857 // ls -R
858 // tar command by adding output
859 type fileSum struct {
860     Err int64 // access error or so
861     Size int64 // content size
862     DupSize int64 // content size from hard links
863     Blocks int64 // number of blocks (of 512 bytes)
864     DupBlocks int64 // Blocks pointed from hard links
865     HLinks int64 // hard links
866     Words int64
867     Lines int64
868     Files int64
869     Dirs int64 // the num. of directories
870     SymLink int64
871     Flats int64 // the num. of flat files
872     MaxDepth int64
873     MaxNamlen int64 // max. name length
874     nextRepo time.Time

```

```

875 }
876 func showFusage(dir string, fusage *fileSum) {
877     bsume := float64(((fusage.Blocks - fusage.DupBlocks) / 2) * 1024) / 1000000.0
878     // bsumdup := float64((fusage.Blocks / 2) * 1024) / 1000000.0
879
880     fmt.Printf("%v: %v files (%vd %vs %vh) %.6f MB (%.2f MBK)\n",
881         dir,
882         fusage.Files,
883         fusage.Dirs,
884         fusage.SymLink,
885         fusage.HLinks,
886         float64(fusage.Size) / 1000000.0, bsume);
887 }
888 const (
889     S_IFMT      = 0170000
890     S_IFCHR     = 0020000
891     S_IFDIR     = 0040000
892     S_IFREG     = 0100000
893     S_IFLNK     = 0120000
894     S_IFSOCK    = 0140000
895 )
896 func cumFinfo(fsum *fileSum, path string, stater error, fstat syscall.Stat_t, argv []string, verb bool) (*fileSum) {
897     now := time.Now()
898     if time.Second <= now.Sub(fsum.nextRepo) {
899         if !fsum.nextRepo.IsZero() {
900             tstamp := now.Format(time.Stamp)
901             showFusage(tstamp, fsum)
902         }
903         fsum.nextRepo = now.Add(time.Second)
904     }
905     if stater != nil {
906         fsum.Err += 1
907         return fsum
908     }
909     fsum.Files += 1
910     if l < fstat.Nlink {
911         // must count only once...
912         // at least ignore ones in the same directory
913         //if finfo.Mode().IsRegular() {
914         if (fstat.Mode & S_IFMT) == S_IFREG {
915             fsum.HLinks += 1
916             fsum.DupBlocks += int64(fstat.Blocks)
917             //fmt.Printf("---Dup HardLink %v %s\n", fstat.Nlink, path)
918         }
919     }
920     //fsum.Size += finfo.Size()
921     fsum.Size += fstat.Size
922     fsum.Blocks += int64(fstat.Blocks)
923     //if verb { fmt.Printf("%dBlk %s", fstat.Blocks/2, path) }
924     if isin("-ls", argv) {
925         //if verb { fmt.Printf("%4d %8d ", fstat.Blksize, fstat.Blocks) }
926         //fmt.Printf("%d\t", fstat.Blocks/2)
927     }
928     //if finfo.IsDir()
929     if (fstat.Mode & S_IFMT) == S_IFDIR {
930         fsum.Dirs += 1
931     }
932     //if (finfo.Mode() & os.ModeSymlink) != 0
933     if (fstat.Mode & S_IFMT) == S_IFLNK {
934         //if verb { fmt.Printf("symlink(%v,%s)\n", fstat.Mode, finfo.Name()) }
935         //if verb { fmt.Printf("symlink(%s,%s)\n", fstat.Mode, finfo.Name()) }
936         fsum.SymLink += 1
937     }
938     return fsum
939 }
940 func (gsh *GshContext) xxFindEntv(depth int, total *fileSum, dir string, dstat syscall.Stat_t, ei int, entv []string, npatv []string, argv []string) (*fileSum) {
941     nols := isin("-grep", argv)
942     // sort entv
943     /*
944     if isin("-t", argv) {
945         sort.Slice(filev, func(i, j int) bool {
946             return 0 < filev[i].ModTime().Sub(filev[j].ModTime())
947         })
948     }
949     */
950     /*
951     if isin("-u", argv) {
952         sort.Slice(filev, func(i, j int) bool {
953             return 0 < filev[i].AccTime().Sub(filev[j].AccTime())
954         })
955     }
956     if isin("-U", argv) {
957         sort.Slice(filev, func(i, j int) bool {
958             return 0 < filev[i].CreateTime().Sub(filev[j].CreateTime())
959         })
960     }
961     */
962     /*
963     if isin("-S", argv) {
964         sort.Slice(filev, func(i, j int) bool {
965             return filev[j].Size() < filev[i].Size()
966         })
967     }
968     */
969     for _, filename := range entv {
970         for _, npat := range npatv {
971             match := true
972             if npat == "*" {
973                 match = true
974             } else {
975                 match, _ = filepath.Match(npat, filename)
976             }
977             path := dir + DIRSEP + filename
978             if !match {
979                 continue
980             }
981             var fstat syscall.Stat_t
982             stater := syscall.Lstat(path, &fstat)
983             if stater != nil {
984                 if !isin("-w", argv) {
985                     fmt.Printf("ufind: %v\n", stater)
986                     continue;
987                 }
988                 if isin("-du", argv) && (fstat.Mode & S_IFMT) == S_IFDIR {
989                     // should not show size of directory in "-du" mode ...
990                 } else {
991                     if !nols && !isin("-s", argv) && (!isin("-du", argv) || isin("-a", argv)) {
992                         if isin("-du", argv) {
993                             fmt.Printf("%d\t", fstat.Blocks/2)
994                         }
995                         showFileInfo(path, argv)
996                     }
997                     if true { // && isin("-du", argv)
998                         total = cumFinfo(total, path, stater, fstat, argv, false)
999                     }
1000                 }
1001             }
1002         }
1003     }

```

```

1000     if isin("-wc",argv) {
1001     }
1002     /*
1003     if gsh.lastCheckSum.SumType != 0 {
1004         gsh.xCksum(path,argv,gsh.lastCheckSum);
1005     }
1006     x := isinX("-grep",argv); // -grep will be convenient like -ls
1007     if 0 <= x && x+1 <= len(argv) { // -grep will be convenient like -ls
1008         if isRegFile(path){
1009             found := gsh.xGrep(path,argv[x+1:])
1010             if 0 < found {
1011                 foundv := gsh.CmdCurrent.FoundFile
1012                 if len(foundv) < 10 {
1013                     gsh.CmdCurrent.FoundFile =
1014                         append(gsh.CmdCurrent.FoundFile,path)
1015                 }
1016             }
1017         }
1018     }
1019     if !isin("-r0",argv) { // -d 0 in du, -depth n in find
1020         //total.Depth += 1
1021         if (fstat.Mode & S_IFMT) == S_IFLNK {
1022             continue
1023         }
1024         if dstat.Rdev != fstat.Rdev {
1025             fmt.Printf("--I-- don't follow differnet device %v(%v) %v(%v)\n",
1026                 dir,dstat.Rdev,path,fstat.Rdev)
1027         }
1028         if (fstat.Mode & S_IFMT) == S_IFDIR {
1029             total = gsh.xxFind(depth+1,total,path,npatv,argv)
1030         }
1031     }
1032 }
1033 }
1034 return total
1035 }
1036 func (gsh*GshContext)xxFind(depth int,total *fileSum,dir string,npatv[]string,argv[]string)(*fileSum){
1037     nols := isin("-grep",argv)
1038     dirfile,oerr := os.OpenFile(dir,os.O_RDONLY,0)
1039     if oerr == nil {
1040         //fmt.Printf("--I-- %v(%v)[%d]\n",dir,dirfile,dirfile.Fd())
1041         defer dirfile.Close()
1042     }else{
1043     }
1044
1045     prev := *total
1046     var dstat syscall.Stat_t
1047     staterr := syscall.Lstat(dir,&dstat) // should be flstat
1048
1049     if staterr != nil {
1050         if !isin("-w",argv){ fmt.Printf("ufind: %v\n",staterr) }
1051         return total
1052     }
1053     //file,err := ioutil.ReadDir(dir)
1054     //_,err := ioutil.ReadDir(dir) // ReadDir() heavy and bad for huge directory
1055     /*
1056     if err != nil {
1057         if !isin("-w",argv){ fmt.Printf("ufind: %v\n",err) }
1058         return total
1059     }
1060     */
1061     if depth == 0 {
1062         total = cumPinfo(total,dir,staterr,dstat,argv,true)
1063         if !nols && !isin("-s",argv) && (!isin("-du",argv) || isin("-a",argv)) {
1064             showFileInfo(dir,argv)
1065         }
1066     }
1067     // it it is not a directory, just scan it and finish
1068
1069     for ei := 0; ; ei++ {
1070         entv,rderr := dirfile.Readdirnames(8*1024)
1071         if len(entv) == 0 || rderr != nil {
1072             //if rderr != nil { fmt.Printf("[%d] len=%d (%v)\n",ei,len(entv),rderr) }
1073             break
1074         }
1075         if 0 < ei {
1076             fmt.Printf("--I-- xxFind[%d] %d large-dir: %s\n",ei,len(entv),dir)
1077         }
1078         total = gsh.xxFindEntv(depth,total,dir,dstat,ei,entv,npatv,argv)
1079     }
1080     if isin("-du",argv) {
1081         // if in "du" mode
1082         fmt.Printf("%d\t%s\n",(total.Blocks-prev.Blocks)/2,dir)
1083     }
1084     return total
1085 }
1086
1087 // {ufind|fu|ls} [Files] [-- Names] [-- Expressions]
1088 // Files is "." by default
1089 // Names is "*" by default
1090 // Expressions is "-print" by default for "ufind", or -du for "fu" command
1091 func (gsh*GshContext)xFind(argv[]string){
1092     if 0 < len(argv) && strBegins(argv[0],"?"){
1093         showFound(gsh,argv)
1094         return
1095     }
1096     if isin("-cksum",argv) || isin("-sum",argv) {
1097         gsh.lastCheckSum = CheckSum{}
1098         if isin("-sum",argv) && isin("-add",argv) {
1099             gsh.lastCheckSum.SumType |= SUM_SUM64
1100         }else
1101         if isin("-sum",argv) && isin("-size",argv) {
1102             gsh.lastCheckSum.SumType |= SUM_SIZE
1103         }else
1104         if isin("-sum",argv) && isin("-bsd",argv) {
1105             gsh.lastCheckSum.SumType |= SUM_SUM16_BSD
1106         }else
1107         if isin("-sum",argv) && isin("-sysv",argv) {
1108             gsh.lastCheckSum.SumType |= SUM_SUM16_SYSV
1109         }else
1110         if isin("-sum",argv) {
1111             gsh.lastCheckSum.SumType |= SUM_SUM64
1112         }
1113         if isin("-unix",argv) {
1114             gsh.lastCheckSum.SumType |= SUM_UNIXFILE
1115             gsh.lastCheckSum.Crc32Table = *Crc32.MakeTable(CRC32UNIX)
1116         }
1117         if isin("-ieee",argv){
1118             gsh.lastCheckSum.SumType |= SUM_CRCIEEE
1119             gsh.lastCheckSum.Crc32Table = *Crc32.MakeTable(CRC32IEEE)
1120         }
1121         gsh.lastCheckSum.RusgAtStart = Getrusagev()
1122     }
1123     var total = fileSum{}
1124     npats := []string{}

```

```

1125 for _,v := range argv {
1126     if 0 < len(v) && v[0] != '-' {
1127         npats = append(npats,v)
1128     }
1129     if v == "/" { break }
1130     if v == "--" { break }
1131     if v == "-grep" { break }
1132     if v == "-ls" { break }
1133 }
1134 if len(npats) == 0 {
1135     npats = []string{"*"}
1136 }
1137 cwd := "."
1138 // if to be fullPath ::: cwd, _ := os.Getwd()
1139 if len(npats) == 0 { npats = []string{"*"} }
1140 fusage := gsh.xxFind(0,&ttotal,cwd,npats,argv)
1141 if gsh.lastCheckSum.SumType != 0 {
1142     var sumi uint64 = 0
1143     sum := &gsh.lastCheckSum
1144     if (sum.SumType & SUM_SIZE) != 0 {
1145         sumi = uint64(sum.Size)
1146     }
1147     if (sum.SumType & SUM_SUM64) != 0 {
1148         sumi = sum.Sum64
1149     }
1150     if (sum.SumType & SUM_SUM16_SYSV) != 0 {
1151         s := uint32(sum.Sum16)
1152         r := (s & 0xFFFF) + ((s & 0xFFFFFFFF) >> 16)
1153         s = (r & 0xFFFF) + (r >> 16)
1154         sum.Crc32Val = uint32(s)
1155         sumi = uint64(s)
1156     }
1157     if (sum.SumType & SUM_SUM16_BSD) != 0 {
1158         sum.Crc32Val = uint32(sum.Sum16)
1159         sumi = uint64(sum.Sum16)
1160     }
1161     if (sum.SumType & SUM_UNIXFILE) != 0 {
1162         sum.Crc32Val = byteCRC32end(sum.Crc32Val,uint64(sum.Size))
1163         sumi = uint64(byteCRC32end(sum.Crc32Val,uint64(sum.Size)))
1164     }
1165     if 1 < sum.Files {
1166         fmt.Printf("%v %v // %v / %v files, %v/file\r\n",
1167             sumi,sum.Size,
1168             abssize(sum.Size),sum.Files,
1169             abssize(sum.Size)/sum.Files)
1170     }else{
1171         fmt.Printf("%v %v %v\n",
1172             sumi,sum.Size,npats[0])
1173     }
1174 }
1175 if !isin("-grep",argv) {
1176     showFusage("total",fusage)
1177 }
1178 if !isin("-s",argv){
1179     hits := len(gsh.CmdCurrent.FoundFile)
1180     if 0 < hits {
1181         fmt.Printf("--I-- %d files hits // can be refered with !&df\n",
1182             hits,len(gsh.CommandHistory))
1183     }
1184 }
1185 if gsh.lastCheckSum.SumType != 0 {
1186     if isin("-ru",argv) {
1187         sum := &gsh.lastCheckSum
1188         sum.Done = time.Now()
1189         gsh.lastCheckSum.RusgAtEnd = Getrusagev()
1190         elps := sum.Done.Sub(sum.Start)
1191         fmt.Printf("--cksum-size: %v (%v) / %v files, %v/file\r\n",
1192             sum.Size,abssize(sum.Size),sum.Files,abssize(sum.Size)/sum.Files)
1193         nanos := int64(elps)
1194         fmt.Printf("--cksum-time: %v/total, %v/file, %1.f files/s, %v\r\n",
1195             abstime(nanos),
1196             abstime(nanos)/sum.Files,
1197             (float64(sum.Files)*1000000000.0)/float64(nanos),
1198             abbspeed(sum.Size, nanos))
1199         diff := RusageSubv(sum.RusgAtEnd, sum.RusgAtStart)
1200         fmt.Printf("--cksum-rusg: %v\n",sRusagef("",argv,diff))
1201     }
1202 }
1203 return
1204 }
1205 }
1206 func showFiles(files[]string){
1207     sp := ""
1208     for i,file := range files {
1209         if 0 < i { sp = " " } else { sp = "" }
1210         fmt.Printf(sp+"%s",escapeWhiteSP(file))
1211     }
1212 }
1213 func showFound(gshCtx *GshContext, argv[]string){
1214     for i,v := range gshCtx.CommandHistory {
1215         if 0 < len(v.FoundFile) {
1216             fmt.Printf("%d (%d)",i,len(v.FoundFile))
1217             if isin("-ls",argv){
1218                 fmt.Printf("\n")
1219                 for _,file := range v.FoundFile {
1220                     fmt.Printf("%s //sub number?"
1221                         showFileInfo(file,argv))
1222                 }
1223             }else{
1224                 showFiles(v.FoundFile)
1225                 fmt.Printf("\n")
1226             }
1227         }
1228     }
1229 }
1230 }
1231 func showMatchFile(filev []os.FileInfo, npat,dir string, argv[]string)(string,bool){
1232     fname := ""
1233     found := false
1234     for _,v := range filev {
1235         match, _ := filepath.Match(npat,(v.Name()))
1236         if match {
1237             fname = v.Name()
1238             found = true
1239             //fmt.Printf("%d %s\n",i,v.Name())
1240             showIfExecutable(fname,dir,argv)
1241         }
1242     }
1243     return fname,found
1244 }
1245 func showIfExecutable(name,dir string,argv[]string)(ffullpath string,ffound bool){
1246     var fullpath string
1247     if strBegins(name,DIRSEP){
1248         fullpath = name
1249     }else{

```

```

1250     fullpath = dir + DIRSEP + name
1251 }
1252 fi, err := os.Stat(fullpath)
1253 if err != nil {
1254     fullpath = dir + DIRSEP + name + ".go"
1255     fi, err = os.Stat(fullpath)
1256 }
1257 if err == nil {
1258     fm := fi.Mode()
1259     if fm.IsRegular() {
1260         // R_OK=4, W_OK=2, X_OK=1, F_OK=0
1261         if syscall.Access(fullpath,5) == nil {
1262             ffullpath = fullpath
1263             ffound = true
1264             if !isin("-s", argv) {
1265                 showFileInfo(fullpath,argv)
1266             }
1267         }
1268     }
1269 }
1270 return ffullpath, ffound
1271 }
1272 func which(list string, argv []string) (fullpathv []string, itis bool){
1273     if len(argv) <= 1 {
1274         fmt.Printf("Usage: which comand [-s] [-a] [-ls]\n")
1275         return []string{"", false
1276     }
1277     path := argv[1]
1278     if strBegins(path, "/") {
1279         // should check if executable?
1280         exOK := showIfExecutable(path, "/", argv)
1281         fmt.Printf("--D-- %v exOK=%v\n", path, exOK)
1282         return []string{path}, exOK
1283     }
1284     pathenv, efound := os.LookupEnv(list)
1285     if ! efound {
1286         fmt.Printf("--E-- which: no \"%s\" environment\n", list)
1287         return []string{"", false
1288     }
1289     showall := isin("-a", argv) || 0 <= strings.Index(path, "*")
1290     dirv := strings.Split(pathenv, PATHSEP)
1291     ffound := false
1292     ffullpath := path
1293     for _, dir := range dirv {
1294         if 0 <= strings.Index(path, "*") { // by wild-card
1295             list, _ := ioutil.ReadDir(dir)
1296             ffullpath, ffound = showMatchFile(list, path, dir, argv)
1297         } else {
1298             ffullpath, ffound = showIfExecutable(path, dir, argv)
1299         }
1300         //if ffound && !isin("-a", argv) {
1301         if ffound && !showall {
1302             break;
1303         }
1304     }
1305     return []string{ffullpath}, ffound
1306 }
1307 }
1308 func stripLeadingWSParg(argv []string) ([]string){
1309     for i, 0 < len(argv); {
1310         if len(argv[i]) == 0 {
1311             argv = argv[1:]
1312         } else {
1313             break
1314         }
1315     }
1316     return argv
1317 }
1318 func xEval(argv []string, nlend bool){
1319     argv = stripLeadingWSParg(argv)
1320     if len(argv) == 0 {
1321         fmt.Printf("eval [%%format] [Go-expression]\n")
1322         return
1323     }
1324     pfmt := "%v"
1325     if argv[0][0] == '%' {
1326         pfmt = argv[0]
1327         argv = argv[1:]
1328     }
1329     if len(argv) == 0 {
1330         return
1331     }
1332     gocode := strings.Join(argv, " ");
1333     //fmt.Printf("eval [%v] [%v]\n", pfmt, gocode)
1334     fset := token.NewFileSet()
1335     rval, _ := types.Eval(fset, nil, token.NoPos, gocode)
1336     fmt.Printf(pfmt, rval.Value)
1337     if nlend { fmt.Printf("\n") }
1338 }
1339 }
1340 func getval(name string) (found bool, val int) {
1341     /* should expand the name here */
1342     if name == "gsh.pid" {
1343         return true, os.Getpid()
1344     } else
1345     if name == "gsh.ppid" {
1346         return true, os.Getppid()
1347     }
1348     return false, 0
1349 }
1350 }
1351 func echo(argv []string, nlend bool){
1352     for ai := 1; ai < len(argv); ai++ {
1353         if 1 < ai {
1354             fmt.Printf(" ");
1355         }
1356         arg := argv[ai]
1357         found, val := getval(arg)
1358         if found {
1359             fmt.Printf("%d", val)
1360         } else {
1361             fmt.Printf("%s", arg)
1362         }
1363     }
1364     if nlend {
1365         fmt.Printf("\n");
1366     }
1367 }
1368 }
1369 func resfile() string {
1370     return "gsh.tmp"
1371 }
1372 //var resF *File
1373 func resmap() {
1374     //_, err := os.OpenFile(resfile(), os.O_RDWR|os.O_CREATE, os.ModeAppend)

```

```

1375 // https://deveppaper.com/solution-to-golang-bad-file-descriptor-problem/
1376 _, err := os.OpenFile(resfile(), os.O_RDWR|os.O_CREATE, 0600)
1377 if err != nil {
1378     fmt.Printf("refF could not open: %s\n",err)
1379 }else{
1380     fmt.Printf("refF opened\n")
1381 }
1382 }
1383 }
1384 // @@2020-0821
1385 func gshScanArg(str string,strip int)(argv []string){
1386     var si = 0
1387     var sb = 0
1388     var inBracket = 0
1389     var arg1 = make([]byte,LINESIZE)
1390     var ax = 0
1391     debug := false
1392
1393     for ; si < len(str); si++ {
1394         if str[si] != ' ' {
1395             break
1396         }
1397     }
1398     sb = si
1399     for ; si < len(str); si++ {
1400         if sb <= si {
1401             if debug {
1402                 fmt.Printf("--Da- +%d %2d-%2d %s ... %s\n",
1403                     inBracket,sb,si,arg1[0:ax],str[si:])
1404             }
1405         }
1406         ch := str[si]
1407         if ch == '{' {
1408             inBracket += 1
1409             if 0 < strip && inBracket <= strip {
1410                 //fmt.Printf("stripLEV %d <= %d?\n",inBracket,strip)
1411                 continue
1412             }
1413         }
1414         if 0 < inBracket {
1415             if ch == '}' {
1416                 inBracket -= 1
1417                 if 0 < strip && inBracket < strip {
1418                     //fmt.Printf("stripLEV %d < %d?\n",inBracket,strip)
1419                     continue
1420                 }
1421             }
1422             arg1[ax] = ch
1423             ax += 1
1424             continue
1425         }
1426         if str[si] == ' ' {
1427             argv = append(argv,string(arg1[0:ax]))
1428             if debug {
1429                 fmt.Printf("--Da- [%v][%v-%v] %s ... %s\n",
1430                     -1+len(argv),sb,si,str[sb:si],string(str[si:]))
1431             }
1432             sb = si+1
1433             ax = 0
1434             continue
1435         }
1436         arg1[ax] = ch
1437         ax += 1
1438     }
1439     if sb < si {
1440         argv = append(argv,string(arg1[0:ax]))
1441         if debug {
1442             fmt.Printf("--Da- [%v][%v-%v] %s ... %s\n",
1443                 -1+len(argv),sb,si,string(arg1[0:ax]),string(str[si:]))
1444         }
1445     }
1446     if debug {
1447         fmt.Printf("--Da- %d [%s] => [%d]%v\n",strip,si,len(argv),argv)
1448     }
1449     return argv
1450 }
1451 }
1452 // should get stderr (into tmpfile ?) and return
1453 func (gsh*GshContext)Popen(name,mode string)(pin*os.File,pout*os.File,err bool){
1454     var pv = []int{-1,-1}
1455     syscall.Pipe(pv)
1456
1457     xarg := gshScanArg(name,1)
1458     name = strings.Join(xarg," ")
1459
1460     pin = os.NewFile(uintptr(pv[0]),"StdoutOf-"+name)
1461     pout = os.NewFile(uintptr(pv[1]),"StdinOf-"+name)
1462     fdix := 0
1463     dir := "?"
1464     if mode == "r" {
1465         dir = "<"
1466         fdix = 1 // read from the stdout of the process
1467     }else{
1468         dir = ">"
1469         fdix = 0 // write to the stdin of the process
1470     }
1471     gshPA := gsh.gshPA
1472     savfd := gshPA.Files[fdix]
1473
1474     var fd uintptr = 0
1475     if mode == "r" {
1476         fd = pout.Fd()
1477         gshPA.Files[fdix] = pout.Fd()
1478     }else{
1479         fd = pin.Fd()
1480         gshPA.Files[fdix] = pin.Fd()
1481     }
1482     // should do this by Goroutine?
1483     if false {
1484         fmt.Printf("--Ip- Opened fd[%v] %s %v\n",fd,dir,name)
1485         fmt.Printf("--RED1 [%d,%d,%d]->[%d,%d,%d]\n",
1486             os.Stdin.Fd(),os.Stdout.Fd(),os.Stderr.Fd(),
1487             pin.Fd(),pout.Fd(),pout.Fd())
1488     }
1489     savi := os.Stdin
1490     savo := os.Stdout
1491     save := os.Stderr
1492     os.Stdin = pin
1493     os.Stdout = pout
1494     os.Stderr = pout
1495     gsh.BackGround = true
1496     gsh.gshellh(name)
1497     gsh.BackGround = false
1498     os.Stdin = savi
1499     os.Stdout = savo

```

```

1500         os.Stderr = save
1501
1502     gshPA.Files[fdix] = savfd
1503     return pin,pout,false
1504 }
1505
1506 // <a name="ex-commands">External commands</a>
1507 func (gsh *GshContext)excommand(exec bool, argv []string) (notf bool,exit bool) {
1508     if gsh.CmdTrace { fmt.Printf("--I-- excommand[%v](%v)\n",exec,argv) }
1509
1510     gshPA := gsh.gshPA
1511     fullpath, itis := which("PATH",[]string{"which",argv[0],"-s"})
1512     if itis == false {
1513         return true,false
1514     }
1515     fullpath := fullpath[0]
1516     argv = unescapeWhiteSPV(argv)
1517     if 0 < strings.Index(fullpath,".go") {
1518         nargv := argv[1:]
1519         gofullpath, itis := which("PATH",[]string{"which","go","-s"})
1520         if itis == false {
1521             fmt.Printf("--F-- Go not found\n")
1522             return false,true
1523         }
1524         gofullpath := gofullpath[0]
1525         nargv = []string{ gofullpath, "run", fullpath }
1526         fmt.Printf("--I-- %s (%s %s %s)\n",gofullpath,
1527             nargv[0],nargv[1],nargv[2])
1528         if exec {
1529             syscall.Exec(gofullpath,nargv,os.Environ())
1530         }else{
1531             pid, _ := syscall.ForkExec(gofullpath,nargv,&gshPA)
1532             if gsh.BackGround {
1533                 fmt.Fprintf(stderr,"--Ip- in Background pid[%d]&d(%v)\n",pid,len(argv),nargv)
1534                 gsh.BackGroundJobs = append(gsh.BackGroundJobs,pid)
1535             }else{
1536                 rusage := syscall.Rusage {}
1537                 syscall.Wait4(pid,nil,0,&rusage)
1538                 gsh.LastRusage = rusage
1539                 gsh.CmdCurrent.Rusagev[1] = rusage
1540             }
1541         }
1542     }else{
1543         if exec {
1544             syscall.Exec(fullpath,argv,os.Environ())
1545         }else{
1546             pid, _ := syscall.ForkExec(fullpath,argv,&gshPA)
1547             //fmt.Printf("[%d]\n",pid); // '&' to be background
1548             if gsh.BackGround {
1549                 fmt.Fprintf(stderr,"--Ip- in Background pid[%d]&d(%v)\n",pid,len(argv),argv)
1550                 gsh.BackGroundJobs = append(gsh.BackGroundJobs,pid)
1551             }else{
1552                 rusage := syscall.Rusage {}
1553                 syscall.Wait4(pid,nil,0,&rusage);
1554                 gsh.LastRusage = rusage
1555                 gsh.CmdCurrent.Rusagev[1] = rusage
1556             }
1557         }
1558     }
1559     return false,false
1560 }
1561
1562 // <a name="builtin">Builtin Commands</a>
1563 func (gshCtx *GshContext) sleep(argv []string) {
1564     if len(argv) < 2 {
1565         fmt.Printf("Sleep 100ms, 100us, 100ns, ...)\n")
1566         return
1567     }
1568     duration := argv[1];
1569     d, err := time.ParseDuration(duration)
1570     if err != nil {
1571         d, err = time.ParseDuration(duration+"s")
1572         if err != nil {
1573             fmt.Printf("duration ? %s (%s)\n",duration,err)
1574             return
1575         }
1576     }
1577     //fmt.Printf("Sleep %v\n",duration)
1578     time.Sleep(d)
1579     if 0 < len(argv[2:]) {
1580         gshCtx.gshellv(argv[2:])
1581     }
1582 }
1583 func (gshCtx *GshContext)repeat(argv []string) {
1584     if len(argv) < 2 {
1585         return
1586     }
1587     start0 := time.Now()
1588     for ri, _ := strconv.Atoi(argv[1]); 0 < ri; ri-- {
1589         if 0 < len(argv[2:]) {
1590             //start := time.Now()
1591             gshCtx.gshellv(argv[2:])
1592             end := time.Now()
1593             elps := end.Sub(start0);
1594             if( 1000000000 < elps ){
1595                 fmt.Printf("(repeat#%d %v)\n",ri,elps);
1596             }
1597         }
1598     }
1599 }
1600
1601 func (gshCtx *GshContext)gen(argv []string) {
1602     gshPA := gshCtx.gshPA
1603     if len(argv) < 2 {
1604         fmt.Printf("Usage: %s N\n",argv[0])
1605         return
1606     }
1607     // should br repeated by "repeat" command
1608     count, _ := strconv.Atoi(argv[1])
1609     fd := gshPA.Files[1] // Stdout
1610     file := os.NewFile(fd,"internalStdOut")
1611     fmt.Printf("--I-- Gen. Count=%d to [%d]\n",count,file.Fd())
1612     //buf := []byte{}
1613     outdata := "0123 5678 0123 5678 0123 5678 0123 5678\r"
1614     for gi := 0; gi < count; gi++ {
1615         file.WriteString(outdata)
1616     }
1617     //file.WriteString("\n")
1618     fmt.Printf("\n(%d B)\n",count*len(outdata));
1619     //file.Close()
1620 }
1621
1622 // <a name="rexec">Remote Execution</a> // 2020-0820
1623 func Elapsed(from time.Time)(string){
1624     elps := time.Now().Sub(from)

```

```

1625     if 1000000000 < elps {
1626         return fmt.Sprintf("[%5d.%02ds]", elps/1000000000, (elps%1000000000)/10000000)
1627     }else{
1628         if 1000000 < elps {
1629             return fmt.Sprintf("[%3d.%03dms]", elps/1000000, (elps%1000000)/1000)
1630         }else{
1631             return fmt.Sprintf("[%3d.%03dus]", elps/1000, (elps%1000))
1632         }
1633     }
1634 func abftime(nanos int64)(string){
1635     if 1000000000 < nanos {
1636         return fmt.Sprintf("%d.%02ds", nanos/1000000000, (nanos%1000000000)/10000000)
1637     }else{
1638         if 1000000 < nanos {
1639             return fmt.Sprintf("%d.%03dms", nanos/1000000, (nanos%1000000)/1000)
1640         }else{
1641             return fmt.Sprintf("%d.%03dus", nanos/1000, (nanos%1000))
1642         }
1643     }
1644 func abszize(size int64)(string){
1645     fsz := float64(size)
1646     if 1024*1024*1024 < size {
1647         return fmt.Sprintf("%.2fGiB", fsz/(1024*1024*1024))
1648     }else{
1649         if 1024*1024 < size {
1650             return fmt.Sprintf("%.3fMiB", fsz/(1024*1024))
1651         }else{
1652             return fmt.Sprintf("%.3fKiB", fsz/1024)
1653         }
1654     }
1655 func abszize(size int64)(string){
1656     fsz := float64(size)
1657     if 1024*1024*1024 < size {
1658         return fmt.Sprintf("%.2fGiB", fsz/(1024*1024*1024))
1659     }else{
1660         if 1024*1024 < size {
1661             return fmt.Sprintf("%.3fMiB", fsz/(1024*1024))
1662         }else{
1663             return fmt.Sprintf("%.3fKiB", fsz/1024)
1664         }
1665     }
1666 func abspspeed(totalB int64, ns int64)(string){
1667     MBs := (float64(totalB)/1000000) / (float64(ns)/1000000000)
1668     if 1000 <= MBs {
1669         return fmt.Sprintf("%.3fGB/s", MBs/1000)
1670     }
1671     if 1 <= MBs {
1672         return fmt.Sprintf("%.3fMB/s", MBs)
1673     }else{
1674         return fmt.Sprintf("%.3fKB/s", MBs*1000)
1675     }
1676 }
1677 func abspspeed(totalB int64, ns time.Duration)(string){
1678     MBs := (float64(totalB)/1000000) / (float64(ns)/1000000000)
1679     if 1000 <= MBs {
1680         return fmt.Sprintf("%.3fGBps", MBs/1000)
1681     }
1682     if 1 <= MBs {
1683         return fmt.Sprintf("%.3fMBps", MBs)
1684     }else{
1685         return fmt.Sprintf("%.3fKBps", MBs*1000)
1686     }
1687 }
1688 func fileRelay(what string, in*os.File, out*os.File, size int64, bsiz int)(wcount int64){
1689     Start := time.Now()
1690     buff := make([]byte, bsiz)
1691     var total int64 = 0
1692     var rem int64 = size
1693     nio := 0
1694     Prev := time.Now()
1695     var PrevSize int64 = 0
1696
1697     fmt.Printf(Elapsed(Start)+"--In- X: %s (%v/%v/%v) START\n",
1698         what, abszize(total), size, nio)
1699
1700     for i:= 0; ; i++ {
1701         var len = bsiz
1702         if int(rem) < len {
1703             len = int(rem)
1704         }
1705         Now := time.Now()
1706         Elps := Now.Sub(Prev);
1707         if 1000000000 < Now.Sub(Prev) {
1708             fmt.Printf(Elapsed(Start)+"--In- X: %s (%v/%v/%v) %s\n",
1709                 what, abszize(total), size, nio,
1710                 abspspeed((total-PrevSize), Elps))
1711             Prev = Now;
1712             PrevSize = total
1713         }
1714         rlen := len
1715         if in != nil {
1716             // should watch the disconnection of out
1717             rcc, err := in.Read(buff[0:rlen])
1718             if err != nil {
1719                 fmt.Printf(Elapsed(Start)+"--En- X: %s read(%v,%v)<%v\n",
1720                     what, rcc, err, in.Name())
1721                 break
1722             }
1723             rlen = rcc
1724             if string(buff[0:10]) == "(SoftEOF " {
1725                 var ecc int64 = 0
1726                 fmt.Sscanf(string(buff), "(SoftEOF %v", &ecc)
1727                 fmt.Printf(Elapsed(Start)+"--En- X: %s Recv ((SoftEOF %v))&v\n",
1728                     what, ecc, total)
1729                 if ecc == total {
1730                     break
1731                 }
1732             }
1733         }
1734
1735         wlen := rlen
1736         if out != nil {
1737             wcc, err := out.Write(buff[0:wlen])
1738             if err != nil {
1739                 fmt.Printf(Elapsed(Start)+"--En-- X: %s write(%v,%v)>%v\n",
1740                     what, wcc, err, out.Name())
1741                 break
1742             }
1743             wlen = wcc
1744         }
1745         if wlen < rlen {
1746             fmt.Printf(Elapsed(Start)+"--En- X: %s incomplete write (%v/%v)\n",
1747                 what, wlen, rlen)
1748             break;
1749         }

```

```

1750
1751     nio += 1
1752     total += int64(rlen)
1753     rem -= int64(rlen)
1754     if rem <= 0 {
1755         break
1756     }
1757 }
1758 Done := time.Now()
1759 Elps := float64(Done.Sub(Start))/1000000000 //Seconds
1760 TotalMB := float64(total)/1000000 //MB
1761 MBps := TotalMB / Elps
1762 fmt.Printf(Elapsed(Start)+"--In- X: %s (%v/%v/%v) %v %v.3fMB/s\n",
1763     what,total,size,nio,absize(total),MBps)
1764 return total
1765 }
1766 func tcpPush(clnt *os.File){
1767     // shrink socket buffer and recover
1768     usleep(100);
1769 }
1770 func (gsh*GshContext)RexecServer(argv[]string){
1771     debug := true
1772     Start0 := time.Now()
1773     Start := Start0
1774     // if local == ";" { local = "0.0.0.0:9999" }
1775     local := "0.0.0.0:9999"
1776
1777     if 0 < len(argv) {
1778         if argv[0] == "-s" {
1779             debug = false
1780             argv = argv[1:]
1781         }
1782     }
1783     if 0 < len(argv) {
1784         argv = argv[1:]
1785     }
1786     port, err := net.ResolveTCPAddr("tcp",local);
1787     if err != nil {
1788         fmt.Printf("--En- S: Address error: %s (%s)\n",local,err)
1789         return
1790     }
1791     fmt.Printf(Elapsed(Start)+"--In- S: Listening at %s...\n",local);
1792     sconn, err := net.ListenTCP("tcp", port)
1793     if err != nil {
1794         fmt.Printf(Elapsed(Start)+"--En- S: Listen error: %s (%s)\n",local,err)
1795         return
1796     }
1797
1798     reqbuf := make([]byte,LINESIZE)
1799     res := ""
1800     for {
1801         fmt.Printf(Elapsed(Start0)+"--In- S: Listening at %s...\n",local);
1802         aconn, err := sconn.AcceptTCP()
1803         Start = time.Now()
1804         if err != nil {
1805             fmt.Printf(Elapsed(Start)+"--En- S: Accept error: %s (%s)\n",local,err)
1806             return
1807         }
1808         clnt, _ := aconn.File()
1809         fd := Clnt.Fd()
1810         ar := aconn.RemoteAddr()
1811         if debug { fmt.Printf(Elapsed(Start0)+"--In- S: Accepted TCP at %s [%d] <- %v\n",
1812             local,fd,ar) }
1813         res = fmt.Sprintf("220 GShell/%s Server\r\n",VERSION)
1814         fmt.Fprintf(clnt,"%s",res)
1815         if debug { fmt.Printf(Elapsed(Start)+"--In- S: %s",res) }
1816         count, err := clnt.Read(reqbuf)
1817         if err != nil {
1818             fmt.Printf(Elapsed(Start)+"--En- C: (%v %v) %v",
1819                 count,err,string(reqbuf))
1820         }
1821         req := string(reqbuf[:count])
1822         if debug { fmt.Printf(Elapsed(Start)+"--In- C: %v",string(req)) }
1823         reqv := strings.Split(string(req),"\r")
1824         cmdv := gshScanArg(reqv[0],0)
1825         //cmdv := strings.Split(reqv[0], " ")
1826         switch cmdv[0] {
1827             case "HELO":
1828                 res = fmt.Sprintf("250 %v",req)
1829             case "GET":
1830                 // download {remotefile|-zN} [localfile]
1831                 var dsize int64 = 32*1024*1024
1832                 var bsize int = 64*1024
1833                 var fname string = ""
1834                 var in *os.File = nil
1835                 var pseudoEOF = false
1836                 if 1 < len(cmdv) {
1837                     fname = cmdv[1]
1838                     if strBegins(fname,"-z") {
1839                         fmt.Sscanf(fname[2:], "%d",&dsize)
1840                     }else
1841                     if strBegins(fname,"{") {
1842                         xin,xout,err := gsh.Popen(fname,"r")
1843                         if err {
1844                             }else{
1845                                 xout.Close()
1846                                 defer xin.Close()
1847                                 in = xin
1848                                 dsize = MaxStreamSize
1849                                 pseudoEOF = true
1850                             }
1851                         }else{
1852                             xin,err := os.Open(fname)
1853                             if err != nil {
1854                                 fmt.Printf("--En- GET (%v)\n",err)
1855                             }else{
1856                                 defer xin.Close()
1857                                 in = xin
1858                                 fi,_ := xin.Stat()
1859                                 dsize = fi.Size()
1860                             }
1861                         }
1862                     }
1863                 }
1864                 //fmt.Printf(Elapsed(Start)+"--In- GET %v:%v\n",dsize,bsize)
1865                 res = fmt.Sprintf("200 %v\r\n",dsize)
1866                 fmt.Fprintf(clnt,"%v",res)
1867                 tcpPush(clnt); // should be separated as line in receiver
1868                 fmt.Printf(Elapsed(Start)+"--In- S: %v",res)
1869                 wcount := fileRelay("SendGET",in,clnt,dsize,bsize)
1870                 if pseudoEOF {
1871                     in.Close() // pipe from the command
1872                     // show end of stream data (its size) by OOB?
1873                     SoftEOF := fmt.Sprintf("({SoftEOF %v})",wcount)
1874                     fmt.Printf(Elapsed(Start)+"--In- S: Send %v\n",SoftEOF)
1875                 }

```

```

1875         tcpPush(clnt); // to let SoftEOF data apper at the top of received data
1876         fmt.Fprintf(clnt, "%v\r\n", softEOF)
1877         tcpPush(clnt); // to let SoftEOF alone in a packet (separate with 200 OK)
1878         // with client generated random?
1879         //fmt.Printf("--In- L: close %v (%v)\n", in.Fd(), in.Name())
1880     }
1881     res = fmt.Sprintf("200 GET done\r\n")
1882     case "PUT":
1883         // upload {srcfile|-zN} [dstfile]
1884         var dsz int64 = 32*1024*1024
1885         var bsize int = 64*1024
1886         var fname string = ""
1887         var out *os.File = nil
1888         if 1 < len(cmdv) { // localfile
1889             fmt.Sscanf(cmdv[1], "%d", &dsz)
1890         }
1891         if 2 < len(cmdv) {
1892             fname = cmdv[2]
1893             if fname == "." {
1894                 // nul dev
1895             }else{
1896                 if strBegins(fname, "{") {
1897                     xin, xout, err := gsh.Popen(fname, "w")
1898                     if err {
1899                         }else{
1900                             xin.Close()
1901                             defer xout.Close()
1902                             out = xout
1903                         }
1904                     }else{
1905                         // should write to temporary file
1906                         // should suppress ^C on tty
1907                     xout, err := os.OpenFile(fname, os.O_CREATE|os.O_RDWR|os.O_TRUNC, 0600)
1908                     //fmt.Printf("--In- S: open(%v) out(%v) err(%v)\n", fname, xout, err)
1909                     if err != nil {
1910                         fmt.Printf("--En- PUT (%v)\n", err)
1911                     }else{
1912                         out = xout
1913                     }
1914                 }
1915                 fmt.Printf(Elapsed(Start)+"--In- L: open(%v,w) %v (%v)\n",
1916                     fname, local, err)
1917             }
1918             fmt.Printf(Elapsed(Start)+"--In- PUT %v (%v)\n", dsz, bsize)
1919             fmt.Printf(Elapsed(Start)+"--In- S: 200 %v OK\r\n", dsz)
1920             fmt.Fprintf(clnt, "200 %v OK\r\n", dsz)
1921             fileRelay("RecvPUT", clnt, out, dsz, bsize)
1922             res = fmt.Sprintf("200 PUT done\r\n")
1923         default:
1924             res = fmt.Sprintf("400 What? %v", req)
1925     }
1926     swcc, serr := clnt.Write([]byte(res))
1927     if serr != nil {
1928         fmt.Printf(Elapsed(Start)+"--In- S: (wc=%v er=%v) %v", swcc, serr, res)
1929     }else{
1930         fmt.Printf(Elapsed(Start)+"--In- S: %v", res)
1931     }
1932     aconn.Close();
1933     clnt.Close();
1934 }
1935 sconn.Close();
1936 }
1937 func (gsh*GshContext)RexecClient(argv []string) (int, string){
1938     debug := true
1939     Start := time.Now()
1940     if len(argv) == 1 {
1941         return -1, "EmptyARG"
1942     }
1943     argv = argv[1:]
1944     if argv[0] == "-serv" {
1945         gsh.RexecServer(argv[1:])
1946         return 0, "Server"
1947     }
1948     remote := "0.0.0.0:9999"
1949     if argv[0][0] == '8' {
1950         remote = argv[0][1:]
1951         argv = argv[1:]
1952     }
1953     if argv[0] == "-s" {
1954         debug = false
1955         argv = argv[1:]
1956     }
1957     dport, err := net.ResolveTCPAddr("tcp", remote);
1958     if err != nil {
1959         fmt.Printf(Elapsed(Start)+"Address error: %s (%s)\n", remote, err)
1960         return -1, "AddressError"
1961     }
1962     fmt.Printf(Elapsed(Start)+"--In- C: Connecting to %s\n", remote)
1963     serv, err := net.DialTCP("tcp", nil, dport)
1964     if err != nil {
1965         fmt.Printf(Elapsed(Start)+"Connection error: %s (%s)\n", remote, err)
1966         return -1, "CannotConnect"
1967     }
1968     if debug {
1969         al := serv.LocalAddr()
1970         fmt.Printf(Elapsed(Start)+"--In- C: Connected to %v <- %v\n", remote, al)
1971     }
1972     req := ""
1973     res := make([]byte, LINE_SIZE)
1974     count, err := serv.Read(res)
1975     if err != nil {
1976         fmt.Printf("--En- S: (%3d,%v) %v", count, err, string(res))
1977     }
1978     if debug { fmt.Printf(Elapsed(Start)+"--In- S: %v", string(res)) }
1979 }
1980 if argv[0] == "GET" {
1981     savPA := gsh.gshPA
1982     var bsize int = 64*1024
1983     req = fmt.Sprintf("%v\r\n", strings.Join(argv, " "))
1984     fmt.Printf(Elapsed(Start)+"--In- C: %v", req)
1985     fmt.Fprintf(serv, req)
1986     count, err = serv.Read(res)
1987     if err != nil {
1988     }else{
1989         var dsz int64 = 0
1990         var out *os.File = nil
1991         var out_tobeclosed *os.File = nil
1992         var fname string = ""
1993         var rcode int = 0
1994         var pid int = -1
1995         fmt.Sscanf(string(res), "%d %d", &rcode, &dsz)
1996         fmt.Printf(Elapsed(Start)+"--In- S: %v", string(res[0:count]))
1997         if 3 <= len(argv) {
1998             fname = argv[2]

```

```

2000     if strBegins(fname, "{") {
2001         xin,xout,err := gsh.Popen(fname,"w")
2002         if err {
2003             }else{
2004                 xin.Close()
2005                 defer xout.Close()
2006                 out = xout
2007                 out_tobeclosed = xout
2008                 pid = 0 // should be its pid
2009             }
2010         }else{
2011             // should write to temporary file
2012             // should suppress ^C on tty
2013             xout,err := os.OpenFile(fname,os.O_CREATE|os.O_RDWR|os.O_TRUNC,0600)
2014             if err != nil {
2015                 fmt.Printf("--En- %v\n",err)
2016             }
2017             out = xout
2018             //fmt.Printf("--In-- %d > %s\n",out.Fd(),fname)
2019         }
2020     }
2021     in,_ := serv.File()
2022     fileRelay("RecvGET",in,out,dsize,bsize)
2023     if 0 <= pid {
2024         gsh.gshPA = savPA // recovery of Fd(), and more?
2025         fmt.Printf(Elapsed(Start)+"--In- L: close Pipe > %v\n",fname)
2026         out_tobeclosed.Close()
2027         //syscall.Wait4(pid,nil,0,nil) @@
2028     }
2029 }
2030 }else
2031 if argv[0] == "PUT" {
2032     remote,_ := serv.File()
2033     var local *os.File = nil
2034     var dsize int64 = 32*1024*1024
2035     var bsize int = 64*1024
2036     var ofile string = "-"
2037     //fmt.Printf("--I-- Rex %v\n",argv)
2038     if 1 < len(argv) {
2039         fname := argv[1]
2040         if strBegins(fname, "-z") {
2041             fmt.Sscanf(fname[2:], "%d", &dsize)
2042         }else
2043         if strBegins(fname, "{") {
2044             xin,xout,err := gsh.Popen(fname,"r")
2045             if err {
2046                 }else{
2047                     xout.Close()
2048                     defer xin.Close()
2049                     //in = xin
2050                     local = xin
2051                     fmt.Printf("--In- [%d] < Upload output of %v\n",
2052                         local.Fd(),fname)
2053                     ofile = "-from."+fname
2054                     dsize = MaxStreamSize
2055                 }
2056             }else{
2057                 xlocal,err := os.Open(fname)
2058                 if err != nil {
2059                     fmt.Printf("--En- (%s)\n",err)
2060                     local = nil
2061                 }else{
2062                     local = xlocal
2063                     fi,_ := local.Stat()
2064                     dsize = fi.Size()
2065                     defer local.Close()
2066                     //fmt.Printf("--I-- Rex in(%v / %v)\n",ofile,dsize)
2067                 }
2068                 ofile = fname
2069                 fmt.Printf(Elapsed(Start)+"--In- L: open(%v,r)=%v %v (%v)\n",
2070                     fname,dsize,local,err)
2071             }
2072         }
2073         if 2 < len(argv) && argv[2] != "" {
2074             ofile = argv[2]
2075             //fmt.Printf("(%d)%v B.ofile=%v\n",len(argv),argv,ofile)
2076         }
2077         //fmt.Printf(Elapsed(Start)+"--I-- Rex out(%v)\n",ofile)
2078         fmt.Printf(Elapsed(Start)+"--In- PUT %v (%v)\n",dsize,bsize)
2079         req = fmt.Sprintf("PUT %v %v \r\n",dsize,ofile)
2080         if debug { fmt.Printf(Elapsed(Start)+"--In- C: %v",req) }
2081         fmt.Fprintf(serv,"%v",req)
2082         count,err = serv.Read(res)
2083         if debug { fmt.Printf(Elapsed(Start)+"--In- S: %v",string(res[0:count])) }
2084         fileRelay("SendPUT",local,remote,dsize,bsize)
2085     }else{
2086         req = fmt.Sprintf("%v\r\n",strings.Join(argv, " "))
2087         if debug { fmt.Printf(Elapsed(Start)+"--In- C: %v",req) }
2088         fmt.Fprintf(serv,"%v",req)
2089         //fmt.Printf("--In- sending RexRequest(%v)\n",len(req))
2090     }
2091     //fmt.Printf(Elapsed(Start)+"--In- waiting RexResponse...\n")
2092     count,err = serv.Read(res)
2093     ress := ""
2094     if count == 0 {
2095         ress = "(nil)\r\n"
2096     }else{
2097         ress = string(res[:count])
2098     }
2099     if err != nil {
2100         fmt.Printf(Elapsed(Start)+"--En- S: (%d,%v) %v",count,err,ress)
2101     }else{
2102         fmt.Printf(Elapsed(Start)+"--In- S: %v",ress)
2103     }
2104     serv.Close()
2105     //conn.Close()
2106 }
2107 var stat string
2108 var rcode int
2109 fmt.Sscanf(ress, "%d %s", &rcode, &stat)
2110 //fmt.Printf("--D-- Client: %v (%v)",rcode,stat)
2111 return rcode,ress
2112 }
2113 }
2114 // <a name="remote-sh">Remote Shell</a>
2115 // gcp file [...] { [host]:[port]:[dir] | dir } // -p | -no-p
2116 func (gsh*GshContext)FileCopy(argv []string){
2117     var host = ""
2118     var port = ""
2119     var upload = false
2120     var download = false
2121     var xargv = []string{"rex-gcp"}
2122     var srcv = []string{}
2123     var dstv = []string{}
2124     argv = argv[1:]

```

```

2125
2126 for _,v := range argv {
2127     /*
2128     if v[0] == '-' { // might be a pseudo file (generated date)
2129         continue
2130     }
2131     */
2132     obj := strings.Split(v,":")
2133     //fmt.Printf("%d %v %v\n",len(obj),v,obj)
2134     if 1 < len(obj) {
2135         host = obj[0]
2136         file := ""
2137         if 0 < len(host) {
2138             gsh.LastServer.host = host
2139         }else{
2140             host = gsh.LastServer.host
2141             port = gsh.LastServer.port
2142         }
2143         if 2 < len(obj) {
2144             port = obj[1]
2145             if 0 < len(port) {
2146                 gsh.LastServer.port = port
2147             }else{
2148                 port = gsh.LastServer.port
2149             }
2150             file = obj[2]
2151         }else{
2152             file = obj[1]
2153         }
2154         if len(srcv) == 0 {
2155             download = true
2156             srcv = append(srcv,file)
2157             continue
2158         }
2159         upload = true
2160         dstv = append(dstv,file)
2161         continue
2162     }
2163     /*
2164     idx := strings.Index(v,":")
2165     if 0 <= idx {
2166         remote = v[0:idx]
2167         if len(srcv) == 0 {
2168             download = true
2169             srcv = append(srcv,v[idx+1:])
2170             continue
2171         }
2172         upload = true
2173         dstv = append(dstv,v[idx+1:])
2174         continue
2175     }
2176     */
2177     if download {
2178         dstv = append(dstv,v)
2179     }else{
2180         srcv = append(srcv,v)
2181     }
2182 }
2183 hostport := "@" + host + ":" + port
2184 if upload {
2185     if host != "" { xargv = append(xargv,hostport) }
2186     xargv = append(xargv,"PUT")
2187     xargv = append(xargv,srcv[0:]...)
2188     xargv = append(xargv,dstv[0:]...)
2189     //fmt.Printf("--I-- FileCopy PUT gsh://%s/%v < %v // %v\n",hostport,dstv,srcv,xargv)
2190     fmt.Printf("--I-- FileCopy PUT gsh://%s/%v < %v\n",hostport,dstv,srcv)
2191     gsh.RexecClient(xargv)
2192 }else{
2193     if download {
2194         if host != "" { xargv = append(xargv,hostport) }
2195         xargv = append(xargv,"GET")
2196         xargv = append(xargv,srcv[0:]...)
2197         xargv = append(xargv,dstv[0:]...)
2198         //fmt.Printf("--I-- FileCopy GET gsh://%v/%v > %v // %v\n",hostport,srcv,dstv,xargv)
2199         fmt.Printf("--I-- FileCopy GET gsh://%v/%v > %v\n",hostport,srcv,dstv)
2200         gsh.RexecClient(xargv)
2201     }else{
2202     }
2203 }
2204 }
2205 // target
2206 func (gsh*GshContext)Trelpath(rloc string)(string){
2207     cwd, _ := os.Getwd()
2208     os.Chdir(gsh.RWD)
2209     os.Chdir(rloc)
2210     twd, _ := os.Getwd()
2211     os.Chdir(cwd)
2212 }
2213 tpath := twd + "/" + rloc
2214 return tpath
2215 }
2216 // join to rremote GShell - [user@]host[:port] or cd host[:port]:path
2217 func (gsh*GshContext)Rjoin(argv[]string){
2218     if len(argv) <= 1 {
2219         fmt.Printf("--I-- current server = %v\n",gsh.RSERV)
2220         return
2221     }
2222     serv := argv[1]
2223     servv := strings.Split(serv,":")
2224     if 1 <= len(servv) {
2225         if servv[0] == "lo" {
2226             servv[0] = "localhost"
2227         }
2228     }
2229     switch len(servv) {
2230     case 1:
2231         //if strings.Index(serv,":") < 0 {
2232             serv = servv[0] + ":" + fmt.Sprintf("%d",GSH_PORT)
2233         //}
2234     case 2: // host:port
2235         serv = strings.Join(servv,":")
2236     }
2237     xargv := []string{"rex-join","@"+serv,"HELO"}
2238     rcode,stat := gsh.RexecClient(xargv)
2239     if (rcode / 100) == 2 {
2240         fmt.Printf("--I-- OK Joined (%v) %v\n",rcode,stat)
2241         gsh.RSERV = serv
2242     }else{
2243         fmt.Printf("--I-- NG, could not joined (%v) %v\n",rcode,stat)
2244     }
2245 }
2246 func (gsh*GshContext)Rexec(argv[]string){
2247     if len(argv) <= 1 {
2248         fmt.Printf("--I-- rexec command [ | {file || {command} ]\n",gsh.RSERV)
2249         return

```

```

2250 }
2251
2252 /*
2253 nargv := gshScanArg(strings.Join(argv, " "),0)
2254 fmt.Printf("--D-- nargc=%d [%v]\n",len(nargv),nargv)
2255 if nargv[1][0] != '{' {
2256     nargv[1] = "{" + nargv[1] + "}"
2257     fmt.Printf("--D-- nargc=%d [%v]\n",len(nargv),nargv)
2258 }
2259 argv = nargv
2260 */
2261 nargv := []string{}
2262 nargv = append(nargv, "{"+strings.Join(argv[1:], " ")+"}")
2263 fmt.Printf("--D-- nargc=%d [%v]\n",len(nargv),nargv)
2264 argv = nargv
2265
2266 xargv := []string{"rex-exec", "@"+gsh.RSERV, "GET"}
2267 xargv = append(xargv,argv...)
2268 xargv = append(xargv,"dev/tty")
2269 rcode,stat := gsh.RexecClient(xargv)
2270 if (rcode / 100) == 2 {
2271     fmt.Printf("--I-- OK Rexec (%v) [%v]\n",rcode,stat)
2272 }else{
2273     fmt.Printf("--I-- NG Rexec (%v) [%v]\n",rcode,stat)
2274 }
2275 }
2276 func (gsh*GshContext)Rchdir(argv []string){
2277     if len(argv) <= 1 {
2278         return
2279     }
2280     cwd, _ := os.Getwd()
2281     os.Chdir(gsh.RWD)
2282     os.Chdir(argv[1])
2283     twd, _ := os.Getwd()
2284     gsh.RWD = twd
2285     fmt.Printf("--I-- JWD=[%v]\n",twd)
2286     os.Chdir(cwd)
2287 }
2288 func (gsh*GshContext)Rpwd(argv []string){
2289     fmt.Printf("[%v]\n",gsh.RWD)
2290 }
2291 func (gsh*GshContext)Rls(argv []string){
2292     cwd, _ := os.Getwd()
2293     os.Chdir(gsh.RWD)
2294     argv[0] = "-ls"
2295     gsh.xFind(argv)
2296     os.Chdir(cwd)
2297 }
2298 func (gsh*GshContext)Rput(argv []string){
2299     var local string = ""
2300     var remote string = ""
2301     if 1 < len(argv) {
2302         local = argv[1]
2303         remote = local // base name
2304     }
2305     if 2 < len(argv) {
2306         remote = argv[2]
2307     }
2308     fmt.Printf("--I-- jput from=[%v] to=[%v]\n",local,gsh.Trelpath(remote))
2309 }
2310 func (gsh*GshContext)Rget(argv []string){
2311     var remote string = ""
2312     var local string = ""
2313     if 1 < len(argv) {
2314         remote = argv[1]
2315         local = remote // base name
2316     }
2317     if 2 < len(argv) {
2318         local = argv[2]
2319     }
2320     fmt.Printf("--I-- jget from=[%v] to=[%v]\n",gsh.Trelpath(remote),local)
2321 }
2322
2323 // <a name="network">network</a>
2324 // -s, -si, -so // bi-directional, source, sync (maybe socket)
2325 func (gshCtx*GshContext)sconnect(inTCP bool, argv []string) {
2326     gshPA := gshCtx.gshPA
2327     if len(argv) < 2 {
2328         fmt.Printf("Usage: -s [host]:[port[.udp]]\n")
2329         return
2330     }
2331     remote := argv[1]
2332     if remote == ":" { remote = "0.0.0.0:9999" }
2333
2334     if inTCP { // TCP
2335         dport, err := net.ResolveTCPAddr("tcp",remote);
2336         if err != nil {
2337             fmt.Printf("Address error: %s (%s)\n",remote,err)
2338             return
2339         }
2340         conn, err := net.DialTCP("tcp",nil,dport)
2341         if err != nil {
2342             fmt.Printf("Connection error: %s (%s)\n",remote,err)
2343             return
2344         }
2345         file, _ := conn.File();
2346         fd := file.Fd()
2347         fmt.Printf("Socket: connected to %s, socket[%d]\n",remote,fd)
2348
2349         savfd := gshPA.Files[1]
2350         gshPA.Files[1] = fd;
2351         gshCtx.gshelly(argv[2:])
2352         gshPA.Files[1] = savfd
2353         file.Close()
2354         conn.Close()
2355     }else{
2356         //dport, err := net.ResolveUDPAddr("udp4",remote);
2357         dport, err := net.ResolveUDPAddr("udp",remote);
2358         if err != nil {
2359             fmt.Printf("Address error: %s (%s)\n",remote,err)
2360             return
2361         }
2362         //conn, err := net.DialUDP("udp4",nil,dport)
2363         conn, err := net.DialUDP("udp",nil,dport)
2364         if err != nil {
2365             fmt.Printf("Connection error: %s (%s)\n",remote,err)
2366             return
2367         }
2368         file, _ := conn.File();
2369         fd := file.Fd()
2370
2371         ar := conn.RemoteAddr()
2372         //al := conn.LocalAddr()
2373         fmt.Printf("Socket: connected to %s [%s], socket[%d]\n",
2374             remote,ar.String(),fd)

```

```

2375
2376     savfd := gshPA.Files[1]
2377     gshPA.Files[1] = fd;
2378     gshCtx.gshellyv(argv[2:])
2379     gshPA.Files[1] = savfd
2380     file.Close()
2381     conn.Close()
2382 }
2383 }
2384 func (gshCtx*GshContext)saccept(inTCP bool, argv []string) {
2385     gshPA := gshCtx.gshPA
2386     if len(argv) < 2 {
2387         fmt.Printf("Usage: -ac [host]:[port.udp]\n")
2388         return
2389     }
2390     local := argv[1]
2391     if local == "" { local = "0.0.0.0:9999" }
2392     if inTCP { // TCP
2393         port, err := net.ResolveTCPAddr("tcp", local);
2394         if err != nil {
2395             fmt.Printf("Address error: %s (%s)\n", local, err)
2396             return
2397         }
2398         //fmt.Printf("Listen at %s...\n", local);
2399         sconn, err := net.ListenTCP("tcp", port)
2400         if err != nil {
2401             fmt.Printf("Listen error: %s (%s)\n", local, err)
2402             return
2403         }
2404         //fmt.Printf("Accepting at %s...\n", local);
2405         acconn, err := sconn.AcceptTCP()
2406         if err != nil {
2407             fmt.Printf("Accept error: %s (%s)\n", local, err)
2408             return
2409         }
2410         file, _ := acconn.File()
2411         fd := file.Fd()
2412         fmt.Printf("Accepted TCP at %s [%d]\n", local, fd)
2413
2414         savfd := gshPA.Files[0]
2415         gshPA.Files[0] = fd;
2416         gshCtx.gshellyv(argv[2:])
2417         gshPA.Files[0] = savfd
2418
2419         sconn.Close();
2420         acconn.Close();
2421         file.Close();
2422     }else{
2423         //port, err := net.ResolveUDPAddr("udp4", local);
2424         port, err := net.ResolveUDPAddr("udp", local);
2425         if err != nil {
2426             fmt.Printf("Address error: %s (%s)\n", local, err)
2427             return
2428         }
2429         fmt.Printf("Listen UDP at %s...\n", local);
2430         //uconn, err := net.ListenUDP("udp4", port)
2431         uconn, err := net.ListenUDP("udp", port)
2432         if err != nil {
2433             fmt.Printf("Listen error: %s (%s)\n", local, err)
2434             return
2435         }
2436         file, _ := uconn.File()
2437         fd := file.Fd()
2438         ar := uconn.RemoteAddr()
2439         remote := ""
2440         if ar != nil { remote = ar.String() }
2441         if remote == "" { remote = "?" }
2442
2443         // not yet received
2444         //fmt.Printf("Accepted at %s [%d] <- %s\n", local, fd, "")
2445
2446         savfd := gshPA.Files[0]
2447         gshPA.Files[0] = fd;
2448         savenv := gshPA.Env
2449         gshPA.Env = append(savenv, "REMOTE_HOST="+remote)
2450         gshCtx.gshellyv(argv[2:])
2451         gshPA.Env = savenv
2452         gshPA.Files[0] = savfd
2453
2454         uconn.Close();
2455         file.Close();
2456     }
2457 }
2458
2459 // empty line command
2460 func (gshCtx*GshContext)xPwd(argv[]string){
2461     // execute context command, pwd + date
2462     // context notation, representation scheme, to be resumed at re-login
2463     cwd, _ := os.Getwd()
2464     switch {
2465     case isin("-a", argv):
2466         gshCtx.ShowChdirHistory(argv)
2467     case isin("-ls", argv):
2468         showFileInfo(cwd, argv)
2469     default:
2470         fmt.Printf("%s\n", cwd)
2471     case isin("-v", argv): // obsolete empty command
2472         t := time.Now()
2473         date := t.Format(time.UnixDate)
2474         exe, _ := os.Executable()
2475         host, _ := os.Hostname()
2476         fmt.Printf("PWD=\"%s\" \", cwd)
2477         fmt.Printf("HOST=\"%s\" \", host)
2478         fmt.Printf("DATE=\"%s\" \", date)
2479         fmt.Printf("TIME=\"%s\" \", t.String())
2480         fmt.Printf("PID=\"%d\" \", os.Getpid())
2481         fmt.Printf("EXE=\"%s\" \", exe)
2482         fmt.Printf("\n")
2483     }
2484 }
2485
2486 // <a name="history">History</a>
2487 // these should be browsed and edited by HTTP browser
2488 // show the time of command with -t and direcotry with -ls
2489 // openfile-history, sort by -a -m -c
2490 // sort by elapsed time by -t -s
2491 // search by "more" like interface
2492 // edit history
2493 // sort history, and wc or uniq
2494 // CPU and other resource consumptions
2495 // limit showing range (by time or so)
2496 // export / import history
2497 func (gshCtx *GshContext)xHistory(argv []string){
2498     atWorkDirX := -1
2499     if 1 < len(argv) && strBegins(argv[1], "e") {

```

```

2500     atWorkDirX,_ = strconv.Atoi(argv[1][1:])
2501 }
2502 //fmt.Printf("--D-- showHistory(&v)\n",argv)
2503 for i, v := range gshCtx.CommandHistory {
2504     // exclude commands not to be listed by default
2505     // internal commands may be suppressed by default
2506     if v.CmdLine == "" && !isin("-a",argv) {
2507         continue;
2508     }
2509     if 0 <= atWorkDirX {
2510         if v.WorkDirX != atWorkDirX {
2511             continue
2512         }
2513     }
2514     if !isin("-n",argv){ // like "fc"
2515         fmt.Printf("!%-2d ",i)
2516     }
2517     if isin("-v",argv){
2518         fmt.Println(v) // should be with it date
2519     }else{
2520         if isin("-l",argv) || isin("-l0",argv) {
2521             elps := v.EndAt.Sub(v.StartAt);
2522             start := v.StartAt.Format(time.Stamp)
2523             fmt.Printf("@%d ",v.WorkDirX)
2524             fmt.Printf("[%v] %11v/t ",start,elps)
2525         }
2526         if isin("-l",argv) && !isin("-l0",argv){
2527             fmt.Printf("%v",Rusagef("%t %u\t// %s",argv,v.Rusagev))
2528         }
2529         if isin("-at",argv) { // isin("-ls",argv){
2530             dhi := v.WorkDirX // workdir history index
2531             fmt.Printf("@%d %s\t",dhi,v.WorkDir)
2532             // show the FileInfo of the output command??
2533         }
2534         fmt.Printf("%s",v.CmdLine)
2535         fmt.Printf("\n")
2536     }
2537 }
2538 }
2539 // ln - history index
2540 func searchHistory(gshCtx GshContext, gline string) (string, bool, bool){
2541     if gline[0] == 'l' {
2542         hix, err := strconv.Atoi(gline[1:])
2543         if err != nil {
2544             fmt.Printf("--E-- (%s : range)\n",hix)
2545             return "", false, true
2546         }
2547         if hix < 0 || len(gshCtx.CommandHistory) <= hix {
2548             fmt.Printf("--E-- (%d : out of range)\n",hix)
2549             return "", false, true
2550         }
2551         return gshCtx.CommandHistory[hix].CmdLine, false, false
2552     }
2553     // search
2554     //for i, v := range gshCtx.CommandHistory {
2555     //}
2556     return gline, false, false
2557 }
2558 func (gsh*GshContext)cmdStringInHistory(hix int)(cmd string, ok bool){
2559     if 0 <= hix && hix < len(gsh.CommandHistory) {
2560         return gsh.CommandHistory[hix].CmdLine,true
2561     }
2562     return "",false
2563 }
2564 }
2565 // temporary adding to PATH environment
2566 // cd name -lib for LD_LIBRARY_PATH
2567 // chdir with directory history (date + full-path)
2568 // -s for sort option (by visit date or so)
2569 func (gsh*GshContext)ShowChdirHistory1(i int,v CChdirHistory, argv []string){
2570     fmt.Printf("!%-2d ",v.CmdIndex) // the first command at this WorkDir
2571     fmt.Printf("@%d ",i)
2572     fmt.Printf("[%v] ",v.MovedAt.Format(time.Stamp))
2573     showFileInfo(v.Dir,argv)
2574 }
2575 func (gsh*GshContext)ShowChdirHistory(argv []string){
2576     for i, v := range gsh.CChdirHistory {
2577         gsh.ShowChdirHistory1(i,v,argv)
2578     }
2579 }
2580 func skipOpts(argv[]string)(int){
2581     for i,v := range argv {
2582         if strBegins(v,"-") {
2583             }else{
2584                 return i
2585             }
2586     }
2587     return -1
2588 }
2589 func (gshCtx*GshContext)xChdir(argv []string){
2590     cdhist := gshCtx.CChdirHistory
2591     if isin("? ",argv) || isin("-t",argv) || isin("-a",argv) {
2592         gshCtx.ShowChdirHistory(argv)
2593         return
2594     }
2595     pwd, _ := os.Getwd()
2596     dir := ""
2597     if len(argv) <= 1 {
2598         dir = toFullPath("-")
2599     }else{
2600         i := skipOpts(argv[1:])
2601         if i < 0 {
2602             dir = toFullPath("-")
2603         }else{
2604             dir = argv[1+i]
2605         }
2606     }
2607     if strBegins(dir,"@") {
2608         if dir == "@0" { // obsolete
2609             dir = gshCtx.StartDir
2610         }else
2611         if dir == "@1" {
2612             index := len(cdhist) - 1
2613             if 0 < index { index -= 1 }
2614             dir = cdhist[index].Dir
2615         }else{
2616             index, err := strconv.Atoi(dir[1:])
2617             if err != nil {
2618                 fmt.Printf("--E-- xChdir(&v)\n",err)
2619                 dir = "?"
2620             }else
2621             if len(gshCtx.CChdirHistory) <= index {
2622                 fmt.Printf("--E-- xChdir(history range error)\n")
2623                 dir = "?"
2624             }else{

```

```

2625         dir = cdhist[index].Dir
2626     }
2627 }
2628 }
2629 if dir != "?" {
2630     err := os.Chdir(dir)
2631     if err != nil {
2632         fmt.Printf("--E-- xChdir(%s)(%v)\n", argv[1], err)
2633     } else {
2634         cwd, _ := os.Getwd()
2635         if cwd != pwd {
2636             hist1 := GChdirHistory { }
2637             hist1.Dir = cwd
2638             hist1.MovedAt = time.Now()
2639             hist1.CmdIndex = len(gshCtx.CommandHistory)+1
2640             gshCtx.ChdirHistory = append(cdhist, hist1)
2641             if !isin("-s", argv) {
2642                 //cwd, _ := os.Getwd()
2643                 //fmt.Printf("%s\n", cwd)
2644                 ix := len(gshCtx.ChdirHistory)-1
2645                 gshCtx.ShowChdirHistory1(ix, hist1, argv)
2646             }
2647         }
2648     }
2649 }
2650 if isin("-ls", argv) {
2651     cwd, _ := os.Getwd()
2652     showFileInfo(cwd, argv);
2653 }
2654 }
2655 func TimeValSub(tv1 *syscall.Timeval, tv2 *syscall.Timeval){
2656     *tv1 = syscall.NsecToTimeval(tv1.Nano() - tv2.Nano())
2657 }
2658 func RusageSubv(ru1, ru2 [2]syscall.Rusage) ([2]syscall.Rusage){
2659     TimeValSub(&ru1[0].Utime, &ru2[0].Utime)
2660     TimeValSub(&ru1[0].Stime, &ru2[0].Stime)
2661     TimeValSub(&ru1[1].Utime, &ru2[1].Utime)
2662     TimeValSub(&ru1[1].Stime, &ru2[1].Stime)
2663     return ru1
2664 }
2665 func TimeValAdd(tv1 syscall.Timeval, tv2 syscall.Timeval)(syscall.Timeval){
2666     tvs := syscall.NsecToTimeval(tv1.Nano() + tv2.Nano())
2667     return tvs
2668 }
2669 /*
2670 func RusageAddv(ru1, ru2 [2]syscall.Rusage) ([2]syscall.Rusage){
2671     TimeValAdd(ru1[0].Utime, ru2[0].Utime)
2672     TimeValAdd(ru1[0].Stime, ru2[0].Stime)
2673     TimeValAdd(ru1[1].Utime, ru2[1].Utime)
2674     TimeValAdd(ru1[1].Stime, ru2[1].Stime)
2675     return ru1
2676 }
2677 */
2678 // <a name="rusage">Resource Usage</a>
2679 func sRusagef(fmtspec string, argv []string, ru [2]syscall.Rusage)(string){
2680     // ru[0] self , ru[1] children
2681     ut := TimeValAdd(ru[0].Utime, ru[1].Utime)
2682     st := TimeValAdd(ru[0].Stime, ru[1].Stime)
2683     uu := (ut.Sec*1000000 + int64(ut.Usec)) * 1000
2684     su := (st.Sec*1000000 + int64(st.Usec)) * 1000
2685     tu := uu + su
2686     ret := fmt.Sprintf("%v/sum", abftime(tu))
2687     ret += fmt.Sprintf(" %v/usr", abftime(uu))
2688     ret += fmt.Sprintf(" %v/sys", abftime(su))
2689     return ret
2690 }
2691 }
2692 func Rusagef(fmtspec string, argv []string, ru [2]syscall.Rusage)(string){
2693     ut := TimeValAdd(ru[0].Utime, ru[1].Utime)
2694     st := TimeValAdd(ru[0].Stime, ru[1].Stime)
2695     fmt.Printf("%d.%06ds/u ", ut.Sec, ut.Usec) //ru[1].Utime.Sec, ru[1].Utime.Usec)
2696     fmt.Printf("%d.%06ds/s ", st.Sec, st.Usec) //ru[1].Stime.Sec, ru[1].Stime.Usec)
2697     return ""
2698 }
2699 func Getrusagev()([2]syscall.Rusage){
2700     var ruv = [2]syscall.Rusage{}
2701     syscall.Getrusage(syscall.RUSAGE_SELF, &ruv[0])
2702     syscall.Getrusage(syscall.RUSAGE_CHILDREN, &ruv[1])
2703     return ruv
2704 }
2705 func showRusage(what string, argv []string, ru *syscall.Rusage){
2706     fmt.Printf("%s: ", what);
2707     fmt.Printf("Uusr=%d.%06ds", ru.Utime.Sec, ru.Utime.Usec)
2708     fmt.Printf(" Sys=%d.%06ds", ru.Stime.Sec, ru.Stime.Usec)
2709     fmt.Printf(" Rss=%vB", ru.Maxrss)
2710     if isin("-l", argv) {
2711         fmt.Printf(" MinFlt=%v", ru.Minflt)
2712         fmt.Printf(" MajFlt=%v", ru.Majflt)
2713         fmt.Printf(" Ixrss=%vB", ru.Ixrss)
2714         fmt.Printf(" IdRSS=%vB", ru.Idrss)
2715         fmt.Printf(" Nswap=%vB", ru.Nswap)
2716         fmt.Printf(" Read=%v", ru.Inblock)
2717         fmt.Printf(" Write=%v", ru.Oublock)
2718     }
2719     fmt.Printf(" Snd=%v", ru.Msgsnd)
2720     fmt.Printf(" Rcv=%v", ru.Msgrcv)
2721     //if isin("-l", argv) {
2722         fmt.Printf(" Sig=%v", ru.Nsignals)
2723     //}
2724     fmt.Printf("\n");
2725 }
2726 func (gshCtx *GshContext)xTime(argv []string)(bool){
2727     if 2 <= len(argv){
2728         gshCtx.LastRusage = syscall.Rusage{}
2729         rusagev1 := Getrusagev()
2730         fin := gshCtx.gshellv(argv[1:])
2731         rusagev2 := Getrusagev()
2732         showRusage(argv[1], argv, &gshCtx.LastRusage)
2733         rusagev := RusageSubv(rusagev2, rusagev1)
2734         showRusage("self", argv, &rusagev[0])
2735         showRusage("chld", argv, &rusagev[1])
2736         return fin
2737     } else {
2738         rusage := syscall.Rusage { }
2739         syscall.Getrusage(syscall.RUSAGE_SELF, &rusage)
2740         showRusage("self", argv, &rusage)
2741         syscall.Getrusage(syscall.RUSAGE_CHILDREN, &rusage)
2742         showRusage("chld", argv, &rusage)
2743         return false
2744     }
2745 }
2746 func (gshCtx *GshContext)xJobs(argv []string){
2747     fmt.Printf("%d Jobs\n", len(gshCtx.BackGroundJobs))
2748     for ji, pid := range gshCtx.BackGroundJobs {
2749         //wstat := syscall.WaitStatus { }

```

```

2750     rusage := syscall.Rusage {}
2751     //wpid, err := syscall.Wait4(pid,&wstat,syscall.WNOHANG,&rusage);
2752     wpid, err := syscall.Wait4(pid,nil,syscall.WNOHANG,&rusage);
2753     if err != nil {
2754         fmt.Printf("--E-- %%d [%d] (%v)\n",ji,pid,err)
2755     }else{
2756         fmt.Printf("%%d[%d] (%d)\n",ji,pid,wpid)
2757         showRusage("chld",argv,&rusage)
2758     }
2759 }
2760 }
2761 func (gsh*GshContext)inBackground(argv[]string)(bool){
2762     if gsh.CmdTrace { fmt.Printf("--I-- inBackground(%v)\n",argv) }
2763     gsh.BackGround = true // set background option
2764     xfin := false
2765     xfin = gsh.gshelly(argv)
2766     gsh.BackGround = false
2767     return xfin
2768 }
2769 // -o file without command means just opening it and refer by #N
2770 // should be listed by "files" command
2771 func (gshCtx*GshContext)xOpen(argv[]string){
2772     var pv = []int{-1,-1}
2773     err := syscall.Pipe(pv)
2774     fmt.Printf("--I-- pipe()-[%#d,%#d] (%v)\n",pv[0],pv[1],err)
2775 }
2776 func (gshCtx*GshContext)fromPipe(argv[]string){
2777 }
2778 func (gshCtx*GshContext)xClose(argv[]string){
2779 }
2780 }
2781 // <a name="redirect">redirect</a>
2782 func (gshCtx*GshContext)redirect(argv[]string)(bool){
2783     if len(argv) < 2 {
2784         return false
2785     }
2786 }
2787 cmd := argv[0]
2788 fname := argv[1]
2789 var file *os.File = nil
2790
2791 fdix := 0
2792 mode := os.O_RDONLY
2793
2794 switch {
2795 case cmd == "-i" || cmd == "<":
2796     fdix = 0
2797     mode = os.O_RDONLY
2798 case cmd == "-o" || cmd == ">":
2799     fdix = 1
2800     mode = os.O_RDWR | os.O_CREATE
2801 case cmd == "-a" || cmd == ">>":
2802     fdix = 1
2803     mode = os.O_RDWR | os.O_CREATE | os.O_APPEND
2804 }
2805 if fname[0] == '#' {
2806     fd, err := strconv.Atoi(fname[1:])
2807     if err != nil {
2808         fmt.Printf("--E-- (%v)\n",err)
2809         return false
2810     }
2811     file = os.NewFile(uintptr(fd),"MaybePipe")
2812 }else{
2813     xfile, err := os.OpenFile(argv[1], mode, 0600)
2814     if err != nil {
2815         fmt.Printf("--E-- (%s)\n",err)
2816         return false
2817     }
2818     file = xfile
2819 }
2820 gshPA := gshCtx.gshPA
2821 savfd := gshPA.Files[fdix]
2822 gshPA.Files[fdix] = file.Fd()
2823 fmt.Printf("--I-- Opened [%d] %s\n",file.Fd(),argv[1])
2824 gshCtx.gshelly(argv[2:])
2825 gshPA.Files[fdix] = savfd
2826
2827 return false
2828 }
2829 }
2830 //fmt.Fprintf(res, "GShell Status: %q", html.EscapeString(req.URL.Path))
2831 func httpHandler(res http.ResponseWriter, req *http.Request){
2832     path := req.URL.Path
2833     fmt.Printf("--I-- Got HTTP Request(%s)\n",path)
2834     {
2835         gshCtxBuf, _ := setupGshContext()
2836         gshCtx := &gshCtxBuf
2837         fmt.Printf("--I-- %s\n",path[1:])
2838         gshCtx.tgshelly(path[1:])
2839     }
2840     fmt.Fprintf(res, "Hello(^-^)/\n%s\n",path)
2841 }
2842 func (gshCtx *GshContext) httpServer(argv []string){
2843     http.HandleFunc("/", httpHandler)
2844     accport := "localhost:9999"
2845     fmt.Printf("--I-- HTTP Server Start at [%s]\n",accport)
2846     http.ListenAndServe(accport,nil)
2847 }
2848 func (gshCtx *GshContext)xGo(argv[]string){
2849     go gshCtx.gshelly(argv[1:]);
2850 }
2851 func (gshCtx *GshContext) xPs(argv[]string)(){
2852 }
2853 }
2854 // <a name="plugin">Plugin</a>
2855 // plugin [-ls [names]] to list plugins
2856 // Reference: <a href="https://golang.org/src/plugin/">plugin</a> source code
2857 func (gshCtx *GshContext) whichPlugin(name string,argv[]string)(pi *PluginInfo){
2858     pi = nil
2859     for _,p := range gshCtx.PluginFuncs {
2860         if p.Name == name && pi == nil {
2861             pi = &p
2862         }
2863         if !isin("-s",argv){
2864             //fmt.Printf("%v %v ",i,p)
2865             if isin("-ls",argv){
2866                 showFileInfo(p.Path,argv)
2867             }else{
2868                 fmt.Printf("%s\n",p.Name)
2869             }
2870         }
2871     }
2872     return pi
2873 }
2874 func (gshCtx *GshContext) xPlugin(argv[]string) (error) {

```

```

2875 if len(argv) == 0 || argv[0] == "-ls" {
2876     gshCtx.whichPlugin("",argv)
2877     return nil
2878 }
2879 name := argv[0]
2880 pin := gshCtx.whichPlugin(name,[]string{"-s"})
2881 if pin != nil {
2882     os.Args = argv // should be recovered?
2883     pin.Addr.(func())()
2884     return nil
2885 }
2886 sofile := toFullPath(argv[0] + ".so") // or find it by which($PATH)
2887
2888 p, err := plugin.Open(sofile)
2889 if err != nil {
2890     fmt.Printf("--E-- plugin.Open(%s)(%v)\n",sofile,err)
2891     return err
2892 }
2893 fname := "Main"
2894 f, err := p.Lookup(fname)
2895 if( err != nil ){
2896     fmt.Printf("--E-- plugin.Lookup(%s)(%v)\n",fname,err)
2897     return err
2898 }
2899 pin := PluginInfo {p,f,name,sofile}
2900 gshCtx.PluginFuncs = append(gshCtx.PluginFuncs,pin)
2901 fmt.Printf("--I-- added (%d)\n",len(gshCtx.PluginFuncs))
2902
2903 //fmt.Printf("--I-- first call(%s:%s)%v\n",sofile,fname,argv)
2904 os.Args = argv
2905 f.(func())()
2906 return err
2907 }
2908 func (gshCtx*GshContext)Args(argv[]string){
2909     for i,v := range os.Args {
2910         fmt.Printf("[%v] %v\n",i,v)
2911     }
2912 }
2913 func (gshCtx *GshContext) showVersion(argv[]string){
2914     if isin("-l",argv) {
2915         fmt.Printf("%v/%v (%v)",NAME,VERSION,DATE);
2916     }else{
2917         fmt.Printf("%v",VERSION);
2918     }
2919     if isin("-a",argv) {
2920         fmt.Printf(" %s",AUTHOR)
2921     }
2922     if !isin("-n",argv) {
2923         fmt.Printf("\n")
2924     }
2925 }
2926
2927 // <a name="scanf">Scanf</a> // string decomposer
2928 // scanf [format] [input]
2929 func scanf(sstr string)(strv[]string){
2930     strv = strings.Split(sstr," ")
2931     return strv
2932 }
2933 func scanUntil(src,end string)(rstr string,leng int){
2934     idx := strings.Index(src,end)
2935     if 0 <= idx {
2936         rstr = src[0:idx]
2937         return rstr,idx+len(end)
2938     }
2939     return src,0
2940 }
2941
2942 // -bn -- display base-name part only // can be in some %fmt, for sed rewriting
2943 func (gsh*GshContext)printVal(fmts string, vstr string, optv[]string){
2944     //vint,err := strconv.Atoi(vstr)
2945     var ival int64 = 0
2946     n := 0
2947     err := error(nil)
2948     if strBegins(vstr," ") {
2949         vx, _ := strconv.Atoi(vstr[1:])
2950         if vx < len(gsh.iValues) {
2951             vstr = gsh.iValues[vx]
2952         }else{
2953         }
2954     }
2955     // should use Eval()
2956     if strBegins(vstr,"0x") {
2957         n,err = fmt.Sscanf(vstr[2:], "%x",&ival)
2958     }else{
2959         n,err = fmt.Sscanf(vstr,"%d",&ival)
2960     }//fmt.Printf("--D-- n=%d err=(%v) {%s}=%v\n",n,err,vstr, ival)
2961 }
2962 if n == 1 && err == nil {
2963     //fmt.Printf("--D-- formatn(%v) ival(%v)\n",fmts,ival)
2964     fmt.Printf("%"+fmts,ival)
2965 }else{
2966     if isin("-bn",optv){
2967         fmt.Printf("%"+fmts,filepath.Base(vstr))
2968     }else{
2969         fmt.Printf("%"+fmts,vstr)
2970     }
2971 }
2972 }
2973 func (gsh*GshContext)printfv(fmts,div string,argv[]string,optv[]string,list[]string){
2974     //fmt.Printf("%d",len(list))
2975     //curfmt := "v"
2976     outlen := 0
2977     curfmt := gsh.iFormat
2978
2979     if 0 < len(fmts) {
2980         for xi := 0; xi < len(fmts); xi++ {
2981             fch := fmts[xi]
2982             if fch == '%' {
2983                 if xi+1 < len(fmts) {
2984                     curfmt = string(fmts[xi+1])
2985                 }
2986                 gsh.iFormat = curfmt
2987                 xi += 1
2988                 if xi+1 < len(fmts) && fmts[xi+1] == '(' {
2989                     vals,leng := scanUntil(fmts[xi+2:],")")
2990                     //fmt.Printf("--D-- show fmt(%v) val(%v) next(%v)\n",curfmt,vals,leng)
2991                     gsh.printVal(curfmt,vals,optv)
2992                     xi += 2+leng-1
2993                 }
2994                 outlen += 1
2995             }
2996             continue
2997         }
2998     }
2999     if fch == '_' {
3000         hi,leng := scanInt(fmts[xi+1:])
3001         if 0 < leng {

```

```

3000         if hi < len(gsh.iValues) {
3001             gsh.printVal(curfmt, gsh.iValues[hi], optv)
3002             outlen += 1 // should be the real length
3003         }else{
3004             fmt.Printf("((out-range))")
3005         }
3006         xi += leng
3007         continue;
3008     }
3009     }
3010     fmt.Printf("%c", fch)
3011     outlen += 1
3012 }
3013 }else{
3014     //fmt.Printf("--D-- print (%s)\n")
3015     for i,v := range list {
3016         if 0 < i {
3017             fmt.Printf(div)
3018         }
3019         gsh.printVal(curfmt, v, optv)
3020         outlen += 1
3021     }
3022 }
3023 if 0 < outlen {
3024     fmt.Printf("\n")
3025 }
3026 }
3027 func (gsh*GshContext)Scanv(argv[]string){
3028     //fmt.Printf("--D-- Scnav(%v)\n", argv)
3029     if len(argv) == 1 {
3030         return
3031     }
3032     argv = argv[1:]
3033     fmts := ""
3034     if strBegins(argv[0], "-F") {
3035         fmts = argv[0]
3036         gsh.iDelimiter = fmts
3037         argv = argv[1:]
3038     }
3039     input := strings.Join(argv, " ")
3040     if fmts == "" { // simple decomposition
3041         v := scanv(input)
3042         gsh.iValues = v
3043         //fmt.Printf("%v\n", strings.Join(v, ","))
3044     }else{
3045         v := make([]string, 8)
3046         n, err := fmt.Sscanf(input, fmts, &v[0], &v[1], &v[2], &v[3])
3047         fmt.Printf("--D-- Sscanf ->(%v) n=%d err=(%v)\n", v, n, err)
3048         gsh.iValues = v
3049     }
3050 }
3051 func (gsh*GshContext)Printv(argv[]string){
3052     if false { //@@@U
3053         fmt.Printf("%v\n", strings.Join(argv[1:], " "))
3054         return
3055     }
3056     //fmt.Printf("--D-- Printv(%v)\n", argv)
3057     //fmt.Printf("%v\n", strings.Join(gsh.iValues, ","))
3058     div := gsh.iDelimiter
3059     fmts := ""
3060     argv = argv[1:]
3061     if 0 < len(argv) {
3062         if strBegins(argv[0], "-F") {
3063             div = argv[0][2:]
3064             argv = argv[1:]
3065         }
3066     }
3067 }
3068 optv := []string{}
3069 for _,v := range argv {
3070     if strBegins(v, "-"){
3071         optv = append(optv, v)
3072         argv = argv[1:]
3073     }else{
3074         break;
3075     }
3076 }
3077 if 0 < len(argv) {
3078     fmts = strings.Join(argv, " ")
3079 }
3080 gsh.printf(fmts, div, argv, optv, gsh.iValues)
3081 }
3082 func (gsh*GshContext)Basename(argv[]string){
3083     for i,v := range gsh.iValues {
3084         gsh.iValues[i] = filepath.Base(v)
3085     }
3086 }
3087 func (gsh*GshContext)Sortv(argv[]string){
3088     sv := gsh.iValues
3089     sort.Slice(sv, func(i,j int) bool {
3090         return sv[i] < sv[j]
3091     })
3092 }
3093 func (gsh*GshContext)Shiftv(argv[]string){
3094     vi := len(gsh.iValues)
3095     if 0 < vi {
3096         if isin("-r", argv) {
3097             top := gsh.iValues[0]
3098             gsh.iValues = append(gsh.iValues[1:], top)
3099         }else{
3100             gsh.iValues = gsh.iValues[1:]
3101         }
3102     }
3103 }
3104 }
3105 func (gsh*GshContext)Enq(argv[]string){
3106 }
3107 func (gsh*GshContext)Deq(argv[]string){
3108 }
3109 func (gsh*GshContext)Push(argv[]string){
3110     gsh.iValStack = append(gsh.iValStack, argv[1:])
3111     fmt.Printf("depth=%d\n", len(gsh.iValStack))
3112 }
3113 func (gsh*GshContext)Dump(argv[]string){
3114     for i,v := range gsh.iValStack {
3115         fmt.Printf("%d %v\n", i, v)
3116     }
3117 }
3118 func (gsh*GshContext)Pop(argv[]string){
3119     depth := len(gsh.iValStack)
3120     if 0 < depth {
3121         v := gsh.iValStack[depth-1]
3122         if isin("-cat", argv){
3123             gsh.iValues = append(gsh.iValues, v...)
3124         }else{

```

```

3125     gsh.iValues = v
3126 }
3127 gsh.iValStack = gsh.iValStack[0:depth-1]
3128 fmt.Printf("depth=%d %s\n", len(gsh.iValStack), gsh.iValues)
3129 }else{
3130     fmt.Printf("depth=%d\n", depth)
3131 }
3132 }
3133
3134 // <a name="interpreter">Command Interpreter</a>
3135 func (gshCtx*GshContext)gshellv(argv []string) (fin bool) {
3136     fin = false
3137
3138     if gshCtx.CmdTrace { fmt.Fprintf(os.Stderr, "--I-- gshellv(%d)\n", len(argv)) }
3139     if len(argv) <= 0 {
3140         return false
3141     }
3142     xargv := []string{}
3143     for ai := 0; ai < len(argv); ai++ {
3144         xargv = append(xargv, strsubst(gshCtx, argv[ai], false))
3145     }
3146     argv = xargv
3147     if false {
3148         for ai := 0; ai < len(argv); ai++ {
3149             fmt.Printf("[%d] %s [%d]T\n",
3150                 ai, argv[ai], len(argv[ai]), argv[ai])
3151         }
3152     }
3153     cmd := argv[0]
3154     if gshCtx.CmdTrace { fmt.Fprintf(os.Stderr, "--I-- gshellv(%d)\n", len(argv), argv) }
3155     switch { // https://tour.golang.org/flowcontrol/11
3156     case cmd == "":
3157         gshCtx.xPwd([]string{}); // empty command
3158     case cmd == "-x":
3159         gshCtx.CmdTrace = ! gshCtx.CmdTrace
3160     case cmd == "-xt":
3161         gshCtx.CmdTime = ! gshCtx.CmdTime
3162     case cmd == "-ot":
3163         gshCtx.sconnect(true, argv)
3164     case cmd == "-ou":
3165         gshCtx.sconnect(false, argv)
3166     case cmd == "-it":
3167         gshCtx.saccept(true, argv)
3168     case cmd == "-iu":
3169         gshCtx.saccept(false, argv)
3170     case cmd == "-i" || cmd == "<" || cmd == "-o" || cmd == ">" || cmd == "-a" || cmd == ">>" || cmd == "-s" || cmd == "><":
3171         gshCtx.redirect(argv)
3172     case cmd == "|":
3173         gshCtx.fromPipe(argv)
3174     case cmd == "args":
3175         gshCtx.Args(argv)
3176     case cmd == "bg" || cmd == "-bg":
3177         rfin := gshCtx.inBackground(argv[1:])
3178         return rfin
3179     case cmd == "-bn":
3180         gshCtx.Basename(argv)
3181     case cmd == "call":
3182         _ = gshCtx.excommand(false, argv[1:])
3183     case cmd == "cd" || cmd == "chdir":
3184         gshCtx.xChdir(argv);
3185     case cmd == "-cksum":
3186         gshCtx.xFind(argv)
3187     case cmd == "-sum":
3188         gshCtx.xFind(argv)
3189     case cmd == "-sumtest":
3190         str := ""
3191         if 1 < len(argv) { str = argv[1] }
3192         crc := strCRC32(str, uint64(len(str)))
3193         fprintf(stderr, "%v %v\n", crc, len(str))
3194     case cmd == "close":
3195         gshCtx.xClose(argv)
3196     case cmd == "gcp":
3197         gshCtx.FileCopy(argv)
3198     case cmd == "dec" || cmd == "decode":
3199         gshCtx.Dec(argv)
3200     case cmd == "#define":
3201     case cmd == "dic" || cmd == "d":
3202         xDic(argv)
3203     case cmd == "dump":
3204         gshCtx.Dump(argv)
3205     case cmd == "echo" || cmd == "e":
3206         echo(argv, true)
3207     case cmd == "enc" || cmd == "encode":
3208         gshCtx.Enc(argv)
3209     case cmd == "env":
3210         env(argv)
3211     case cmd == "eval":
3212         xEval(argv[1:], true)
3213     case cmd == "ev" || cmd == "events":
3214         dumpEvents(argv)
3215     case cmd == "exec":
3216         _ = gshCtx.excommand(true, argv[1:])
3217         // should not return here
3218     case cmd == "exit" || cmd == "quit":
3219         // write Result code EXIT to 3>
3220         return true
3221     case cmd == "fds":
3222         // dump the attributes of fds (of other process)
3223     case cmd == "-find" || cmd == "fin" || cmd == "ufind" || cmd == "uf":
3224         gshCtx.xFind(argv[1:])
3225     case cmd == "fu":
3226         gshCtx.xFind(argv[1:])
3227     case cmd == "fork":
3228         // mainly for a server
3229     case cmd == "-gen":
3230         gshCtx.gen(argv)
3231     case cmd == "-go":
3232         gshCtx.xGo(argv)
3233     case cmd == "-grep":
3234         gshCtx.xFind(argv)
3235     case cmd == "gdeg":
3236         gshCtx.Deg(argv)
3237     case cmd == "genq":
3238         gshCtx.Enq(argv)
3239     case cmd == "gpop":
3240         gshCtx.Pop(argv)
3241     case cmd == "gpush":
3242         gshCtx.Push(argv)
3243     case cmd == "history" || cmd == "hi": // hi should be alias
3244         gshCtx.xHistory(argv)
3245     case cmd == "jobs":
3246         gshCtx.xJobs(argv)
3247     case cmd == "lisp" || cmd == "nlsp":
3248         gshCtx.SplitLine(argv)
3249     case cmd == "-ls":

```

```

3250     gshCtx.xFind(argv)
3251 case cmd == "nop":
3252 // do nothing
3253 case cmd == "pipe":
3254     gshCtx.xOpen(argv)
3255 case cmd == "plug" || cmd == "plugin" || cmd == "pin":
3256     gshCtx.xPlugin(argv[1:])
3257 case cmd == "print" || cmd == "-pr":
3258 // output internal slice // also sprintf should be
3259     gshCtx.Printv(argv)
3260 case cmd == "ps":
3261     gshCtx.xPs(argv)
3262 case cmd == "ps:title":
3263 // to be gsh.title
3264 case cmd == "rexeod" || cmd == "rexd":
3265     gshCtx.RexecServer(argv)
3266 case cmd == "rexec" || cmd == "rex":
3267     gshCtx.RexecClient(argv)
3268 case cmd == "repeat" || cmd == "rep": // repeat cond command
3269     gshCtx.repeat(argv)
3270 case cmd == "replay":
3271     gshCtx.xReplay(argv)
3272 case cmd == "scan":
3273 // scan input (or so in fscanf) to internal slice (like Files or map)
3274     gshCtx.Scanv(argv)
3275 case cmd == "set":
3276 // set name ...
3277 case cmd == "serv":
3278     gshCtx.httpServer(argv)
3279 case cmd == "shift":
3280     gshCtx.Shiftv(argv)
3281 case cmd == "sleep":
3282     gshCtx.sleep(argv)
3283 case cmd == "-sort":
3284     gshCtx.Sortv(argv)
3285
3286 case cmd == "j" || cmd == "join":
3287     gshCtx.RJoin(argv)
3288 case cmd == "a" || cmd == "alpa":
3289     gshCtx.Rexec(argv)
3290 case cmd == "jcd" || cmd == "jchdir":
3291     gshCtx.Rchdir(argv)
3292 case cmd == "jget":
3293     gshCtx.Rget(argv)
3294 case cmd == "jls":
3295     gshCtx.Rls(argv)
3296 case cmd == "jput":
3297     gshCtx.Rput(argv)
3298 case cmd == "jpwd":
3299     gshCtx.Rpwd(argv)
3300
3301 case cmd == "time":
3302     fin = gshCtx.xTime(argv)
3303 case cmd == "ungets":
3304     if l < len(argv) {
3305         ungets(argv[1]+\n")
3306     }else{
3307     }
3308 case cmd == "pwd":
3309     gshCtx.xPwd(argv);
3310 case cmd == "ver" || cmd == "-ver" || cmd == "version":
3311     gshCtx.showVersion(argv)
3312 case cmd == "where":
3313 // data file or so?
3314 case cmd == "which":
3315     which("PATH",argv);
3316 default:
3317     if gshCtx.whichPlugin(cmd,[jstring{"-s"}]) != nil {
3318         gshCtx.xPlugin(argv)
3319     }else{
3320         notfound,_ := gshCtx.excommand(false,argv)
3321         if notfound {
3322             fmt.Printf("--E-- command not found (%v)\n",cmd)
3323         }
3324     }
3325 }
3326 return fin
3327 }
3328
3329 func (gsh*GshContext)gshell(gline string) (rfin bool) {
3330     argv := strings.Split(string(gline)," ")
3331     fin := gsh.gshellv(argv)
3332     return fin
3333 }
3334 func (gsh*GshContext)tgshell(gline string)(xfin bool){
3335     start := time.Now()
3336     fin := gsh.gshell(gline)
3337     end := time.Now()
3338     elps := end.Sub(start);
3339     if gsh.CmdTime {
3340         fmt.Printf("--T-- " + time.Now().Format(time.Stamp) + " (%d.%09ds)\n",
3341             elps/1000000000,elps%1000000000)
3342     }
3343     return fin
3344 }
3345 func Ttyid() (int) {
3346     fi, err := os.Stdin.Stat()
3347     if err != nil {
3348         return 0;
3349     }
3350     //fmt.Printf("Stdin: %v Dev=%d\n",
3351     // fi.Mode(),fi.Mode()&os.ModeDevice)
3352     if (fi.Mode() & os.ModeDevice) != 0 {
3353         stat := syscall.Stat_t{};
3354         err := syscall.Fstat(0,&stat)
3355         if err != nil {
3356             //fmt.Printf("--I-- Stdin: (%v)\n",err)
3357         }else{
3358             //fmt.Printf("--I-- Stdin: rdev=%d %d\n",
3359             // stat.Rdev&0xFF,stat.Rdev);
3360             //fmt.Printf("--I-- Stdin: tty%d\n",stat.Rdev&0xFF);
3361             return int(stat.Rdev & 0xFF)
3362         }
3363     }
3364     return 0
3365 }
3366 func (gshCtx *GshContext) ttyfile() string {
3367     //fmt.Printf("--I-- GSH_HOME=%s\n",gshCtx.GshHomeDir)
3368     ttyfile := gshCtx.GshHomeDir + "/" + "gsh-tty" +
3369         fmt.Sprintf("%02d",gshCtx.TerminalId)
3370     //strconv.Itoa(gshCtx.TerminalId)
3371     //fmt.Printf("--I-- ttyfile=%s\n",ttyfile)
3372     return ttyfile
3373 }
3374 func (gshCtx *GshContext) ttyline>(*os.File){

```

```

3375 file, err := os.OpenFile(gshCtx.ttyfile(), os.O_RDWR|os.O_CREATE|os.O_TRUNC, 0600)
3376 if err != nil {
3377     fmt.Printf("--F-- cannot open %s (%s)\n", gshCtx.ttyfile(), err)
3378     return file;
3379 }
3380 return file
3381 }
3382 func (gshCtx *GshContext)getline(hix int, skipping bool, prevline string) (string) {
3383     if( skipping ) {
3384         reader := bufio.NewReaderSize(os.Stdin, LINESIZE)
3385         line, _, _ := reader.ReadLine()
3386         return string(line)
3387     }else
3388     if true {
3389         return xgetline(hix, prevline, gshCtx)
3390     }
3391     /*
3392     else
3393     if( with_exgetline && gshCtx.GetLine != "" ){
3394         //var xhix int64 = int64(hix); // cast
3395         newenv := os.Environ()
3396         newenv = append(newenv, "GSH_LINENO="+strconv.FormatInt(int64(hix), 10) )
3397
3398         tty := gshCtx.ttyline()
3399         tty.WriteString(prevline)
3400         Pa := os.ProcAttr {
3401             "", // start dir
3402             newenv, //os.Environ(),
3403             []*os.File{os.Stdin, os.Stdout, os.Stderr, tty},
3404             nil,
3405         }
3406         //fmt.Printf("--I-- getline=%s // %s\n", gsh_getlinev[0], gshCtx.GetLine)
3407         proc, err := os.StartProcess(gsh_getlinev[0], []string{"getline", "getline"}, &Pa)
3408         if err != nil {
3409             fmt.Printf("--F-- getline process error (%v)\n", err)
3410             // for ; { }
3411             return "exit (getline program failed)"
3412         }
3413         //stat, err := proc.Wait()
3414         proc.Wait()
3415         buff := make([]byte, LINESIZE)
3416         count, err := tty.Read(buff)
3417         //_, err = tty.Read(buff)
3418         //fmt.Printf("--D-- getline (%d)\n", count)
3419         if err != nil {
3420             if ! (count == 0) { // && err.String() == "EOF" } {
3421                 fmt.Printf("--E-- getline error (%s)\n", err)
3422             }
3423         }else{
3424             //fmt.Printf("--I-- getline OK \"%s\"\n", buff)
3425         }
3426         tty.Close()
3427         gline := string(buff[0:count])
3428         return gline
3429     }else
3430     /*
3431     {
3432         // if isatty {
3433         fmt.Printf("!%d", hix)
3434         fmt.Print(PROMPT)
3435         // }
3436         reader := bufio.NewReaderSize(os.Stdin, LINESIZE)
3437         line, _, _ := reader.ReadLine()
3438         return string(line)
3439     }
3440 }
3441
3442 //== begin ===== getline
3443 /*
3444 * getline.c
3445 * 2020-0819 extracted from dog.c
3446 * getline.go
3447 * 2020-0822 ported to Go
3448 */
3449 /*
3450 package main // getline main
3451 import (
3452     "fmt" // <a href="https://golang.org/pkg/fmt/">fmt</a>
3453     "strings" // <a href="https://golang.org/pkg/strings/">strings</a>
3454     "os" // <a href="https://golang.org/pkg/os/">os</a>
3455     "syscall" // <a href="https://golang.org/pkg/syscall/">syscall</a>
3456     // "bytes" // <a href="https://golang.org/pkg/bytes/">bytes</a>
3457     // "os/exec" // <a href="https://golang.org/pkg/os/exec/">os/exec</a>
3458 )
3459 */
3460
3461 // C language compatibility functions
3462 var errno = 0
3463 var stdin *os.File = os.Stdin
3464 var stdout *os.File = os.Stdout
3465 var stderr *os.File = os.Stderr
3466 var EOF = -1
3467 var NULL = 0
3468 type FILE os.File
3469 type StrBuff []byte
3470 var NULL_FP *os.File = nil
3471 var NULLSP = 0
3472 //var LINESIZE = 1024
3473
3474 func system(cmdstr string)(int){
3475     PA := syscall.ProcAttr {
3476         "", // the starting directory
3477         os.Environ(),
3478         []uintptr{os.Stdin.Fd(), os.Stdout.Fd(), os.Stderr.Fd()},
3479         nil,
3480     }
3481     argv := strings.Split(cmdstr, " ")
3482     pid, err := syscall.ForkExec(argv[0], argv, &PA)
3483     if( err != nil ){
3484         fmt.Printf("--E-- syscall(%v) err(%v)\n", cmdstr, err)
3485     }
3486     syscall.Wait4(pid, nil, 0, nil)
3487
3488     /*
3489     argv := strings.Split(cmdstr, " ")
3490     fmt.Fprintf(os.Stderr, "--I-- system(%v)\n", argv)
3491     //cmd := exec.Command(argv[0], ...)
3492     cmd := exec.Command(argv[0], argv[1], argv[2])
3493     cmd.Stdin = strings.NewReader("output of system")
3494     var out bytes.Buffer
3495     cmd.Stdout = &out
3496     var serr bytes.Buffer
3497     cmd.Stderr = &serr
3498     err := cmd.Run()
3499     if err != nil {

```

```

3500     fmt.Fprintf(os.Stderr, "--E-- system(%v)err(%v)\n", argv, err)
3501     fmt.Printf("ERR:%s\n", serr.String())
3502 }else{
3503     fmt.Printf("%s", out.String())
3504 }
3505 */
3506 return 0
3507 }
3508 func atoi(str string)(ret int){
3509     ret, err := fmt.Sscanf(str, "%d", &ret)
3510     if err == nil {
3511         return ret
3512     }else{
3513         // should set errno
3514         return 0
3515     }
3516 }
3517 func getenv(name string)(string){
3518     val, got := os.LookupEnv(name)
3519     if got {
3520         return val
3521     }else{
3522         return "?"
3523     }
3524 }
3525 func strcpy(dst StrBuff, src string){
3526     var i int
3527     srcb := []byte(src)
3528     for i = 0; i < len(src) && srcb[i] != 0; i++ {
3529         dst[i] = srcb[i]
3530     }
3531     dst[i] = 0
3532 }
3533 func xstrcpy(dst StrBuff, src StrBuff){
3534     dst = src
3535 }
3536 func strcat(dst StrBuff, src StrBuff){
3537     dst = append(dst, src...)
3538 }
3539 func strdup(str StrBuff)(string){
3540     return string(str[0:strlen(str)])
3541 }
3542 func strlen(str string)(int){
3543     return len(str)
3544 }
3545 func strlen(StrBuff)(int){
3546     var i int
3547     for i = 0; i < len(str) && str[i] != 0; i++ {
3548     }
3549     return i
3550 }
3551 func sizeof(data StrBuff)(int){
3552     return len(data)
3553 }
3554 func isatty(fd int)(ret int){
3555     return 1
3556 }
3557 }
3558 func fopen(file string, mode string)(fp*os.File){
3559     if mode == "r" {
3560         fp, err := os.Open(file)
3561         if( err != nil ){
3562             fmt.Printf("--E-- fopen(%s,%s)=(%v)\n", file, mode, err)
3563             return NULL_FP;
3564         }
3565         return fp;
3566     }else{
3567         fp, err := os.OpenFile(file, os.O_RDWR|os.O_CREATE|os.O_TRUNC, 0600)
3568         if( err != nil ){
3569             return NULL_FP;
3570         }
3571         return fp;
3572     }
3573 }
3574 func fclose(fp*os.File){
3575     fp.Close()
3576 }
3577 func fflush(fp *os.File)(int){
3578     return 0
3579 }
3580 func fgetc(fp*os.File)(int){
3581     var buf [1]byte
3582     _, err := fp.Read(buf[0:1])
3583     if( err != nil ){
3584         return EOF;
3585     }else{
3586         return int(buf[0])
3587     }
3588 }
3589 func sfgets(str*string, size int, fp*os.File)(int){
3590     buf := make(StrBuff, size)
3591     var ch int
3592     var i int
3593     for i = 0; i < len(buf)-1; i++ {
3594         ch = fgetc(fp)
3595         //fprintf(stderr, "--fgets %d/%d %X\n", i, len(buf), ch)
3596         if( ch == EOF ){
3597             break;
3598         }
3599         buf[i] = byte(ch);
3600         if( ch == '\n' ){
3601             break;
3602         }
3603     }
3604     buf[i] = 0
3605     //fprintf(stderr, "--fgets %d/%d (%s)\n", i, len(buf), buf[0:i])
3606     return i
3607 }
3608 func fgets(buf StrBuff, size int, fp*os.File)(int){
3609     var ch int
3610     var i int
3611     for i = 0; i < len(buf)-1; i++ {
3612         ch = fgetc(fp)
3613         //fprintf(stderr, "--fgets %d/%d %X\n", i, len(buf), ch)
3614         if( ch == EOF ){
3615             break;
3616         }
3617         buf[i] = byte(ch);
3618         if( ch == '\n' ){
3619             break;
3620         }
3621     }
3622     buf[i] = 0
3623     //fprintf(stderr, "--fgets %d/%d (%s)\n", i, len(buf), buf[0:i])
3624     return i

```

```

3625 }
3626 func fputc(ch int , fp*os.File)(int){
3627     var buf [1]byte
3628     buf[0] = byte(ch)
3629     fp.Write(buf[0:1])
3630     return 0
3631 }
3632 func fputs(buf StrBuff, fp*os.File)(int){
3633     fp.Write(buf)
3634     return 0
3635 }
3636 func xfputss(str string, fp*os.File)(int){
3637     return fputs([]byte(str),fp)
3638 }
3639 func sscanf(str StrBuff,fmts string, params ...interface{})(int){
3640     fmt.Sscanf(string(str[0:strlen(str)]),fmts,params...)
3641     return 0
3642 }
3643 func fprintf(fp*os.File,fmts string, params ...interface{})(int){
3644     fmt.Fprintf(fp,fmts,params...)
3645     return 0
3646 }
3647
3648 // <a name="IME">Command Line IME</a>
3649 //----- MyIME
3650 var MyIMEVER = "MyIME/0.0.2";
3651 type RomKana struct {
3652     dic string // dictionaly ID
3653     pat string // input pattern
3654     out string // output pattern
3655     hit int64 // count of hit and used
3656 }
3657 var dicents = 0
3658 var romkana [1024]RomKana
3659 var Romkan []RomKana
3660
3661 func isinDic(str string)(int){
3662     for i,v := range Romkan {
3663         if v.pat == str {
3664             return i
3665         }
3666     }
3667     return -1
3668 }
3669 const (
3670     DIC_COM_LOAD = "im"
3671     DIC_COM_DUMP = "g"
3672     DIC_COM_LIST = "ls"
3673     DIC_COM_ENA = "en"
3674     DIC_COM_DIS = "di"
3675 )
3676 func helpDic(argv []string){
3677     out := stderr
3678     cmd := ""
3679     if 0 < len(argv) { cmd = argv[0] }
3680     fprintf(out,"--- %v Usage\n",cmd)
3681     fprintf(out,"... Commands\n")
3682     fprintf(out,"... %v %v [dicName] [dicURL] -- Import dictionary\n",cmd,DIC_COM_LOAD)
3683     fprintf(out,"... %v %v [pattern] -- Search in dictionary\n",cmd,DIC_COM_DUMP)
3684     fprintf(out,"... %v %v [dicName] -- List dictionaries\n",cmd,DIC_COM_LIST)
3685     fprintf(out,"... %v %v [dicName] -- Disable dictionaries\n",cmd,DIC_COM_DIS)
3686     fprintf(out,"... %v %v [dicName] -- Enable dictionaries\n",cmd,DIC_COM_ENA)
3687     fprintf(out,"... Keys .. %v\n","ESC can be used for '\\'.")
3688     fprintf(out,"... \\c -- Reverse the case of the last character\n",)
3689     fprintf(out,"... \\i -- Replace input with translated text\n",)
3690     fprintf(out,"... \\j -- On/Off translation mode\n",)
3691     fprintf(out,"... \\l -- Force Lower Case\n",)
3692     fprintf(out,"... \\u -- Force Upper Case (software CapsLock)\n",)
3693     fprintf(out,"... \\v -- Show translation actions\n",)
3694     fprintf(out,"... \\x -- Replace the last input character with it Hexa-Decimal\n",)
3695 }
3696 func xDic(argv[]string){
3697     if len(argv) <= 1 {
3698         helpDic(argv)
3699         return
3700     }
3701     argv = argv[1:]
3702     var debug = false
3703     var info = false
3704     var silent = false
3705     var dump = false
3706     var builtin = false
3707     cmd := argv[0]
3708     argv = argv[1:]
3709     opt := ""
3710     arg := ""
3711
3712     if 0 < len(argv) {
3713         arg1 := argv[0]
3714         if arg1[0] == '-' {
3715             switch arg1 {
3716                 default: fmt.Printf("--Ed-- Unknown option(%v)\n",arg1)
3717                     return
3718                 case "-b": builtin = true
3719                 case "-d": debug = true
3720                 case "-s": silent = true
3721                 case "-v": info = true
3722             }
3723             opt = arg1
3724             argv = argv[1:]
3725         }
3726     }
3727
3728     dicName := ""
3729     dicURL := ""
3730     if 0 < len(argv) {
3731         arg = argv[0]
3732         dicName = arg
3733         argv = argv[1:]
3734     }
3735     if 0 < len(argv) {
3736         dicURL = argv[0]
3737         argv = argv[1:]
3738     }
3739     if false {
3740         fprintf(stderr,"--Dd-- com(%v) opt(%v) arg(%v)\n",cmd,opt,arg)
3741     }
3742     if cmd == DIC_COM_LOAD {
3743         //dicType := ""
3744         dicBody := ""
3745         if !builtin && dicName != "" && dicURL == "" {
3746             f,err := os.Open(dicName)
3747             if err == nil {
3748                 dicURL = dicName
3749             }else{

```

```

3750         f,err = os.Open(dicName+".html")
3751         if err == nil {
3752             dicURL = dicName+".html"
3753         }else{
3754             f,err = os.Open("gshdic-"+dicName+".html")
3755             if err == nil {
3756                 dicURL = "gshdic-"+dicName+".html"
3757             }
3758         }
3759     }
3760     if err == nil {
3761         var buf = make([]byte,128*1024)
3762         count,err := f.Read(buf)
3763         f.Close()
3764         if info {
3765             fprintf(stderr,"--Id-- ReadDic(%v,%v)\n",count,err)
3766         }
3767         dicBody = string(buf[0:count])
3768     }
3769 }
3770 if dicBody == "" {
3771     switch arg {
3772     default:
3773         dicName = "WorldDic"
3774         dicURL = WorldDic
3775         if info {
3776             fprintf(stderr,"--Id-- default dictionary \"%v\"\n",
3777                 dicName);
3778         }
3779     case "wnn":
3780         dicName = "WnnDic"
3781         dicURL = WnnDic
3782     case "sumomo":
3783         dicName = "SumomoDic"
3784         dicURL = SumomoDic
3785     case "sijimi":
3786         dicName = "SijimiDic"
3787         dicURL = SijimiDic
3788     case "jkl":
3789         dicName = "JKLJaDic"
3790         dicURL = JA_JKLDic
3791     }
3792     if debug {
3793         fprintf(stderr,"--Id-- %v URL=%v\n\n",dicName,dicURL);
3794     }
3795     dicv := strings.Split(dicURL,",")
3796     if debug {
3797         fprintf(stderr,"--Id-- %v encoded data...\n",dicName)
3798         fprintf(stderr,"Type: %v\n",dicv[0])
3799         fprintf(stderr,"Body: %v\n",dicv[1])
3800         fprintf(stderr,"\n")
3801     }
3802     body,_ := base64.StdEncoding.DecodeString(dicv[1])
3803     dicBody = string(body)
3804 }
3805 if info {
3806     fmt.Printf("--Id-- %v %v\n",dicName,dicURL)
3807     fmt.Printf("%s\n",dicBody)
3808 }
3809 if debug {
3810     fprintf(stderr,"--Id-- dicName %v text...\n",dicName)
3811     fprintf(stderr,"%v\n",string(dicBody))
3812 }
3813 entv := strings.Split(dicBody,"\n");
3814 if info {
3815     fprintf(stderr,"--Id-- %v scan...\n",dicName);
3816 }
3817 var added int = 0
3818 var dup int = 0
3819 for i,v := range entv {
3820     var pat string
3821     var out string
3822     fmt.Sscanf(v,"%s %s",&pat,&out)
3823     if len(pat) <= 0 {
3824     }else{
3825         if 0 <= isinDic(pat) {
3826             dup += 1
3827             continue
3828         }
3829         romkana[dicents] = RomKana(dicName,pat,out,0)
3830         dicents += 1
3831         added += 1
3832         Romkan = append(Romkan,RomKana(dicName,pat,out,0))
3833         if debug {
3834             fmt.Printf("[%3v]:[%2v]%-8v [%2v]%-8v\n",
3835                 i,len(pat),pat,len(out),out)
3836         }
3837     }
3838 }
3839 if !silent {
3840     url := dicURL
3841     if strBegins(url,"data:") {
3842         url = "builtin"
3843     }
3844     fprintf(stderr,"--Id-- %v scan... %v added, %v dup. / %v total (%v)\n",
3845         dicName,added,dup,len(Romkan),url);
3846 }
3847 // should sort by pattern length for conplete match, for performance
3848 if debug {
3849     arg = "" // search pattern
3850     dump = true
3851 }
3852 }
3853 if cmd == DIC_COM_DUMP || dump {
3854     fprintf(stderr,"--Id-- %v dump... %v entries:\n",dicName,len(Romkan));
3855     var match = 0
3856     for i := 0; i < len(Romkan); i++ {
3857         dic := Romkan[i].dic
3858         pat := Romkan[i].pat
3859         out := Romkan[i].out
3860         if arg == "" || 0 <= strings.Index(pat,arg)||0 <= strings.Index(out,arg) {
3861             fmt.Printf("\\\\%v\\t%v [%2v]%-8v [%2v]%-8v\n",
3862                 i,dic,len(pat),pat,len(out),out)
3863             match += 1
3864         }
3865     }
3866     fprintf(stderr,"--Id-- %v matched %v / %v entries:\n",arg,match,len(Romkan));
3867 }
3868 }
3869 func loadDefaultDic(dic int){
3870     if( 0 < len(Romkan) ){
3871         return
3872     }
3873     //fprintf(stderr,"\r\n")
3874     xDic([]string{"dic",DIC_COM_LOAD});

```

```

3875
3876 var info = false
3877 if info {
3878     fprintf(stderr, "--Id-- Conguraturations!! WorldDic is now activated.\r\n")
3879     fprintf(stderr, "--Id-- enter \"dic\" command for help.\r\n")
3880 }
3881 }
3882 func readDic()(int){
3883     /*
3884     var rk *os.File;
3885     var dic = "MyIME-dic.txt";
3886     //rk = fopen("romkana.txt", "r");
3887     //rk = fopen("JK-JA-morse-dic.txt", "r");
3888     rk = fopen(dic, "r");
3889     if( rk == NULL_FP ){
3890         if( true ){
3891             fprintf(stderr, "--s-- Could not load %s\n", MyIMEVER, dic);
3892         }
3893         return -1;
3894     }
3895     if( true ){
3896         var di int;
3897         var line = make(StrBuff, 1024);
3898         var pat string
3899         var out string
3900         for di = 0; di < 1024; di++ {
3901             if( fgets(line, sizeof(line), rk) == NULLSP ){
3902                 break;
3903             }
3904             fmt.Sscanf(string(line[0:strlen(line)]), "%s %s", &pat, &out);
3905             //sscanf(line, "%s %[^\r\n]", &pat, &out);
3906             romkana[di].pat = pat;
3907             romkana[di].out = out;
3908             //fprintf(stderr, "--Dd- %-10s %s\n", pat, out)
3909         }
3910         dicents += di
3911         if( false ){
3912             fprintf(stderr, "--s-- loaded romkana.txt [%d]\n", MyIMEVER, di);
3913             for di = 0; di < dicents; di++ {
3914                 fprintf(stderr,
3915                     "%s %s\n", romkana[di].pat, romkana[di].out);
3916             }
3917         }
3918     }
3919     fclose(rk);
3920
3921     //romkana[dicents].pat = "//ddump"
3922     //romkana[dicents].pat = "//ddump" // dump the dic. and clean the command input
3923     */
3924     return 0;
3925 }
3926 func matchlen(stri string, pati string)(int){
3927     if strBegins(stri, pati) {
3928         return len(pati)
3929     }else{
3930         return 0
3931     }
3932 }
3933 func convs(src string)(string){
3934     var si int;
3935     var sx = len(src);
3936     var di int;
3937     var mi int;
3938     var dstb []byte
3939
3940     for si = 0; si < sx; { // search max. match from the position
3941         if strBegins(src[si:], "%x/") {
3942             // %x/integer/ // s/a/b/
3943             ix := strings.Index(src[si+3:], "/")
3944             if 0 < ix {
3945                 var iv int = 0
3946                 //fmt.Sscanf(src[si+3:si+3+ix], "%d", &iv)
3947                 fmt.Sscanf(src[si+3:si+3+ix], "%v", &iv)
3948                 sval := fmt.Sprintf("%x", iv)
3949                 bval := []byte(sval)
3950                 dstb = append(dstb, bval...)
3951                 si = si+3+ix+1
3952                 continue
3953             }
3954         }
3955         if strBegins(src[si:], "%d/") {
3956             // %d/integer/ // s/a/b/
3957             ix := strings.Index(src[si+3:], "/")
3958             if 0 < ix {
3959                 var iv int = 0
3960                 fmt.Sscanf(src[si+3:si+3+ix], "%v", &iv)
3961                 sval := fmt.Sprintf("%d", iv)
3962                 bval := []byte(sval)
3963                 dstb = append(dstb, bval...)
3964                 si = si+3+ix+1
3965                 continue
3966             }
3967         }
3968         if strBegins(src[si:], "%t") {
3969             now := time.Now()
3970             if true {
3971                 date := now.Format(time.Stamp)
3972                 dstb = append(dstb, []byte(date)...)
3973                 si = si+3
3974             }
3975             continue
3976         }
3977         var maxlen int = 0;
3978         var len int;
3979         mi = -1;
3980         for di = 0; di < dicents; di++ {
3981             len = matchlen(src[si:], romkana[di].pat);
3982             if( maxlen < len ){
3983                 maxlen = len;
3984                 mi = di;
3985             }
3986         }
3987         if( 0 < maxlen ){
3988             out := romkana[mi].out;
3989             dstb = append(dstb, []byte(out)...);
3990             si += maxlen;
3991         }else{
3992             dstb = append(dstb, src[si])
3993             si += 1;
3994         }
3995     }
3996     return string(dstb)
3997 }
3998 func trans(src string)(int){
3999     dst := convs(src);

```

```

4000     xfputss(dst,stderr);
4001     return 0;
4002 }
4003
4004 //----- LINEEDIT
4005 // "?" at the top of the line means searching history
4006
4007 // should be compatilbe with Telnet
4008 const (
4009     EV_MODE     = 255
4010     EV_IDLE     = 254
4011     EV_TIMEOUT  = 253
4012
4013     GO_UP       = 252 // k
4014     GO_DOWN    = 251 // j
4015     GO_RIGHT   = 250 // l
4016     GO_LEFT    = 249 // h
4017     DEL_RIGHT  = 248 // x
4018     GO_TOPL    = 'A'-0x40 // 0
4019     GO_ENDL    = 'E'-0x40 // $
4020
4021     GO_TOPW    = 239 // b
4022     GO_ENDW    = 238 // e
4023     GO_NEXTW   = 237 // w
4024
4025     GO_FORWCH  = 229 // f
4026     GO_PAIRCH  = 228 // %
4027
4028     GO_DEL     = 219 // d
4029
4030     HI_SRCH_FW = 209 // /
4031     HI_SRCH_BK = 208 // ?
4032     HI_SRCH_RFW = 207 // n
4033     HI_SRCH_RBK = 206 // N
4034 )
4035
4036 // should return number of octets ready to be read immediately
4037 //fprintf(stderr, "\n--Select(%v %v)\n",err,r.Bits[0])
4038
4039
4040 var EventRecvFd = -1 // file descriptor
4041 var EventSendFd = -1
4042 const EventFdOffset = 1000000
4043 const NormalFdOffset = 100
4044
4045 func putEvent(event int, evarg int){
4046     if true {
4047         if EventRecvFd < 0 {
4048             var pv = [int{-1,-1}]
4049             syscall.Pipe(pv)
4050             EventRecvFd = pv[0]
4051             EventSendFd = pv[1]
4052             //fmt.Printf("--De-- EventPipe created[%v,%v]\n",EventRecvFd,EventSendFd)
4053         }
4054     }else{
4055         if EventRecvFd < 0 {
4056             // the document differs from this spec
4057             // https://golang.org/src/syscall/syscall_unix.go?s=8096:8158#L1340
4058             sv,err := syscall.Socketpair(syscall.AF_UNIX,syscall.SOCK_STREAM,0)
4059             EventRecvFd = sv[0]
4060             EventSendFd = sv[1]
4061             if err != nil {
4062                 fmt.Printf("--De-- EventSock created[%v,%v](%v)\n",
4063                     EventRecvFd,EventSendFd,err)
4064             }
4065         }
4066     }
4067     var buf = []byte{ byte(event)}
4068     n,err := syscall.Write(EventSendFd,buf)
4069     if err != nil {
4070         fmt.Printf("--De-- putEvent[%v](%3v) (%v %v)\n",EventSendFd,event,n,err)
4071     }
4072 }
4073 func ungets(str string){
4074     for _,ch := range str {
4075         putEvent(int(ch),0)
4076     }
4077 }
4078 func (gsh*GshContext)xReplay(argv []string){
4079     hix := 0
4080     tempo := 1.0
4081     xtempo := 1.0
4082     repeat := 1
4083
4084     for _,a := range argv { // tempo
4085         if strBegins(a,"x") {
4086             fmt.Sscanf(a[1:], "%f",&xtempo)
4087             tempo = 1 / xtempo
4088             //fprintf(stderr, "--Dr-- tempo=[%v]%v\n",a[2:],tempo);
4089         }else
4090         if strBegins(a,"r") { // repeat
4091             fmt.Sscanf(a[1:], "%v",&repeat)
4092         }else
4093         if strBegins(a,"l") {
4094             fmt.Sscanf(a[1:], "%d",&hix)
4095         }else{
4096             fmt.Sscanf(a, "%d",&hix)
4097         }
4098     }
4099     if hix == 0 || len(argv) <= 1 {
4100         hix = len(gsh.CommandHistory)-1
4101     }
4102     fmt.Printf("--Ir-- Replay(!%v x%v r%v)\n",hix,xtempo,repeat)
4103     //dumpEvents(hix)
4104     //gsh.xScanReplay(hix,false,repeat,tempo,argv)
4105     go gsh.xScanReplay(hix,true,repeat,tempo,argv)
4106 }
4107
4108 // <a href="https://golang.org/pkg/syscall/#FdSet">syscall.Select</a>
4109 // 2020-0827 GShell-0.2.3
4110 /*
4111 func FpollIn1(fp *os.File,usec int)(uintptr){
4112     nfd := 1
4113
4114     rdv := syscall.FdSet {}
4115     fd1 := fp.Fd()
4116     bank1 := fd1/32
4117     mask1 := int32(1 << fd1)
4118     rdv.Bits[bank1] = mask1
4119
4120     fd2 := -1
4121     bank2 := -1
4122     var mask2 int32 = 0
4123
4124     if 0 <= EventRecvFd {

```

```

4125     fd2 = EventRecvFd
4126     nfd = fd2 + 1
4127     bank2 = fd2/32
4128     mask2 = int32(1 << fd2)
4129     rdv.Bits[bank2] |= mask2
4130     //fmt.Printf("--De-- EventPoll mask added [%d][%v][%v]\n",fd2,bank2,mask2)
4131 }
4132
4133 tout := syscall.NsecToTimeval(int64(usec*1000))
4134 //n,err := syscall.Select(nfd,&rdv,nil,nil,&tout) // spec. mismatch
4135 err := syscall.Select(nfd,&rdv,nil,nil,&tout)
4136 if err != nil {
4137     //fmt.Printf("--De-- select() err(%v)\n",err)
4138 }
4139 if err == nil {
4140     if 0 <= fd2 && (rdv.Bits[bank2] & mask2) != 0 {
4141         if false {
4142             fmt.Printf("--De-- got Event\n")
4143         }
4144         return uintptr(EventFdOffset + fd2)
4145     }else
4146     if (rdv.Bits[bank1] & mask1) != 0 {
4147         return uintptr(NormalFdOffset + fd1)
4148     }else{
4149         return 1
4150     }
4151 }else{
4152     return 0
4153 }
4154 }
4155 */
4156 func fgetcTimeout1(fp *os.File,usec int)(int){
4157     READ1:
4158     //readyFd := FpollIn1(fp,usec)
4159     readyFd := CFPollIn1(fp,usec)
4160     if readyFd < 100 {
4161         return EV_TIMEOUT
4162     }
4163
4164     var buf [1]byte
4165
4166     if EventFdOffset <= readyFd {
4167         fd := int(readyFd-EventFdOffset)
4168         _,err := syscall.Read(fd,buf[0:1])
4169         if( err != nil ){
4170             return EOF;
4171         }else{
4172             if buf[0] == EV_MODE {
4173                 recvEvent(fd)
4174                 goto READ1
4175             }
4176             return int(buf[0])
4177         }
4178     }
4179     _,err := fp.Read(buf[0:1])
4180     if( err != nil ){
4181         return EOF;
4182     }else{
4183         return int(buf[0])
4184     }
4185 }
4186 }
4187
4188 func visibleChar(ch int)(string){
4189     switch {
4190     case '!' <= ch && ch <= '-':
4191         return string(ch)
4192     }
4193     switch ch {
4194     case ' ': return "\\s"
4195     case '\n': return "\\n"
4196     case '\r': return "\\r"
4197     case '\t': return "\\t"
4198     }
4199     switch ch {
4200     case 0x00: return "NUL"
4201     case 0x07: return "BEL"
4202     case 0x08: return "BS"
4203     case 0x0E: return "SO"
4204     case 0x0F: return "SI"
4205     case 0x1B: return "ESC"
4206     case 0x7F: return "DEL"
4207     }
4208     switch ch {
4209     case EV_IDLE: return fmt.Sprintf("IDLE")
4210     case EV_MODE: return fmt.Sprintf("MODE")
4211     }
4212     return fmt.Sprintf("%X",ch)
4213 }
4214 func recvEvent(fd int){
4215     var buf = make([]byte,1)
4216     _,_ = syscall.Read(fd,buf[0:1])
4217     if( buf[0] != 0 ){
4218         romkanmode = true
4219     }else{
4220         romkanmode = false
4221     }
4222 }
4223 func (gsh*GshContext)xScanReplay(hix int,replay bool,repeat int,tempo float64,argv[string]){
4224     var Start time.Time
4225     var events = []Event{}
4226     for _,e := range Events {
4227         if hix == 0 || e.CmdIndex == hix {
4228             events = append(events,e)
4229         }
4230     }
4231     elen := len(events)
4232     if 0 < elen {
4233         if events[elen-1].event == EV_IDLE {
4234             events = events[0:elen-1]
4235         }
4236     }
4237     for r := 0; r < repeat; r++ {
4238         for i,e := range events {
4239             nano := e.when.Nanosecond()
4240             micro := nano / 1000
4241             if Start.Second() == 0 {
4242                 Start = time.Now()
4243             }
4244             diff := time.Now().Sub(Start)
4245             if replay {
4246                 if e.event != EV_IDLE {
4247                     putEvent(e.event,0)
4248                 }
4249                 if e.event == EV_MODE { // event with arg
4250                     putEvent(int(e.evarg),0)

```

```

4250     }
4251     }
4252     }else{
4253     fmt.Printf("%7.3fms %#-3v !%-3v [%v.%06d] %3v %02X %-4v %10.3fms\n",
4254     float64(diff)/1000000.0,
4255     i,
4256     e.CmdIndex,
4257     e.when.Format(time.Stamp),micro,
4258     e.event,e.event,visibleChar(e.event),
4259     float64(e.evarg)/1000000.0)
4260     }
4261     if e.event == EV_IDLE {
4262     d := time.Duration(float64(time.Duration(e.evarg)) * tempo)
4263     //nsleep(time.Duration(e.evarg))
4264     nsleep(d)
4265     }
4266     }
4267     }
4268 }
4269 func dumpEvents(arg[]string){
4270 hix := 0
4271 if l < len(arg) {
4272     fmt.Sscanf(arg[1],"%d",&hix)
4273 }
4274 for i,e := range Events {
4275     nano := e.when.Nanosecond()
4276     micro := nano / 1000
4277     //if e.event != EV_TIMEOUT {
4278     if hix == 0 || e.CmdIndex == hix {
4279         fmt.Printf("%#-3v !%-3v [%v.%06d] %3v %02X %-4v %10.3fms\n",i,
4280         e.CmdIndex,
4281         e.when.Format(time.Stamp),micro,
4282         e.event,e.event,visibleChar(e.event),float64(e.evarg)/1000000.0)
4283     }
4284     //}
4285 }
4286 }
4287 func fgetcTimeout(fp *os.File,usec int)(int){
4288     ch := fgetcTimeout1(fp,usec)
4289     if ch != EV_TIMEOUT {
4290         now := Time.Now()
4291         if 0 < len(Events) {
4292             last := Events[len(Events)-1]
4293             dura := int64(now.Sub(last.when))
4294             Events = append(Events,Event{last.when,EV_IDLE,dura,last.CmdIndex})
4295         }
4296         Events = append(Events,Event{time.Now(),ch,0,CmdIndex})
4297     }
4298     return ch
4299 }
4300 }
4301 var TtyMaxCol = 72 // to be obtained by ioctl?
4302 var EscTimeout = (100*1000)
4303 var (
4304     MODE_VicMode    bool    // vi compatible command mode
4305     MODE_ShowMode  bool
4306     romkanmode     bool    // shown translation mode, the mode to be retained
4307     MODE_Recursive bool    // recursive translation
4308     MODE_CapsLock  bool    // software CapsLock
4309     MODE_LowerLock bool    // force lower-case character lock
4310     MODE_Vinsert  int     // visible insert mode, should be like "I" icon in X Window
4311     MODE_ViTrace  bool    // output newline before translation
4312 )
4313 type IInput struct {
4314     lno      int
4315     lastlno int
4316     pch      []int // input queue
4317     prompt   string
4318     line     string
4319     right    string
4320     inJmode  bool
4321     pinJmode bool
4322     waitingMeta string // waiting meta character
4323     LastCmd   string
4324 }
4325 func (iin*IInput)Getc(timeoutUs int)(int){
4326     ch1 := EOF
4327     ch2 := EOF
4328     ch3 := EOF
4329     if( 0 < len(iin.pch) ){ // deQ
4330         ch1 = iin.pch[0]
4331         iin.pch = iin.pch[1:]
4332     }else{
4333         ch1 = fgetcTimeout(stdin,timeoutUs);
4334     }
4335     if( ch1 == 033 ){ // escape sequence
4336         ch2 = fgetcTimeout(stdin,EscTimeout);
4337         if( ch2 == EV_TIMEOUT ){
4338             }else{
4339                 ch3 = fgetcTimeout(stdin,EscTimeout);
4340                 if( ch3 == EV_TIMEOUT ){
4341                     iin.pch = append(iin.pch,ch2) // enQ
4342                 }else{
4343                     switch( ch2 ){
4344                     default:
4345                         iin.pch = append(iin.pch,ch2) // enQ
4346                         iin.pch = append(iin.pch,ch3) // enQ
4347                     case '[':
4348                         switch( ch3 ){
4349                         case 'A': ch1 = GO_UP; // ^
4350                         case 'B': ch1 = GO_DOWN; // v
4351                         case 'C': ch1 = GO_RIGHT; // >
4352                         case 'D': ch1 = GO_LEFT; // <
4353                         case '3':
4354                             ch4 := fgetcTimeout(stdin,EscTimeout);
4355                             if( ch4 == '-' ){
4356                                 //fprintf(stderr,"x[%02X %02X %02X %02X]\n",ch1,ch2,ch3,ch4);
4357                                 ch1 = DEL_RIGHT
4358                             }
4359                         }
4360                     case '\\':
4361                         //ch4 := fgetcTimeout(stdin,EscTimeout);
4362                         //fprintf(stderr,"y[%02X %02X %02X %02X]\n",ch1,ch2,ch3,ch4);
4363                         switch( ch3 ){
4364                         case '-': ch1 = DEL_RIGHT
4365                         }
4366                     }
4367                 }
4368             }
4369         }
4370     }
4371     return ch1
4372 }
4373 func (inn*IInput)clearline(){
4374     var i int
4375     fprintf(stderr,"\r");

```

```

4375 // should be ANSI ESC sequence
4376 for i = 0; i < TtyMaxCol; i++ { // to the max. position in this input action
4377     fputc(' ',os.Stderr);
4378 }
4379 fprintf(stderr, "\r");
4380 }
4381 func (iin*IInput)Redraw(){
4382     redraw(iin,iin.lno,iin.line,iin.right)
4383 }
4384 func redraw(iin *IInput,lno int,line string,right string){
4385     inMeta := false
4386     showMode := ""
4387     showMeta := "" // visible Meta mode on the cursor position
4388     showLino := fmt.Sprintf("%d!", lno)
4389     insertMark := "" // in visible insert mode
4390
4391     if MODE_VicMode {
4392     }else
4393     if 0 < len(iin.right) {
4394         InsertMark = " "
4395     }
4396
4397     if( 0 < len(iin.waitingMeta) ){
4398         inMeta = true
4399         if iin.waitingMeta[0] != 033 {
4400             showMeta = iin.waitingMeta
4401         }
4402     }
4403     if( romkanmode ){
4404         //romkanmark = " *";
4405     }else{
4406         //romkanmark = "";
4407     }
4408     if MODE_ShowMode {
4409         romkan := ""
4410         inmeta := ""
4411         inveri := ""
4412         if MODE_CapsLock {
4413             inmeta = "A"
4414         }
4415         if MODE_LowerLock {
4416             inmeta = "a"
4417         }
4418         if MODE_ViTrace {
4419             inveri = "v"
4420         }
4421         if MODE_VicMode {
4422             inveri = ":"
4423         }
4424         if romkanmode {
4425             romkan = "\343\201\202"
4426             if MODE_CapsLock {
4427                 inmeta = "R"
4428             }else{
4429                 inmeta = "r"
4430             }
4431         }
4432         if inMeta {
4433             inmeta = "\\ "
4434         }
4435         showMode = "["+romkan+inmeta+inveri+"];";
4436     }
4437     Pre := "\r" + showMode + showLino
4438     Output := ""
4439     Left := ""
4440     Right := ""
4441     if romkanmode {
4442         Left = convs(line)
4443         Right = InsertMark+convs(right)
4444     }else{
4445         Left = line
4446         Right = InsertMark+right
4447     }
4448     Output = Pre+Left
4449     if MODE_ViTrace {
4450         Output += iin.LastCmd
4451     }
4452     Output += showMeta+Right
4453     for len(Output) < TtyMaxCol { // to the max. position that may be dirty
4454         Output += " "
4455         // should be ANSI ESC sequence
4456         // not necessary just after newline
4457     }
4458     Output += Pre+Left+showMeta // to set the cursor to the current input position
4459     fprintf(stderr, "%s",Output)
4460
4461     if MODE_ViTrace {
4462         if 0 < len(iin.LastCmd) {
4463             iin.LastCmd = ""
4464             fprintf(stderr, "\r\n")
4465         }
4466     }
4467 }
4468 // <a href="https://golang.org/pkg/unicode/utf8/">utf8</a>
4469 func delHeadChar(str string)(rline string,head string){
4470     clen := utf8.DecodeRune([]byte(str))
4471     head = string(str[0:clen])
4472     return str[clen:],head
4473 }
4474 func delTailChar(str string)(rline string, last string){
4475     var i = 0
4476     var clen = 0
4477     for {
4478         _,siz := utf8.DecodeRune([]byte(str)[i:])
4479         if siz <= 0 { break }
4480         clen = siz
4481         i += siz
4482     }
4483     last = str[len(str)-clen:]
4484     return str[0:len(str)-clen],last
4485 }
4486
4487 // 3> for output and history
4488 // 4> for keylog?
4489 // <a name="getline">Command Line Editor</a>
4490 func xgetline(lno int, prevline string, gsh*GshContext)(string){
4491     var iin IInput
4492     iin.lastlno = lno
4493     iin.lno = lno
4494
4495     CmdIndex = len(gsh.CommandHistory)
4496     if( isatty(0) == 0 ){
4497         if( sfgets(&iin.line,LINESIZE,stdin) == NULL ){
4498             iin.line = "exit\n";
4499         }else{

```

```

4500     }
4501     return iin.line
4502 }
4503 if( true ){
4504     //var pts string;
4505     //pts = ptsname(0);
4506     //pts = ttyname(0);
4507     //fprintf(stderr,"--pts[0] = %s\n",pts?pts:"");
4508 }
4509 if( false ){
4510     fprintf(stderr,"! ");
4511     fflush(stderr);
4512     sfgets(&iin.line,LINESIZE,stdin);
4513     return iin.line
4514 }
4515 system("/bin/stty -echo -icanon");
4516 xline := iin.xgetline1(prevline,gsh)
4517 system("/bin/stty echo sane");
4518 return xline
4519 }
4520 func (iin*IInput)Translate(cmdch int){
4521     romkanmode = !romkanmode;
4522     if MODE_ViTrace {
4523         fprintf(stderr,"%v\r\n",string(cmdch));
4524     }else
4525     if( cmdch == 'J' ){
4526         fprintf(stderr,"J\r\n");
4527         iin.inJmode = true
4528     }
4529     iin.Redraw();
4530     loadDefaultDic(cmdch);
4531     iin.Redraw();
4532 }
4533 func (iin*IInput)Replace(cmdch int){
4534     iin.LastCmd = fmt.Sprintf("\\%v",string(cmdch))
4535     iin.Redraw();
4536     loadDefaultDic(cmdch);
4537     dst := convs(iin.line+iin.right);
4538     iin.line = dst
4539     iin.right = ""
4540     if( cmdch == 'I' ){
4541         fprintf(stderr,"I\r\n");
4542         iin.inJmode = true
4543     }
4544     iin.Redraw();
4545 }
4546 // aa 12 alal
4547 func isAlpha(ch rune)(bool){
4548     if 'a' <= ch && ch <= 'z' || 'A' <= ch && ch <= 'Z' {
4549         return true
4550     }
4551     return false
4552 }
4553 func isAlnum(ch rune)(bool){
4554     if 'a' <= ch && ch <= 'z' || 'A' <= ch && ch <= 'Z' {
4555         return true
4556     }
4557     if '0' <= ch && ch <= '9' {
4558         return true
4559     }
4560     return false
4561 }
4562
4563 // 0.2.8 2020-0901 created
4564 // <a href="https://golang.org/pkg/unicode/utf8/#DecodeRuneInString">DecodeRuneInString</a>
4565 func (iin*IInput)GotoTOPW(){
4566     str := iin.line
4567     i := len(str)
4568     if i <= 0 {
4569         return
4570     }
4571     //i0 := i
4572     i -= 1
4573     lastSize := 0
4574     var lastRune rune
4575     var found = -1
4576     for 0 < i { // skip preamble spaces
4577         lastRune,lastSize = utf8.DecodeRuneInString(str[i:])
4578         if !isAlnum(lastRune) { // character, type, or string to be searched
4579             i -= lastSize
4580             continue
4581         }
4582         break
4583     }
4584     for 0 < i {
4585         lastRune,lastSize = utf8.DecodeRuneInString(str[i:])
4586         if lastSize <= 0 { continue } // not the character top
4587         if !isAlnum(lastRune) { // character, type, or string to be searched
4588             found = i
4589             break
4590         }
4591         i -= lastSize
4592     }
4593     if found < 0 && i == 0 {
4594         found = 0
4595     }
4596     if 0 <= found {
4597         if isAlnum(lastRune) { // or non-kana character
4598             }else{ // when positioning to the top o the word
4599                 i += lastSize
4600             }
4601         iin.right = str[i:] + iin.right
4602         if 0 < i {
4603             iin.line = str[0:i]
4604         }else{
4605             iin.line = ""
4606         }
4607     }
4608     //fmt.Printf("\n(%d,%d,%d)[%s][%s]\n",i0,i,found,iin.line,iin.right)
4609     //fmt.Printf("") // set debug messae at the end of line
4610 }
4611 // 0.2.8 2020-0901 created
4612 func (iin*IInput)GotoENDW(){
4613     str := iin.right
4614     if len(str) <= 0 {
4615         return
4616     }
4617     lastSize := 0
4618     var lastRune rune
4619     var lastW = 0
4620     i := 0
4621     inWord := false
4622
4623     lastRune,lastSize = utf8.DecodeRuneInString(str[0:])
4624     if isAlnum(lastRune) {

```

```

4625     r,z := utf8.DecodeRuneInString(str[lastSize:])
4626     if 0 < z && isAlnum(r) {
4627         inWord = true
4628     }
4629 }
4630 for i < len(str) {
4631     lastRune,lastSize = utf8.DecodeRuneInString(str[i:])
4632     if lastSize <= 0 { break } // broken data?
4633     if !isAlnum(lastRune) { // character, type, or string to be searched
4634         break
4635     }
4636     lastW = i // the last alnum if in alnum word
4637     i += lastSize
4638 }
4639 if inWord {
4640     goto DISP
4641 }
4642 for i < len(str) {
4643     lastRune,lastSize = utf8.DecodeRuneInString(str[i:])
4644     if lastSize <= 0 { break } // broken data?
4645     if isAlnum(lastRune) { // character, type, or string to be searched
4646         break
4647     }
4648     i += lastSize
4649 }
4650 for i < len(str) {
4651     lastRune,lastSize = utf8.DecodeRuneInString(str[i:])
4652     if lastSize <= 0 { break } // broken data?
4653     if !isAlnum(lastRune) { // character, type, or string to be searched
4654         break
4655     }
4656     lastW = i
4657     i += lastSize
4658 }
4659 DISP:
4660 if 0 < lastW {
4661     iin.line = iin.line + str[0:lastW]
4662     iin.right = str[lastW:]
4663 }
4664 //fmt.Printf("\n(%d)[%s][%s]\n",i,iin.line,iin.right)
4665 //fmt.Printf("") // set debug messae at the end of line
4666 }
4667 // 0.2.8 2020-0901 created
4668 func (iin*Input)GotoNEXTW(){
4669     str := iin.right
4670     if len(str) <= 0 {
4671         return
4672     }
4673     lastSize := 0
4674     var lastRune rune
4675     var found = -1
4676     i := 1
4677     for i < len(str) {
4678         lastRune,lastSize = utf8.DecodeRuneInString(str[i:])
4679         if lastSize <= 0 { break } // broken data?
4680         if !isAlnum(lastRune) { // character, type, or string to be searched
4681             found = i
4682             break
4683         }
4684         i += lastSize
4685     }
4686     if 0 < found {
4687         if isAlnum(lastRune) { // or non-kana character
4688             }else{ // when positioning to the top o the word
4689                 found += lastSize
4690             }
4691             iin.line = iin.line + str[0:found]
4692             if 0 < found {
4693                 iin.right = str[found:]
4694             }else{
4695                 iin.right = ""
4696             }
4697         }
4698         //fmt.Printf("\n(%d)[%s][%s]\n",i,iin.line,iin.right)
4699         //fmt.Printf("") // set debug messae at the end of line
4700     }
4701 // 0.2.8 2020-0902 created
4702 func (iin*Input)GotoPAIRCH(){
4703     str := iin.right
4704     if len(str) <= 0 {
4705         return
4706     }
4707     lastRune,lastSize := utf8.DecodeRuneInString(str[0:])
4708     if lastSize <= 0 {
4709         return
4710     }
4711     forw := false
4712     back := false
4713     pair := ""
4714     switch string(lastRune){
4715     case "{": pair = "}"; forw = true
4716     case "}": pair = "{"; back = true
4717     case "(": pair = ")"; forw = true
4718     case ")": pair = "("; back = true
4719     case "[": pair = "]"; forw = true
4720     case "]": pair = "["; back = true
4721     case "<": pair = ">"; forw = true
4722     case ">": pair = "<"; back = true
4723     case "\\": pair = "\\"; // context depednet, can be f" or back-double quote
4724     case "'": pair = "'"; // context depednet, can be f' or back-quote
4725     // case Japanese Kakkos
4726     }
4727     if forw {
4728         iin.SearchForward(pair)
4729     }
4730     if back {
4731         iin.SearchBackward(pair)
4732     }
4733 }
4734 // 0.2.8 2020-0902 created
4735 func (iin*Input)SearchForward(pat string)(bool){
4736     right := iin.right
4737     found := -1
4738     i := 0
4739     if strBegins(right,pat) {
4740         r,z := utf8.DecodeRuneInString(right[i:])
4741         if 0 < z {
4742             i += z
4743         }
4744     }
4745     for i < len(right) {
4746         if strBegins(right[i:],pat) {
4747             found = i
4748             break
4749         }

```

```

4750     _,z := utf8.DecodeRuneInString(right[i:])
4751     if z <= 0 { break }
4752     i += z
4753 }
4754 if 0 <= found {
4755     iin.line = iin.line + right[0:found]
4756     iin.right = iin.right[found:]
4757     return true
4758 }else{
4759     return false
4760 }
4761 }
4762 // 0.2.8 2020-0902 created
4763 func (iin*IInput)SearchBackward(pat string)(bool){
4764     line := iin.line
4765     found := -1
4766     i := len(line)-1
4767     for i = i; 0 <= i; i-- {
4768         _,z := utf8.DecodeRuneInString(line[i:])
4769         if z <= 0 {
4770             continue
4771         }
4772         //fprintf(stderr,"-- %v\n",pat,line[i:])
4773         if strBegins(line[i:],pat) {
4774             found = i
4775             break
4776         }
4777     }
4778     //fprintf(stderr,"--%d\n",found)
4779     if 0 <= found {
4780         iin.right = line[found:] + iin.right
4781         iin.line = line[0:found]
4782         return true
4783     }else{
4784         return false
4785     }
4786 }
4787 // 0.2.8 2020-0902 created
4788 // search from top, end, or current position
4789 func (gsh*GshContext)SearchHistory(pat string, forw bool)(bool,string){
4790     if forw {
4791         for _,v := range gsh.CommandHistory {
4792             if 0 <= strings.Index(v.CmdLine,pat) {
4793                 //fprintf(stderr,"\n--De-- found !%v [%v]\n",i,pat,v.CmdLine)
4794                 return true,v.CmdLine
4795             }
4796         }
4797     }else{
4798         hlen := len(gsh.CommandHistory)
4799         for i := hlen-1; 0 < i; i-- {
4800             v := gsh.CommandHistory[i]
4801             if 0 <= strings.Index(v.CmdLine,pat) {
4802                 //fprintf(stderr,"\n--De-- found !%v [%v]\n",i,pat,v.CmdLine)
4803                 return true,v.CmdLine
4804             }
4805         }
4806     }
4807     //fprintf(stderr,"\n--De-- not-found(%v)\n",pat)
4808     return false,"(Not Found in History)"
4809 }
4810 // 0.2.8 2020-0902 created
4811 func (iin*IInput)GotoFORWSTR(pat string, gsh*GshContext){
4812     found := false
4813     if 0 < len(iin.right) {
4814         found = iin.SearchForward(pat)
4815     }
4816     if !found {
4817         found,line := gsh.SearchHistory(pat,true)
4818         if found {
4819             iin.line = line
4820             iin.right = ""
4821         }
4822     }
4823 }
4824 func (iin*IInput)GotoBACKSTR(pat string, gsh*GshContext){
4825     found := false
4826     if 0 < len(iin.line) {
4827         found = iin.SearchBackward(pat)
4828     }
4829     if !found {
4830         found,line := gsh.SearchHistory(pat,false)
4831         if found {
4832             iin.line = line
4833             iin.right = ""
4834         }
4835     }
4836 }
4837 func (iin*IInput)getString1(prompt string)(string){ // should be editable
4838     iin.clearline();
4839     fprintf(stderr,"\r%s",prompt)
4840     str := ""
4841     for {
4842         ch := iin.Getc(10*1000*1000)
4843         if ch == '\n' || ch == '\r' {
4844             break
4845         }
4846         sch := string(ch)
4847         str += sch
4848         fprintf(stderr,"%s",sch)
4849     }
4850     return str
4851 }
4852
4853 // search pattern must be an array and selectable with ^N/^P
4854 var SearchPat = ""
4855 var SearchForw = true
4856
4857 func (iin*IInput)xgetline1(prevline string, gsh*GshContext)(string){
4858     var ch int;
4859
4860     MODE_ShowMode = false
4861     MODE_VicMode = false
4862     iin.Redraw();
4863     first := true
4864
4865     for cix := 0; ; cix++ {
4866         iin.pinJmode = iin.inJmode
4867         iin.inJmode = false
4868
4869         ch = iin.Getc(1000*1000)
4870
4871         if ch != EV_TIMEOUT && first {
4872             first = false
4873             mode := 0
4874             if romkanmode {

```

```

4875     mode = 1
4876     }
4877     now := time.Now()
4878     Events = append(Events, Event{now, EV_MODE, int64(mode), CmdIndex})
4879 }
4880 if ch == 033 {
4881     MODE_ShowMode = true
4882     MODE_VicMode = !MODE_VicMode
4883     iin.Redraw();
4884     continue
4885 }
4886 if MODE_VicMode {
4887     switch ch {
4888     case '0': ch = GO_TOPL
4889     case '$': ch = GO_ENDL
4890     case 'b': ch = GO_TOPW
4891     case 'e': ch = GO_ENDW
4892     case 'w': ch = GO_NEXTW
4893     case '$': ch = GO_PAIRCH
4894
4895     case 'j': ch = GO_DOWN
4896     case 'k': ch = GO_UP
4897     case 'h': ch = GO_LEFT
4898     case 'l': ch = GO_RIGHT
4899     case 'x': ch = DEL_RIGHT
4900     case 'a': MODE_VicMode = !MODE_VicMode
4901             ch = GO_RIGHT
4902     case 'i': MODE_VicMode = !MODE_VicMode
4903             iin.Redraw();
4904             continue
4905     case '-':
4906         right, head := delHeadChar(iin.right)
4907         if len([]byte(head)) == 1 {
4908             ch = int(head[0])
4909             if( 'a' <= ch && ch <= 'z' ){
4910                 ch = ch + 'A'-'a'
4911             }else
4912                 if( 'A' <= ch && ch <= 'Z' ){
4913                     ch = ch + 'a'-'A'
4914                 }
4915             iin.right = string(ch) + right
4916         }
4917         iin.Redraw();
4918         continue
4919     case 'f': // GO_FORWCH
4920         iin.Redraw();
4921         ch = iin.Getc(3*1000*1000)
4922         if ch == EV_TIMEOUT {
4923             iin.Redraw();
4924             continue
4925         }
4926         SearchPat = string(ch)
4927         SearchForw = true
4928         iin.GotoFORWSTR(SearchPat, gsh)
4929         iin.Redraw();
4930         continue
4931     case '/':
4932         SearchPat = iin.getstring1("/") // should be editable
4933         SearchForw = true
4934         iin.GotoFORWSTR(SearchPat, gsh)
4935         iin.Redraw();
4936         continue
4937     case '?':
4938         SearchPat = iin.getstring1("?") // should be editable
4939         SearchForw = false
4940         iin.GotoBACKSTR(SearchPat, gsh)
4941         iin.Redraw();
4942         continue
4943     case 'n':
4944         if SearchForw {
4945             iin.GotoFORWSTR(SearchPat, gsh)
4946         }else{
4947             iin.GotoBACKSTR(SearchPat, gsh)
4948         }
4949         iin.Redraw();
4950         continue
4951     case 'N':
4952         if !SearchForw {
4953             iin.GotoFORWSTR(SearchPat, gsh)
4954         }else{
4955             iin.GotoBACKSTR(SearchPat, gsh)
4956         }
4957         iin.Redraw();
4958         continue
4959     }
4960 }
4961 switch ch {
4962 case GO_TOPW:
4963     iin.GotoTOPW()
4964     iin.Redraw();
4965     continue
4966 case GO_ENDW:
4967     iin.GotoENDW()
4968     iin.Redraw();
4969     continue
4970 case GO_NEXTW:
4971     // To next space then
4972     iin.GotoNEXTW()
4973     iin.Redraw();
4974     continue
4975 case GO_PAIRCH:
4976     iin.GotoPAIRCH()
4977     iin.Redraw();
4978     continue
4979 }
4980 //fprintf(stderr, "A[%02X]\n", ch);
4981 if( ch == '\\ ' || ch == 033 ){
4982     MODE_ShowMode = true
4983     metach := ch
4984     iin.waitingMeta = string(ch)
4985     iin.Redraw();
4986     // set cursor //fprintf(stderr, "???\b\b")
4987     ch = fgetcTimeout(stdin, 2000*1000)
4988     // reset cursor
4989     iin.waitingMeta = ""
4990
4991     cmdch := ch
4992     if( ch == EV_TIMEOUT ){
4993         if metach == 033 {
4994             continue
4995         }
4996     }
4997     ch = metach
4998 }else
4999 /*

```

```

5000     if( ch == 'm' || ch == 'M' ){
5001         mch := fgetcTimeout(stdin,1000*1000)
5002         if mch == 'r' {
5003             romkanmode = true
5004         }else{
5005             romkanmode = false
5006         }
5007         continue
5008     }else
5009     /*
5010     if( ch == 'k' || ch == 'K' ){
5011         MODE_Recursive = IMODE_Recursive
5012         iin.Translate(cmdch);
5013         continue
5014     }else
5015     if( ch == 'j' || ch == 'J' ){
5016         iin.Translate(cmdch);
5017         continue
5018     }else
5019     if( ch == 'i' || ch == 'I' ){
5020         iin.Replace(cmdch);
5021         continue
5022     }else
5023     if( ch == 'l' || ch == 'L' ){
5024         MODE_LowerLock = IMODE_LowerLock
5025         MODE_CapsLock = false
5026         if MODE_ViTrace {
5027             fprintf(stderr,"%v\r\n",string(cmdch));
5028         }
5029         iin.Redraw();
5030         continue
5031     }else
5032     if( ch == 'u' || ch == 'U' ){
5033         MODE_CapsLock = IMODE_CapsLock
5034         MODE_LowerLock = false
5035         if MODE_ViTrace {
5036             fprintf(stderr,"%v\r\n",string(cmdch));
5037         }
5038         iin.Redraw();
5039         continue
5040     }else
5041     if( ch == 'v' || ch == 'V' ){
5042         MODE_ViTrace = IMODE_ViTrace
5043         if MODE_ViTrace {
5044             fprintf(stderr,"%v\r\n",string(cmdch));
5045         }
5046         iin.Redraw();
5047         continue
5048     }else
5049     if( ch == 'c' || ch == 'C' ){
5050         if 0 < len(iin.line) {
5051             xline,tail := delTailChar(iin.line)
5052             if len([]byte(tail)) == 1 {
5053                 ch = int(tail[0])
5054                 if( 'a' <= ch && ch <= 'z' ){
5055                     ch = ch + 'A'-'a'
5056                 }else
5057                 if( 'A' <= ch && ch <= 'Z' ){
5058                     ch = ch + 'a'-'A'
5059                 }
5060                 iin.line = xline + string(ch)
5061             }
5062         }
5063         if MODE_ViTrace {
5064             fprintf(stderr,"%v\r\n",string(cmdch));
5065         }
5066         iin.Redraw();
5067         continue
5068     }else{
5069         iin.pch = append(iin.pch,ch) // push
5070         ch = '\\'
5071     }
5072 }
5073 switch( ch ){
5074 case 'P'-0x40: ch = GO_UP
5075 case 'N'-0x40: ch = GO_DOWN
5076 case 'B'-0x40: ch = GO_LEFT
5077 case 'F'-0x40: ch = GO_RIGHT
5078 }
5079 //fprintf(stderr,"B[02X]\n",ch);
5080 switch( ch ){
5081 case 0:
5082     continue;
5083
5084 case '\t':
5085     iin.Replace('j');
5086     continue
5087 case 'X'-0x40:
5088     iin.Replace('j');
5089     continue
5090
5091 case EV_TIMEOUT:
5092     iin.Redraw();
5093     if iin.pinJmode {
5094         fprintf(stderr,"\\J\r\n")
5095         iin.inJmode = true
5096     }
5097     continue
5098 case GO_UP:
5099     if iin.lno == 1 {
5100         continue
5101     }
5102     cmd,ok := gsh.cmdStringInHistory(iin.lno-1)
5103     if ok {
5104         iin.line = cmd
5105         iin.right = ""
5106         iin.lno = iin.lno - 1
5107     }
5108     iin.Redraw();
5109     continue
5110 case GO_DOWN:
5111     cmd,ok := gsh.cmdStringInHistory(iin.lno+1)
5112     if ok {
5113         iin.line = cmd
5114         iin.right = ""
5115         iin.lno = iin.lno + 1
5116     }else{
5117         iin.line = ""
5118         iin.right = ""
5119         if iin.lno == iin.lastlno-1 {
5120             iin.lno = iin.lno + 1
5121         }
5122     }
5123     iin.Redraw();
5124     continue

```

```

5125     case GO_LEFT:
5126         if 0 < len(iin.line) {
5127             xline,tail := delTailChar(iin.line)
5128             iin.line = xline
5129             iin.right = tail + iin.right
5130         }
5131         iin.Redraw();
5132         continue;
5133     case GO_RIGHT:
5134         if( 0 < len(iin.right) && iin.right[0] != 0 ){
5135             xright,head := delHeadChar(iin.right)
5136             iin.right = xright
5137             iin.line += head
5138         }
5139         iin.Redraw();
5140         continue;
5141     case EOF:
5142         goto EXIT;
5143     case 'R'-0x40: // replace
5144         dst := convs(iin.line+iin.right);
5145         iin.line = dst
5146         iin.right = ""
5147         iin.Redraw();
5148         continue;
5149     case 'T'-0x40: // just show the result
5150         readDic();
5151         romkanmode = !romkanmode;
5152         iin.Redraw();
5153         continue;
5154     case 'L'-0x40:
5155         iin.Redraw();
5156         continue;
5157     case 'K'-0x40:
5158         iin.right = ""
5159         iin.Redraw();
5160         continue;
5161     case 'E'-0x40:
5162         iin.line += iin.right
5163         iin.right = ""
5164         iin.Redraw();
5165         continue;
5166     case 'A'-0x40:
5167         iin.right = iin.line + iin.right
5168         iin.line = ""
5169         iin.Redraw();
5170         continue;
5171     case 'U'-0x40:
5172         iin.line = ""
5173         iin.right = ""
5174         iin.clearline();
5175         iin.Redraw();
5176         continue;
5177     case DEL_RIGHT:
5178         if( 0 < len(iin.right) ){
5179             iin.right,_ = delHeadChar(iin.right)
5180             iin.Redraw();
5181         }
5182         continue;
5183     case 0x7F: // BS? not DEL
5184         if( 0 < len(iin.line) ){
5185             iin.line,_ = delTailChar(iin.line)
5186             iin.Redraw();
5187         }
5188         /*
5189         else
5190             if( 0 < len(iin.right) ){
5191                 iin.right,_ = delHeadChar(iin.right)
5192                 iin.Redraw();
5193             }
5194         */
5195         continue;
5196     case 'H'-0x40:
5197         if( 0 < len(iin.line) ){
5198             iin.line,_ = delTailChar(iin.line)
5199             iin.Redraw();
5200         }
5201         continue;
5202     }
5203     if( ch == '\n' || ch == '\r' ){
5204         iin.line += iin.right;
5205         iin.right = ""
5206         iin.Redraw();
5207         fputc(ch,stderr);
5208         break;
5209     }
5210     if MODE_CapsLock {
5211         if 'a' <= ch && ch <= 'z' {
5212             ch = ch+'A'-'a'
5213         }
5214     }
5215     if MODE_LowerLock {
5216         if 'A' <= ch && ch <= 'Z' {
5217             ch = ch+'a'-'A'
5218         }
5219     }
5220     iin.line += string(ch);
5221     iin.Redraw();
5222 }
5223 EXIT:
5224     return iin.line + iin.right;
5225 }
5226
5227 func getline_main(){
5228     line := xgetline(0,"",nil)
5229     fprintf(stderr,"%s\n",line);
5230 /*
5231     dp = strpbrk(line,"\r\n");
5232     if( dp != NULL ){
5233         *dp = 0;
5234     }
5235
5236     if( 0 ){
5237         fprintf(stderr,"\n(%d)\n",int(strlen(line)));
5238     }
5239     if( lseek(3,0,0) == 0 ){
5240         if( romkanmode ){
5241             var buf [8*1024]byte;
5242             convs(line,buf);
5243             strcpy(line,buf);
5244         }
5245         write(3,line,strlen(line));
5246         ftruncate(3,lseek(3,0,SEEK_CUR));
5247         //fprintf(stderr,"outsize=%d\n",int(lseek(3,0,SEEK_END)));
5248         lseek(3,0,SEEK_SET);
5249         close(3);

```

```

5250 }else{
5251     fprintf(stderr, "\r\n gotline: ");
5252     trans(line);
5253     //printf("%s\n", line);
5254     printf("\n");
5255 }
5256 */
5257 }
5258 //== end ===== getline
5259
5260 //
5261 // $USERHOME/.gsh/
5262 // gsh-rc.txt, or gsh-configure.txt
5263 // gsh-history.txt
5264 // gsh-aliases.txt // should be conditional?
5265 //
5266 func (gshCtx *GshContext)gshSetupHomedir()(bool) {
5267     homedir, found := userHomeDir()
5268     if !found {
5269         fmt.Printf("--E-- You have no UserHomeDir\n")
5270         return true
5271     }
5272     gshhome := homedir + "/" + GSH_HOME
5273     _, err2 := os.Stat(gshhome)
5274     if err2 != nil {
5275         err3 := os.Mkdir(gshhome, 0700)
5276         if err3 != nil {
5277             fmt.Printf("--E-- Could not Create %s (%s)\n",
5278                 gshhome, err3)
5279             return true
5280         }
5281         fmt.Printf("--I-- Created %s\n", gshhome)
5282     }
5283     gshCtx.GshHomeDir = gshhome
5284     return false
5285 }
5286 func setupGshContext()(GshContext, bool){
5287     gshPA := syscall.ProcAttr {
5288         "", // the starting directory
5289         os.Environ(), // environ[]
5290         []uintptr{os.Stdin.Fd(), os.Stdout.Fd(), os.Stderr.Fd()},
5291         nil, // OS specific
5292     }
5293     cwd, _ := os.Getwd()
5294     gshCtx := GshContext {
5295         cwd, // StartDir
5296         "", // GetLine
5297         []GchdirHistory { {cwd, time.Now(), 0} }, // ChdirHistory
5298         gshPA,
5299         []GCommandHistory {}, // something for invokation?
5300         GCommandHistory {}, // CmdCurrent
5301         false,
5302         []int {},
5303         syscall.Rusage {},
5304         "", // GshHomeDir
5305         Ttyid(),
5306         false,
5307         false,
5308         []PluginInfo {},
5309         []string {},
5310         "",
5311         "v",
5312         ValueStack {},
5313         GServer{"", ""}, // LastServer
5314         "", // RSERV
5315         cwd, // RND
5316         CheckSum {},
5317     }
5318     err := gshCtx.gshSetupHomedir()
5319     return gshCtx, err
5320 }
5321 func (gsh *GshContext)gshellh(gline string)(bool){
5322     ghist := gsh.CmdCurrent
5323     ghist.WorkDir_ = os.Getwd()
5324     ghist.WorkDirX = len(gsh.ChdirHistory) - 1
5325     //fmt.Printf("--D--ChdirHistory(%#d)\n", len(gsh.ChdirHistory))
5326     ghist.StartAt = time.Now()
5327     rusagev1 := Getrusagev()
5328     gsh.CmdCurrent.FoundFile = []string{}
5329     fin := gsh.tgshellh(gline)
5330     rusagev2 := Getrusagev()
5331     ghist.Rusagev = RusageSubv(rusagev2, rusagev1)
5332     ghist.EndAt = time.Now()
5333     ghist.CmdLine = gline
5334     ghist.FoundFile = gsh.CmdCurrent.FoundFile
5335
5336     /* record it but not show in list by default
5337     if len(gline) == 0 {
5338         continue
5339     }
5340     if gline == "hi" || gline == "history" { // don't record it
5341         continue
5342     }
5343     */
5344     gsh.CommandHistory = append(gsh.CommandHistory, ghist)
5345     return fin
5346 }
5347 // <a name="main">Main loop</a>
5348 func script(gshCtxGiven *GshContext) (_ GshContext) {
5349     gshCtxBuf, err0 := setupGshContext()
5350     if err0 {
5351         return gshCtxBuf;
5352     }
5353     gshCtx := &gshCtxBuf
5354
5355     //fmt.Printf("--I-- GSH_HOME=%s\n", gshCtx.GshHomeDir)
5356     //resmap()
5357
5358     /*
5359     if false {
5360         gsh_getlinev, with_exgetline :=
5361             which("PATH", []string{"which", "gsh-getline", "-s"})
5362         if with_exgetline {
5363             gsh_getlinev[0] = toFullpath(gsh_getlinev[0])
5364             gshCtx.GetLine = toFullpath(gsh_getlinev[0])
5365         }else{
5366             fmt.Printf("--W-- No gsh-getline found. Using internal getline.\n");
5367         }
5368     }
5369     */
5370
5371     ghist0 := gshCtx.CmdCurrent // something special, or gshrc script, or permanent history
5372     gshCtx.CommandHistory = append(gshCtx.CommandHistory, ghist0)
5373
5374     prevline := ""

```

```

5375 skipping := false
5376 for hix := len(gshCtx.CommandHistory); {
5377     gline := gshCtx.Getline(hix, skipping, prevline)
5378     if skipping {
5379         if strings.Index(gline, "fi") == 0 {
5380             fmt.Printf("fi\n");
5381             skipping = false;
5382         }else{
5383             //fmt.Printf("%s\n", gline);
5384         }
5385         continue
5386     }
5387     if strings.Index(gline, "if") == 0 {
5388         //fmt.Printf("--D-- if start: %s\n", gline);
5389         skipping = true;
5390         continue
5391     }
5392     if false {
5393         os.Stdout.Write([]byte("gotline:"))
5394         os.Stdout.Write([]byte(gline))
5395         os.Stdout.Write([]byte("\n"))
5396     }
5397     gline = strsubst(gshCtx, gline, true)
5398     if false {
5399         fmt.Printf("fmt.Printf %%v - %v\n", gline)
5400         fmt.Printf("fmt.Printf %%s - %s\n", gline)
5401         fmt.Printf("fmt.Printf %%x - %x\n", gline)
5402         fmt.Printf("fmt.Printf %%U - %U\n", gline)
5403         fmt.Printf("Stoutout.Write -")
5404         os.Stdout.Write([]byte(gline))
5405         fmt.Printf("\n")
5406     }
5407     /*
5408     // should be cared in substitution ?
5409     if 0 < len(gline) && gline[0] == '!' {
5410         xgline, set, err := searchHistory(gshCtx, gline)
5411         if err {
5412             continue
5413         }
5414         if set {
5415             // set the line in command line editor
5416         }
5417         gline = xgline
5418     }
5419     */
5420     fin := gshCtx.gshellh(gline)
5421     if fin {
5422         break;
5423     }
5424     prevline = gline;
5425     hix++;
5426 }
5427 return *gshCtx
5428 }
5429 func main() {
5430     gshCtxBuf := GshContext{}
5431     gsh := *gshCtxBuf
5432     argv := os.Args
5433     if 1 < len(argv) {
5434         if isin("version", argv){
5435             gsh.showVersion(argv)
5436             return
5437         }
5438         comx := isinX("-c", argv)
5439         if 0 < comx {
5440             gshCtxBuf, err := setupGshContext()
5441             gsh := *gshCtxBuf
5442             if !err {
5443                 gsh.gshellv(argv[comx+1:])
5444             }
5445             return
5446         }
5447     }
5448     if 1 < len(argv) && isin("-s", argv) {
5449     }else{
5450         gsh.showVersion(append(argv, []string{"-l", "-a"}...))
5451     }
5452     script(nil)
5453     //gshCtx := script(nil)
5454     //gshell(gshCtx, "time")
5455 }
5456
5457 </div></details>
5458 <details id="gsh-todo"><summary>Considerations</summary><div class="gsh-src">
5459 // - inter gsh communication, possibly running in remote hosts -- to be remote shell
5460 // - merged histories of multiple parallel gsh sessions
5461 // - alias as a function or macro
5462 // - instant alias end environ export to the permanent > ~/.gsh/gsh-alias and gsh-environ
5463 // - retrieval PATH of files by its type
5464 // - gsh as an IME with completion using history and file names as dictionaies
5465 // - gsh a scheduler in precise time of within a millisecond
5466 // - all commands have its subucomand after "---" symbol
5467 // - filename expansion by "-find" command
5468 // - history of ext code and output of each commoand
5469 // - "script" output for each command by pty-tee or telnet-tee
5470 // - $BULLETIN command in PATH to show the priority
5471 // - "?" symbol in the command (not as in arguments) shows help request
5472 // - searching command with wild card like: which ssh-*
5473 // - longformat prompt after long idle time (should dismiss by BS)
5474 // - customizing by building plugin and dynamically linking it
5475 // - generating syntactic element like "if" by macro expansion (like CPP) >> alias
5476 // - "!" symbol should be used for negation, don't wast it just for job control
5477 // - don't put too long output to tty, record it into GSH_HOME/session-id/comand-id.log
5478 // - making canonical form of command at the start adding quotation or white spaces
5479 // - name(a,b,c) ... use "(" and ")" to show both delimiter and realm
5480 // - name? or name! might be useful
5481 // - htar format - packing directory contents into a single html file using data scheme
5482 // - filepath substitution should be done by each command, especially in case of builtins
5483 // - @N substitution for the history of working directory, and @spec for more generic ones
5484 // - @dir prefix to do the command at there, that means like (chdir @dir; command)
5485 // - GSH_PATH for plugins
5486 // - standard command output: list of data with name, size, resouce usage, modified time
5487 // - generic sort key option -nm name, -sz size, -ru rusage, -ts start-time, -tm mod-time
5488 // -wc word-count, grep match line count, ...
5489 // - standard command execution result: a list of string, -tm, -ts, -ru, -sz, ...
5490 // - -tailf-filename like tail -f filename, repeat close and open before read
5491 // - max. size and max. duration and timeout of (generated) data transfer
5492 // - auto. numbering, aliasing, IME completion of file name (especially rm of quieer name)
5493 // - IME "?" at the top of the command line means searching history
5494 // - IME %d/0x10000/ %x/ffff/
5495 // - IME ESC to go the edit mode like in vi, and use :command as :s/x/y/g to edit history
5496 // - gsh in WebAssembly
5497 // - gsh as a HTTP server of online-manual
5498 //---END--- (^-^)/ITS more</div></details>
5499

```

```

5500 //<span class="gsh-golang-data">
5501
5502 var WorldDic = //<span id="gsh-world-dic">
5503 "data:text/dic;base64,"+
5504 "Ly8yTXlJTUUVuMw4wLjEg6L6e5pu4ICgyMDiWLTAA4MThlKQpzZWthaSDkuJbnlYwKa28g44GT"+
5505 "Cm5u1OOCkwpuaSDjgasKY2hpIOOBoQp0aSDjgaEKaEGg44GvCnNlIOOBmwrYSDjgYsKaSDj"+
5506 "gYQK";
5507 //</span>
5508
5509 var WnnDic = //<span id="gsh-wnn-dic">
5510 "data:text/dic;base64,"+
5511 "Pgl1dEGy2hhcn1dD0iVVRGLTgiPgo8dGV4dGFyZWegY29scz04MCIybz3dzPTQwPgovL2Rp"+
5512 "Y3ZlcglHU2h2hbcx01NRVxzZG1jdg1vbmFyeVxzZm5yXHNxbm5ccy8vXHMvMDiWLTAA4MzAK"+
5513 "RlNOZkxscUdTaGVCyBArjgo/jg5/jg5cJ56eBCndhdGFzaGk56eBCndhdGFzaQnnp4EK44Gg"+
5514 "44G+44GICeWQjehJjOpuyWlhZQnlkI3liY0K44Gq44GL44GuCeS4remjJpuyWlhbm8J5LlI"+
5515 "6YeOCndhCeOCjwpp0YonjgZ8K2k2j44GKcNNoaQnjgZcKbm8J44GuCm5hceOBggptYQnjg4k"+
5516 "ZonjgYgKaCEJ44GvCm5hceOBggprYonjgYsKbm8J44GuCmRlCeOBwpzdQnjgZkZVxzCfVj"+
5517 "a88ZG1jCWRpYp1Y2hvcWVjg8KcmvWbCF5CX1lcGkheQpyZXBLYXQJcmVwZWF0CmR0CWhh"+
5518 "dGccyasnJvKl8sVklSVIOiVtVjWp0aW9uCXRPb24KJXQJXJXQJLY8gdG8g8gmUgY4gYWN0"+
5519 "aW9uCXJvdGV4dGFyZWeg+Cg==";
5520 //</span>
5521
5522 var SumomoDic = //<span id="gsh-sumomo-dic">
5523 "data:text/dic;base64,"+
5524 "Pgl1dEGy2hhcn1dD0iVVRGLTgiPgo8dGV4dGFyZWegY29scz04MCIybz3dzPTQwPgovL3Zl"+
5525 "cg1HU2h2hbcx01NRVxzZG1jdg1vbmFyeVxzZm5yXHNtdW1vbW9ccy8vXHMvMDiWLTAA4MzAK"+
5526 "c3UJ44GZCmlveCeOCgpubwnjga4KdQnjgYKY2hpCeOB0Qp0aQnjgKaEKdWNoQnlh0KdXRP"+
5527 "CeWghQpzd1vW8J44GZ44KC44KCCnNlBw9tb21vCeOBmeOCguOCguOCggptb21vCeahgwpT"+
5528 "b21vbW8J5qGD44KCCiwsCeAgQouLgnjgiIKPC90ZKh0YXJlYT4K";
5529 //</span>
5530
5531 var SijimiDic = //<span id="gsh-sijimi-dic">
5532 "data:text/dic;base64,"+
5533 "Pgl1dEGy2hhcn1dD0iVVRGLTgiPgo8dGV4dGFyZWegY29scz04MCIybz3dzPTQwPgovL3Zl"+
5534 "cg1HU2h2hbcx01NRVxzZG1jdg1vbmFyeVxzZm5yXHNtaGlqaW1pXHMvL1xzMjAyMjAwODMw"+
5535 "CnNpCeOB1wvpaGkJ44GXCMppCeOBmApraQnjgB8KbmEJ44GqCmpICeOBmoOCp4eXUJ44KF"+
5536 "CnUJ44GCm5pCeOBgqprbwnjgZMKYnUJ44G2Cm5uCeOCkpubwnjga4KY2hpCeOB0Qp0aQnj"+
5537 "gaEKa2EJ44GLCnThCeOCiQosLAnjgIERLlI44J44CCnHuYw5hCeS4gpp4anVlCeWNgOp4bmkJ"+
5538 "5LgCmTveAnlIeKa29xCeWaiwprb3gJ5VCLCm5hbmFgdXVuaXgJNzIKhbmFuYp1dW5peHgJ"+
5539 "7Yx77YsCm5hbmFgdXVuaVg37Yx77YsCuS4g+WNg56jHgJNzIKa29dW5uCeWai+Wihgp0"+
5540 "aWthcmFXCeOB0eOBi+OCiQp0aWthcmEJ5YqbcCmNoaWthcmEJ5YqbcJvvdGV4dGFyZWeg+Cg="
5541 //</span>
5542
5543 var JAJKIDic = //<span id="gsh-ja-jkl-dic">
5544 "data:text/dic;base64,"+
5545 "Ly92ZjJsCU15SUlFamRyY2ptb3JzZWpKQWpKS0w0mJyAyMGowODE5KSheLV4pL1NhdG94SVRT"+
5546 "CmtgampRbGtqa2tsa2psIOS4lueVjApqamtqamwJ44GCmtqbAnjgYKQa2tqbAnjgYKamtg"+
5547 "amwJ44GICmtqa2trbAnjgYoKa2pra2wJ44GLCmpamtrbAnjgYKQa2tFramwJ44GFCmpampr"+
5548 "CeOBKOpqampqBAnjgZMKamtqa2psCeOB1Opqamtqa2wJ44GXCMpamtqbAnjgZkKa2pqa2ps"+
5549 "CeOBmwpqampqBAnjgZKamtqa2psCeOBnwrA2prbAnjgaEKa2pqa2wJ44GKCMpamtqbAnjgYK"+
5550 "a2tqa2tsCeOBApramtsCeOBgppqa2prbAnjgasKa2tra2wJ44GScmpqa2psCeOBpOpra2pqa2ps"+
5551 "banjga4Kamtra2wJ44GvCmpqa2tqbAnjgIKamptra2wJ44GICmtqa2psCeOBuApra2tsCeOBuwpq"+
5552 "a2tqbAnjgKa2tqa2psCeOBvwpqBAnjgAKamtra2psCeOCOpqa2tqa2wJ44KCCmtqamwJ"+
5553 "44KECmptra2pqbAnjgYKampsCeOCiApra2tsCeOCiQpamtqa2psCeOCiQpqa2pqa2wJ44KLCmpq"+
5554 "amwJ44KCCmtqa2psCeOCjwpramtra2wJ44KQCMtqamtrbAnjgEKA2pqa2wJ44KCCmtqamwJ"+
5555 "44KCCmtqa2prbAnjgpMKa2pqa2psCeODvApra2wJ44KbCmtrampbAnjgpwKa2pramtqbAnj"+
5556 "gIEK";
5557 //</span>
5558
5559 //</span>
5560 /*
5561 <details id="references"><summary>References</summary><div class="gsh-src">
5562 <p>
5563 <a href="https://golang.org">The Go Programming Language</a>
5564 <iframe src="https://golang.org" width="100%" height="300"></iframe>
5565
5566 <a href="https://developer.mozilla.org/ja/docs/Web">MDN web docs</a>
5567 <a href="https://developer.mozilla.org/ja/docs/Web/HTML/Element">HTML</a>
5568 CSS:
5569 <a href="https://developer.mozilla.org/en-US/docs/Web/CSS/CSS_Selectors">Selectors</a>
5570 <a href="https://developer.mozilla.org/en-US/docs/Web/CSS/background-repeat">repeat</a>
5571 HTTP
5572 JavaScript:
5573 ...
5574 </p>
5575 </div></details>
5576 */
5577 /*
5578 <details id="html-src" onclick="frame_open();"><summary>Raw Source</summary><div>
5579 <!-- h2>The full of this HTML including the Go code is here.</h2 -->
5580 <details id="gsh-whole-view"><summary>Whole file</summary>
5581 <a name="whole-src-view"></a>
5582 <span id="src-frame"></span><!-- a window to show source code -->
5583 </details>
5584
5585 <details id="gsh-style-frame" onclick="fill_CSSView()"><summary>CSS part</summary>
5586 <a name="style-src-view"></a>
5587 <span id="gsh-style-view"></span>
5588 </details>
5589
5590 <details id="gsh-script-frame" onclick="fill_JavaScriptView()"><summary>JavaScript part</summary>
5591 <a name="script-src-view"></a>
5592 <span id="gsh-script-view"></span>
5593 </details>
5594
5595 <details id="gsh-data-frame" onclick="fill_DataView()"><summary>Builtin data part</summary>
5596 <a name="gsh-data-frame"></a>
5597 <span id="gsh-data-view"></span>
5598 </details>
5599
5600 </div></details>
5601 */
5602 /*
5603 */
5604 <div id="GshFooter"></div><!-- ----- END-OF-VISIBLE-PART ----- -->
5605
5606 <!--
5607 // 2020-0906 added,
5608 https://developer.mozilla.org/en-US/docs/Web/CSS/z-index
5609 https://developer.mozilla.org/en-US/docs/Web/CSS/position
5610 -->
5611 <span id="GshGrid">(^_^)/<small>{Hit j k l h}</small></span>
5612
5613 <span id="GStat"><br>
5614 </span>
5615 <span id="GMenu" onclick="GShellMenu(this)"></span>
5616 <span id="GTop"></span>
5617 <div id="GShellPlane" onclick="showGShellPlane();"></div>
5618 <div id="RawTextViewer"></div>
5619 <div id="RawTextViewerClose" onclick="hideRawTextViewer();"> CLOSE </div>
5620
5621 <style id="GshStyleDef">
5622 #LineNumbered table,tr,td {
5623 margin:0;
5624 padding:4px;

```

```
5625     spacing:0;
5626     border:12px;
5627 }
5628 textarea.LineNumber {
5629     font-size:12px;
5630     font-family:monospace,Courier New;
5631     color:#282;
5632     padding:4px;
5633     text-align:right;
5634 }
5635 textarea.LineNumbered {
5636     font-size:12px;
5637     font-family:monospace,Courier New;
5638     padding:4px;
5639     wrap:off;
5640 }
5641 #RawTextViewer{
5642     z-index:0;
5643     position:fixed; top:0px; left:0px;
5644     width:100%; height:50px;
5645     overflow:auto;
5646     color:#fff; background-color:rgba(128,128,256,0.4);
5647     font-size:12px;
5648     spellcheck:false;
5649 }
5650 #RawTextViewerClose{
5651     z-index:0;
5652     position:fixed; top:-100px; left:-100px;
5653     color:#fff; background-color:rgba(128,128,256,0.4);
5654     font-size:20px; font-family:Georgia;
5655     white-space:pre;
5656 }
5657 #GShellPlane{
5658     z-index:0;
5659     position:fixed; top:0px; left:0px;
5660     width:100%; height:50px;
5661     overflow:auto;
5662     color:#fff; background-color:rgba(128,128,256,0.6);
5663     font-size:12px;
5664 }
5665 #CTop{
5666     z-index:9;
5667     opacity:1.0;
5668     position:fixed; top:0px; left:0px;
5669     width:320px; height:20px;
5670     color:#fff; background-color:rgba(32,32,160,0.3);
5671     color:#fff; font-size:12px;
5672 }
5673 #GPos{
5674     z-index:12;
5675     position:fixed; top:0px; left:0px;
5676     opacity:1.0;
5677     width:640px; height:30px;
5678     color:#fff; background-color:rgba(0,0,0,0.4);
5679     color:#fff; font-size:12px;
5680 }
5681 #GMenu{
5682     z-index:2000;
5683     position:fixed; top:250px; left:0px;
5684     opacity:1.0;
5685     width:100px; height:100px;
5686     color:#fff;
5687     color:#fff; background-color:rgba(0,0,0,0.0);
5688     color:#fff; font-size:16px; font-family:Georgia;
5689     background-repeat:no-repeat;
5690 }
5691 #GStat{
5692     z-index:8;
5693     xopacity:0.0;
5694     position:fixed; top:20px; left:0px;
5695     xwidth:640px;
5696     width:100%; height:90px;
5697     color:#fff; background-color:rgba(0,0,128,0.10);
5698     font-size:20px; font-family:Georgia;
5699 }
5700 #GLog{
5701     z-index:10;
5702     position:fixed; top:50px; left:0px;
5703     opacity:1.0;
5704     width:640px; height:60px;
5705     color:#fff; background-color:rgba(0,0,128,0.10);
5706     font-size:12px;
5707 }
5708 #GshGrid {
5709     z-index:11;
5710     xopacity:0.0;
5711     position:fixed; top:0px; left:0px;
5712     width:320px; height:30px;
5713     color:#9f9; font-size:16px;
5714 }
5715 xbody {display:none;}
5716 .gsh-link{color:green;}
5717 #gsh {border-width:1;margin:0;padding:0;}
5718 #gsh {font-family:monospace,Courier New;color:#ddf;font-size:8px;}
5719 #gsh header{height:100px;}
5720 #gsh header{height:100px;background-image:url(GShell-Logo00.png);}
5721 #GshMenu{font-size:14pt;color:#f88;}
5722 #GshFooter{height:100px;background-size:80px;background-repeat:no-repeat;}
5723 #gsh note{color:#000;font-size:10pt;}
5724 #gsh h2{color:#24a;font-family:Georgia;font-size:18pt;}
5725 #gsh h3{color:#24a;font-family:Georgia;font-size:16pt;}
5726 #gsh details{color:#888;background-color:#fff;font-family:monospace;}
5727 #gsh summary{font-size:16pt;color:#fff;background-color:#8af;height:30px;}
5728 #gsh pre{font-size:11pt;color:#223;background-color:#faffff;}
5729 #gsh a{color:#24a;}
5730 #gsh a[name]{color:#24a;font-size:16pt;}
5731 #gsh .gsh-src{white-space:pre;font-family:monospace,Courier New;font-size:11pt;}
5732 #gsh .gsh-src{background-color:#faffff;color:#223;}
5733 #gsh-src-src{spellcheck:false}
5734 #src-frame-textarea{white-space:pre;font-family:monospace,Courier New;font-size:11pt;}
5735 #src-frame-textarea{background-color:#faffff;color:#223;}
5736 .gsh-code {white-space:pre;font-family:monospace !important;}
5737 .gsh-code {color:#088;font-size:11pt; background-color:#eef;}
5738 .gsh-golang-data {display:none;}
5739 #gsh-winId {color:#000;font-size:14pt;}
5740
5741 .gsh-document {font-size:11pt;background-color:#fff;font-family:Georgia;}
5742 .gsh-document {color:#000;background-color:#fff !important;}
5743 .gsh-document > h2{color:#000;background-color:#fff !important;}
5744 .gsh-document details{color:#000;background-color:#fff;font-family:Georgia;}
5745 .gsh-document p{max-width:550pt;color:#000;background-color:#fff;font-family:Georgia;}
5746 .gsh-document address{width:500pt;color:#000;background-color:#fff;font-family:Georgia;}
5747
5748 @media print {
5749     #gsh pre{font-size:11pt !important;}

```

```

5750 }
5751 </style>
5752
5753 <!--
5754 // Logo image should be drawn by JavaScript from a meta-font.
5755 // CSS seems not follow line-splitting URL
5756 -->
5757 <script id="gsh-data">
5758 //GSellLogo="QR-ITS-more.jp.png"
5759 GSellLogo="data:image/png;base64\
5760 TU0AKgAAAQAABAAEAAUAUAAAABAAAPgEBdAAUAAAABAAARgEQoAAWAAAABAAIAAIdpAAQAAAAB
5761 AAAATgAAAABAAIAAAAQAABAAEAAAABAAAPgEBdAAUAAAABAAARgEQoAAWAAAABAAIAAIdpAAQAAAAB
5762 AAAAQAABAAIAAAAQAABAAEAAAABAAAPgEBdAAUAAAABAAARgEQoAAWAAAABAAIAAIdpAAQAAAAB
5763 x+tTukZ3iCgG0/jY60sb9ngMzAvn7uG4+IbSTR7YnQxdOPCkGj2AnW1LD2MS1RkeUgPnoDCW
5764 4iUx7jrlYz50DGMf2VqIBESggCoLmMa+mu+vu//ZMD9U1dau6a2uByv91Krg3vdx6/q
5765 fnXvdX0tBA85IAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAES
5766 IAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAES
5767 IAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAES
5768 IAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAES
5769 IAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAES
5770 2eXs9H9+ftSkSDHxlc2qgdE7Yus+1gaalKfnY5YaokMHwEptdK4MQF25UeExlBlYsAYU15
5771 npDIKXEZClPiRmS3JUuaq98qcU6i+2Kk3StuOnY5reBGKJ7Qw7M0vKec2TogOIzwo1jHFS
5772 jBOVHCsthrb3UXEXEJ8Fu7DsdmFb2+uU4vWVFXbBpMeZU1AE/hcKoGAb66KGLNykH56PC
5773 HxH2VVBKORqkq3UeKi1YdaOFONJ560kI6w5BwomOQlyPzi0N9DLMxpFK/60p2P/Piyovf
5774 N8mfM+/nJWNGjnJw9KqOTOlVGSFt2p2Rl1gn3iJOvK7YsoVmwZEuVFPFRKYdOaK2LRSB0q
5775 zrWocCOG6EhvgRacj/dktj3g7dXxH4gKN6A80zpzYerqG6AraOZDqGfk79SKTRXHu/+e9FM
5776 L66s88pU/PnlN1TLQJKS73dPXSR20ur7iWpEc8QhbNnCyhU1LrYyOTQvYF5.1fvqBL7jX
5777 +cNHjBj5gJryD1JHy39o84D40H2QxT8HaPeFIOU+wlC+KnyhK5FGEvOWGgAExB83eXoLUH
5778 rIkb49gHEP52Vq014h89FUA6KJyYfbbQbnZLj4zFieSnDHCwVooeiVQob/5CY9F101UeOH
5779 +zGhU9n8SgQm0uWgurki9RpjBD4Y6uqQd5TU0W63zD3Mheey14V491sbdKyxkCh1CPFR
5780 UJ6toACF7F9Vf58NBEDHT0MBAE74Ent+eWrrW+Lz/Qtw60AdB7QUjUs/OA7COObNbcEUM
5781 ttCu/COG28f1pVKE1TPFV8JuRasEahhVxar1guoeeBPyfUdo4+0feBdyb8L4tz9XeSXPfMOC
5782 bgGsov0lgzG6W4JF392xnHhdC+MwF3JTjntZ2yCIYBJXNUT5KIKYk1sxXRdl68mceovW
5783 AJovy/VbacMeVgEP46/Z1njJt9x17VL53Z15MtVap1QGLNHW5pQdYqNYQT0122b8nCG2ZV
5784 qOoFJsdyV00AZdEayidv6FJ35CS4jXZk9hir7e27zmp3T8LJpkyIcJpV1HtK/DJFU4Jw1
5785 1ImhM5IR9fzgzRkx4W/C+HQSPB+krbIYrN3gEPTNahsHalD2x5S5SQPPvDgGqcm/8e
5786 7/zdoAptag/mLKJ7U0VGOxybTdx/Ex/Ptfa/iTr7Ku+cSoiCXUwroUx16wE9H+ccVJ1
5787 pd/CEU42AK2IUP1YTK1L/sjYj55PVHq728NzrvfuzvDODGy9GoopuuhNLNfCx48YHL2Gh
5788 f/8hpXvu/43Oq9xtq6Ytcv1XDC3femNDQn9nbE2le7wKE1bOK65icBu0Eghd3IaW8zdWkPUM
5789 hrauc6ZwKdzkUJZK8EUXMae71ZuqCu2nbi6veN1J19/P7eW+ioMaogF+NI31JLSf8dn9ipA
5790 WNW4Py9jXuPcdL/HXZnzgTsvsID2veWHWT9mu5rvVvZX9fS4v/LfmgdEPHGD1f2uCDL
5791 gJ1y2wOENPaZ3Eci+vdZYNCNJYrNyhYGAo8JRoJTAUmrIqOCJnrW5FPpTn+frTwh4S1Uv
5792 bV1WbfffLERF04qazRD7176/zBjKyLD5pBiZ5Wia4WQu7tikPBeCOpuhW1Kj0sgP8GNaoZuW1L
5793 1OzywDh9Zer2zODRQVQF15Qxh6owvJrKAAM46pVT+RxaJvJjw7vY9/+CeUBMk168/rPQn
5794 mCuifKzaldFN/y18ga5iWc3dkIkhsyvZUCYSVG/KhevHfWDRKAMMEd8EKx+HF12A9bt2d172
5795 2gNzOvzCDYmEtN7Y0oqDXWIKAIQI7COZqZeaADWnerqN5VXtCzsdGp2OtwgmJU7A+EH7
5796 yHbUgm1IX7f7k1DwaRyUfN42F1uxNddVEam166Yc9R26VbZaW2px8fmezh3EM+mgs01k
5797 d3/znBGE1XPGUWzXg1Yq5eW5/zBYG54aWogWkKfnwbptcewWT4FUBov32ge8DLzDTMAj
5798 aug7t/bmX+Yv/egJGKoTksy2d+gFbb9v0DvX5B12TOR+wfjy0p6UOXOYngR/3atv3B
5799 Fgeua6qv2747v8dFv3r1dBw34GSPg9i0DC955XWkh9kAaMmyJ6dkPzmtD3cnu7vtw5C
5800 H/YrGl7WxP/VvuRDuc+wsq54ymm+8zzXOgyRSPra4IKoGzli8b6ytagcEPm9v/m09eUATz
5801 Jow6VnPCmHz+3nNpHsCJYja6cRrRsMyrGkiwF415UouliLiLRW7EmLEx3z2+/GfW1LU2
5802 572b6Eazkfy0PctJi15QlnJyLdrFrUzP1/3pmkuG/YN9gaOgyWTF7neV1vx/6CHUgh1uh/
5803 F9Uov+qG703q7zFL8xQ+zW+8F6PWf7x5XhInlayWdz2XULm/4uLmPWoNA5UgedoL9
5804 ZFA6cgoxzhT66Q41NR5D0j9xuvlcy+rFbcuJVsnnkV0CefphUbICLRMv1+9KP4vngHgF62
5805 NCqM5iCsnkCfXed+mTfLBwuxdmbFozQt/19422537PcrzPQWhtH2zHraJO/yb0kdhpanZq
5806 KxWF66/8Cb5AChbzdphnUjeC6YFowlgzEmtqNCDekTixXVuc3LK4YvTJepuq5tgSFWKkdA
5807 ufu9MfWiG3sgntcx76+3EXOQWzVeqSpvrZcm2afYsVY461+O4KvyVgicCugG2r2poyPtVeJ
5808 0U1m2JwZEO+f6k0dFtNXfw2U9x70/bgZct5z0Poi0+vdpjDJcdxrd34U9XcHrloSktt3uq
5809 AcwtX009PFn+gWdS60DCFOdrAXneOCFRXWUSO93pZBN7VAe+qwr506/20ALXgngLbrC
5810 7HgRdVetHz2M1MYVvgm5zTPP5+7volRR/z10Ylx+8ohOzEb+CV/OTU5ic3NGfjks30MZ
5811 tFute1l+Yi4yFackjzqzYb6h1gJebwqLYxo09/j8k//WW3xS32qQPHv5AMpt1IDFN2Op6
5812 fz5yW4HfMxdT+Buy4Nvu73yEFBOK65icot+zjP+8qf4JkyiTngKTB/gz0TMKAC181jJPL
5813 A4PCxYnMPKotJREv84HpyOsws/BsqyT2RGZ6r210ga9sBhEp46hsE2ratmOJegrugBWB2Pw
5814 NYD1B4OSTMbmcds2E/GG2ZvrF7UeJsqm/7A7guEH6ky19q3fp0QvGxt4dz+Ueg+Lmy5V
5815 bjjY+0+b5Lsgp5Nz6nwbFhUdaYgemZy4ap1z5d1bbyA3NQTc4F3RKYFOTKaUP9Xry0LWU8
5816 sDMC/H29v0GTmV1C+izhTua27rgAebkb4+8H3P553q0oyu/WHj21ZWbd72XLUv4fa1qmQSV
5817 2GML+6kmhorvaWqnel1yZ/g1LX+IBnCN2P07F9Y5XQEn/qua+Hr3URAgJLMLR3G3fPEtP
5818 m645oyCzCzX9nQ2JAggBymXSL9vzQsgBfxUBjHpbXbz+m+VkuERBRiotE/Bw8ogf/LiZHy
5819 197Cnsb681T7DgnQRE1EVT29eWTS5JF1F5z0v1YfTLvqUT0b62etccBR01Hs68S8YqS
5820 202UdegmwT757ng7dKrV19zLztoMPBK73naAYrdzfm+5DZsymDymaHnClkvPOVHGSFRqE
5821 wC76Rw09Dkx5MU9vQXMaX+ePguLw8/dvG6ULLPvsPbpXspOniQwagElm9ggNxc2OEO1vj5
5822 7tBBBjAdhMkdV0/q/irW1b44t5cNKQKwq7dsuJzH16CLz8bk+1u2u78FYXWfklQ4/qY2x
5823 TyYjX8boyW6z9c9/Ojwz7Putu1Lp0NQ2UXoL8PKODmLuvootDjlyxcrNWHEHjQWsyKrkPS
5824 2JH14Lp3iCOXQOyp6nMs5fysKeilleOG95+WxCEj3m5mcmjNe5b+1yBZYELXgJrMdnY/HMK0S
5825 aP7M34PueYt8DWDovJzXVf/xsFe+Lpz/wjQ09eIh94ZwqV562+CUHv31MtnjSfHxorfE
5826 kGzq9FWiRtCRJwJh5+/ocSL2Q1zG52BvItG+wpqXRYEwcarfRdbSGC5BD/PySxBHakPWO
5827 qZx9Y4L10UABB4x5we8qDSH06++bnwzjzFXyAUv1y6Ece0017SAZkx0uqxmZB9RcaYvYxk
5828 2CBMBjAdTRWwYkrIwy4myTH9zt3R93j8X1j0ESWety7qPIj1odwkAmhFEA2KD6D1NwEh8
5829 H52HwWwLaLQH00YUzYr6zvnTlS7rgu40YBJq4JBWJCayRhTyeY4X8/xCw+rUS9L5ye50A+W
5830 8v0w0N2ZAxW7ADPzCEDPxdSLXodKefrWEM+yj47AeA7YxzMjXm+61FZUL46ch70oD6Q0
5831 Wncf9BTXbs623hnXPIvm1KJhJubTFKRBqag1QCMiwbui1PtyK1hWzq87YkOemCj191y9Ly
5832 PwK79U/55Bk75FSXmchwhj79Y35xY7qu8YspvtBqSG+55hdj1n6YS6ERfyQV02XoLrhmWJ
5833 YwqG5S2p1IOK5dJzgs+2L1B14Z6/g+uoa6yUWOY1jzcCuog411qxVQOYep1wul1Xg4pPR
5834 zD3GL6w1VE4JA35xekP1NLSuBb/34RcbW6JXGz6rflBBjBjH7t1WbGDRvd4bieXgP1Xp
5835 NQ31qGMHzZETHUrxvn45r8PfpQWRNdQfV2qBlXEF16+rQDLV82CtNvYBids2JfBpWMPJ
5836 a3rYXybm9qKMLmChJcnvUN5fkmrC2LbZJBk8mU55cn4/2rLdJQzJntKkyuu01pdqccfZ
5837 gKp/ahfXooV+JtoFimZuJyn8F7QhmAMXdAaUeTX6C7F07SUUkgYq50z33vV/Z0C7b+scH
5838 Ltnp1tH3Yew841pGt4JWAnu7Pn5xwqjxB4IMabC3Q8rFlZPCJfTc0Sf08nAdzSFwHfBU
5839 nmlDJTHGHn3eSR+42Mk5KwCtsXrMe35R7TvorP3rm49VMogfP801D191X61dvbKmkqjvb
5840 NfydX9m8Wim1MLKzESL/VzQskDPzcdYcyt71q/B4XKfKQAneK3mL47z9fQL/gaT+/vrEO
5841 qDTTX0U9UWbKUVMFh9MYLzJpzxxu0fP00/pTehdod/1XXGzawFuxP6G1Lz+eme2X9lbo
5842 0xuU119F0blAKGqGhafa5NVPxk7X70LuUMRM+JAFefsnnaKzLRhZLYBf5ed1UwK1/wD7
5843 fd+JL72VetDEPEIGWkZj6zFP/d5duzt+ZhiXfKlnhs7umT01AJkykVScenpJ1WA1AACzAE
5844 qd2Xs/S+nlND0PelXVtD/SkUr+JL59VsbL75z+bvNS8Q2BuQN/Oa3x1/FJZS/VZ30EGCB
5845 ePdtCYCROCRK3q6vL0pof7FXEvDAaVzcgJQECZ56CYcmxZ/7CyUwar2IIN2X4NOC075/
5846 4ymTRK3XuyvFGJmxt/xdbpt8uSR1711luUfJtQm3U17cXkfyGMvsFdvpv9RPAesh07FRv
5847 HUL4693pwu1Yn+FXOC+Cy0VrIwXzylh/w3n7fEi1breUtSvURmitjpkWRWYmPKkZmHd2FciM
5848 dm1f6+eW10/651MmCDD2YFE12dfycqj38ARAbQSPGX1sCGUCaCRDOUysZauvczX6zAVTF
5849 LLGqFLXPjYfjYIChkphr+cn+r76LOJ1d3d451+sndV9Yr4cVwG9+SrXtc6G/areZLB4WX
5850 tgzv7Wk4n+Z8f/FfzUkIa3ky5ULmo9CE8N3HGLin15ISrN32hsXoRnTBMbWmiP9t7T03
5851 j0g8vnn35zecGFy1GcmLw2/fwiciJoJXytieoL10xvRGHMynZ1/IJL6W3j3y58j+711dy057
5852 xLjJmM+X0FQOTrucgEUTDVIpFcnovWAE2KAeVrAG5T3tjBGQT+5rCIU+U1BzXPIRumpRVP
5853 4YEu29wP9XlfvW/oppuyDp9UNPiyh91/XXNOVns5dGG88wms31CzfrkCQUTCZSHj+vm8Q
5854 JV7X83M6wqjL5r6LVb668TOExtHjJ4Cdw24uzFvsJrT11RkFOoALtZnPFz2D12QrQ
5855 8Y5888pdsboHRLQD6exvEOj9y4q9DQPk5ZmJzjy021LdV7y3zfl8qmsDmOFArTWF3C1i
5856 N1NQGW1J1eavQM0z78D2ZVeFmHedFCU86nbfBB55KF1EPMRHE6FOOS0Aotvm/d8V98km7D
5857 C58YrseFulVspLpX79z64erdZNYUkLileJdaUak7Joor315x+YA9CbQBDf/ck7JHDDb
5858 E5g690KM89pdRjD6v3vgEvybdOcuc1VM9no/Qapp3KZ1ve82WcmJk30kx+30RK0E8K1wN
5859 blXaFhe29JqBL8oF8Gkam6n5P9mdG5BmtIkpmc22R7BHSKjPj0kMctCtK/KAM10JtXeJK
5860 vq7/OzmZbn/Z5IOHT3+NpGzn2ey7uiZODJm9xoyTcZBTOya+vndqW3URP1jyXmboDe1
5861 zq4BzYggsLmpgdLIXcmLwXszBgwa94ostveb+f714iK3oi05Mxod+r9/12Vx0P9E3c
5862 xp7XQYU8TjGmcat0+NeY/99v3xhb+21bh03cnol1JdfCZnzkeapsDN/vjDg4XPcNb8+w9p
5863 9zduKz2Q3fev05lytqto30pz9Ec5sHOY+FXFV150r6x5HkDFMGaadKQ3yAO9dydfdj
5864 ppf5kjqG6rnY13dfyKI5h140okj1azehBJNWTfBAGvU1IawS2XVtAhfESB0dEpeP
5865 mR1fLXOm8XmXnp/fby6AvG2fY5SkWno2mPFSF3sgCf3o4UGGSj/wI548WVlfbvVab720b
5866 Xx/Mwglf9zXFPQMbx5CiAfjhiTyJhsr7BkMfG8mLT+D3cdJF2qod1vnn3v3d60xw7fE
5867 koSF0pEpKzFeqJWQ1d70c6dnp1H7zi02933OHLHYU1urEhZ7pTpeVe69XW+3Jdsasm6tO
5868 EmsY1G5j8EajZNR0adga7ievOR2LBSceV820u5Ue1JbSpVqHecusjRkY1LW0V5S1ntmW
5869 LaycFxhPswtKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIK
5870 QAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIK
5871 QAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIK
5872 QAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIK
5873 QAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIK
5874 QAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIK

```

```
5975 m38w0ncAAAAASUVORK5CYII="";
5976
5977 GShellInsideIcon="
5978 iVBORw0KGgoAAAANSUHeUGAAAFQAAAA4CAYAAABJkd/gAAAAAXNSR0IArs4c6QAAAHhLWE1m+
5979 TU0AKgAAAAGABAEAAUAAABAAAFgEBAUAAABAAABAAAgEoAAAAAABAAIAAIdpAAQAAAAB+
5980 AAAATgAAAAAABAAIAAAQAAAAAAsF1zAAALEwAAACMBAJqCGAAAD8XJREFUeAhTwt0VMUz+
5981 AAAAQAAADgAAAA2CjwAAAAAAsF1zAAALEwAAACMBAJqCGAAAD8XJREFUeAhTwt0VMUz+
5982 npm7m5BEIKgP1LlFv0VjQokG5LzVjzK2k61VU4qgIkkFAgr9QXJJuZ0eWVpSri8VbV+
5983 hSgTKN0Qj4BfM1oIAEzAKKIKIYQ8du9W7nZuWuYXzABg1w7k7d/7555+zb/5/Hv/MenL0+
5984 isoCNKRkEgY6rwyC2ZwqkRehoL/DSBKfAYhBKRRKARLUEKwCqog2BV5ayJ/ASge9HQut+
5985 oaxwCFpDhNj053TPcbw1m5camaJL5kP5H1u1AM2dW/prvwgQxqGF+AdhXeoGfW5Vz1G1z+
5986 JwWbFqgPNEdOxvY9GmWmu8z5dVycMwakk9+fh4c/Adv/Fb4p1GE0VoJoge84Vhw9AB4N1+
5987 BM6hhNDP0AvIdLuPaUz0/5TubvyceQAQz4xndBZrTgJiEBDKRGLVOKFEITtboor515c+m+
5988 7Y5216H567b6mNUlmsANyXy9P9mFhT+j8vdl81e/7kaU120ApuUngzhvJYyeg1RcUyW+
5989 Q50WDt2720fWxR1HTKykKpEzq4EuFcliiCEvEAFfhnUX6buUcco/Eq04XmQSY3r2oZwR0+
5990 16uhikUrcm1ro1DXqIp1z604nzF204Reg9dLOX+qOD+18mAlRggJhyvNKvHuaHjYm4F1da9+
5991 umLxKadRWP57982p45r6t12PsnY2ytma4eSdl1x2oUenKDP91WVGzsdR5W53BoHa+
5992 8ba8eGV+znY7T+p1Q8be005CFCEwFW5eY5Y/7prt10mBAZQdhh3VrYGzsdR5W53BoHa+
5993 oagUmbi71feg18U+evXt11iXDWvlhqXlF+cmP9ad+h0QoOn0VUMZ5W8hcyN1+h0rFkz4ujF+
5994 9gpe1Fkf2d1+1+Eest4Ldon5U+Nrc1KvbsNaCZOZQo4XnX4E8X59e7EohvZnH4fTeh+Es+
5995 mwr+h2Yxsr02tItQDyP2PRY4VEiBtKXLaSzoQflumOmZ5UwukbUKLPuK1I+2tX1wHNYPfG+
5996 wKa5RLCJA7a76/cn9HMS3NG6Z2QLKWEzi30S10uqYlIdAJQ23eFlmN/F5RnuHNTMKQsdrJT+
5997 024z9Q0Uga/wds53PHLw7W30UDORUjgcBewell17yqknBCjisaPafyQrEB7p0UoSkrr8T+
5998 bTSLJQTHX0xbyWY17F8mUuzHzK3L1F+GTebCa+i+JtzBe8tSSqjOD0hoySGC+CFzFL/x8+
5999 MH0/3T8nesTV/3UBBpshuvMnr01UuvV15Ww/LDduzV59hTtgcM20CNKwHppEnt+CZFfTT+
5990 Pg/1U7c7q4MuJyVjBczn0Oxiz3h6QFaSb2liSaytyZhsu6d+3Z07KfCS431IayrUmTYh+
5991 eFpvgz0Eftun4VgWno3FeQ80btGoYL9HHxunb623WfWu47vGvokLmQ+0zV6KjGUJskdi+
5992 3EK0510/Y77nM01prZKOVn+W5NmcmUGWMSIewGRwLoGpAntWn7zt/58p6UA/UfhGMCH3N1U+
5993 Oq15V/Omr/hNRWH1qM3En5mb76kukVC5VpuxQ6RFNHHk6N6WbafGrNPLymzHo5Yeo1a1D+
5994 M+B5eThvdfv8W1DOanbUkyw6T5I5kGvOY3e19h2raG0qbi4YshFqOwxh9Bcrz00LT0xbx+
5995 4Bc16lmsN4THfwhqjCEflg9ZEqb1h9o6C6YsBj1LDXzU7j6bdEdvkH0ky/wEdiWLVJZ2azg+
5996 tLA0eS65G502du4rZHeAYPg/IbgMwkoXyoJf5J5YXpFOYX+X3+05mMAIDBQNO/evUWLS+
5997 sxySYfdZ3JErcFLz1BpPKU6LFfg05fbBEW930Y/DBStB84xGrAh8H11Bo5mEK72epkh0+
5998 knznUQH21eSf0bte0OqG6XhVLd6/5boj8prCmLZ31UNMGEbE7E5Cawjdlcz9+hda9KyM6+
5999 0U1AGRMbJEGCAdoFJLnBsB22xjPpEOBPgMDU7PhoEnRwGpALGT0oULSs3tHRakbJhs/J+
5990 M1x9hdgX/f5e271TUsBtKwVA+PkamLLDcc6PbQ1XchUN1aogdaV8ou1dQ1Q5S5m4vd6UF0w9+
5991 Q/EA8Btg/mvcrurXQAMr9JDSUpwN2T2B4wrHAfEYJourBuicfo9we14Epe0e+EGE13f200/u+
5992 rHJNaVY8ntKfKviY6H5h0Wnm7H0vnpKGAhynpB8qUPHXwuyJLkog1D25yA11E7L3CEvi+
5993 n9N00d+QaWE1FD03lnPi2SczcHEl/goOEIdn708m35EVd2jY3LJnERH6paABnBpOngVhxrU+
5994 H+B/MbmyTDQ24fr73CdInoFw8AwxmTWpL61qFG2VMZCkYAKCoh8mL0zVixODr:FY9hmcS+
5995 jYnFWRKdfrqWfkrBYD/gtO1VOp95adY/BSN171aE2LktfFO/dlV8vhIdPj5Btd1h1AYxm+
5996 nCAV3RkStz3K2PnbhGD/x1wbHg7XLLZ4zgs/tYooJFPQCO2B/0h4ae1U09JINKd3j8dtat2+
5997 Bx1mAgppF+pl49V0qGH6ivH2fohQ+ZmaVXYSEH9NdjjsW5pebU5pf1k5zF1XrBrVjDZ3CUE+
5998 OX5GocYagocfUrmc013Rw508EgffvtJ8r5iCQX04RfYmkgmV3mzSrc7Rc8Ai1kqghXitWUX+
5999 U06RuyB1tS2rUnQoX+D2k5WzId5AmoCkCxMelaSwt4dkDbC6goLnfhhWpgTh6VpOE3ZK+
5990 PpP5LcZyG1E+Q2bkfEDQhpzr8RWY7D11Id0KwYey9mgoI03J3Jg10Wkca9vbw1gfazt+
5991 ZYHrIaC3tgxlnDCYAppDVR0NhbX5JLW1W8pWhnHDr0BniOUy/s1qHmi3hb23K4wj5mVbuz+
5992 rxwAe6t9U31q+AKvB98tUgCNDH6q2Xom0EjibuX9dn4YlEP52EVreT/IAJDr9ajGsbZ1+
5993 g0r89DbaZefFIPsx8Bbkv9zt/LPKntY9AZFLLbh14DA2NREd84c14rdkHexqk1wRo14un+
5994 PVYx0QzFugD4xLXU/HKF699pT9F9shDqdL2dPb0BBAupbFw0AZy9giy/eUumvvtf4+
5995 eTbLS20qucZCWTAEbJcok386rPmZTiySyo06SoowGqbUAzqJUH8qz55CF5e4k93U1ie+
5996 k/WT+anFaspH/yodkGR6DJppK15tjBSDOTORKmyXcnB1OCCar9zvQrda04DjTLDyZrJfL+
5997 9/mMMRQVX1pSap49NPMW5j4mdz5ieS2RLjmgEo01lhmLZxfAMS0dyK0netGBlpgGHU1z6W+
5998 X4F+67eK1sY9s4v10YrKTro6932be+13JGqDqNPNkHWq09IdJueLqRcDeetjDkvevgvVDV+
5999 XDMAMepwFpPwU11LFSmwSuk3QcxZgTFwuzRjHEMy6dyp+L567YUgagKfKdb1k5Gw9+
5990 zV2YsKhouLD/nj8yH6ziZscwKNJ1K1KIDXM341Q0GHAjgg1aZngWdzuh+mfiXASSHEer+
5991 QKcXEYMPVJ70mCjsgn8td1pbjs1JodNGAEj5Fkoz+ntV5BVMx1Lrn4BMMD+wFhvn10Hu+
5992 mrxWQwUvPuddNM1QOXVNG26B0jNI5ca58RSuhXQgi2xjNwg11EY2nE+b2LSR1b14xCuvL+
5993 d6CAqgdqGxZq7FU2mOxNflzqH4g5F+SykrZb7MIzU9Whf4iAuiN852Qa521Bgo3yG8CO+
5994 wj35kMknf6kz40XALahvE8d24AZAfhueZnm33FbKHG0t/DnwfSO/wTwmZohv8WgSHSD+
5995 L8TPbr9kwLkzVDLlav+8j3VID+rBUOPvHBXYd+zKMBbac9Z+caefAKU/CR0s/DyGwL7912d+
5996 eZgwYRyEGwU3GAE6Gf5JLbtz10pxw2BcINER21rEVffzqxP/MDpeJ0+I73sG4yiy+oWXX+
5997 f+RvH8LV1ErHjg/7paY9GzflfbziURX6So0jtb183CTYmorXOPnjvVK7ZdCkbrAke11dSAe+
5998 jXRa06sZhdKvZ4RTApxr8p1hpk1/EsENF2dVntJr5+OCGTOXhky/ArX425UVYBKRRECL3jw9+
5999 9N+5+1qpcG1bb65sSHTRHJDL5pFBTmq9/dB+pmhZ1yPNPCYdx1SRk53tB5011jX1M35E+
5990 I+ykPBJGDjg48DYpJxnKCoer+27mqZ2EC/ganWzJ8D71VCJ3GyR91nmc3/38E9AJe0+
5991 m5Yz+osGCM1EN0N8Zk7BR0ySTP0DEAZ8J3w54C9Pr9rjyKo6mteAhzm4NDY35Ha3yVA+
5992 ZWZ5TRGepm4Fe2zqZEKngY0JozKtMJO8uww5jV2XXNtSFOUHYnG8gtvQhHEXAG6LUAU7D+
5993 KY61+Ey0zyYul10T9ctiCiH51c/11xdBY9t0waagLhOUX280DdehrV6BNhyDQ7HrSggS3S1+
5994 Pd3W0GChWd48d1xPpEQMSBQtumTeyLTI9N37LC7E1DTunY1UzB+vvwIFba5/qzpb8DgpQ+
5995 CzjSesHAR/ehWvJ3/ty3Xb692pwc8J9MANwoe9X9tANZ1V6dR3f3U+aECVBy0PHY4jgd+
5996 ytuEfbJ0Uac0A5X5zwl/5ksu2JuxJyA17X1B4yVe7yVkaqctQAVQXI/wJxj3G6Y4D0d1+G+
5997 2+Z5nYvq1T2sQXmKMrzGicCpfbijsgqXC+bD7xn2pLc78qMoqCrcuIDP9kwnN941ex8r+
5998 gtdu28YVysYe1/pcBrfKNTBgnP9DRPXUjghN0vevYokPwOJ5vg1v8Khz9/j7RdkUorxmd+
5999 Q/5M8uA0uzxpLRPwbGogYxB/q9ivb59RLM+PQ7oXm8A1rb6Ddxu/sMeb/ogrCO3anKs5b+
5990 DxfHqLANoQ0sa0pxnK93VfGud00XMS40E2La+2j9W06SIRvOXfngSpg0T8Z1nAKVh3S038C+
5991 xvKNOCGogppBKNevLH4quTzceWdGk9TigrL4110xj1ieLXbZ3ums8ulEcPMPPE1ahdeeVwS+
5992 z731+Zfa2UnvuhWbaEoAN00mHENLmd8DdpXue21QU/Vyvyft+99U6T36PB+kC7ARQR6NgdE+
5993 mxnEQUMt7RwVtd3IT1L2s3Zz3f3h1VCKFSHBFCN6+/qJd0z6rUrt9V9e0fa7q7m5t1/dD+
5994 295mCh25YkHSDY9t4XKHq03sYf/3Eha+AxrWnBBeH6Guq6XXUAbKSDC0VK47H7eJ0YsmZt+
5995 REMNEKf9WdH18hly/wA+R1DRJHOJ221j1p0A5DH40yaQkQoccuVZ1b14JrW8H82+7LA+
5996 0FuxPWSASoCgmV4sZzZhW5rXGyecX1wny7+E/+IqFeUK/R89kneGSwJ7WAAAABJRU5ErkJg+
5997 gg="";
5998
5999 GShellFavicon="data:image/png;base64,\
6000 iVBORw0KGgoAAAANSUHeUGAAAKAAAB/CAYAAABymylZAAAAAXNSR0IArs4c6QAAAHhLWE1m\
6001 TU0AKgAAAAGABAEAAUAAABAAAFgEBAUAAABAAABAAAgEoAAAAAABAAIAAIdpAAQAAAAB+
6002 AAAATgAAAAAABAAIAAAQAAAAAAsF1zAAALEwAAACMBAJqCGAAAD8XJREFUeAhTwt0VMUz+
6003 AAAAQAAAH8AAAAACt6zAAAAA1wSF1zAAALEwAAACMBAJqCGAAAD8XJREFUeAhTwt0VMUz+
6004 x9/b21+1YCKIK1K1amW1/jj16BCKstFEFthI1CpRwdstQoqEunttW2nFq01YTIatinZ0\
6005 amAdqY6j1YOX17kgglarVv743BAQpkbVAjJ3e3r4WcJpe93csmcbj784kd/ve7723+3nF\
6006 ffv+nx8SIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAE\
6007 SIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAE\
6008 XiE65tAHewad8Imp2wLTXtadyBmzrT+42pRSrd3peQvPxsMtrhngYNc8fewHXfUap+2yh\
6009 UASIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAE\
6010 hf7VweE6PyDz+0M6JmXwz2n6REVCq54SQXwhL18xtFFcuWqHx7AMRgIKQA1KQAJHIAH/\
6011 Nbgem30981Ho058sa50440Umz+EzCEAE/FWHXfnjsoFlD/YP80ZJKRALVawJEGG4C/BGS/E\
6012 rgK0AMB/d3ucJ1W1jsYvnsIy0KAQ8FeVynMsYwYR5F3cmUmLT6v/FwDD1QAv4S7EBpZyQ/\
6013 65pVScdz46QeHyZiLZeDt1K7m51Ayw2ywmXNDa8cLcpLj1Ww0i01U1/53d05692nzqBp\
6014 2D8BZtDxp+28K1xicyG9Fve6Eh5VcINOVeQOFLK1K7qgpVwBunKnPoodS814tKywGPT\
6015 0e2e8+3+ra1p1162LEVYnPs6SQfapwSqmV0Kf8pDwGkzleSbaWfPDrEuyTUVERW9e\
6016 faWf190qt4Cz27yOroBvF9CrE/2qnEo/ElFa4DqHaloCUT4rpJszGLGN56z10QvRrtE\
6017 RhdXjvnnSHwSYMTq6UEZEEGJeS2EWmpj4sk88VQat/zSeLuz5aeM1zRVkdrAVH0\
6018 F6R52azf88510gmVort1seXG/oTLB9s+r5h8u0ihusYfz191fGlP2cNSyt1IA2/w008aeK\
6019 Ix87zhymPTkTb3oclBxa/DKX3bYpoeHh686jgcXSEcUgYXALy+CVN0S08mMM19U00H+oH\
6020 zFN7phGqb3k0oJ1F09zr7RvGn3d1QNRtg4570TS1hkYsJSuok6478h1PhRo614d4mmU7N\
6021 4t2xw1BFI1BE6u0Gw2+T9JpFNkn7WUbrm5WgppjG7K13801ulApe1WCLADaXqEoc1E4\
6022 LB703kKUBt04panz0+9y0NN9ANsdPQmN4oxSnokzgTn+f0CANUSNmm3unJxgAovhZsuc6+\
6023 G3pZDufdWmGRf0n8BezIjXDYscHa+vntgEDT10QH1kCVceJ9jsVjebVqEtoSfV1/ERXV9FE\
6024 74zvA8+Eyc/v6WF7Xamn05Kqnr60Ylem/+GqTOA6dKXNTz8weCCamh8Moubur815bb1bk6E\
6025 Rbhvm2brm7h195Jv11hSPpwyEn9sXhL6JNE7k1k1+UwQNK2hcmG5M6V3ZwU1U1Yt9TUXe+G\
6026 s0ng1shHoWt/2Fw5q6wVhWvnt4r/OkuK2WP20x1ghfSnYqgYaz25tBav0/Pdh1DX8FuW\
6027 lfhP1h6FTfbp7VCGPfkUXFvHsOZSjzclTK3TtjwR1jecr0HtS1rJCXhIu09N1x1fVgK\
6028 5wZudRzKXN211vU8pLmXuBCa2paVgVJde1Z0+SUpox3S11+3idYU2NxcEDUVaJ2K0847e\
6029 Gqpe4UatP7/74/wPD77y76+A3c574a/FyENPby9YB/cvZPn30YftrV3CPJGJ0fAKAet3\
6030 7T4w6cJEqpKBy0eAKudXFG7FKKKh72wX453a+vBkSbt1a7r0hPrY9M9Syt01dVotKd/1\
6031 Tr/7DA8W53k8WVTLKfUmtS4CsRv411A+Y8t/zd1L0n0w1VcTe7fDHK3+TazStJk12K6\
6032 C8v1gcGfhKsrNeUxncQ9Uv0K390MfZTUyZa8prA05YneJKA0/hu0tNw+cc5Y9264CLN\
6033 TyPH01R+3pl9VMIdCpG6pLLTstasnpJrc0+BiH0q9kGnrXmH4drYnEzJfzvK2b1NQZKX\
6034 eQd16tyHZX6MCw21h9eY9+0/wj2jR+Q+hFTFPFKytZQqipvsrX0z6Zobw1yJ0ePsfN3\
6035 cSNYwSfS13RxtKH17ky7cT+GEaorst0dzvHgmI/09rVtaHPulzsyok0f99UCzDB1z1HQgT\
6036 2yDwd1sVHX9Fdrt1h1f0qMKF/29w2Yq7k7ZDUuz1butncUdLmKYkR600L450Y2R51uy8E\
6037 213vcxGbeYzDF3bH6GAT7f3yc0VArnDToMx/886D1mVSB1TzPt58DnaCMhXwpHmaF0Mbbfm\
6038 vhdsgJNGjXhR08u0481F/WeBp4PPALZG1gtD1Zu7VBWRp9q/ubAB6EVVYK/ulF8EXgsvC\
6039 V9ecEnbQ/DSrWOYsRrX1QB34EOx/ssYPD73Wk9owb7pEezP++jftTsoyQaZcx6R/ofj5QzDY
```

```

6000 BnasW4ZhsV+2rDYr5gZQAvdp5We1t/GQSumZYW6HgmGfPJRo/y4aaU+7Gffyl+LS0KKWcC+3\
6001 AjxxvWcLD+BYJ07RAG1HTuc8jclEpNNZ5qZ4P8S8XK09H9p55d2S3TmJngu8zUPTN+OL/PC\
6002 dc74UFahmsf17H6RP12VnwjzrZ5LufLwSLBs0f772KosSQJyIzN2fL00acgK4U6b8+BXyQ\
6003 TkKvweVtgeupTgZ2fth6ghg26/jB8aPKnoBo59jZLh9L+084E59USUQhk165Vw6P3njyDW\
6004 85ziR5001+qabRR6FS0+rzbMqXwv2xr0csSSmQI/FCFY7LPdz21JzrSKf+C5dELh6ixITTWL\
6005 V1/nm4/cmBCW+nXmNWee48EznelWaoF+EKyUro1IDOGpL3Pawp2RGFPInIhtCOXYQ5ClgPQW\
6006 RG14fbl+LEuV3VncC8bZf4KVLsaeZfVNVs6gjsQv++Yot29BuzqWrgjwZDI1oBJwzE18VIX\
6007 KE19fdsBxp/2X6sgXKM3dfLatfd8adBN1u0UNh1AEwg6Bw93sevej1HhMULPw/b14a6npg\
6008 pksWlwr06FXMn+v3MLU6mWfbD3KwyWstXwj2zUcu04jSj+6WUyJBTLLlpSv1okE327S/NuWx\
6009 Mg+721W6vtW1T14TY/bUnDxms71u9baga20YX5DbUX1z9BRpGEVdrDHJ51k3m3z394VgdsYp\
6010 qZnk1kQbbVhBteH1610vu/ZgszaeLR+tNOBCX90ka7q7BbtQ6tbuV/oYiPhu8xhz2A4R\
6011 o1HaDu3Q4pYZWHWc1a17Ndi3bXo2P7v2p70cmEpycew8L4Q6770Ev+htZPnED+mNFy/W2\
6012 9LRAHr5EJ/vQ5gFlw7StRrEMd4gAu5rQ3T6aRSqdmx7z+qB47ui290Uwv9JX4AnJ71LIs\
6013 16+xi8srm6YcRoxul4K1ysH6Be9110YHs791/4cxvghn2jWb1j1XXxecYQuZU0g5Wduq\
6014 Y6xMfg2XReb6wTrTjP5NO7ZuP3v9lrmDnn4F5eSbKOH0t.ab6aStQot7/beUgSubPmhrC27B1\
6015 OYQh510JvclY04FkKoz+kgv+oaJdVEsgVEr9PehP+SrXWnkMNLm6VpOnUikLzm+PveQgF\
6016 h4F8J1j9WwOrt+64Stf500WEzd2C5tCd/FZS/VXH3naqrQUL+4B2j8m8SsS/Fm19D3McBjwo\
6017 kRn3KXzuzgppsZkU1cbOcrjmPWhQlabXm1gsdui315d3JlR9y0Vm9Np1kTie/CQY1dtWZV2\
6018 8/PkpxnKkvc1bdveIDDt0Usc+RmxmDtpnxm1w78tYm6HZGdCt2fgZn+8xzuSRBvQ4zrhE9\
6019 H926s9VJSOHFzRdII7AAPQwzKI7LepLurBj0Qpxvbyb/8dmn2//ll/qgnago2Awgf/38+WE1\
6020 I4af5Q5EXEMARkAOI2CCP2xjNV+LMZ78LkH3V27LWvt2n9w4/+6jgdkXJPLq7b1TAdkw1p\
6021 nIhS+QSt+HiEW5RPUvengV20d6Nf7K0tloF1dj/iKuSatCEBEIABEIABEIABEIABEIABEIAB\
6022 EIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIAB\
6023 EIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIAB\
6024 EIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIAB\
6025 EIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIABEIAB\
6026
6027 ITSmoreQR="data:image/png;base64,\
6028 iVBORw0KGgoAAANSUHEUGAAAGSAAABvAQMAAADYCVwJAAAAB1BMVEXE///9BaeFHqDaJAAAB\
6029 HkLEQVQ4jdXtsa2EMAWGYCMX7sICkVqjXvACBe7CarASxdAtLAWgS4HwM5zEVS+mvSgS+ZbcV\
6030 8gcb4BdHyZvW8szMSaUBHm+KAd4QC8LDpDn8ogT4UpPGci2jI8IGFX3eLwPwHknVYveWQ\
6031 UEBDXaB0X2aJueYD0zNk1QassPCKjc4nW3E1SfWqYk6ju/vAKPhg0ALSFhve8Jt0dkWDMwr\
6032 yMSSuSuPyWHAR19k0tkV2s3sdm2rUCqW88g4Rp1A9s1JPv9cTPlNRD4XFKin8XaQCICW76LzG\
6033 Z08dhw/4+U2Gzq1S8gbqVmkfR1N6YK8OqLD00mLGTWvzPERA8AL9vboiFpSoL33fVytrL\
6034 S9wiqDznhUI38v5n783/gBUUs2ELgic8GAAAABJRJU5ErkJggg=";
6035
6036 </script>
6037
6038 <div id="GJFactory_1" class="GJFactory"></div>
6039 <style>
6040 .GJFactory{
6041   resize:both; overflow:scroll;
6042   position:static;
6043   border:1px dashed #000; border-radius:2px;
6044   margin:0; padding:10 limportant;
6045   width:300px; height:300px;
6046   flex-wrap: wrap;
6047 }
6048 .GJWin{
6049   xposition:relative;
6050   flex-wrap: wrap;
6051   top:0; left:0px;
6052   width:280px; height:180px;
6053   border:0px solid #000; border-radius:2px;
6054   margin:0; padding:0;
6055   font-size:8pt;
6056   color:#fff; background-color:rgba(0,0,64,0.1);
6057 }
6058 .GJTab{
6059   position:relative;
6060   top:0px; left:0px;
6061   width:80px; height:20px;
6062   border:0px solid #000; border-radius:2px;
6063   margin:0; padding:0;
6064   font-size:9pt;
6065   color:#fff; background-color:rgba(0,0,64,0.7);
6066   text-align:center;
6067   vertical-align:middle;
6068 }
6069 .GJStat{
6070   position:relative;
6071   top:0px; left:0px;
6072   border:0px solid #000; border-radius:2px;
6073   margin:0; padding:0;
6074   width:176px; height:20px;
6075   font-size:9pt;
6076   color:#fff; background-color:rgba(0,0,64,0.3);
6077   text-align:center;
6078   vertical-align:middle;
6079 }
6080 .GJIcon{
6081   position:relative;
6082   top:0px; left:1px;
6083   border:2px solid #44a;
6084   margin:0; padding:1;
6085   width:25px; height:16px;
6086   border-radius:2px;
6087   font-size:13.6px;
6088   xline-height:12px;
6089   color:#fff; background-color:rgba(32,32,160,0.8);
6090   font-family:Georgia;
6091   text-align:center;
6092   vertical-align:middle;
6093 }
6094 .GJText{
6095   position:relative;
6096   top:0px; left:0px;
6097   border:0px solid #000; margin:0; padding:0;
6098   width:280px; height:160px;
6099   border:0px;
6100   font-size:8pt;
6101   color:#fff; background-color:rgba(0,0,64,0.5);
6102 }
6103 </style>
6104
6105 <script id="gsh-script">
6106 // 2020-0909 added, permanet local storage
6107 // https://developer.mozilla.org/en-US/docs/Web/API/Window/localStorage
6108 var MyHistory = ""
6109 Permanent = localStorage;
6110 MyHistory = Permanent.getItem('MyHistory')
6111 if( MyHistory == null ){ MyHistory = "" }
6112 d = new Date()
6113 MyHistory = d.getTime()/1000+" "+document.URL+"\n" + MyHistory
6114 Permanent.setItem('MyHistory',MyHistory)
6115 //Permanent.setItem('MyWindow',window)
6116
6117 var GJLog_Win = null
6118 var GJLog_Tab = null
6119 var GJLog_Stat = null
6120 var GJLog_Text = null
6121
6122 var GJ_FactoryID = -1
6123 var GJFactory = null
6124 if( e = document.getElementById('GJFactory_0') ){

```

```

6125 GJFactory_1.height = 0
6126 GJFactory = e
6127 e.setAttribute('class', 'GJFactory')
6128 var GJ_FactoryID = 0
6129 }else{
6130 GJFactory = GJFactory_1
6131 var GJ_FactoryID = 1
6132 }
6133 }
6134 function GJFactory_Destroy(){
6135 gjf = GJFactory
6136 //gjf = document.getElementById('GJFactory')
6137 //alert('gjf='+gjf)
6138 if( gjf != null ){
6139     if( gjf.childNodes != null ){
6140         for( i = 0; i < gjf.childNodes.length; i++ ){
6141             gjf.removeChild(gjf.childNodes[i])
6142         }
6143     }
6144     gjf.innerHTML = ''
6145     gjf.style.width = 0
6146     gjf.style.height = 0
6147     gjf.removeAttribute('style')
6148     return '-- Destroy: work product destroyed'
6149 }else{
6150     return '-- Destroy: work product not exist'
6151 }
6152 }
6153 }
6154 function GJWin_OnKeyDown(ev){
6155     ev.stopPropagation()
6156     //ev.preventDefault()
6157 }
6158 function GJWin_OnScroll(ev){
6159     x = DragStartX = gsh.getBoundingClientRect().left.toFixed(0)
6160     y = DragStartY = gsh.getBoundingClientRect().top.toFixed(0)
6161     GJLog_append('OnScroll: x='+x+',y='+y)
6162 }
6163 document.addEventListener('scroll',GJWin_OnScroll)
6164 function GJWin_OnResize(ev){
6165     w = window.innerWidth
6166     h = window.innerHeight
6167     GJLog_append('OnResize: w='+w+',h='+h)
6168 }
6169 window.addEventListener('resize',GJWin_OnResize)
6170 }
6171 var DragStartX = 0
6172 var DragStartY = 0
6173 function GJWin_DragStart(ev){
6174     // maybe this is the grabbing position
6175     this.style.position = 'fixed'
6176     x = DragStartX = this.getBoundingClientRect().left.toFixed(0)
6177     y = DragStartY = this.getBoundingClientRect().top.toFixed(0)
6178     GJLog_Stat.value = 'DragStart: x='+x+',y='+y
6179 }
6180 function GJWin_Drag(ev){
6181     x = ev.clientX; y = ev.clientY // x = ev.pageX; y = ev.pageY
6182     this.style.left = x - DragStartX
6183     this.style.top = y - DragStartY
6184     this.style.zIndex = '30000'
6185     this.style.position = 'fixed'
6186     x = this.getBoundingClientRect().left.toFixed(0)
6187     y = this.getBoundingClientRect().top.toFixed(0)
6188     GJLog_Stat.value = 'x='+x+',y='+y
6189     ev.preventDefault()
6190     ev.stopPropagation()
6191 }
6192 function GJWin_DragEnd(ev){
6193     x = ev.clientX; y = ev.clientY
6194     //x = ev.pageX; y = ev.pageY
6195     this.style.left = x - DragStartX
6196     this.style.top = y - DragStartY
6197     this.style.zIndex = '30000'
6198     this.style.position = 'fixed'
6199     if( true ){
6200         console.log("Dropped: "+this.nodeName+'#'+this.id+' x='+x+' y='+y
6201             + ' parent='+this.parentNode.id)
6202     }
6203     x = this.getBoundingClientRect().left.toFixed(0)
6204     y = this.getBoundingClientRect().top.toFixed(0)
6205     GJLog_Stat.value = 'x='+x+',y='+y
6206     ev.preventDefault()
6207     ev.stopPropagation()
6208 }
6209 function GJWin_DragIgnore(ev){
6210     ev.preventDefault()
6211     ev.stopPropagation()
6212 }
6213 // 2020-09-15 let every object have console view!
6214 var GJ_ConsoleID = 0
6215 function GJLog_StatUpdate(){
6216     GJLog_Stat.value = DateShort()
6217 }
6218 function GJ_NewConsole(wname){
6219     wid = wname + '_' + GJ_ConsoleID
6220     GJ_ConsoleID += 1
6221 }
6222 GJFactory.style.setProperty('width',300+'px')
6223 if( GJFactory.innerHTML == "" ){
6224     GJFactory.innerHTML = '<'+H3>GJ Factory_' + GJ_FactoryID + '<'+/H3><'+hr>\n'
6225 }else{
6226     GJFactory.innerHTML += '<'+hr>\n'
6227 }
6228 }
6229 gjwin = GJLog_Win = document.createElement('span')
6230 gjwin.id = wid
6231 gjwin.setAttribute('class', 'GJWin')
6232 gjwin.setAttribute('draggable', 'true')
6233 gjwin.addEventListener('dragstart',GJWin_DragStart)
6234 gjwin.addEventListener('drag',GJWin_Drag)
6235 gjwin.addEventListener('dragend',GJWin_Drag)
6236 gjwin.addEventListener('dragover',GJWin_DragIgnore)
6237 gjwin.addEventListener('dragenter',GJWin_DragIgnore)
6238 gjwin.addEventListener('dragleave',GJWin_DragIgnore)
6239 gjwin.addEventListener('dragexit',GJWin_DragIgnore)
6240 gjwin.addEventListener('drop',GJWin_DragIgnore)
6241 gjwin.addEventListener('keydown',GJWin_OnKeyDown)
6242 }
6243 gjtab = GJLog_Tab = document.createElement('textarea')
6244 gjtab.addEventListener('keydown',GJWin_OnKeyDown)
6245 gjtab.style.readonly = true
6246 gjtab.contentEditable = false
6247 gjtab.value = wid
6248 gjtab.id = wid + '_Tab'
6249 gjtab.setAttribute('class', 'GJTab')

```

```

6250 gjtab.setAttribute('spellcheck','false')
6251 gjwin.appendChild(gjtab)
6252
6253 gjstat = GJLog_Stat = document.createElement('textarea')
6254 gjstat.addEventListener('keydown',GJWin_OnKeyDown)
6255 gjstat.id = wid + 'Stat'
6256 gjstat.value = DateShort()
6257 gjstat.setAttribute('class','GJStat')
6258 gjstat.setAttribute('spellcheck','false')
6259 gjwin.appendChild(gjstat)
6260
6261 gjicon = document.createElement('span')
6262 gjicon.addEventListener('keydown',GJWin_OnKeyDown)
6263 gjicon.id = wid + 'Icon'
6264 gjicon.innerHTML = "<font color='#f44'>J</font>"
6265 gjicon.setAttribute('class','GJIcon')
6266 gjicon.setAttribute('spellcheck','false')
6267 gjwin.appendChild(gjicon)
6268
6269 gjtext = GJLog_Text = document.createElement('textarea')
6270 gjtext.addEventListener('keydown',GJWin_OnKeyDown)
6271 gjtext.id = wid + 'Text'
6272 gjtext.addEventListener('keydown',GJWin_OnKeyDown)
6273 gjtext.setAttribute('class','GJText')
6274 gjtext.setAttribute('spellcheck','false')
6275 gjwin.appendChild(gjtext)
6276
6277 gjwin.zIndex = 30000
6278 GJFactory.appendChild(gjwin)
6279
6280 gjtab.scrollTop = 0
6281 gjstat.scrollTop = 0
6282
6283 //x = gjwin.getBoundingClientRect().left.toFixed(0)
6284 //y = gjwin.getBoundingClientRect().top.toFixed(0)
6285 //gjwin.style.position = 'static'
6286 //gjwin.style.left = 0
6287 //gjwin.style.top = 0
6288
6289 update = '{'+wid+'.value=DateShort()}',
6290 window.setInterval(update)
6291 return update
6292 }
6293 function xxxGJF_StripeClass(){
6294 GJLog_Win.style.removeProperty('width')
6295 GJLog_Tab.style.removeProperty('width')
6296 GJLog_Stat.style.removeProperty('width')
6297 GJLog_Text.style.removeProperty('width')
6298 return "Stripped classes"
6299 }
6300 function GJLog_append(...args){
6301 txt = GJLog_Text
6302 logs = args.join(' ')
6303 txt.value += logs + '\n'
6304 txt.scrollTop = txt.scrollHeight
6305 //GJLog_Stat.value = DateShort()
6306 }
6307 //window.addEventListener('time',GJLog_StatUpdate)
6308 window.setInterval(GJLog_StatUpdate,1000);
6309 GJ_NewConsole('GJ_Console')
6310
6311 // 2020-09-15 added,
6312 // log should be saved to permanet memory
6313 // const px = new Proxy(console.log,{ alert() })
6314 __console_log = console.log
6315 __console_info = console.info
6316 __console_warn = console.warn
6317 __console_error = console.error
6318 __console_exception = console.exception
6319 // should pop callstack info.
6320 console.exception = function(...args){
6321 __console_exception(...args)
6322 alert('-- got console.exception("+args+")')
6323 }
6324 console.error = function(...args){
6325 __console_error(...args)
6326 alert('-- got console.error("+args+")')
6327 }
6328 console.warn = function(...args){
6329 __console_warn(...args)
6330 alert('-- got console.warn("+args+")')
6331 }
6332 console.info = function(...args){
6333 alert('-- got console.info("+args+")')
6334 __console_info(...args)
6335 }
6336 console.log = function(...args){
6337 __console_log(...args)
6338 if( 0 <= args[0].indexOf('!') ){
6339 //alert('-- got console.log("+args+")')
6340 }
6341 GJLog_append(...args)
6342 }
6343 console.log('Hello, GJShell!')
6344
6345 //document.getElementById('GshFaviconURL').href = GShellFavicon
6346 document.getElementById('GshFaviconURL').href = GShellInsideIcon
6347 //document.getElementById('GshFaviconURL').href = ITSMOREQR
6348 //document.getElementById('GshFaviconURL').href = GShellLogo
6349
6350 // id of GShell HTML elemets
6351 var E_BANNER = "GshBanner" // banner element in HTML
6352 var E_FOOTER = "GshFooter" // footer element in HTML
6353 var E_GINDEX = "gsh-gindex" // index of Golang code of GShell
6354 var E_GOCODE = "gsh-gocode" // Golang code of GShell
6355 var E_TODO = "gsh-todo" // TODO of GShell
6356 var E_DICT = "gsh-dict" // Dictionaly of GShell
6357
6358 function bannerElem(){ return document.getElementById(E_BANNER); }
6359 function bannerStyleFunc(){ return bannerElem().style; }
6360 var bannerStyle = bannerStyleFunc()
6361 bannerStyle.backgroundImage = "url("+GShellLogo+")";
6362 //bannerStyle.backgroundImage = "url("+GShellInsideIcon+")";
6363 //bannerStyle.backgroundImage = "url("+GShellFavicon+")";
6364 GMenu.style.backgroundImage = "url("+GShellInsideIcon+")";
6365
6366 function footerElem(){ return document.getElementById(E_FOOTER); }
6367 function footerStyle(){ return footerElem().style; }
6368 footerElem().style.backgroundImage="url("+ITSMOREQR+")";
6369 //footerStyle().backgroundImage = "url("+ITSMOREQR+")";
6370
6371 function html_fold(e){
6372 if( e.innerHTML == "Fold" ){
6373 e.innerHTML = "Unfold"
6374 document.getElementById('gsh-menu-exit').innerHTML=""

```

```

6375     document.getElementById('GshStatement').open=false
6376     GshFeatures.open = false
6377     document.getElementById('html-src').open=false
6378     document.getElementById(E_GINDEX).open=false
6379     document.getElementById(E_GOCODE).open=false
6380     document.getElementById(E_TODO).open=false
6381     document.getElementById('References').open=false
6382 }else{
6383     e.innerHTML = "Fold"
6384     document.getElementById('GshStatement').open=true
6385     GshFeatures.open = true
6386     document.getElementById(E_GINDEX).open=true
6387     document.getElementById(E_GOCODE).open=true
6388     document.getElementById(E_TODO).open=true
6389     document.getElementById('References').open=true
6390 }
6391 }
6392 function html_pure(e){
6393     if( e.innerHTML == "Pure" ){
6394         document.getElementById('gsh').style.display=true
6395         //document.style.display = false
6396         e.innerHTML = "Unpure"
6397     }else{
6398         document.getElementById('gsh').style.display=false
6399         //document.style.display = true
6400         e.innerHTML = "Pure"
6401     }
6402 }
6403
6404 var bannerIsStopping = false
6405 //NOTE: .com/JSREF/prop_style_backgroundposition.asp
6406 function shiftBG(){
6407     bannerIsStopping = !bannerIsStopping
6408     bannerStyle.backgroundPosition = "0 0";
6409 }
6410 // status should be inherited on Window Fork(), so use the status in DOM
6411 function html_stop(e,toggle){
6412     if( toggle ){
6413         if( e.innerHTML == "Stop" ){
6414             bannerIsStopping = true
6415             e.innerHTML = "Start"
6416         }else{
6417             bannerIsStopping = false
6418             e.innerHTML = "Stop"
6419         }
6420     }else{
6421         // update JavaScript variable from DOM status
6422         if( e.innerHTML == "Stop" ){ // shown if it's running
6423             bannerIsStopping = false
6424         }else{
6425             bannerIsStopping = true
6426         }
6427     }
6428 }
6429 html_stop(document.getElementById('GshMenuStop'),false) // onInit.
6430 //html_stop(bannerElem(),false) // onInit.
6431
6432 //https://www.w3schools.com/jsref/met_win_setinterval.asp
6433 function shiftBanner(){
6434     var now = new Date().getTime();
6435     //console.log("now="+now%10)
6436     if( !bannerIsStopping ){
6437         bannerStyle.backgroundPosition = ((now/10)%100000)+" 0";
6438     }
6439 }
6440 setInterval(shiftBanner,10); // onInit.
6441
6442 // <a href="https://developer.mozilla.org/ja/docs/Web/API/Window/open">window.open()</a>
6443 // from embedded html to standalone page
6444 var MyChildren = 0
6445 function html_fork(){
6446     GJFactory_Destroy()
6447     MyChildren += 1
6448     WinId = document.getElementById('gsh-WinId').innerHTML + "." + MyChildren;
6449     newwin = window.open("",WinId,"");
6450     src = document.getElementById("gsh");
6451     srhtml = src.outerHTML
6452     newwin.document.write("<"+srhtml>\n");
6453     newwin.document.write(srhtml);
6454     newwin.document.write("<"+"/html>\n");
6455     newwin.document.getElementById('gsh-menu-exit').innerHTML = "Close";
6456     newwin.document.getElementById('gsh-WinId').innerHTML = WinId;
6457     newwin.document.close();
6458     newwin.focus();
6459 }
6460 function html_close(){
6461     window.close()
6462 }
6463 function win_jump(win){
6464     //win = window.top;
6465     win = window.opener; // https://developer.mozilla.org/ja/docs/Web/API/window/opener
6466     if( win == null ){
6467         console.log("jump to window.opener("+win+") (Error)\n")
6468     }else{
6469         console.log("jump to window.opener("+win+")\n")
6470         win.focus();
6471     }
6472 }
6473
6474 // 0.2.9 2020-0902 created chekcsom of HTML
6475 CRC32UNIX = 0x04c11db7 // Unix cksum
6476 function byteCRC32add(bigcrc,octstr,octlen){
6477     var crc = new Int32Array(1)
6478     crc[0] = bigcrc
6479
6480     let oi = 0
6481     for( ; oi < octlen; oi++ ){
6482         var oct = new Int8Array(1)
6483         oct[0] = octstr[oi]
6484         for( bi = 0; bi < 8; bi++ ){
6485             //console.log("--CRC32 "+crc[0]+" "+oct[0].toString(16)+" ["+oi+"."+bi+"]\n")
6486             ovf1 = crc[0] < 0 ? 1 : 0
6487             ovf2 = oct[0] < 0 ? 1 : 0
6488             ovf = ovf1 ^ ovf2
6489             oct[0] <<= 1
6490             crc[0] <<= 1
6491             if( ovf ){ crc[0] ^= CRC32UNIX }
6492         }
6493     }
6494     //console.log("--CRC32 byteAdd return crc="+crc[0]+","+oi+"/"+octlen+"\n")
6495     return crc[0];
6496 }
6497 function strCRC32add(bigcrc,stri,strlen){
6498     var crc = new Uint32Array(1)
6499     crc[0] = bigcrc

```

```

6500 var code = new Uint8Array(strlen);
6501 for( i = 0; i < strlen; i++){
6502     code[i] = stri.charCodeAt(i) // not charAt() !!!!
6503     //console.log("==" +code[i].toString(16)+" <== "+stri[i]+\n")
6504 }
6505 crc[0] = byteCRC32add(crc,code,strlen)
6506 //console.log("--CRC32 strAdd return crc="+crc[0]+\n")
6507 return crc[0]
6508 }
6509 function byteCRC32end(bigcrc,len){
6510     var crc = new Uint32Array(1)
6511     crc[0] = bigcrc
6512     var slen = new Uint8Array(4)
6513     let li = 0
6514     for( ; li < 4; ){
6515         slen[li] = len
6516         li += 1
6517         len >>= 8
6518         if( len == 0 ){
6519             break
6520         }
6521     }
6522     crc[0] = byteCRC32add(crc[0],slen,li)
6523     crc[0] ^= 0xFFFFFFFF
6524     return crc[0]
6525 }
6526 function strCRC32(stri,len){
6527     var crc = new Uint32Array(1)
6528     crc[0] = 0
6529     crc[0] = strCRC32add(0,stri,len)
6530     crc[0] = byteCRC32end(crc[0],len)
6531     //console.log("--CRC32 "+crc[0]+" "+len+"\n")
6532     return crc[0]
6533 }
6534 function getSourceText(){
6535     version = document.getElementById('GshVersion').innerHTML
6536     sfavico = document.getElementById('GshFaviconURL').href;
6537     sbanner = document.getElementById('GshBanner').style.backgroundImage;
6538     spositi = document.getElementById('GshBanner').style.backgroundPosition;
6539     sfooter = document.getElementById('GshFooter').style.backgroundImage;
6540
6541     if( document.getElementById('GJC_1') ){ GJC_1.remove() }
6542
6543     // these should be removed by CSS selector or class, after sevaed to non-printed attribute
6544     GshBanner.removeAttribute('style');
6545     GshFooter.removeAttribute('style');
6546     document.getElementById('GshMenuSign').removeAttribute("style");
6547     styleGMenu = GMenu.getAttribute("style")
6548     GMenu.removeAttribute("style");
6549     styleGStat = GStat.getAttribute("style")
6550     GStat.removeAttribute("style");
6551     styleGTop = GTop.getAttribute("style")
6552     GTop.removeAttribute("style");
6553     styleGshGrid = GshGrid.getAttribute("style")
6554     GshGrid.removeAttribute("style");
6555     //styleGPos = GPos.getAttribute("style");
6556     //GPos.removeAttribute("style");
6557     //GPos.innerHTML = "";
6558     //styleGLog = GLog.getAttribute("style");
6559     //GLog.removeAttribute("style");
6560     //GLog.innerHTML = "";
6561     styleGShellPlane = GShellPlane.getAttribute("style")
6562     GShellPlane.removeAttribute("style")
6563     styleRawTextViewer = RawTextViewer.getAttribute("style")
6564     RawTextViewer.removeAttribute("style")
6565     styleRawTextViewerClose = RawTextViewerClose.getAttribute("style")
6566     RawTextViewerClose.removeAttribute("style")
6567
6568     GshFaviconURL.href = "";
6569
6570     //it seems that interHTML and outerHTML generate style="" for these (??)
6571     //GshBanner.removeAttribute('style');
6572     //GshFooter.removeAttribute('style');
6573     //GshMenuSign.removeAttribute('style');
6574     GshBanner.style=""
6575     GshFooter.style=""
6576     GshMenuSign.style=""
6577
6578     textarea = document.createElement("textarea")
6579     srchtml = document.getElementById("gsh").outerHTML;
6580     //textarea = document.createElement("textarea")
6581     // 2020-0910 ?? ... this causes inserting style="" to Banner and Footer,
6582     // with Chromium?/ after reloading from file:///
6583     textarea.innerHTML = srchtml
6584     // <a href="https://stackoverflow.com/questions/5796718/html-entity-decode">Thanks</a>
6585     var rawtext = textarea.value
6586     //textarea.destroy()
6587     //rawtext = gsh.textContent // this removes #include <FILENAME> too
6588     var orgtext = ""
6589     + "/*<+>html>\n" // lost preamble text
6590     + rawtext
6591     + "<+>/html>\n" // lost trail text
6592     ;
6593
6594     tlen = orgtext.length
6595     //console.log("getSourceText: length="+tlen+"\n")
6596     document.getElementById('GshFaviconURL').href = sfavico;
6597
6598     document.getElementById('GshBanner').style.backgroundImage = sbanner;
6599     document.getElementById('GshBanner').style.backgroundPosition = spositi;
6600     document.getElementById('GshFooter').style.backgroundImage = sfooter;
6601
6602     GStat.setAttribute("style",styleGStat)
6603     GMenu.setAttribute("style",styleGMenu)
6604     GTop.setAttribute("style",styleGTop)
6605     //GLog.setAttribute("style",styleGLog)
6606     //GPos.setAttribute("style",styleGPos)
6607     GshGrid.setAttribute("style",styleGshGrid)
6608     GShellPlane.setAttribute("style",styleGShellPlane)
6609     RawTextViewer.setAttribute("style",styleRawTextViewer)
6610     RawTextViewerClose.setAttribute("style",styleRawTextViewerClose)
6611     canontext = orgtext.replace(' style=""','')
6612     // open="" too
6613     return canontext
6614 }
6615 function getDigest(){
6616     var text = ""
6617     text = getSourceText()
6618     var digest = ""
6619     tlen = text.length
6620     digest = strCRC32(text,tlen) + " " + tlen
6621     return { text, digest }
6622 }
6623 function html_digest(){
6624     version = document.getElementById('GshVersion').innerHTML

```

```

6625     let {text, digest} = getDigest()
6626     alert("cksum: " + digest + " " + version)
6627 }
6628 function charsIn(str, char){
6629     ln = 0;
6630     for( i = 0; i < str.length; i++){
6631         if( str.charCodeAt(i) == char.charCodeAt(0) )
6632             ln++;
6633     }
6634     return ln;
6635 }
6636
6637 //class digestElement extends HTMLElement { }
6638 //< script>customElements.define('digest',digestElement)< /script>
6639 function showDigest(e){
6640     result = 'version=' + GshVersion.innerHTML + '\n'
6641     result += 'lines=' + e.dataset.lines + '\n'
6642     result += 'length=' + e.dataset.length + '\n'
6643     result += 'crc32u=' + e.dataset.crc32u + '\n'
6644     result += 'time=' + e.dataset.time + '\n';
6645
6646     alert(result)
6647 }
6648
6649 function html_sign(e){
6650     if( RawTextViewer.style.zIndex == 1000 ){
6651         hideRawTextViewer()
6652         return
6653     }
6654     GJFactory_Destroy()
6655     //gsh digest _innerHTML = "";
6656     text = getSourceText() // the original text
6657     tlen = text.length
6658     digest = strCRC32(text,tlen)
6659     //gsh digest _innerHTML = digest + " " + tlen
6660     //text = getSourceText() // the text with its digest
6661     Lines = charsIn(text,'\n')
6662
6663     name = "gsh"
6664     sid = name + "-digest"
6665     d = new Date()
6666     signedAt = d.getTime()
6667
6668     sign = '/' + '<' + 'span\n'
6669     + ' id="' + sid + '"\n'
6670     + ' class=" digest "\n'
6671     + ' data-target-id="' + name + '"\n'
6672     + ' data-crc32u="' + digest + '"\n'
6673     + ' data-length="' + tlen + '"\n'
6674     + ' data-lines="' + Lines + '"\n'
6675     + ' data-time="' + signedAt + '"\n'
6676     + '>' + '/span>\n*' + '/\n'
6677
6678     text = sign + text
6679
6680     txthtml = '<' + 'table id="LineNumbered"><' + 'tr><' + 'td'
6681     + '<' + 'textarea cols=5 rows=' + Lines + ' class="LineNumber">'
6682     for( i = 1; i <= Lines; i++){
6683         txthtml += i.toString() + '\n'
6684     }
6685     txthtml += ""
6686     + '<' + '/textarea>'
6687     + '<' + '/td><' + 'td'
6688     + '<' + 'textarea cols=150 rows=' + Lines + 'spellcheck="false"'
6689     + ' class="LineNumbered">'
6690     + text + '<' + '/textarea>'
6691     + '<' + '/td><' + '/tr><' + '/table>'
6692
6693     for( i = 1; i <= 30; i++){
6694         txthtml += '<br>\n'
6695     }
6696     RawTextViewer.innerHTML = txthtml
6697
6698     btn = e
6699     e.style.color = "rgba(128,128,255,0.9)";
6700     y = e.getBoudingClientRect().top.toFixed(0)
6701     //h = e.getBoudingClientRect().height.toFixed(0)
6702     RawTextViewer.style.top = Number(y) + 30
6703     RawTextViewer.style.left = 100;
6704     RawTextViewer.style.height = window.innerHeight - 20;
6705     //RawTextViewer.style.Opacity = 1.0;
6706     //RawTextViewer.style.backgroundColor = "rgba(0,0,0,0.0)";
6707     RawTextViewer.style.backgroundColor = "rgba(255,255,255,0.8)";
6708     RawTextViewer.style.zIndex = 1000;
6709     RawTextViewer.style.display = true;
6710
6711     if( RawTextViewerClose.style == null ){
6712         RawTextViewerClose.style = "";
6713     }
6714     RawTextViewerClose.style.top = Number(y) + 10
6715     RawTextViewerClose.style.left = 100;
6716     RawTextViewerClose.style.zIndex = 1001;
6717
6718     ScrollToElement(CurElement,RawTextViewerClose)
6719 }
6720 function hideRawTextViewer(){
6721     RawTextViewer.style.left = 10000;
6722     RawTextViewer.style.zIndex = -100;
6723     RawTextViewer.style.Opacity = 0.0;
6724     RawTextViewer.style = null
6725     RawTextViewer.innerHTML = "";
6726
6727     GshMenuSign.style.color = "rgba(255,128,128,1.0)";
6728     RawTextViewerClose.style.top = 0;
6729     RawTextViewerClose.style = null
6730 }
6731
6732 // source code viewr
6733 function frame_close(){
6734     srcframe = document.getElementById("src-frame");
6735     srcframe.innterHTML = "";
6736     //srcframe.style.cols = 1;
6737     srcframe.style.rows = 1;
6738     srcframe.style.height = 0;
6739     srcframe.style.display = false;
6740     src = document.getElementById("src-frame-textarea");
6741     src.innerHTML = ""
6742     //src.cols = 0
6743     src.rows = 0
6744     src.display = false
6745     //alert("--closed--")
6746 }
6747 //<<!-- | <span onclick="html_view();">Source</span> -->
6748 //<<!-- | <span onclick="frame_close();">SourceClose</span> -->
6749 //<<!-- | <span>Download</span> -->

```

```

6750 function frame_open(){
6751     document.getElementById('GshFaviconURL').href = "";
6752     oldsrc = document.getElementById("GENSRC");
6753     if( oldsrc != null ){
6754         //alert("--I--(erasing old text)")
6755         oldsrc.innerHTML = "";
6756         return
6757     }else{
6758         //alert("--I--(no old text)")
6759     }
6760     styleBanner = GshBanner.getAttribute("style")
6761     GshBanner.removeAttribute("style")
6762     styleFooter = GshFooter.getAttribute("style")
6763     GshFooter.removeAttribute("style")
6764     if( document.getElementById('GJC_1') ){ GJC_1.remove() }
6765
6766     GshFaviconURL.href = "";
6767     CStat.removeAttribute('style')
6768     GshGrid.removeAttribute('style')
6769     GshMenuSign.removeAttribute('style')
6770     //GPos.removeAttribute('style')
6771     //GPos.innerHTML = "";
6772     //GLog.removeAttribute('style')
6773     //GLog.innerHTML = "";
6774     GMenu.removeAttribute('style')
6775     CTop.removeAttribute('style')
6776     GShellPlane.removeAttribute('style')
6777     RawTextViewer.removeAttribute('style')
6778     RawTextViewerClose.removeAttribute('style')
6779
6780     GJFactory_Destroy()
6781
6782     src = document.getElementById("gsh");
6783     srchtml = src.outerHTML
6784     srcframe = document.getElementById("src-frame");
6785     srcframe.innerHTML = "
6786     + "<"+cite id=\"GENSRC\">\n"
6787     + "<"+style>\n"
6788     + "#GENSRC textarea{tab-size:4;}\n"
6789     + "#GENSRC textarea(-o-tab-size:4;)\n"
6790     + "#GENSRC textarea(-moz-tab-size:4;)\n"
6791     + "#GENSRC textarea(spellcheck:false;)\n"
6792     + "</"+style>\n"
6793     + "<"+textarea id=\"src-frame-textarea\" cols=100 rows=20 class=\"gsh-code\">"
6794     + "/*<+html>\n" // lost preamble text
6795     + srchtml
6796     + "<"+/html>\n" // lost trail text
6797     + "<"+textarea>\n"
6798     + "</"+cite><!-- GENSRC -->\n";
6799
6800     //srcframe.style.cols = 80;
6801     //srcframe.style.rows = 80;
6802
6803     GshBanner.setAttribute('style',styleBanner)
6804     GshFooter.setAttribute('style',styleFooter)
6805 }
6806 function fill_CSSView(){
6807     part = document.getElementById('GshStyleDef')
6808     view = document.getElementById('gsh-style-view')
6809     view.innerHTML = "
6810     + "<"+textarea cols=100 rows=20 class=\"gsh-code\">"
6811     + part.innerHTML
6812     + "<"+/textarea>"
6813 }
6814 function fill_JavaScriptView(){
6815     jspart = document.getElementById('gsh-script')
6816     view = document.getElementById('gsh-script-view')
6817     view.innerHTML = "
6818     + "<"+textarea cols=100 rows=20 class=\"gsh-code\">"
6819     + jspart.innerHTML
6820     + "<"+/textarea>"
6821 }
6822 function fill_DataView(){
6823     part = document.getElementById('gsh-data')
6824     view = document.getElementById('gsh-data-view')
6825     view.innerHTML = "
6826     + "<"+textarea cols=100 rows=20 class=\"gsh-code\">"
6827     + part.innerHTML
6828     + "<"+/textarea>"
6829 }
6830 function jumpto_StyleView(){
6831     jsview = document.getElementById('html-src')
6832     jsview.open = true
6833     jsview = document.getElementById('gsh-style-frame')
6834     jsview.open = true
6835     fill_CSSView()
6836 }
6837 function jumpto_JavaScriptView(){
6838     jsview = document.getElementById('html-src')
6839     jsview.open = true
6840     jsview = document.getElementById('gsh-script-frame')
6841     jsview.open = true
6842     fill_JavaScriptView()
6843 }
6844 function jumpto_DataView(){
6845     jsview = document.getElementById('html-src')
6846     jsview.open = true
6847     jsview = document.getElementById('gsh-data-frame')
6848     jsview.open = true
6849     fill_DataView()
6850 }
6851 function jumpto_WholeView(){
6852     jsview = document.getElementById('html-src')
6853     jsview.open = true
6854     jsview = document.getElementById('gsh-whole-view')
6855     jsview.open = true
6856     frame_open()
6857 }
6858 function html_view(){
6859     html_stop();
6860
6861     banner = document.getElementById('GshBanner').style.backgroundImage;
6862     footer = document.getElementById('GshFooter').style.backgroundImage;
6863     document.getElementById('GshBanner').style.backgroundImage = "";
6864     document.getElementById('GshBanner').style.backgroundPosition = "";
6865     document.getElementById('GshFooter').style.backgroundImage = "";
6866
6867     //srcwin = window.open("", "CodeView2", "");
6868     srcwin = window.open("", "", "");
6869     srcwin.document.write("<span id=\"gsh\">\n");
6870
6871     src = document.getElementById("gsh");
6872     srcwin.document.write("<"+style>\n");
6873     srcwin.document.write("textarea{tab-size:4;}\n");
6874     srcwin.document.write("textarea(-o-tab-size:4;)\n");

```

```

6875 srcwin.document.write("textarea{-moz-tab-size:4;}\n");
6876 srcwin.document.write("</style>\n");
6877 srcwin.document.write("<h2>\n");
6878 srcwin.document.write("<+>span onclick=\"window.close();\">Close</span> | \n");
6879 //srcwin.document.write("<+>span onclick=\"html_stop();\">Run</span>\n");
6880 srcwin.document.write("</h2>\n");
6881 srcwin.document.write("<textarea id=\"gsh-src-src\" cols=100 rows=60>\n");
6882 srcwin.document.write("<+>html>\n");
6883 srcwin.document.write("<+>span id=\"gsh\">");
6884 srcwin.document.write(src.innerHTML);
6885 srcwin.document.write("<+>span>+>/html>\n");
6886 srcwin.document.write("</+>textarea>\n");
6887
6888 document.getElementById('GshBanner').style.backgroundImage = banner;
6889 document.getElementById('GshFooter').style.backgroundImage = footer
6890
6891 sty = document.getElementById("GshStyleDef");
6892 srcwin.document.write("<+>style>\n");
6893 srcwin.document.write(sty.innerHTML);
6894 srcwin.document.write("<+>/style>\n");
6895
6896 run = document.getElementById("gsh-script");
6897 srcwin.document.write("<+>script>\n");
6898 srcwin.document.write(run.innerHTML);
6899 srcwin.document.write("<+>/script>\n");
6900
6901 srcwin.document.write("<+>/span><+>/html>\n"); // gsh span
6902 srcwin.document.close();
6903 srcwin.focus();
6904 }
6905 GSH = document.getElementById("gsh")
6906
6907 //GSH.onclick = "alert('Ouch!');"
6908 //GSH.css = "{background-color:#eef;}";
6909 //GSH.style = "background-color:#eef;";
6910 //GSH.style.display = false;
6911 //alert('Ouch0!')
6912 //GSH.style.display = true;
6913
6914 // 2020-0904 created, tentative
6915 document.addEventListener('keydown', jgshCommand);
6916 //CurElement = GshStatement
6917 CurElement = GshMenu
6918 MemElement = GshMenu
6919
6920 function nextSib(e){
6921     n = e.nextSibling;
6922     for( i = 0; i < 100; i++ ){
6923         if( n == null ){
6924             break;
6925         }
6926         if( n.nodeName == "DETAILS" ){
6927             return n;
6928         }
6929         n = n.nextSibling;
6930     }
6931     return null;
6932 }
6933 function prevSib(e){
6934     n = e.previousSibling;
6935     for( i = 0; i < 100; i++ ){
6936         if( n == null ){
6937             break;
6938         }
6939         if( n.nodeName == "DETAILS" ){
6940             return n;
6941         }
6942         n = n.previousSibling;
6943     }
6944     return null;
6945 }
6946 function setColor(e,eName,eColor){
6947     if( e.hasChildNodes() ){
6948         s = e.childNodes;
6949         if( s != null ){
6950             for( ci = 0; ci < s.length; ci++ ){
6951                 if( s[ci].nodeName == eName ){
6952                     s[ci].style.color = eColor;
6953                     //s[ci].style.backgroundColor = eColor;
6954                     break;
6955                 }
6956             }
6957         }
6958     }
6959 }
6960
6961 // https://docs.microsoft.com/en-us/previous-versions//hh781509(v=vs.85)
6962 function showCurElementPosition(ev){
6963     // if( document.getElementById("GPos") == null ){
6964     //     return;
6965     // }
6966     // if( GPos == null ){
6967     //     return;
6968     // }
6969     e = CurElement
6970     y = e.getBoundingClientRect().top.toFixed(0)
6971     x = e.getBoundingClientRect().left.toFixed(0)
6972
6973     h = ev + " "
6974     h += 'y='+y+" "+ 'x='+x+" -- "
6975     h += "w=" + window.innerWidth + " , h=" + window.innerHeight + " -- "
6976     //GPos.test = h
6977     //GPos.innerHTML = h
6978     // GPos.innerHTML = h
6979 }
6980
6981 function DateShort(){
6982     d = new Date()
6983     return d.getFullYear() + "/" + d.getMonth() + "/" + d.getDate() + " "
6984     + d.getHours() + ":" + d.getMinutes() + ":" + d.getSeconds()
6985 }
6986 function DateLong(){
6987     d = new Date()
6988     return d.getFullYear() + "/" + d.getMonth() + "/" + d.getDate() + " "
6989     + d.getHours() + ":" + d.getMinutes() + ":" + d.getSeconds()
6990     + "." + d.getMilliseconds()
6991     + " " + d.getTimezoneOffset()/60
6992     + " "
6993     + d.getTime() + " " + d.getMilliseconds()
6994 }
6995 }
6996 function GShellMenu(e){
6997     //GLog.innerHTML = "Hello, World! (" + DateLong() + ")"
6998     showGShellPlane()
6999 }

```

```

7000 // placements of planes
7001 function GShellResizeX(ev){
7002     //if( document.getElementById("GMenu") != null ){
7003         GMenu.style.left = window.innerWidth - 100
7004         GMenu.style.top = window.innerHeight - 90
7005         //console.log("place GMENU "+GMenu.style.left+" "+GMenu.style.top)
7006     }
7007     //}
7008     GStat.style.width = window.innerWidth
7009     //if( document.getElementById("GPos") != null ){
7010         //GPos.style.width = window.innerWidth
7011         //GPos.style.top = window.innerHeight - 30; //GPos.style.height
7012     //}
7013     //if( document.getElementById("GLog") != null ){
7014         // GLog.style.width = window.innerWidth
7015         //GLog.innerHTML = ""
7016     //}
7017     //if( document.getElementById("GLog") != null ){
7018         //GLog.innerHTML = "Resize: w=" + window.innerWidth +
7019         //", h=" + window.innerHeight
7020     //}
7021     showCurElementPosition(ev)
7022 }
7023 function GShellResize(){
7024     GShellResizeX(["RESIZE"])
7025 }
7026 window.onresize = GShellResize
7027 var prevNode = null
7028 function GJSH_OnMouseMove(ev){
7029     x = ev.clientX
7030     y = ev.clientY
7031     d = new Date()
7032     t = d.getTime() / 1000
7033     if( document.elementFromPoint ){
7034         e = document.elementFromPoint(x,y)
7035         if( e != null ){
7036             if( e == prevNode ){
7037                 }else{
7038                     console.log(t+'('+x+', '+y+') '
7039                         +e.nodeType+' '+e.tagName+'#'+e.id)
7040                     prevNode = e
7041                 }
7042             }else{
7043                 console.log(t+'('+x+', '+y+') no element')
7044             }
7045         }else{
7046             console.log(t+'('+x+', '+y+') no elementFromPoint')
7047         }
7048     }
7049     window.addEventListener('mousemove', GJSH_OnMouseMove);
7050 }
7051 function GJSH_OnMouseMoveScreen(ev){
7052     x = ev.screenX
7053     y = ev.screenY
7054     d = new Date()
7055     t = d.getTime() / 1000
7056     console.log(t+'('+x+', '+y+') no elementFromPoint')
7057 }
7058 //screen.addEventListener('mousemove', GJSH_OnMouseMoveScreen);
7059 }
7060 function ScrollToElement(oe, ne){
7061     ne.scrollIntoView()
7062     ny = ne.getBoundingClientRect().top.toFixed(0)
7063     nx = ne.getBoundingClientRect().left.toFixed(0)
7064     //GLog.innerHTML = "["+ny+", "+nx+"]"
7065     //window.scrollTo(0,0)
7066 }
7067     CTop.style.backgroundColor = "rgba(0,0,0,0.0)"
7068     GshGrid.style.left = '250px';
7069     GshGrid.style.zIndex = 0
7070     return
7071     oy = oe.getBoundingClientRect().top.toFixed(0)
7072     ox = oe.getBoundingClientRect().left.toFixed(0)
7073     y = e.getBoundingClientRect().top.toFixed(0)
7074     x = e.getBoundingClientRect().left.toFixed(0)
7075     window.scrollTo(x,y)
7076     ny = e.getBoundingClientRect().top.toFixed(0)
7077     nx = e.getBoundingClientRect().left.toFixed(0)
7078     //GLog.innerHTML = "["+oy+", "+ox+"]->["+y+", "+x+"]->["+ny+", "+nx+"]"
7079 }
7080 function showGShellPlane(){
7081     if( GShellPlane.style.zIndex == 0 ){
7082         GShellPlane.style.zIndex = 1000;
7083         GShellPlane.style.left = 30;
7084         GShellPlane.style.height = 320;
7085         GShellPlane.innerHTML = DateLong() + "<br>" +
7086         "-- History --<br>" + MyHistory;
7087     }else{
7088         GShellPlane.style.zIndex = 0;
7089         GShellPlane.style.left = 0;
7090         GShellPlane.style.height = 50;
7091         GShellPlane.innerHTML = "";
7092     }
7093 }
7094 var SuppressGJShell = false
7095 function jgshCommand(kevent){
7096     if( SuppressGJShell ){
7097         return
7098     }
7099     key = kevent
7100     keycode = key.code
7101     //GStat.style.width = window.innerWidth
7102     GStat.style.backgroundColor = "rgba(0,0,0,0.4)"
7103 }
7104     console.log("JSGsh-Key: "+keycode+"(^-)/")
7105     if( keycode == "Slash" ){
7106         console.log('('+x+', '+y+') ')
7107         e = document.elementFromPoint(x,y)
7108         console.log('('+x+', '+y+') '+e.nodeType+' '+e.tagName+'#'+e.id)
7109     }else
7110     if( keycode == "Digit0" ){ // fold side-bar
7111         // "Zero page"
7112         showGShellPlane();
7113     }else
7114     if( keycode == "Digit1" ){ // fold side-bar
7115         primary.style.width = "94%"
7116         secondary.style.width = "0%"
7117         secondary.style.opacity = 0
7118         GStat.innerHTML = "[Single Column View]"
7119     }else
7120     if( keycode == "Digit2" ){ // unfold side-bar
7121         primary.style.width = "58%"
7122         secondary.style.width = "36%"
7123         secondary.style.opacity = 1
7124         GStat.innerHTML = "[Double Column View]"

```

```

7125 }else
7126 if( keycode == "KeyU" ){ // fold/unfold all
7127     html_fold(GshMenuFold);
7128     location.href = "#"+CurElement.id;
7129 }else
7130 if( keycode == "KeyO" || keycode == "ArrowRight" ){ // fold the element
7131     CurElement.open = !CurElement.open;
7132 }else
7133 if( keycode == "ArrowRight" ){ // unfold the element
7134     CurElement.open = true
7135 }else
7136 if( keycode == "ArrowLeft" ){ // unfold the element
7137     CurElement.open = false
7138 }else
7139 if( keycode == "KeyI" ){ // inspect the element
7140     e = CurElement
7141     //GLog.innerHTML =
7142     GJLog_append("Current Element: " + e + "<br>"
7143         + "name="+e.nodeName + ", "
7144         + "id="+e.id + " "
7145         + "children="+e.childNodes.length + ", "
7146         + "parent="+e.parentNode.id + "<br>"
7147         + "text="+e.textContent)
7148     GStat.style.backgroundColor = "rgba(0,0,0,0.8)"
7149     return
7150 }else
7151 if( keycode == "KeyM" ){ // memory the position
7152     MemElement = CurElement
7153 }else
7154 if( keycode == "KeyN" || keycode == "ArrowDown" ){ // next element
7155     e = nextSib(CurElement)
7156     if( e != null ){
7157         setColor(CurElement,"SUMMARY","#fff")
7158         setColor(e,"SUMMARY","#8f8") // should be complement ?
7159         oe = CurElement
7160         CurElement = e
7161         //location.href = "#"+e.id;
7162         ScrollToElement(oe,e)
7163     }
7164 }else
7165 if( keycode == "KeyP" || keycode == "ArrowUp" ){ // previous element
7166     oe = CurElement
7167     e = prevSib(CurElement)
7168     if( e != null ){
7169         setColor(CurElement,"SUMMARY","#fff")
7170         setColor(e,"SUMMARY","#8f8") // should be complement ?
7171         CurElement = e
7172         //location.href = "#"+e.id;
7173         ScrollToElement(oe,e)
7174     }else{
7175         e = document.getElementById("GshBanner")
7176         if( e != null ){
7177             setColor(CurElement,"SUMMARY","#fff")
7178             CurElement = e
7179             ScrollToElement(oe,e)
7180         }else{
7181             e = document.getElementById("primary")
7182             if( e != null ){
7183                 setColor(CurElement,"SUMMARY","#fff")
7184                 CurElement = e
7185                 ScrollToElement(oe,e)
7186             }
7187         }
7188     }
7189 }else
7190 if( keycode == "KeyR" ){
7191     location.reload()
7192 }else
7193 if( keycode == "KeyJ" ){
7194     GshGrid.style.top = '120px';
7195     GshGrid.innerHTML = '>_<{Down}';
7196 }else
7197 if( keycode == "KeyK" ){
7198     GshGrid.style.top = '0px';
7199     GshGrid.innerHTML = '^_^){Up}';
7200 }else
7201 if( keycode == "KeyH" ){
7202     GshGrid.style.left = '0px';
7203     GshGrid.innerHTML = '(_){Left}';
7204 }else
7205 if( keycode == "KeyL" ){
7206     //GLog.innerHTML +=
7207     GJLog_append(
7208         'screen='+screen.width+'px'+<br>'+
7209         'window='+window.innerWidth+'px'+<br>'+
7210     )
7211     GshGrid.style.left = (document.documentElement.clientWidth-160).toString(10)+'px';
7212     GshGrid.innerHTML = '@_@){Right}';
7213 }else
7214 if( keycode == "KeyS" ){
7215     html_stop(GshMenuStop,true)
7216 }else
7217 if( keycode == "KeyF" ){
7218     html_fork()
7219 }else
7220 if( keycode == "KeyC" ){
7221     window.close()
7222 }else
7223 if( keycode == "KeyD" ){
7224     html_digest()
7225 }else
7226 if( keycode == "KeyV" ){
7227     e = document.getElementById('gsh-digest')
7228     if( e != null ){
7229         showDigest(e)
7230     }
7231 }
7232 }
7233 showCurElementPosition(["+key.code+" --]);
7234 //if( document.getElementById("GPos") != null ){
7235 //GPos.innerHTML += ["+key.code+" --]
7236 //}
7237 //GShellResizeX(["+key.code+" --]);
7238 }
7239 GShellResizeX(["INIT"]);
7240
7241 DisplaySize = '-- Display: '+ 'screen='+screen.width+'px, '+ 'window='+window.innerWidth+'px';
7242
7243 let {text, digest} = getDigest()
7244 //GLog.innerHTML +=
7245 GJLog_append(
7246     '-- GShell: ' + GshVersion.innerHTML + '\n' +
7247     '-- Digest: ' + digest + '\n' +
7248     DisplaySize
7249 //+ "<br>" + "-- LastVisit:<br>" + MyHistory

```

```

7250 }
7251 GShellResizeX(null);
7252
7253 // <a href="https://www.w3.org/TR/WebCryptoAPI/">Web Cryptography API</a>
7254 // Convert a string into an ArrayBuffer
7255 // from https://developers.google.com/web/updates/2012/06/How-to-convert-ArrayBuffer-to-and-from-String
7256 function str2ab(str) {
7257     const buf = new ArrayBuffer(str.length);
7258     const bufView = new Uint8Array(buf);
7259     for (let i = 0, strLen = str.length; i < strLen; i++) {
7260         bufView[i] = str.charCodeAt(i);
7261     }
7262     return buf;
7263 }
7264 function importPrivateKey(pem) {
7265     const binaryDerString = window.atob(pemContents);
7266     const binaryDer = str2ab(binaryDerString);
7267     return window.crypto.subtle.ImportKey(
7268         "pkcs8",
7269         binaryDer,
7270         {
7271             name: "RSA-PSS",
7272             modulusLength: 2048,
7273             publicExponent: new Uint8Array([1, 0, 1]),
7274             hash: "SHA-256",
7275         },
7276         true,
7277         ["sign"]
7278     );
7279 }
7280 //importPrivateKey(ppem)
7281
7282 //key = {}
7283 //buf = "abc"
7284 //enc = "xyzxxxxxx"; //crypto.publicEncrypt(key,buf)
7285 //b64 = btoa(enc)
7286 //dec = atob(b64)
7287 //GLog.innerHTML = "enc:" + b64 + ", dec:" + dec
7288
7289 </script>
7290
7291 <span id="gjc" data-title="GJConsole" data-author="sato@its-more.jp">
7292 <!-- ----- GJConsole BEGIN { ----- -->
7293 <p>
7294 <span id="GJE_RootNode"></span>
7295 </p>
7296 <style id="GJConsoleStyle">
7297 .GJConsole {
7298     z-index:1000;
7299     width:400px; height:200px;
7300     margin:2px;
7301     color:#fff; background-color:#66a;
7302     font-size:12px; font-family:monospace,Courier New;
7303 }
7304 </style>
7305
7306 <script id="GJConsoleScript" class="GJConsole">
7307 var PS1 = "$ "
7308 function GJC_KeyDown(keyevent){
7309     key = keyevent.code
7310     if( key == "Enter" ){
7311         GJC_Command(this)
7312         this.value += "\n" + PS1 // prompt
7313     }else
7314     if( key == "Escape" ){
7315         SuppressGJShell = false
7316         GshMenu.focus() // should be previous focus
7317     }
7318 }
7319 var GJC_SessionId
7320 function GJC_SetSessionId(){
7321     var xd = new Date()
7322     GJC_SessionId = xd.getTime() / 1000
7323 }
7324 GJC_SetSessionId()
7325 function GJC_Memory(mem,args,text){
7326     argv = args.split(' ')
7327     cmd = argv[0]
7328     argv.shift()
7329     args = argv.join(' ')
7330     ret = ""
7331
7332     if( cmd == 'clear' ){
7333         Permanent.setItem(mem,'')
7334     }else
7335     if( cmd == 'read' ){
7336         ret = Permanent.getItem(mem)
7337     }else
7338     if( cmd == 'save' ){
7339         val = Permanent.getItem(mem)
7340         if( val == null ){ val = "" }
7341         d = new Date()
7342         val += d.getTime()/1000+" "+GJC_SessionId+" "+document.URL+" "+args+"\n"
7343         val += text.value
7344         Permanent.setItem(mem,val)
7345     }else
7346     if( cmd == 'write' ){
7347         val = Permanent.getItem(mem)
7348         if( val == null ){ val = "" }
7349         d = new Date()
7350         val += d.getTime()/1000+" "+GJC_SessionId+" "+document.URL+" "+args+"\n"
7351         Permanent.setItem(mem,val)
7352     }else{
7353         ret = "Commands: write | read | save | clear"
7354     }
7355     return ret
7356 }
7357 // -- 2020-09-14 added TableEditor
7358 GJE_CurElement = GJE_RootNode
7359 GJE_NodeSaved = null
7360 GJE_TableNo = 1
7361 function GJE_SetTableStyle(ev){
7362     stid = this.parentNode.id+this.id+"-style"
7363     e = document.getElementById(stid)
7364     //alert('SetTableStyle #' +e.id+'\n'+this.value)
7365     if( e != null ){
7366         e.innerHTML = this.value
7367     }else{
7368         console.log('Not found: '+stid)
7369     }
7370     //alert('event StopPropagation: '+ev)
7371 }
7372 function GJE_StyleKeyCommand(kev){
7373     keycode = kev.code
7374     console.log('GJE-Key: '+keycode)

```

```

7375     if( keycode == 'Escape' ){
7376         //console.log('Apply the style:')
7377         //stid = this.parentNode.id+this.id+"
7378         //stid = this.id+" +style"
7379         stid = this.parentNode.id+" +style"
7380         e = document.getElementById(stid)
7381         if( e != null ){
7382             console.log('Apply the style:'+e.id+'\n'+this.value)
7383             e.innerHTML = this.value
7384         }else{
7385             console.log('No element to Apply the style: '+stid)
7386         }
7387     }
7388     kev.stopPropagation()
7389     // https://developer.mozilla.org/en-US/docs/Web/API/Event/stopPropagation
7390 }
7391 var GJE_CommandMode = false
7392 function GJE_TableKeyCommand(kev,tab){
7393     wasCmdMode = GJE_CommandMode
7394     key = kev.code
7395     if( key == 'Escape' ){
7396         console.log("To command mode: "+tab.nodeName+"#" +tab.id)
7397         //tab.setAttribute('contenteditable','false')
7398         tab.style.caretColor = "blue"
7399         GJE_CommandMode = true
7400     }else
7401     if( key == "KeyA" ){
7402         tab.style.caretColor = "red"
7403         GJE_CommandMode = false
7404     }else
7405     if( key == "KeyI" ){
7406         tab.style.caretColor = "red"
7407         GJE_CommandMode = false
7408     }else
7409     if( key == "KeyO" ){
7410         tab.style.caretColor = "red"
7411         GJE_CommandMode = false
7412     }else
7413     if( key == "KeyJ" ){
7414         console.log("ROW-DOWN")
7415     }else
7416     if( key == "KeyK" ){
7417         console.log("ROW-UP")
7418     }else
7419     if( key == "Keyw" ){
7420         console.log("COL-FORW")
7421     }else
7422     if( key == "Keyb" ){
7423         console.log("COL-BACK")
7424     }
7425
7426     kev.stopPropagation()
7427     if( wasCmdMode ){
7428         kev.preventDefault()
7429     }
7430 }
7431 function GJE_DragEvent(ev,elem){
7432     x = ev.clientX
7433     y = ev.clientY
7434     console.log("Dragged: "+this.nodeName+'#' +this.id+' x='+x+' y='+y)
7435 }
7436 // https://developer.mozilla.org/en-US/docs/Web/API/DragEvent
7437 // https://www.w3.org/TR/uievents/#events-mouseevents
7438 function GJE_DropEvent(ev,elem){
7439     x = ev.clientX
7440     y = ev.clientY
7441     this.style.x = x
7442     this.style.y = y
7443     this.style.position = 'absolute' // 'fixed'
7444     this.parentNode = gsh // just for test
7445     console.log("Dropped: "+this.nodeName+'#' +this.id+' x='+x+' y='+y
7446     + ' parent='+this.parentNode.id)
7447 }
7448 function makeTable(argv){
7449     tid = ''
7450     cwe = GJE_CurElement
7451     ne = document.createElement('span')
7452     cwe.appendChild(ne)
7453     ne.setAttribute('draggable','true')
7454     ne.addEventListener('drag',GJE_DragEvent);
7455     ne.addEventListener('dragend',GJE_DropEvent);
7456
7457     nt = new Text('\n')
7458     ne.appendChild(nt)
7459     ne.contentEditable = true
7460
7461     var col = 3
7462     var row = 2
7463
7464     if( argv[0] != null ){
7465         col = argv[0]
7466         argv.shift()
7467     }
7468     if( argv[0] != null ){
7469         row = argv[0]
7470         argv.shift()
7471     }
7472
7473     //ne.addEventListener('keydown',GJE_TableKeyCommand);
7474     tid = 'table_' + GJE_TableNo
7475     ne.id = tid
7476     ht = ""
7477     ht += '<'+tid+' table id="'+tid+'.table" class="'+tid+' '
7478     + ' onkeydown="GJE_TableKeyCommand(event,this)" '
7479     //+ ' ondrag="GJE_DragEvent(event,this)"\n'
7480     //+ ' ondragend="GJE_DropEvent(event,this)"\n'
7481     //+ ' draggable="true"\n'
7482     + ' contentEditable="true">\n'
7483     for( r = 0; r < row; r++){
7484         ht += "<"+tr>\n"
7485         for( c = 0; c < col; c++){
7486             ht += "<"+td>"
7487             ht += "ABCDEFGHIJKLMNPOQRSTUVWXYZ".charAt(c) + r
7488             ht += "<"+/td>\n"
7489         }
7490         ht += "<"+/tr>\n"
7491     }
7492     ht += "<"+/table>\n"
7493     ne.innerHTML = ht
7494
7495     st = '.'+tid+' table,tr,td {\n'
7496     + ' +border:1px solid #000;\n'
7497     + ' +background-color:#fff;\n'
7498     + ' +color:#000;\n'
7499     +'}\n'

```

```

7500
7501
7502 //nj = document.createElement('script')
7503 //ne.appendChild(nj)
7504 //ne.innerHTML = 'function SetStyle(e){'
7505
7506
7507 ns = document.createElement('style')
7508 ne.appendChild(ns)
7509 ns.id = tid + '.style'
7510 ns.innerHTML = '\n'+st
7511 nt = new Text('\n')
7512 ne.appendChild(nt)
7513
7514
7515 nx = document.createElement('textarea')
7516 ne.appendChild(nx)
7517 nx.id = tid + '.style_editor'
7518 nx.spellcheck = false
7519 nx.cols = 30
7520 nx.rows = 7
7521 nx.innerHTML = '\n'+st
7522 nx.addEventListener('change',GJE_SetTableStyle);
7523 nx.addEventListener('keydown',GJE_StyleKeyCommand);
7524 //nx.addEventListener('click',GJE_SetTableStyle);
7525
7526 nt = new Text('\n')
7527 cwe.appendChild(nt)
7528
7529 GJE_TableNo += 1
7530 return 'created TABLE id="'+tid+'"'
7531 }
7532 function GJE_NodeEdit(argv){
7533     cwe = GJE_CurElement
7534     cmd = argv[0]
7535     argv.shift()
7536     args = argv.join(' ')
7537     ret = ""
7538
7539     if( cmd == '.u' || cmd == '.un' || cmd == 'undo' ){
7540         if( GJE_NodeSaved != null ){
7541             xn = GJE_RootNode
7542             GJE_RootNode = GJE_NodeSaved
7543             GJE_NodeSaved = xn
7544             ret = '-- did undo'
7545         }else{
7546             ret = '-- could not undo'
7547         }
7548         return ret
7549     }
7550     GJE_NodeSaved = GJE_RootNode.cloneNode()
7551     if( cmd == '.c' || cmd == '.cd' || cmd == 'cd' ){
7552         if( argv[0] == null ){
7553             ne = GJE_RootNode
7554         }else
7555         if( argv[0] == '..' ){
7556             ne = cwe.parentNode
7557         }else{
7558             ne = document.getElementById(argv[0])
7559         }
7560         if( ne != null ){
7561             GJE_CurElement = ne
7562             ret = "-- current node: " + ne.id
7563         }else{
7564             ret = "-- not found: " + argv[0]
7565         }
7566     }else
7567     if( cmd == '.mkt' || cmd == '.mktable' ){
7568         makeTable(argv)
7569     }else
7570     if( cmd == '.m' || cmd == '.mk' || cmd == 'mk' ){
7571         ne = document.createElement(argv[0])
7572         //ne.id = argv[0]
7573         ret = "-- created " + ne + " under " + cwe.tagName + "#" + cwe.id
7574         cwe.appendChild(ne)
7575         if( cmd == '.m' || cmd == '.mk' ){
7576             GJE_CurElement = ne
7577         }
7578     }else
7579     if( cmd == '.n' || cmd == '.nm' || cmd == 'nm' ){
7580         cwe.id = argv[0]
7581     }else
7582     if( cmd == '.r' || cmd == '.rm' || cmd == 'rm' ){
7583     }else
7584     if( cmd == '.h' || cmd == '.sh' || cmd == 'sh' ){
7585         s = argv.join(' ')
7586         cwe.innerHTML = s
7587     }else
7588     if( cmd == '.a' || cmd == '.sa' || cmd == 'sa' ){
7589         cwe.setAttribute(argv[0],argv[1])
7590     }else
7591     if( cmd == '.l' ){
7592     }else
7593     if( cmd == '.i' || cmd == '.ih' || cmd == 'ih' ){
7594         ret = cwe.innerHTML
7595     }else
7596     if( cmd == '.p' || cmd == '.pw' || cmd == 'pw' ){
7597         ret = cwe.nodeType + " " + cwe.tagName + " " + cwe.id
7598         for( we = cwe.parentNode; we != null; ){
7599             ret += "\n" + " " + we.nodeType + " " + we.tagName + " " + we.id
7600             we = we.parentNode
7601         }
7602     }else
7603     {
7604         ret = "Command: mk | rm \n"
7605         ret += " pw -- print current node\n"
7606         ret += " mk type -- make node with name and type\n"
7607         ret += " nm name -- set the id #name of current node\n"
7608         ret += " rm name -- remove named node\n"
7609         ret += " cd name -- change current node\n"
7610     }
7611     //alert(ret)
7612     return ret
7613 }
7614 function GJC_Command(text){
7615     lines = text.value.split('\n')
7616     line = lines[lines.length-1]
7617     argv = line.split(' ')
7618     text.value += '\n'
7619     if( argv[0] == '&' ){ argv.shift() }
7620     args0 = argv.join(' ')
7621     cmd = argv[0]
7622     argv.shift()
7623     args = argv.join(' ')
7624

```

```

7625 if( cmd == 'new' ){
7626     if( argv[0] == 'table' ){
7627         argv.shift()
7628         console.log('argv='+argv)
7629         text.value += makeTable(argv)
7630     }else
7631     if( argv[0] == 'console' ){
7632         text.value += GJ_NewConsole('GJ_Console')
7633     }else{
7634         text.value += '-- new { console | table }'
7635     }
7636 }else
7637 if( cmd == 'strip' ){
7638     //text.value += GJF_StripClass()
7639 }else
7640 if( cmd == 'print' ){
7641     e = document.getElementById('GJFactory_0')
7642     if( e == null ){
7643         e = document.getElementById('GJFactory_1')
7644     }
7645     if( argv[0] != null ){
7646         id = argv[0]
7647         e = document.getElementById(id)
7648         if( e != null ){
7649             text.value += e.outerHTML
7650         }else{
7651             text.value += "Not found: " + id
7652         }
7653     }else{
7654         //text.value += GJE_RootNode.outerHTML
7655         text.value += e.innerHTML
7656     }
7657 }else
7658 if( cmd == 'destroy' ){
7659     text.value += GJFactory_Destroy()
7660 }else
7661 if( cmd == 'save' ){
7662     e = document.getElementById('GJFactory')
7663     Permanent.setItem('GJFactory-1',e.innerHTML)
7664     text.value += "--- Saved GJFactory"
7665 }else
7666 if( cmd == 'load' ){
7667     gjf = Permanent.getItem('GJFactory-1')
7668     e = document.getElementById('GJFactory')
7669     e.innerHTML = gjf
7670     // must restore EventListener
7671     text.value += "--- EventListener was not restored"
7672 }else
7673 if( cmd.charAt(0) == '.' ){
7674     argv0 = args0.split('.')
7675     text.value += GJE_NodeEdit(argv0)
7676 }else
7677 if( cmd == 'cont' ){
7678     bannerIsStopping = false
7679     GshMenuStop.innerHTML = "Stop"
7680 }else
7681 if( cmd == 'date' ){
7682     text.value += DateLong()
7683 }else
7684 if( cmd == 'echo' ){
7685     text.value += args
7686 }else
7687 if( cmd == 'fork' ){
7688     html_fork()
7689 }else
7690 if( cmd == 'last' ){
7691     text.value += MyHistory
7692     //h = document.createElement("span")
7693     //h.innerHTML = MyHistory
7694     //text.value += h.innerHTML
7695     //tx = MyHistory.replace("\n","")
7696     //text.value += tx.replace("<"+"br>","\n") + "xxxx<"+"br>yyyy"
7697 }else
7698 if( cmd == 'ne' ){
7699     text.value += GJE_NodeEdit(argv)
7700 }else
7701 if( cmd == 'reload' ){
7702     location.reload()
7703 }else
7704 if( cmd == 'mem' ){
7705     text.value += GJC_Memory('GJC_Storage',args,text)
7706 }else
7707 if( cmd == 'stop' ){
7708     bannerIsStopping = true
7709     GshMenuStop.innerHTML = "Start"
7710 }else
7711 if( cmd == 'who' ){
7712     text.value += "SessionId="+GJC_SessionId+" "+document.URL
7713 }else
7714 if( cmd == 'wall' ){
7715     text.value += GJC_Memory('GJC_Wall','write',text)
7716 }else
7717 {
7718     text.value += "Commands: help | echo | date | last \n"
7719     + '      new | save | load | mem \n'
7720     + '      who | wall | fork | nife'
7721 }
7722 }
7723
7724 function GJC_Input(){
7725     if( this.value.endsWith("\n") ){ // remove NL added by textarea
7726         this.value = this.value.slice(0,this.value.length-1)
7727     }
7728 }
7729
7730 var GCJ_Id = null
7731 function GJC_Resize(){
7732     GJC_Id.style.zIndex = 20000
7733     GJC_Id.style.width = window.innerWidth - 16
7734     GJC_Id.style.height = 300
7735     GJC_Id.style.backgroundColor = "rgba(0,64,16,1.0)" // blackboard color
7736     GJC_Id.style.color = "rgba(255,255,255,1.0)"
7737 }
7738 function GJC_FocusIn(){
7739     this.spellcheck = false
7740     SuppressGJShell = true
7741     this.onkeydown = GJC_Keydown
7742     GJC_Resize()
7743 }
7744 function GJC_FocusOut(){
7745     SuppressGJShell = false
7746     this.removeEventListener('keydown',GJC_Keydown);
7747 }
7748 window.addEventListener('resize',GJC_Resize);
7749

```

```
7750 function GJC_OnStorage(e){
7751     //alert('Got Message')
7752     //GJC.value += "\n((ReceivedMessage))\n"
7753 }
7754 window.addEventListener('storage',GJC_OnStorage);
7755 //window.addEventListener('storage',()=>{alert('GotMessage')})
7756
7757 function GJC_Setup(gjcId){
7758     gjcId.style.width = gsh.getBoundingClientRect().width
7759     gjcId.value = "GJShell Console // " + GshVersion.innerHTML + "\n"
7760     //gjcId.value += "Date: " + DateLong() + "\n"
7761     gjcId.value += PS1
7762     gjcId.onfocus = GJC_FocusIn
7763     gjcId.addEventListener('input',GJC_Input);
7764     gjcId.addEventListener('focusout',GJC_FocusOut);
7765     GJC_Id = gjcId
7766 }
7767 function GJC_Clear(id){
7768 }
7769 if( document.getElementById("GJC_0") != null ){
7770     GJC_Setup(GJC_0)
7771 }else{
7772     document.write('<'+ 'textarea id="GJC_1" class="GJConsole"><'+ '/textarea>')
7773     GJC_Setup(GJC_1)
7774 }
7775
7776 // TODO: focus handling
7777 </script>
7778 <!-- ----- GJConsole END } ----- -->
7779 </span>
7780
7781 *///<br></span></html>
7782
```