

```

1  /*<html>
2  <span id="gsh">
3  <meta charset="UTF-8">
4  <meta name="viewport" content="width=device-width, initial-scale=1.0">
5  <link rel="icon" id="gsh-faviconurl" href=""/><!-- place holder -->
6  <span id="gsh-version" style="display:none;">gsh--0.3.1--2020-09-04--SatoxITS</span>
7  <title>GShell-0.3.1 by SatoxITS</title>
8  <header id="gsh-banner" height="100px" onclick="shiftBG();" style="">
9  <div align="right"><note>GShell version 0.3.1 // 2020-09-04 // SatoxITS</note></div>
10 </header>
11 <h2>GShell // a General purpose Shell built on the top of Golang</h2>
12 <p>
13 <note>
14 It is a shell for myself, by myself, of myself. --SatoxITS(^-^ )
15 </note>
16 </p>
17 <span id="gsh-WinId" onclick="win_jump('0.1');">0</span>
18 <span id="gsh-menu">
19 | <span id="gsh-menu-exit" onclick="html_close();"></span>
20 | <span id="gsh-menu-fork" onclick="html_fork();">Fork</span>
21 | <span id="gsh-menu-stop" onclick="html_stop(this,true);">Stop</span>
22 | <span id="gsh-menu-fold" onclick="html_fold(this);">Unfold</span>
23 | <span id="gsh-menu-cksum" onclick="html_cksum(this);">Cksum</span>
24 |<!-- | <span id="gsh-menu-pure" onclick="html_pure(this);">Pure</span> -->
25 |</span>
26 */
27 /*
28 <details id="GshStatement" class="gsh-document"><summary>Statement</summary>
29 <h3>Fun to create a shell</h3>
30 <p>For a programmer, it must be far easy and fun to create his own simple shell
31 rightly fitting to his favor and necessities, than learning existing shells with
32 complex full features that he never use.
33 I, as one of programmers, am writing this tiny shell for my own real needs,
34 totally from scratch, with fun.
35 </p><p>
36 For a programmer, it is fun to learn new computer languages. For long years before
37 writing this software, I had been specialized to C and early HTML2 :-).
38 Now writing this software, I'm learning Go language, HTML5, JavaScript and CSS
39 on demand as a novice of these, with fun.
40 </p><p>
41 This single file "gsh.go", that is executable by Go, contains all of the code written
42 in Go. Also it can be displayed as "gsh.go.html" by browsers. It is a standalone
43 HTML file that works as the viewer of the code of itself, and as the "home page" of
44 this software.
45 </p><p>
46 Because this HTML file is a Go program, you may run it as a real shell program
47 on your computer.
48 But you must be aware that this program is written under situation like above.
49 Needless to say, there is no warranty for this program in any means.
50 </p>
51 <address>Aug 2020, SatoxITS (sato@its-more.jp)</address>
52 </details>
53 */
54 /*
55 <details id="GshFeatures" class="gsh-document"><summary>Features</summary><p>
56 </p>
57 <h3>Vi compatible command line editor</h3>
58 <p>
59 The command line of GShell can be edited with commands compatible with
60 <a href="https://www.washington.edu/computing/unix/vi.html">vi</a>.
61 As in vi, you can enter <i><b>command mode</b></i> by <b>ESC</b> key,
62 then move around in the history by <b><code>j k ? n N</code></b>,
63 or within the current line by <b><code>l h f w b o $ %</code></b> or so.
64 </p>
65 </details>
66 */
67 /*
68 <details id="gsh-gindex">
69 <summary>Index</summary><div class="gsh-src">
70 Documents
71 <span class="gsh-link" onclick="jumpto_JavaScriptView();">Command summary</span>
72 Go lang part<span class="gsh-src" onclick="document.getElementById('gsh-gocode').open=true;">
73 Package structures
74 <a href="#import">import</a>
75 <a href="#struct">struct</a>
76 Main functions
77 <a href="#comexpansion">str-expansion</a> // macro processor
78 <a href="#finder">finder</a> // builtin find + du
79 <a href="#grep">grep</a> // builtin grep + wc + cksum + ...
80 <a href="#plugin">plugin</a> // plugin commands
81 <a href="#ex-commands">system</a> // external commands
82 <a href="#builtin">builtin</a> // builtin commands
83 <a href="#network">network</a> // socket handler
84 <a href="#remote-sh">remote-sh</a> // remote shell
85 <a href="#redirect">redirect</a> // StdIn/Out redirection
86 <a href="#history">history</a> // command history
87 <a href="#rusage">rusage</a> // resource usage
88 <a href="#encode">encode</a> // encode / decode
89 <a href="#IME">IME</a> // command line IME
90 <a href="#getline">getline</a> // line editor
91 <a href="#scanf">scanf</a> // string decomposer
92 <a href="#interpreter">interpreter</a> // command interpreter
93 <a href="#main">main</a>
94 </span>
95 JavaScript part
96 <a href="#script-src-view" class="gsh-link" onclick="jumpto_JavaScriptView();">Source</a>
97 <a href="#gsh-data-frame" class="gsh-link" onclick="jumpto_DataView();">Builtin data</a>
98 CSS part
99 <a href="#style-src-view" class="gsh-link" onclick="jumpto_StyleView();">Source</a>
100 References
101 <a href="#" class="gsh-link" onclick="jumpto_WholeView();">Internal</a>
102 <a href="#gsh-reference" class="gsh-link" onclick="jumpto_ReferenceView();">External</a>
103 Whole parts
104 <a href="#whole-src-view" class="gsh-link" onclick="jumpto_WholeView();">Source</a>
105 <a href="#whole-src-view" class="gsh-link" onclick="jumpto_WholeView();">Download</a>
106 <a href="#whole-src-view" class="gsh-link" onclick="jumpto_WholeView();">Dump</a>
107
108 </div>
109 </details>
110 */
111 </<details id="gsh-gocode">
112 </<summary>Go Source</summary>><div class="gsh-src" onclick="document.getElementById('gsh-gocode').open=false;">
113 // gsh - Go lang based Shell
114 // (c) 2020 ITS more Co., Ltd.
115 // 2020-0807 created by SatoxITS (sato@its-more.jp)
116
117 package main // gsh main
118 // <a name="import">Imported packages</a> // <a href="https://golang.org/pkg/">Packages</a>
119 import (
120 "fmt" // <a href="https://golang.org/pkg/fmt/">fmt</a>
121 "strings" // <a href="https://golang.org/pkg/strings/">strings</a>
122 "strconv" // <a href="https://golang.org/pkg/strconv/">strconv</a>
123 "sort" // <a href="https://golang.org/pkg/sort/">sort</a>
124 "time" // <a href="https://golang.org/pkg/time/">time</a>

```

```

125 "bufio" // <a href="https://golang.org/pkg/bufio/">bufio</a>
126 "io/ioutil" // <a href="https://golang.org/pkg/io/ioutil/">ioutil</a>
127 "os" // <a href="https://golang.org/pkg/os/">os</a>
128 "syscall" // <a href="https://golang.org/pkg/syscall/">syscall</a>
129 "plugin" // <a href="https://golang.org/pkg/plugin/">plugin</a>
130 "net" // <a href="https://golang.org/pkg/net/">net</a>
131 "net/http" // <a href="https://golang.org/pkg/net/http/">http</a>
132 // "html" // <a href="https://golang.org/pkg/html/">html</a>
133 "path/filepath" // <a href="https://golang.org/pkg/path/filepath/">filepath</a>
134 "go/types" // <a href="https://golang.org/pkg/go/types/">types</a>
135 "go/token" // <a href="https://golang.org/pkg/go/token/">token</a>
136 "encoding/base64" // <a href="https://golang.org/pkg/encoding/base64/">base64</a>
137 "unicode/utf8" // <a href="https://golang.org/pkg/unicode/utf8/">utf8</a>
138 // "gshdata" // gshell's logo and source code
139 "hash/crc32" // <a href="https://golang.org/pkg/hash/crc32/">crc32</a>
140 )
141 const (
142     NAME = "gsh"
143     VERSION = "0.3.1"
144     DATE = "2020-09-04"
145     AUTHOR = "SatoxITS(^-^)/"
146 )
147 var (
148     GSH_HOME = ".gsh" // under home directory
149     GSH_PORT = 9999
150     MaxStreamSize = int64(128*1024*1024*1024) // 128GiB is too large?
151     PROMPT = "> "
152     LINESIZE = (8*1024)
153     PATHSEP = ";" // should be ";" in Windows
154     DIRSEP = "/" // canbe \ in Windows
155 )
156
157 // -xX logging control
158 // --A-- all
159 // --I-- info.
160 // --D-- debug
161 // --T-- time and resource usage
162 // --W-- warning
163 // --E-- error
164 // --F-- fatal error
165 // --Xn- network
166
167 // <a name="struct">Structures</a>
168 type GCommandHistory struct {
169     StartAt time.Time // command line execution started at
170     EndAt time.Time // command line execution ended at
171     ResCode int // exit code of (external command)
172     CmdError error // error string
173     OutData *os.File // output of the command
174     FoundFile []string // output - result of unfind
175     Rusagev [2]syscall.Rusage // Resource consumption, CPU time or so
176     CmdId int // maybe with identified with arguments or impact
177     // redirection commands should not be the CmdId
178     WorkDir string // working directory at start
179     WorkDirX int // index in CkdirHistory
180     CmdLine string // command line
181 }
182 type GChdirHistory struct {
183     Dir string
184     MovedAt time.Time
185     CmdIndex int
186 }
187 type CmdMode struct {
188     Background bool
189 }
190 type Event struct {
191     when time.Time
192     event int
193     evarg int64
194     CmdIndex int
195 }
196 var CmdIndex int
197 var Events []Event
198 type PluginInfo struct {
199     Spec *plugin.Plugin
200     Addr plugin.Symbol
201     Name string // maybe relative
202     Path string // this is in Plugin but hidden
203 }
204 type GServer struct {
205     host string
206     port string
207 }
208
209 // <a href="https://tools.ietf.org/html/rfc3230">Digest</a>
210 const ( // SumType
211     SUM_ITEMS = 0x000001 // items count
212     SUM_SIZE = 0x000002 // data length (simply added)
213     SUM_SIZEHASH = 0x000004 // data length (hashed sequence)
214     SUM_DATEHASH = 0x000008 // date of data (hashed sequence)
215     // also envelope attributes like time stamp can be a part of digest
216     // hashed value of sizes or mod-date of files will be useful to detect changes
217
218     SUM_WORDS = 0x000010 // word count is a kind of digest
219     SUM_LINES = 0x000020 // line count is a kind of digest
220     SUM_SUM64 = 0x000040 // simple add of bytes, useful for human too
221
222     SUM_SUM32_BITS = 0x000100 // the number of true bits
223     SUM_SUM32_2BYTE = 0x000200 // 16bits words
224     SUM_SUM32_4BYTE = 0x000400 // 32bits words
225     SUM_SUM32_8BYTE = 0x000800 // 64bits words
226
227     SUM_SUM16_BSD = 0x001000 // UNIXsum -sum -bsd
228     SUM_SUM16_SYSV = 0x002000 // UNIXsum -sum -sysv
229     SUM_UNIXFILE = 0x004000
230     SUM_CRCIEEE = 0x008000
231 )
232 type CheckSum struct {
233     Files int64 // the number of files (or data)
234     Size int64 // content size
235     Words int64 // word count
236     Lines int64 // line count
237     SumType int
238     Sum64 uint64
239     Crc32Table crc32.Table
240     Crc32Val uint32
241     Sum16 int
242     Ctime time.Time
243     Atime time.Time
244     Mtime time.Time
245     Start time.Time
246     Done time.Time
247     RusgAtStart [2]syscall.Rusage
248     RusgAtEnd [2]syscall.Rusage
249 }

```

```

250 type ValueStack [][]string
251 type GshContext struct {
252     StartDir    string // the current directory at the start
253     GetLine     string // gsh-getline command as a input line editor
254     ChdirHistory []CChdirHistory // the 1st entry is wd at the start
255     gshPA       syscall.ProcAttr
256     CommandHistory []GCommandHistory
257     CmdCurrent  GCommandHistory
258     BackGround  bool
259     BackGroundJobs []int
260     LastRusage    syscall.Rusage
261     GshHomeDir    string
262     TerminalId    int
263     CmdTrace      bool // should be [map]
264     CmdTime       bool // should be [map]
265     PluginFuncs  []PluginInfo
266     iValues       []string
267     iDelimiter    string // field separator of print out
268     iFormat       string // default print format (of integer)
269     iValStack     ValueStack
270     LastServer    GServer
271     RSERVER       string // [gsh://]host[:port]
272     RWD           string // remote (target, there) working directory
273     lastChecksum  CheckSum
274 }
275
276 func nsleep(ns time.Duration){
277     time.Sleep(ns)
278 }
279 func usleep(ns time.Duration){
280     nsleep(ns*1000)
281 }
282 func msleep(ns time.Duration){
283     nsleep(ns*1000000)
284 }
285 func sleep(ns time.Duration){
286     nsleep(ns*1000000000)
287 }
288
289 func strBegins(str, pat string)(bool){
290     if len(pat) <= len(str){
291         yes := str[0:len(pat)] == pat
292         //fmt.Printf("--D-- strBegins(%v,%v)=%v\n",str,pat, yes)
293         return yes
294     }
295     //fmt.Printf("--D-- strBegins(%v,%v)=%v\n",str,pat,false)
296     return false
297 }
298 func isin(what string, list []string) bool {
299     for _, v := range list {
300         if v == what {
301             return true
302         }
303     }
304     return false
305 }
306 func isinX(what string, list[]string)(int){
307     for i,v := range list {
308         if v == what {
309             return i
310         }
311     }
312     return -1
313 }
314
315 func env(opts []string) {
316     env := os.Environ()
317     if isin("-s", opts){
318         sort.Slice(env, func(i,j int) bool {
319             return env[i] < env[j]
320         })
321     }
322     for _, v := range env {
323         fmt.Printf("%v\n",v)
324     }
325 }
326
327 // - rewriting should be context dependent
328 // - should postpone until the real point of evaluation
329 // - should rewrite only known notation of symobl
330 func scanInt(str string)(val int, leng int){
331     leng = -1
332     for i,ch := range str {
333         if '0' <= ch && ch <= '9' {
334             leng = i+1
335         }else{
336             break
337         }
338     }
339     if 0 < leng {
340         ival, _ := strconv.Atoi(str[0:leng])
341         return ival, leng
342     }else{
343         return 0,0
344     }
345 }
346 func substHistory(gshCtx *GshContext, str string, i int, rstr string)(leng int, rst string){
347     if len(str[i+1:]) == 0 {
348         return 0, rstr
349     }
350     hi := 0
351     histlen := len(gshCtx.CommandHistory)
352     if str[i+1] == '|' {
353         hi = histlen - 1
354         leng = 1
355     }else{
356         hi, leng = scanInt(str[i+1:])
357         if leng == 0 {
358             return 0, rstr
359         }
360         if hi < 0 {
361             hi = histlen + hi
362         }
363     }
364     if 0 <= hi && hi < histlen {
365         var ext byte
366         if 1 < len(str[i+leng:]) {
367             ext = str[i+leng:][1]
368         }
369         //fmt.Printf("--D-- %v(%c)\n",str[i+leng:],str[i+leng])
370         if ext == 'f' {
371             leng += 1
372             xlist := []string{}
373             list := gshCtx.CommandHistory[hi].FoundFile
374             for _,v := range list {

```

```

375         //list[i] = escapeWhiteSP(v)
376         xlist = append(xlist,escapeWhiteSP(v))
377     }
378     //rstr += strings.Join(list," ")
379     rstr += strings.Join(xlist," ")
380 }else
381 if ext == 'e' || ext == 'd' {
382     // IN@ .. workdir at the start of the command
383     leng += 1
384     rstr += gshCtx.CommandHistory[hi].WorkDir
385 }else{
386     rstr += gshCtx.CommandHistory[hi].CmdLine
387 }
388 }else{
389     leng = 0
390 }
391 return leng,rstr
392 }
393 func escapeWhiteSP(str string)(string){
394 if len(str) == 0 {
395     return "\\z" // empty, to be ignored
396 }
397 rstr := ""
398 for _,ch := range str {
399     switch ch {
400         case '\\': rstr += "\\\\"
401         case ' ': rstr += "\\s"
402         case '\t': rstr += "\\t"
403         case '\r': rstr += "\\r"
404         case '\n': rstr += "\\n"
405         default: rstr += string(ch)
406     }
407 }
408 return rstr
409 }
410 func unescapeWhiteSP(str string)(string){ // strip original escapes
411 rstr := ""
412 for i := 0; i < len(str); i++ {
413     ch := str[i]
414     if ch == '\\' {
415         if i+1 < len(str) {
416             switch str[i+1] {
417                 case 'z':
418                     continue;
419             }
420         }
421     }
422     rstr += string(ch)
423 }
424 return rstr
425 }
426 func unescapeWhiteSPV(strv []string)([]string){ // strip original escapes
427     ustrv := []string{}
428     for _,v := range strv {
429         ustrv = append(ustrv,unescapeWhiteSP(v))
430     }
431     return ustrv
432 }
433 }
434 // <a name="comexpansion">str-expansion</a>
435 // - this should be a macro processor
436 func strsubst(gshCtx *GshContext,str string,histonly bool) string {
437     rbuff := []byte{}
438     if false {
439         //@@@ Unicode should be cared as a character
440         return str
441     }
442     //rstr := ""
443     inEsc := 0 // escape characer mode
444     for i := 0; i < len(str); i++ {
445         //fmt.Printf("--D--Subst %v:%v\n",i,str[i:])
446         ch := str[i]
447         if inEsc == 0 {
448             if ch == '|' {
449                 //leng,xrstr := substHistory(gshCtx,str,i,rstr)
450                 leng,rs := substHistory(gshCtx,str,i,"")
451                 if 0 < leng {
452                     //_,rs := substHistory(gshCtx,str,i,"")
453                     rbuff = append(rbuff,[]byte(rs)...)
454                     i += leng
455                     //rstr = xrstr
456                     continue
457                 }
458             }
459             switch ch {
460                 case '\\': inEsc = '\\'; continue
461                 case '%': inEsc = '%'; continue
462                 case '$':
463             }
464         }
465         switch inEsc {
466             case '\\':
467                 switch ch {
468                     case '\\': ch = '\\'
469                     case 's': ch = ' '
470                     case 't': ch = '\t'
471                     case 'r': ch = '\r'
472                     case 'n': ch = '\n'
473                     case 'z': inEsc = 0; continue // empty, to be ignored
474                 }
475             case '%':
476                 switch {
477                     case ch == '%': ch = '%'
478                     case ch == 'm':
479                         //rstr = rstr + time.Now().Format(time.Stamp)
480                         rs := time.Now().Format(time.Stamp)
481                         rbuff = append(rbuff,[]byte(rs)...)
482                         inEsc = 0
483                         continue;
484                     default:
485                         // postpone the interpretation
486                         //rstr = rstr + "%" + string(ch)
487                         rbuff = append(rbuff,ch)
488                         inEsc = 0
489                         continue;
490                 }
491             case '$':
492                 inEsc = 0
493             }
494         //rstr = rstr + string(ch)
495         rbuff = append(rbuff,ch)
496     }
497     //fmt.Printf("--D--subst(%s)(%s)\n",str,string(rbuff))
498     return string(rbuff)
499     //return rstr

```

```

500 }
501 func showFileInfo(path string, opts []string) {
502     if isin("-l",opts) || isin("-ls",opts) {
503         fi, err := os.Stat(path)
504         if err != nil {
505             fmt.Printf("----- ((%v))",err)
506         }else{
507             mod := fi.ModTime()
508             date := mod.Format(time.Stamp)
509             fmt.Printf("%v %v %s ",fi.Mode(),fi.Size(),date)
510         }
511     }
512     fmt.Printf("%s",path)
513     if isin("-sp",opts) {
514         fmt.Printf(" ")
515     }else
516     if ! isin("-n",opts) {
517         fmt.Printf("\n")
518     }
519 }
520 func userHomeDir()(string,bool){
521     /*
522     homedir,_ = os.UserHomeDir() // not implemented in older Golang
523     */
524     homedir,found := os.LookupEnv("HOME")
525     //fmt.Printf("--I-- HOME=%v(%v)\n",homedir,found)
526     if !found {
527         return "/tmp",found
528     }
529     return homedir,found
530 }
531 }
532 func toFullpath(path string) (fullpath string) {
533     if path[0] == '/' {
534         return path
535     }
536     pathv := strings.Split(path,DIRSEP)
537     switch {
538     case pathv[0] == ".":
539         pathv[0],_ = os.Getwd()
540     case pathv[0] == "..": // all ones should be interpreted
541         cwd,_ = os.Getwd()
542         ppathv := strings.Split(cwd,DIRSEP)
543         pathv[0] = strings.Join(ppathv,DIRSEP)
544     case pathv[0] == "-":
545         pathv[0],_ = userHomeDir()
546     default:
547         cwd,_ = os.Getwd()
548         pathv[0] = cwd + DIRSEP + pathv[0]
549     }
550     return strings.Join(pathv,DIRSEP)
551 }
552 }
553 func IsRegFile(path string)(bool){
554     fi, err := os.Stat(path)
555     if err == nil {
556         fm := fi.Mode()
557         return fm.IsRegular();
558     }
559     return false
560 }
561 }
562 // <a name="encode">Encode / Decode</a>
563 // <a href="https://golang.org/pkg/encoding/base64/#example_NewEncoder">Encoder</a>
564 func (gshCtx *GshContext)Enc(argv[]string){
565     file := os.Stdin
566     buff := make([]byte,LINESIZE)
567     li := 0
568     encoder := base64.NewEncoder(base64.StdEncoding,os.Stdout)
569     for li = 0; ; li++ {
570         count, err := file.Read(buff)
571         if count <= 0 {
572             break
573         }
574         if err != nil {
575             break
576         }
577         encoder.Write(buff[0:count])
578     }
579     encoder.Close()
580 }
581 func (gshCtx *GshContext)Dec(argv[]string){
582     decoder := base64.NewDecoder(base64.StdEncoding,os.Stdin)
583     li := 0
584     buff := make([]byte,LINESIZE)
585     for li = 0; ; li++ {
586         count, err := decoder.Read(buff)
587         if count <= 0 {
588             break
589         }
590         if err != nil {
591             break
592         }
593         os.Stdout.Write(buff[0:count])
594     }
595 }
596 // lnspl [N] [-crLf][-C \\\]
597 func (gshCtx *GshContext)SplitLine(argv[]string){
598     reader := bufio.NewReaderSize(os.Stdin,64*1024)
599     ni := 0
600     toi := 0
601     for ni = 0; ; ni++ {
602         line, err := reader.ReadString('\n')
603         if len(line) <= 0 {
604             if err != nil {
605                 fmt.Fprintf(os.Stderr,"--I-- lnspl %d to %d (%v)\n",ni,toi,err)
606                 break
607             }
608         }
609         off := 0
610         ilen := len(line)
611         remlen := len(line)
612         for oi := 0; 0 < remlen; oi++ {
613             olen := remlen
614             addnl := false
615             if 72 < olen {
616                 olen = 72
617                 addnl = true
618             }
619             fmt.Fprintf(os.Stderr,"--D-- write %d [%d.%d] %d %d/%d\n",
620                 toi,ni,oi,off,olen,remlen,ilen)
621             toi += 1
622             os.Stdout.Write([]byte(line[0:olen]))
623             if addnl {
624                 //os.Stdout.Write([]byte("\r\n"))

```

```

625         os.Stdout.Write([]byte("\\"))
626         os.Stdout.Write([]byte("\n"))
627     }
628     line = line[olen:]
629     off += olen
630     remlen -= olen
631 }
632 }
633 fmt.Fprintf(os.Stderr, "--I-- lnspp %d to %d\n", ni, toi)
634 }
635
636 // CRC32 <a href="http://golang.jp/pkg/hash-crc32">crc32</a>
637 // 1 0000 0100 1100 0001 0001 1101 1011 0111
638 var CRC32UNIX uint32 = uint32(0x04C11DB7) // Unix cksum
639 var CRC32IEEE uint32 = uint32(0xEDB88320)
640 func byteCRC32add(crc uint32, str []byte, len uint64)(uint32){
641     var oi uint64
642     for oi = 0; oi < len; oi++ {
643         var oct = str[oi]
644         for bi := 0; bi < 8; bi++ {
645             //fprintf(stderr, "--CRC32 %d %X (%d.%d)\n", crc, oct, oi, bi)
646             ovf1 := (crc & 0x80000000) != 0
647             ovf2 := (oct & 0x80) != 0
648             ovf := (ovf1 && !ovf2) || (!ovf1 && ovf2)
649             oct <<= 1
650             crc <<= 1
651             if ovf { crc ^= CRC32UNIX }
652         }
653     }
654     //fprintf(stderr, "--CRC32 return %d %d\n", crc, len)
655     return crc;
656 }
657 func byteCRC32end(crc uint32, len uint64)(uint32){
658     var slen = make([]byte, 4)
659     var li = 0
660     for li = 0; li < 4; {
661         slen[li] = byte(len)
662         li += 1
663         len >>= 8
664         if( len == 0 ){
665             break
666         }
667     }
668     crc = byteCRC32add(crc, slen, uint64(li))
669     crc ^= 0xFFFFFFFF
670     return crc
671 }
672 func strCRC32(str string, len uint64)(crc uint32){
673     crc = byteCRC32add(0, []byte(str), len)
674     crc = byteCRC32end(crc, len)
675     //fprintf(stderr, "--CRC32 %d %d\n", crc, len)
676     return crc
677 }
678 func CRC32Finish(crc uint32, table *crc32.Table, len uint64)(uint32){
679     var slen = make([]byte, 4)
680     var li = 0
681     for li = 0; li < 4; {
682         slen[li] = byte(len & 0xFF)
683         li += 1
684         len >>= 8
685         if( len == 0 ){
686             break
687         }
688     }
689     crc = crc32.Update(crc, table, slen)
690     crc ^= 0xFFFFFFFF
691     return crc
692 }
693
694 func (gsh*GshContext)xChecksum(path string, argv []string, sum*Checksum)(int64){
695     if isin("-type/f", argv) && !IsRegFile(path){
696         return 0
697     }
698     if isin("-type/d", argv) && IsRegFile(path){
699         return 0
700     }
701     file, err := os.OpenFile(path, os.O_RDONLY, 0)
702     if err != nil {
703         fmt.Printf("--E-- cksum %v (%v)\n", path, err)
704         return -1
705     }
706     defer file.Close()
707     if gsh.CmdTrace { fmt.Printf("--I-- cksum %v %v\n", path, argv) }
708
709     bi := 0
710     var buff = make([]byte, 32*1024)
711     var total int64 = 0
712     var initTime = time.Time{}
713     if sum.Start == initTime {
714         sum.Start = time.Now()
715     }
716     for bi = 0; ; bi++ {
717         count, err := file.Read(buff)
718         if count <= 0 || err != nil {
719             break
720         }
721         if (sum.SumType & SUM_SUM64) != 0 {
722             s := sum.Sum64
723             for _, c := range buff[0:count] {
724                 s += uint64(c)
725             }
726             sum.Sum64 = s
727         }
728         if (sum.SumType & SUM_UNIXFILE) != 0 {
729             sum.Crc32Val = byteCRC32add(sum.Crc32Val, buff, uint64(count))
730         }
731         if (sum.SumType & SUM_CRCIEEE) != 0 {
732             sum.Crc32Val = crc32.Update(sum.Crc32Val, &sum.Crc32Table, buff[0:count])
733         }
734         // <a href="https://en.wikipedia.org/wiki/BSD_checksum">BSD checksum</a>
735         if (sum.SumType & SUM_SUM16_BSD) != 0 {
736             s := sum.Sum16
737             for _, c := range buff[0:count] {
738                 s = (s >> 1) + ((s & 1) << 15)
739                 s += int(c)
740                 s &= 0xFFFF
741                 //fmt.Printf("BSDsum: %d[%d] %d\n", sum.Size+int64(i), i, s)
742             }
743             sum.Sum16 = s
744         }
745         if (sum.SumType & SUM_SUM16_SYSV) != 0 {
746             for bj := 0; bj < count; bj++ {
747                 sum.Sum16 += int(buff[bj])
748             }
749         }

```

```

750     total += int64(count)
751 }
752 sum.Done = time.Now()
753 sum.Files += 1
754 sum.Size += total
755 if !isin("-s",argv) {
756     fmt.Printf("%v ",total)
757 }
758 return 0
759 }
760
761 // <a name="grep">grep</a>
762 // "lines", "lin" or "lnp" for "(text) line processor" or "scanner"
763 // a*,lab,c,... sequential combination of patterns
764 // what "LINE" is should be definable
765 // generic line-by-line processing
766 // grep [-v]
767 // cat -n -v
768 // uniq [-c]
769 // tail -f
770 // sed s/x/y/ or awk
771 // grep with line count like wc
772 // rewrite contents if specified
773 func (gsh*GshContext)XGrep(path string, rexpv[]string)(int){
774     file, err := os.OpenFile(path,os.O_RDONLY,0)
775     if err != nil {
776         fmt.Printf("--E-- grep %v (%v)\n",path,err)
777         return -1
778     }
779     defer file.Close()
780     if gsh.CmdTrace { fmt.Printf("--I-- grep %v %v\n",path, rexpv) }
781     //reader := bufio.NewReaderSize(file,LINESIZE)
782     reader := bufio.NewReaderSize(file,80)
783     li := 0
784     found := 0
785     for li = 0; ; li++ {
786         line, err := reader.ReadString('\n')
787         if len(line) <= 0 {
788             break
789         }
790         if 150 < len(line) {
791             // maybe binary
792             break;
793         }
794         if err != nil {
795             break
796         }
797         if 0 <= strings.Index(string(line),rexpv[0]) {
798             found += 1
799             fmt.Printf("%s:%d: %s",path,li,line)
800         }
801     }
802     //fmt.Printf("total %d lines %s\n",li,path)
803     //if( 0 < found ){ fmt.Printf("(found %d lines %s)\n",found,path); }
804     return found
805 }
806
807 // <a name="finder">Finder</a>
808 // finding files with it name and contents
809 // file names are ORED
810 // show the content with %x fmt list
811 // ls -R
812 // tar command by adding output
813 type fileSum struct {
814     Err int64 // access error or so
815     Size int64 // content size
816     DupSize int64 // content size from hard links
817     Blocks int64 // number of blocks (of 512 bytes)
818     DupBlocks int64 // Blocks pointed from hard links
819     HLinks int64 // hard links
820     Words int64
821     Lines int64
822     Files int64
823     Dirs int64 // the num. of directories
824     SymLink int64
825     Flats int64 // the num. of flat files
826     MaxDepth int64
827     MaxNamlen int64 // max. name length
828     nextRepo time.Time
829 }
830 func showFusage(dir string,fusage *fileSum){
831     bsume := float64(((fusage.Blocks-fusage.DupBlocks)/2)*1024)/1000000.0
832     //bsumdup := float64((fusage.Blocks/2)*1024)/1000000.0
833
834     fmt.Printf("%v: %v files (%vd %vs %vh) %.6f MB (%.2f MBK)\n",
835         dir,
836         fusage.Files,
837         fusage.Dirs,
838         fusage.SymLink,
839         fusage.HLinks,
840         float64(fusage.Size)/1000000.0,bsume);
841 }
842 const (
843     S_IFMT = 0170000
844     S_IFCHR = 0020000
845     S_IFDIR = 0040000
846     S_IFREG = 0100000
847     S_IFLNK = 0120000
848     S_IFSOCK = 0140000
849 )
850 func cumPinfo(fsum *fileSum, path string, staterr error, fstat syscall.Stat_t, argv[]string,verb bool)(*fileSum){
851     now := time.Now()
852     if time.Second <= now.Sub(fsum.nextRepo) {
853         if !fsum.nextRepo.IsZero(){
854             tstamp := now.Format(time.Stamp)
855             showFusage(tstamp, fsum)
856         }
857         fsum.nextRepo = now.Add(time.Second)
858     }
859     if staterr != nil {
860         fsum.Err += 1
861         return fsum
862     }
863     fsum.Files += 1
864     if 1 < fstat.Nlink {
865         // must count only once...
866         // at least ignore ones in the same directory
867         //if finfo.Mode().IsRegular() {
868         if (fstat.Mode & S_IFMT) == S_IFREG {
869             fsum.HLinks += 1
870             fsum.DupBlocks += int64(fstat.Blocks)
871             //fmt.Printf("---Dup HardLink %v %s\n",fstat.Nlink,path)
872         }
873     }
874     //fsum.Size += finfo.Size()

```

```

875 fsum.Size += fstat.Size
876 fsum.Blocks += int64(fstat.Blocks)
877 //if verb { fmt.Printf("%8dBlk) %s", fstat.Blocks/2, path) }
878 //if isin("-ls", argv){
879 //if verb { fmt.Printf("%4d %8d ", fstat.Blksize, fstat.Blocks) }
880 // fmt.Printf("%d\t", fstat.Blocks/2)
881 }
882 //if finfo.IsDir()
883 if (fstat.Mode & S_IFMT) == S_IFDIR {
884 fsum.Dirs += 1
885 }
886 //if (finfo.Mode() & os.ModeSymlink) != 0
887 if (fstat.Mode & S_IFMT) == S_IFLNK {
888 //if verb { fmt.Printf("symlink(%v,%s)\n", fstat.Mode, finfo.Name()) }
889 //{ fmt.Printf("symlink(%o,%s)\n", fstat.Mode, finfo.Name()) }
890 fsum.SymLink += 1
891 }
892 return fsum
893 }
894 func (gsh*GshContext)xxFindEntv(depth int, total *fileSum, dir string, dstat syscall.Stat_t, ei int, entv []string, npatv[]string, argv[]string)(*fileSum){
895 nols := isin("-grep", argv)
896 // sort entv
897 /*
898 if isin("-t", argv){
899 sort.Slice(filev, func(i,j int) bool {
900 return 0 < filev[i].ModTime().Sub(filev[j].ModTime())
901 })
902 }
903 */
904 /*
905 if isin("-u", argv){
906 sort.Slice(filev, func(i,j int) bool {
907 return 0 < filev[i].AccTime().Sub(filev[j].AccTime())
908 })
909 }
910 if isin("-U", argv){
911 sort.Slice(filev, func(i,j int) bool {
912 return 0 < filev[i].CreateTime().Sub(filev[j].CreateTime())
913 })
914 }
915 */
916 /*
917 if isin("-S", argv){
918 sort.Slice(filev, func(i,j int) bool {
919 return filev[j].Size() < filev[i].Size()
920 })
921 }
922 */
923 for _, filename := range entv {
924 for _, npat := range npatv {
925 match := true
926 if npat == "*" {
927 match = true
928 }else{
929 match, _ = filepath.Match(npat, filename)
930 }
931 path := dir + DIRSEP + filename
932 if !match {
933 continue
934 }
935 var fstat syscall.Stat_t
936 staterr := syscall.Lstat(path, &fstat)
937 if staterr != nil {
938 if !isin("-w", argv){fmt.Printf("ufind: %v\n", staterr) }
939 continue;
940 }
941 if isin("-du", argv) && (fstat.Mode & S_IFMT) == S_IFDIR {
942 // should not show size of directory in "-du" mode ...
943 }else
944 if !nols && !isin("-s", argv) && (!isin("-du", argv) || isin("-a", argv)) {
945 if isin("-du", argv) {
946 fmt.Printf("%d\t", fstat.Blocks/2)
947 }
948 showFileInfo(path, argv)
949 }
950 if true { // && isin("-du", argv)
951 total = cumFinfo(total, path, staterr, fstat, argv, false)
952 }
953 /*
954 if isin("-wc", argv) {
955 }
956 */
957 if gsh.lastCheckSum.SumType != 0 {
958 gsh.xCksum(path, argv, &gsh.lastCheckSum);
959 }
960 x := isinX("-grep", argv); // -grep will be convenient like -ls
961 if 0 <= x && x+1 <= len(argv) { // -grep will be convenient like -ls
962 if IsRegFile(path){
963 found := gsh.xGrep(path, argv[x+1:])
964 if 0 < found {
965 foundv := gsh.CmdCurrent.FoundFile
966 if len(foundv) < 10 {
967 gsh.CmdCurrent.FoundFile =
968 append(gsh.CmdCurrent.FoundFile, path)
969 }
970 }
971 }
972 }
973 if !isin("-r0", argv) { // -d 0 in du, -depth n in find
974 //total.Depth += 1
975 if (fstat.Mode & S_IFMT) == S_IFLNK {
976 continue
977 }
978 if dstat.Rdev != fstat.Rdev {
979 fmt.Printf("--I-- don't follow differnet device %v(%v) %v(%v)\n",
980 dir, dstat.Rdev, path, fstat.Rdev)
981 }
982 if (fstat.Mode & S_IFMT) == S_IFDIR {
983 total = gsh.xxFind(depth+1, total, path, npatv, argv)
984 }
985 }
986 }
987 }
988 return total
989 }
990 func (gsh*GshContext)xxFind(depth int, total *fileSum, dir string, npatv[]string, argv[]string)(*fileSum){
991 nols := isin("-grep", argv)
992 dirfile, oerr := os.OpenFile(dir, os.O_RDONLY, 0)
993 if oerr == nil {
994 //fmt.Printf("--I-- %v(%v)[%d]\n", dir, dirfile, dirfile.Fd())
995 defer dirfile.Close()
996 }else{
997 }
998 }
999 prev := *total

```



```

1000 var dstat syscall.Stat_t
1001 staterr := syscall.Lstat(dir,&dstat) // should be flstat
1002
1003 if staterr != nil {
1004     if !isin("-w",argv){ fmt.Printf("ufind: %v\n",staterr) }
1005     return total
1006 }
1007 //filev,err := ioutil.ReadDir(dir)
1008 //_,err := ioutil.ReadDir(dir) // ReadDir() heavy and bad for huge directory
1009 //
1010 if err != nil {
1011     if !isin("-w",argv){ fmt.Printf("ufind: %v\n",err) }
1012     return total
1013 }
1014 //
1015 if depth == 0 {
1016     total = cumPinfo(total,dir,staterr,dstat,argv,true)
1017     if !nols && !isin("-s",argv) && (!isin("-du",argv) || isin("-a",argv)) {
1018         showFileInfo(dir,argv)
1019     }
1020 }
1021 // it it is not a directory, just scan it and finish
1022
1023 for ei := 0; ; ei++ {
1024     entv,rderr := dirfile.Readdirnames(8*1024)
1025     if len(entv) == 0 || rderr != nil {
1026         //if rderr != nil { fmt.Printf("[%d] len=%d (%v)\n",ei,len(entv),rderr) }
1027         break
1028     }
1029     if 0 < ei {
1030         fmt.Printf("--I-- xxFind[%d] %d large-dir: %s\n",ei,len(entv),dir)
1031     }
1032     total = gsh.xxFindEntv(depth,total,dir,dstat,ei,entv,npats,argv)
1033 }
1034 if isin("-du",argv) {
1035     // if in "du" mode
1036     fmt.Printf("%d\t%s\n",(total.Blocks-prev.Blocks)/2,dir)
1037 }
1038 return total
1039 }
1040
1041 // {ufind|fu|ls} [Files] [-- Names] [-- Expressions]
1042 // Files is "." by default
1043 // Names is "*" by default
1044 // Expressions is "-print" by default for "ufind", or -du for "fu" command
1045 func (gsh*GshContext)xFind(argv[]string){
1046     if 0 < len(argv) && strBegins(argv[0],"?"){
1047         showFound(gsh,argv)
1048         return
1049     }
1050     if isin("-cksum",argv) || isin("-sum",argv) {
1051         gsh.lastCheckSum = CheckSum{}
1052         if isin("-sum",argv) && isin("-add",argv) {
1053             gsh.lastCheckSum.SumType |= SUM_SUM64
1054         }else
1055         if isin("-sum",argv) && isin("-size",argv) {
1056             gsh.lastCheckSum.SumType |= SUM_SIZE
1057         }else
1058         if isin("-sum",argv) && isin("-bsd",argv) {
1059             gsh.lastCheckSum.SumType |= SUM_SUM16_BSD
1060         }else
1061         if isin("-sum",argv) && isin("-sysv",argv) {
1062             gsh.lastCheckSum.SumType |= SUM_SUM16_SYSV
1063         }else
1064         if isin("-sum",argv) {
1065             gsh.lastCheckSum.SumType |= SUM_SUM64
1066         }
1067         if isin("-unix",argv) {
1068             gsh.lastCheckSum.SumType |= SUM_UNIXFILE
1069             gsh.lastCheckSum.Crc32Table = *Crc32.MakeTable(CRC32UNIX)
1070         }
1071         if isin("-ieee",argv){
1072             gsh.lastCheckSum.SumType |= SUM_CRCIEEE
1073             gsh.lastCheckSum.Crc32Table = *Crc32.MakeTable(CRC32IEEE)
1074         }
1075         gsh.lastCheckSum.RusgAtStart = Getrusagev()
1076     }
1077     var total = fileSum{}
1078     npats := []string{}
1079     for _,v := range argv {
1080         if 0 < len(v) && v[0] != '-' {
1081             npats = append(npats,v)
1082         }
1083         if v == "/" { break }
1084         if v == "--" { break }
1085         if v == "-grep" { break }
1086         if v == "-ls" { break }
1087     }
1088     if len(npats) == 0 {
1089         npats = []string{"*"}
1090     }
1091     cwd := "."
1092     // if to be fullpath ::: cwd, _ := os.Getwd()
1093     if len(npats) == 0 { npats = []string{"*"} }
1094     fusage := gsh.xxFind(0,&total,cwd,npats,argv)
1095     if gsh.lastCheckSum.SumType != 0 {
1096         var sumi uint64 = 0
1097         sum := &gsh.lastCheckSum
1098         if (sum.SumType & SUM_SIZE) != 0 {
1099             sumi = uint64(sum.Size)
1100         }
1101         if (sum.SumType & SUM_SUM64) != 0 {
1102             sumi = sum.Sum64
1103         }
1104         if (sum.SumType & SUM_SUM16_SYSV) != 0 {
1105             s := uint32(sum.Sum16)
1106             r := (s & 0xFFFF) + ((s & 0xFFFFFFFF) >> 16)
1107             s = (r & 0xFFFF) + (r >> 16)
1108             sum.Crc32Val = uint32(s)
1109             sumi = uint64(s)
1110         }
1111         if (sum.SumType & SUM_SUM16_BSD) != 0 {
1112             sum.Crc32Val = uint32(sum.Sum16)
1113             sumi = uint64(sum.Sum16)
1114         }
1115         if (sum.SumType & SUM_UNIXFILE) != 0 {
1116             sum.Crc32Val = byteCRC32end(sum.Crc32Val,uint64(sum.Size))
1117             sumi = uint64(byteCRC32end(sum.Crc32Val,uint64(sum.Size)))
1118         }
1119         if 1 < sum.Files {
1120             fmt.Printf("%v %v // %v / %v files, %v/file\r\n",
1121                 sumi,sum.Size,
1122                 abssize(sum.Size),sum.Files,
1123                 abssize(sum.Size/sum.Files))
1124         }else{

```

```

1125         fmt.Printf("%v %v %v\n", .Start
1126             sum1,sum.Size,npats[0])
1127     }
1128 }
1129 if !isin("-grep",argv) {
1130     showFusage("total",fusage)
1131 }
1132 if !isin("-s",argv){
1133     hits := len(gsh.CmdCurrent.FoundFile)
1134     if 0 < hits {
1135         fmt.Printf("--I-- %d files hits // can be refered with !&df\n",
1136             hits,len(gsh.CommandHistory))
1137     }
1138 }
1139 if gsh.lastCheckSum.SumType != 0 {
1140     if isin("-ru",argv){
1141         sum := gsh.lastCheckSum
1142         sum.Done = time.Now()
1143         gsh.lastCheckSum.RusgAtEnd = Getrusagev()
1144         elps := sum.Done.Sub(sum.Start)
1145         fmt.Printf("--cksum-size: %v (%v) / %v files, %v/file\r\n",
1146             sum.Size,abssize(sum.Size),sum.Files,abssize(sum.Size/sum.Files))
1147         nanos := int64(elps)
1148         fmt.Printf("--cksum-time: %v/total, %v/file, %.1f files/s, %v\r\n",
1149             abftime(nanos),
1150             abftime(nanos/sum.Files),
1151             (float64(sum.Files)*1000000000.0)/float64(nanos),
1152             abbspeed(sum.Size,nanos))
1153         diff := RusageSubv(sum.RusgAtEnd,sum.RusgAtStart)
1154         fmt.Printf("--cksum-rusg: %v\n",sRusagef("",argv,diff))
1155     }
1156 }
1157 return
1158 }
1159 }
1160 func showFiles(files[]string){
1161     sp := ""
1162     for i,file := range files {
1163         if 0 < i { sp = " " } else { sp = "" }
1164         fmt.Printf(sp+"%s",escapeWhiteSP(file))
1165     }
1166 }
1167 func showFound(gshCtx *GshContext, argv[]string){
1168     for i,v := range gshCtx.CommandHistory {
1169         if 0 < len(v.FoundFile) {
1170             fmt.Printf("%d (%d) ",i,len(v.FoundFile))
1171             if isin("-ls",argv){
1172                 fmt.Printf("\n")
1173                 for _,file := range v.FoundFile {
1174                     fmt.Printf("%s //sub number?")
1175                     showFileInfo(file,argv)
1176                 }
1177             }else{
1178                 showFiles(v.FoundFile)
1179                 fmt.Printf("\n")
1180             }
1181         }
1182     }
1183 }
1184 }
1185 func showMatchFile(filev []os.FileInfo, npat,dir string, argv[]string)(string,bool){
1186     fname := ""
1187     found := false
1188     for _,v := range filev {
1189         match, := filepath.Match(npat,(v.Name()))
1190         if match {
1191             fname = v.Name()
1192             found = true
1193             //fmt.Printf("%d %s\n",i,v.Name())
1194             showIfExecutable(fname,dir,argv)
1195         }
1196     }
1197     return fname,found
1198 }
1199 func showIfExecutable(name,dir string,argv[]string)(ffullpath string,ffound bool){
1200     var fullpath string
1201     if strBegins(name,DIRSEP){
1202         fullpath = name
1203     }else{
1204         fullpath = dir + DIRSEP + name
1205     }
1206     fi, err := os.Stat(fullpath)
1207     if err != nil {
1208         fullpath = dir + DIRSEP + name + ".go"
1209         fi, err = os.Stat(fullpath)
1210     }
1211     if err == nil {
1212         fm := fi.Mode()
1213         if fm.IsRegular() {
1214             // R_OK=4, W_OK=2, X_OK=1, F_OK=0
1215             if syscall.Access(fullpath,5) == nil {
1216                 ffullpath = fullpath
1217                 ffound = true
1218                 if ! isin("-s", argv) {
1219                     showFileInfo(fullpath,argv)
1220                 }
1221             }
1222         }
1223     }
1224     return ffullpath, ffound
1225 }
1226 func which(list string, argv []string) (fullpathv []string, itis bool){
1227     if len(argv) <= 1 {
1228         fmt.Printf("Usage: which comand [-s] [-a] [-ls]\n")
1229         return []string{"", false}
1230     }
1231     path := argv[1]
1232     if strBegins(path,"/") {
1233         // should check if executable?
1234         _,exOK := showIfExecutable(path,"",argv)
1235         fmt.Printf("--D-- %v exOK=%v\n",path,exOK)
1236         return []string{path},exOK
1237     }
1238     pathenv, efound := os.LookupEnv(list)
1239     if ! efound {
1240         fmt.Printf("--E-- which: no \"%s\" environment\n",list)
1241         return []string{"", false}
1242     }
1243     showall := isin("-a",argv) || 0 < strings.Index(path,"*")
1244     dirv := strings.Split(pathenv,PATHSEP)
1245     ffound := false
1246     ffullpath := path
1247     for _, dir := range dirv {
1248         if 0 <= strings.Index(path,"*") { // by wild-card
1249             list,_ := ioutil.ReadDir(dir)

```

```

1250         ffullpath, ffound = showMatchFile(list,path,dir,argv)
1251     }else{
1252         ffullpath, ffound = showIfExecutable(path,dir,argv)
1253     }
1254     //if ffound && !isin("-a", argv) {
1255     if ffound && !showall {
1256         break;
1257     }
1258 }
1259 return []string{ffullpath}, ffound
1260 }
1261
1262 func stripLeadingWSParg(argv []string)([]string){
1263     for ; 0 < len(argv); {
1264         if len(argv[0]) == 0 {
1265             argv = argv[1:]
1266         }else{
1267             break
1268         }
1269     }
1270     return argv
1271 }
1272 func xEval(argv []string, nlend bool){
1273     argv = stripLeadingWSParg(argv)
1274     if len(argv) == 0 {
1275         fmt.Printf("eval [%sformat] [Go-expression]\n")
1276         return
1277     }
1278     pfmt := "%v"
1279     if argv[0][0] == '%' {
1280         pfmt = argv[0]
1281         argv = argv[1:]
1282     }
1283     if len(argv) == 0 {
1284         return
1285     }
1286     gocode := strings.Join(argv, " ");
1287     //fmt.Printf("eval [%v] [%v]\n",pfmt,gocode)
1288     fset := token.NewFileSet()
1289     rval, _ := types.Eval(fset,nil,token.NoPos,gocode)
1290     fmt.Printf(pfmt,rval.Value)
1291     if nlend { fmt.Printf("\n") }
1292 }
1293
1294 func getval(name string) (found bool, val int) {
1295     /* should expand the name here */
1296     if name == "gsh.pid" {
1297         return true, os.Getpid()
1298     }else
1299     if name == "gsh.ppid" {
1300         return true, os.Getppid()
1301     }
1302     return false, 0
1303 }
1304
1305 func echo(argv []string, nlend bool){
1306     for ai := 1; ai < len(argv); ai++ {
1307         if 1 < ai {
1308             fmt.Printf(" ");
1309         }
1310         arg := argv[ai]
1311         found, val := getval(arg)
1312         if found {
1313             fmt.Printf("%d",val)
1314         }else{
1315             fmt.Printf("%s",arg)
1316         }
1317     }
1318     if nlend {
1319         fmt.Printf("\n");
1320     }
1321 }
1322
1323 func resfile() string {
1324     return "gsh.tmp"
1325 }
1326 //var resF *File
1327 func resmap() {
1328     //_, err := os.OpenFile(resfile(), os.O_RDWR|os.O_CREATE, os.ModeAppend)
1329     // https://developpaper.com/solution-to-golang-bad-file-descriptor-problem/
1330     _, err := os.OpenFile(resfile(), os.O_RDWR|os.O_CREATE, 0600)
1331     if err != nil {
1332         fmt.Printf("refF could not open: %s\n",err)
1333     }else{
1334         fmt.Printf("refF opened\n")
1335     }
1336 }
1337
1338 // @2020-0821
1339 func gshScanArg(str string,strip int)(argv []string){
1340     var si = 0
1341     var sb = 0
1342     var inBracket = 0
1343     var arg1 = make([]byte,LINESIZE)
1344     var ax = 0
1345     debug := false
1346
1347     for ; si < len(str); si++ {
1348         if str[si] != ' ' {
1349             break
1350         }
1351     }
1352     sb = si
1353     for ; si < len(str); si++ {
1354         if sb <= si {
1355             if debug {
1356                 fmt.Printf("--Da- +%d %2d-%2d %s ... %s\n",
1357                     inBracket,sb,si,arg1[0:ax],str[si:])
1358             }
1359         }
1360         ch := str[si]
1361         if ch == '{' {
1362             inBracket += 1
1363             if 0 < strip && inBracket <= strip {
1364                 //fmt.Printf("stripLEV %d <= %d?\n",inBracket,strip)
1365                 continue
1366             }
1367         }
1368         if 0 < inBracket {
1369             if ch == '}' {
1370                 inBracket -= 1
1371                 if 0 < strip && inBracket < strip {
1372                     //fmt.Printf("stripLEV %d < %d?\n",inBracket,strip)
1373                     continue
1374                 }
1375             }
1376         }
1377     }

```

```

1375     }
1376     argl[ax] = ch
1377     ax += 1
1378     continue
1379 }
1380 if str[si] == ' ' {
1381     argv = append(argv, string(argl[0:ax]))
1382     if debug {
1383         fmt.Printf("--Da- [%v][%v-%v] %s ... %s\n",
1384             -1+len(argv), sb, si, str[sb:si], string(str[si:]))
1385     }
1386     sb = si+1
1387     ax = 0
1388     continue
1389 }
1390 argl[ax] = ch
1391 ax += 1
1392 }
1393 if sb < si {
1394     argv = append(argv, string(argl[0:ax]))
1395     if debug {
1396         fmt.Printf("--Da- [%v][%v-%v] %s ... %s\n",
1397             -1+len(argv), sb, si, string(argl[0:ax]), string(str[si:]))
1398     }
1399 }
1400 if debug {
1401     fmt.Printf("--Da- %d [%s] => [%d]%v\n", strip, str, len(argv), argv)
1402 }
1403 return argv
1404 }
1405
1406 // should get stderr (into tmpfile ?) and return
1407 func (gsh*GshContext)Popen(name, mode string)(pin*os.File, pout*os.File, err bool){
1408     var pv = []int{-1, -1}
1409     syscall.Pipe(pv)
1410
1411     xarg := gshScanArg(name, 1)
1412     name = strings.Join(xarg, " ")
1413
1414     pin = os.NewFile(uintptr(pv[0]), "StdoutOf-"+name)
1415     pout = os.NewFile(uintptr(pv[1]), "StdinOf-"+name)
1416     fdix := 0
1417     dir := "?"
1418     if mode == "r" {
1419         dir = "<"
1420         fdix = 1 // read from the stdout of the process
1421     } else {
1422         dir = ">"
1423         fdix = 0 // write to the stdin of the process
1424     }
1425     gshPA := gsh.gshPA
1426     savfd := gshPA.Files[fdix]
1427
1428     var fd uintptr = 0
1429     if mode == "r" {
1430         fd = pout.Fd()
1431         gshPA.Files[fdix] = pout.Fd()
1432     } else {
1433         fd = pin.Fd()
1434         gshPA.Files[fdix] = pin.Fd()
1435     }
1436     // should do this by Goroutine?
1437     if false {
1438         fmt.Printf("--Ip- Opened fd[%v] %s %v\n", fd, dir, name)
1439         fmt.Printf("--RED1 [%d,%d,%d]->[%d,%d,%d]\n",
1440             os.Stdin.Fd(), os.Stdout.Fd(), os.Stderr.Fd(),
1441             pin.Fd(), pout.Fd(), pout.Fd())
1442     }
1443     savi := os.Stdin
1444     savo := os.Stdout
1445     save := os.Stderr
1446     os.Stdin = pin
1447     os.Stdout = pout
1448     os.Stderr = pout
1449     gsh.BackGround = true
1450     gsh.gshellh(name)
1451     gsh.BackGround = false
1452     os.Stdin = savi
1453     os.Stdout = savo
1454     os.Stderr = save
1455
1456     gshPA.Files[fdix] = savfd
1457     return pin, pout, false
1458 }
1459
1460 // <a name="ex-commands">External commands</a>
1461 func (gsh*GshContext)excommand(exec bool, argv []string)(notf bool, exit bool) {
1462     if gsh.CmdTrace { fmt.Printf("--I-- excommand[%v](%v)\n", exec, argv) }
1463
1464     gshPA := gsh.gshPA
1465     fullpathv, itis := which("PATH", []string{"which", argv[0], "-s"})
1466     if itis == false {
1467         return true, false
1468     }
1469     fullpath := fullpathv[0]
1470     argv = unescapeWhiteSPV(argv)
1471     if 0 < strings.Index(fullpath, ".go") {
1472         nargv := argv // []string{}
1473         gofullpathv, itis := which("PATH", []string{"which", ".go", "-s"})
1474         if itis == false {
1475             fmt.Printf("--F-- Go not found\n")
1476             return false, true
1477         }
1478         gofullpath := gofullpathv[0]
1479         nargv = []string{ gofullpath, "run", fullpath }
1480         fmt.Printf("--I-- %s [%s %s %s]\n", gofullpath,
1481             nargv[0], nargv[1], nargv[2])
1482         if exec {
1483             syscall.Exec(gofullpath, nargv, os.Environ())
1484         } else {
1485             pid, _ := syscall.ForkExec(gofullpath, nargv, &gshPA)
1486             if gsh.BackGround {
1487                 fmt.Fprintf(stderr, "--Ip- in Background pid[%d]%d(%v)\n", pid, len(argv), nargv)
1488                 gsh.BackGroundJobs = append(gsh.BackGroundJobs, pid)
1489             } else {
1490                 rusage := syscall.Rusage{}
1491                 syscall.Wait4(pid, nil, 0, &rusage)
1492                 gsh.LastRusage = rusage
1493                 gsh.CmdCurrent.Rusagev[1] = rusage
1494             }
1495         }
1496     } else {
1497         if exec {
1498             syscall.Exec(fullpath, argv, os.Environ())
1499         } else {

```

```

1500     pid, _ := syscall.ForkExec(fullpath,argv,&gshPA)
1501     //fmt.Printf("[%d]\n",pid); // '*' to be background
1502     if gsh.BackGround {
1503         fmt.Fprintf(stderr, "--Ip- in Background pid[%d]d(%v)\n",pid,len(argv),argv)
1504         gsh.BackGroundJobs = append(gsh.BackGroundJobs,pid)
1505     }else{
1506         rusage := syscall.Rusage {}
1507         syscall.Wait4(pid,nil,0,&rusage);
1508         gsh.LastRusage = rusage
1509         gsh.CmdCurrent.Rusagev[1] = rusage
1510     }
1511 }
1512 }
1513 return false,false
1514 }
1515 }
1516 // <a name="builtin">Builtin Commands</a>
1517 func (gshCtx *GshContext) sleep(argv []string) {
1518     if len(argv) < 2 {
1519         fmt.Printf("Sleep 100ms, 100us, 100ns, ...)\n")
1520         return
1521     }
1522     duration := argv[1];
1523     d, err := time.ParseDuration(duration)
1524     if err != nil {
1525         d, err = time.ParseDuration(duration+"s")
1526         if err != nil {
1527             fmt.Printf("duration ? %s (%s)\n",duration,err)
1528             return
1529         }
1530     }
1531     //fmt.Printf("Sleep %v\n",duration)
1532     time.Sleep(d)
1533     if 0 < len(argv[2:]) {
1534         gshCtx.gshellv(argv[2:])
1535     }
1536 }
1537 func (gshCtx *GshContext)repeat(argv []string) {
1538     if len(argv) < 2 {
1539         return
1540     }
1541     start0 := time.Now()
1542     for ri, _ := strconv.Atoi(argv[1]); 0 < ri; ri-- {
1543         if 0 < len(argv[2:]) {
1544             //start := time.Now()
1545             gshCtx.gshellv(argv[2:])
1546             end := time.Now()
1547             elps := end.Sub(start0);
1548             if( 1000000000 < elps ){
1549                 fmt.Printf("(repeat#%d %v)\n",ri,elps);
1550             }
1551         }
1552     }
1553 }
1554 }
1555 func (gshCtx *GshContext)gen(argv []string) {
1556     gshPA := gshCtx.gshPA
1557     if len(argv) < 2 {
1558         fmt.Printf("Usage: %s N\n",argv[0])
1559         return
1560     }
1561     // should br repeated by "repeat" command
1562     count, _ := strconv.Atoi(argv[1])
1563     fd := gshPA.Files[1] // Stdout
1564     file := os.NewFile(fd,"internalStdOut")
1565     fmt.Printf("--I-- Gen. Count=%d to [%d]\n",count,file.Fd())
1566     //buf := []byte{}
1567     outdata := "0123 5678 0123 5678 0123 5678 0123 5678\r"
1568     for gi := 0; gi < count; gi++ {
1569         file.WriteString(outdata)
1570     }
1571     //file.WriteString("\n")
1572     fmt.Printf("\n(%d B)\n",count*len(outdata));
1573     //file.Close()
1574 }
1575 }
1576 // <a name="rexec">Remote Execution</a> // 2020-0820
1577 func Elapsed(from time.Time)(string){
1578     elps := time.Now().Sub(from)
1579     if 1000000000 < elps {
1580         return fmt.Sprintf("[%d.%02ds]",elps/1000000000,(elps%1000000000)/1000000)
1581     }else
1582     if 1000000 < elps {
1583         return fmt.Sprintf("[%d.%03dms]",elps/1000000,(elps%1000000)/1000)
1584     }else{
1585         return fmt.Sprintf("[%d.%03dus]",elps/1000,(elps%1000))
1586     }
1587 }
1588 func abftime(nanos int64)(string){
1589     if 1000000000 < nanos {
1590         return fmt.Sprintf("%d.%02ds",nanos/1000000000,(nanos%1000000000)/1000000)
1591     }else
1592     if 1000000 < nanos {
1593         return fmt.Sprintf("%d.%03dms",nanos/1000000,(nanos%1000000)/1000)
1594     }else{
1595         return fmt.Sprintf("%d.%03dus",nanos/1000,(nanos%1000))
1596     }
1597 }
1598 func abssize(size int64)(string){
1599     fsize := float64(size)
1600     if 1024*1024*1024 < size {
1601         return fmt.Sprintf("%.2fGiB",fsize/(1024*1024*1024))
1602     }else
1603     if 1024*1024 < size {
1604         return fmt.Sprintf("%.3fMiB",fsize/(1024*1024))
1605     }else{
1606         return fmt.Sprintf("%.3fKiB",fsize/1024)
1607     }
1608 }
1609 func absze(size int64)(string){
1610     fsize := float64(size)
1611     if 1024*1024*1024 < size {
1612         return fmt.Sprintf("%.2fGiB",fsize/(1024*1024*1024))
1613     }else
1614     if 1024*1024 < size {
1615         return fmt.Sprintf("%.3fMiB",fsize/(1024*1024))
1616     }else{
1617         return fmt.Sprintf("%.3fKiB",fsize/1024)
1618     }
1619 }
1620 func abbspeed(totalB int64,ns int64)(string){
1621     MBs := (float64(totalB)/1000000) / (float64(ns)/1000000000)
1622     if 1000 <= MBs {
1623         return fmt.Sprintf("%.3fGB/s",MBs/1000)
1624     }

```

```

1625     if l <= MBS {
1626         return fmt.Sprintf("%6.3fMB/s",MBS)
1627     }else{
1628         return fmt.Sprintf("%6.3fKB/s",MBS*1000)
1629     }
1630 }
1631 func abspeed(totalB int64,ns time.Duration)(string){
1632     MBS := (float64(totalB)/1000000) / (float64(ns)/1000000000)
1633     if 1000 <= MBS {
1634         return fmt.Sprintf("%6.3fGBps",MBS/1000)
1635     }
1636     if l <= MBS {
1637         return fmt.Sprintf("%6.3fMBps",MBS)
1638     }else{
1639         return fmt.Sprintf("%6.3fKBps",MBS*1000)
1640     }
1641 }
1642 func fileRelay(what string,in*os.File,out*os.File,size int64,bsiz int)(wcount int64){
1643     Start := time.Now()
1644     buff := make([]byte,bsiz)
1645     var total int64 = 0
1646     var rem int64 = size
1647     nio := 0
1648     Prev := time.Now()
1649     var PrevSize int64 = 0
1650
1651     fmt.Printf(Elapsed(Start)+"--In- X: %s (%v/%v/%v) START\n",
1652         what,absize(total),size,nio)
1653
1654     for i:= 0; ; i++ {
1655         var len = bsiz
1656         if int(rem) < len {
1657             len = int(rem)
1658         }
1659         Now := time.Now()
1660         Elps := Now.Sub(Prev);
1661         if 1000000000 < Now.Sub(Prev) {
1662             fmt.Printf(Elapsed(Start)+"--In- X: %s (%v/%v/%v) %s\n",
1663                 what,absize(total),size,nio,
1664                 abspeed((total-PrevSize),Elps))
1665             Prev = Now;
1666             PrevSize = total
1667         }
1668         rlen := len
1669         if in != nil {
1670             // should watch the disconnection of out
1671             rcc,err := in.Read(buff[0:rlen])
1672             if err != nil {
1673                 fmt.Printf(Elapsed(Start)+"--En- X: %s read(%v,%v)<%v\n",
1674                     what,rcc,err,in.Name())
1675                 break
1676             }
1677             rlen = rcc
1678             if string(buff[0:10]) == "(SoftEOF " {
1679                 var ecc int64 = 0
1680                 fmt.Sscanf(string(buff),"(SoftEOF %v",&ecc)
1681                 fmt.Printf(Elapsed(Start)+"--En- X: %s Recv ((SoftEOF %v))/&v\n",
1682                     what,ecc,total)
1683                 if ecc == total {
1684                     break
1685                 }
1686             }
1687         }
1688
1689         wlen := rlen
1690         if out != nil {
1691             wcc,err := out.Write(buff[0:rlen])
1692             if err != nil {
1693                 fmt.Printf(Elapsed(Start)+"--En-- X: %s write(%v,%v)>%v\n",
1694                     what,wcc,err,out.Name())
1695                 break
1696             }
1697             wlen = wcc
1698         }
1699         if wlen < rlen {
1700             fmt.Printf(Elapsed(Start)+"--En- X: %s incomplete write (%v/%v)\n",
1701                 what,wlen,rlen)
1702             break;
1703         }
1704
1705         nio += 1
1706         total += int64(rlen)
1707         rem -= int64(rlen)
1708         if rem <= 0 {
1709             break
1710         }
1711     }
1712     Done := time.Now()
1713     Elps := float64(Done.Sub(Start))/1000000000 //Seconds
1714     TotalMB := float64(total)/1000000 //MB
1715     MBps := TotalMB / Elps
1716     fmt.Printf(Elapsed(Start)+"--In- X: %s (%v/%v/%v) %v %6.3fMB/s\n",
1717         what,total,size,nio,absize(total),MBps)
1718     return total
1719 }
1720 func tcpPush(clnt *os.File){
1721     // shrink socket buffer and recover
1722     usleep(100);
1723 }
1724 func (gsh*GshContext)RexecServer(argv[]string){
1725     debug := true
1726     Start0 := time.Now()
1727     Start := Start0
1728     // if local == ""; { local = "0.0.0.0:9999" }
1729     local := "0.0.0.0:9999"
1730
1731     if 0 < len(argv) {
1732         if argv[0] == "-s" {
1733             debug = false
1734             argv = argv[1:]
1735         }
1736     }
1737     if 0 < len(argv) {
1738         argv = argv[1:]
1739     }
1740     port, err := net.ResolveTCPAddr("tcp",local);
1741     if err != nil {
1742         fmt.Printf("--En- S: Address error: %s (%s)\n",local,err)
1743         return
1744     }
1745     fmt.Printf(Elapsed(Start)+"--In- S: Listening at %s...\n",local);
1746     sconn, err := net.ListenTCP("tcp", port)
1747     if err != nil {
1748         fmt.Printf(Elapsed(Start)+"--En- S: Listen error: %s (%s)\n",local,err)
1749         return

```

```

1750 }
1751
1752 reqbuf := make([]byte,LINESIZE)
1753 res := ""
1754 for {
1755     fmt.Printf(Elapsed(Start0)+"--In- S: Listening at %s...\n",local);
1756     aconn, err := sconn.AcceptTCP()
1757     Start = time.Now()
1758     if err != nil {
1759         fmt.Printf(Elapsed(Start)+"--En- S: Accept error: %s (%s)\n",local,err)
1760         return
1761     }
1762     clnt, _ := aconn.File()
1763     fd := clnt.Fd()
1764     ar := aconn.RemoteAddr()
1765     if debug { fmt.Printf(Elapsed(Start0)+"--In- S: Accepted TCP at %s [%d] <- %v\n",
1766         local,fd,ar) }
1767     res = fmt.Sprintf("220 GShell/%s Server\r\n",VERSION)
1768     fmt.Fprintf(clnt,"%s",res)
1769     if debug { fmt.Printf(Elapsed(Start)+"--In- S: %s",res) }
1770     count, err := clnt.Read(reqbuf)
1771     if err != nil {
1772         fmt.Printf(Elapsed(Start)+"--En- C: (%v %v) %v",
1773             count,err,string(reqbuf))
1774     }
1775     req := string(reqbuf[:count])
1776     if debug { fmt.Printf(Elapsed(Start)+"--In- C: %v",string(req)) }
1777     reqv := strings.Split(string(req),"\r")
1778     cmdv := gshScanArg(reqv[0],0)
1779     //cmdv := strings.Split(reqv[0]," ")
1780     switch cmdv[0] {
1781     case "HELO":
1782         res = fmt.Sprintf("250 %v",req)
1783     case "GET":
1784         // download {remotefile|-zN} [localfile]
1785         var dsz int64 = 32*1024*1024
1786         var bsz int = 64*1024
1787         var fname string = ""
1788         var in *os.File = nil
1789         var pseudoEOF = false
1790         if 1 < len(cmdv) {
1791             fname = cmdv[1]
1792             if strBegins(fname,"-z") {
1793                 fmt.Sscanf(fname[2:], "%d",&dsz)
1794             }else{
1795                 if strBegins(fname,"{") {
1796                     xin,xout,err := gsh.Popen(fname,"r")
1797                     if err {
1798                         }else{
1799                             xout.Close()
1800                             defer xin.Close()
1801                             in = xin
1802                             dsz = MaxStreamSize
1803                             pseudoEOF = true
1804                         }
1805                     }else{
1806                         xin,err := os.Open(fname)
1807                         if err != nil {
1808                             fmt.Printf("--En- GET (%v)\n",err)
1809                         }else{
1810                             defer xin.Close()
1811                             in = xin
1812                             fi,_ := xin.Stat()
1813                             dsz = fi.Size()
1814                         }
1815                     }
1816                 }
1817             //fmt.Printf(Elapsed(Start)+"--In- GET %v:%v\n",dsz,bsz)
1818             res = fmt.Sprintf("200 %v\r\n",dsz)
1819             fmt.Fprintf(clnt,"%v",res)
1820             tcpPush(clnt); // should be separated as line in receiver
1821             fmt.Printf(Elapsed(Start)+"--In- S: %v",res)
1822             wcount := fileRelay("SendGET",in,clnt,dsz,bsz)
1823             if pseudoEOF {
1824                 in.Close() // pipe from the command
1825                 // show end of stream data (its size) by OOB?
1826                 SoftEOF := fmt.Sprintf("({SoftEOF %v})",wcount)
1827                 fmt.Printf(Elapsed(Start)+"--In- S: Send %v\n",SoftEOF)
1828             }
1829             tcpPush(clnt); // to let SoftEOF data apper at the top of received data
1830             fmt.Fprintf(clnt,"%v\r\n",SoftEOF)
1831             tcpPush(clnt); // to let SoftEOF alone in a packet (separate with 200 OK)
1832             // with client generated random?
1833             //fmt.Printf("--In- L: close %v (%v)\n",in.Fd(),in.Name())
1834         }
1835         res = fmt.Sprintf("200 GET done\r\n")
1836     case "PUT":
1837         // upload {srcfile|-zN} [dstfile]
1838         var dsz int64 = 32*1024*1024
1839         var bsz int = 64*1024
1840         var fname string = ""
1841         var out *os.File = nil
1842         if 1 < len(cmdv) { // localfile
1843             fmt.Sscanf(cmdv[1],"%d",&dsz)
1844         }
1845         if 2 < len(cmdv) {
1846             fname = cmdv[2]
1847             if fname == "-" {
1848                 // nul dev
1849             }else{
1850                 if strBegins(fname,"{") {
1851                     xin,xout,err := gsh.Popen(fname,"w")
1852                     if err {
1853                         }else{
1854                             xin.Close()
1855                             defer xout.Close()
1856                             out = xout
1857                         }
1858                     }else{
1859                         // should write to temporary file
1860                         // should suppress ^C on tty
1861                     xout,err := os.OpenFile(fname,os.O_CREATE|os.O_RDWR|os.O_TRUNC,0600)
1862                     //fmt.Printf("--In- S: open(%v) out(%v) err(%v)\n",fname,xout,err)
1863                     if err != nil {
1864                         fmt.Printf("--En- PUT (%v)\n",err)
1865                     }else{
1866                         out = xout
1867                     }
1868                 }
1869             }
1870             fmt.Printf(Elapsed(Start)+"--In- L: open(%v,w) %v (%v)\n",
1871                 fname,local,err)
1872         }
1873         fmt.Printf(Elapsed(Start)+"--In- PUT %v (%v)\n",dsz,bsz)
1874         fmt.Printf(Elapsed(Start)+"--In- S: 200 %v OK\r\n",dsz)
1875         fmt.Fprintf(clnt,"200 %v OK\r\n",dsz)

```

```

1875         fileRelay("RecvPUT",clnt,out,dsize,bsize)
1876         res = fmt.Sprintf("200 PUT done\r\n")
1877         default:
1878             res = fmt.Sprintf("400 What? %v",req)
1879     }
1880     swcc,serr := clnt.Write([]byte(res))
1881     if serr != nil {
1882         fmt.Printf(Elapsed(Start)+"--In- S: (wc=%v er=%v) %v",swcc,serr,res)
1883     }else{
1884         fmt.Printf(Elapsed(Start)+"--In- S: %v",res)
1885     }
1886     aconn.Close();
1887     clnt.Close();
1888 }
1889     sconn.Close();
1890 }
1891 func (gsh*GshContext)RexecClient(argv[]string)(int,string){
1892     debug := true
1893     Start := time.Now()
1894     if len(argv) == 1 {
1895         return -1,"EmptyARG"
1896     }
1897     argv = argv[1:]
1898     if argv[0] == "-serv" {
1899         gsh.RexecServer(argv[1:])
1900         return 0,"Server"
1901     }
1902     remote := "0.0.0.0:9999"
1903     if argv[0][0] == '8' {
1904         remote = argv[0][1:]
1905         argv = argv[1:]
1906     }
1907     if argv[0] == "-s" {
1908         debug = false
1909         argv = argv[1:]
1910     }
1911     dport, err := net.ResolveTCPAddr("tcp",remote);
1912     if err != nil {
1913         fmt.Printf(Elapsed(Start)+"Address error: %s (%s)\n",remote,err)
1914         return -1,"AddressError"
1915     }
1916     fmt.Printf(Elapsed(Start)+"--In- C: Connecting to %s\n",remote)
1917     serv, err := net.DialTCP("tcp",nil,dport)
1918     if err != nil {
1919         fmt.Printf(Elapsed(Start)+"Connection error: %s (%s)\n",remote,err)
1920         return -1,"CannotConnect"
1921     }
1922     if debug {
1923         al := serv.LocalAddr()
1924         fmt.Printf(Elapsed(Start)+"--In- C: Connected to %v <- %v\n",remote,al)
1925     }
1926
1927     req := ""
1928     res := make([]byte,LINESIZE)
1929     count,err := serv.Read(res)
1930     if err != nil {
1931         fmt.Printf("--En- S: (%3d,%v) %v",count,err,string(res))
1932     }
1933     if debug { fmt.Printf(Elapsed(Start)+"--In- S: %v",string(res)) }
1934
1935     if argv[0] == "GET" {
1936         savPA := gsh.gshPA
1937         var bsize int = 64*1024
1938         req = fmt.Sprintf("%v\r\n",strings.Join(argv," "))
1939         fmt.Printf(Elapsed(Start)+"--In- C: %v",req)
1940         fmt.Fprint(serv,req)
1941         count,err = serv.Read(res)
1942         if err != nil {
1943             }else{
1944                 var dsize int64 = 0
1945                 var out *os.File = nil
1946                 var out_tobeclosed *os.File = nil
1947                 var fname string = ""
1948                 var rcode int = 0
1949                 var pid int = -1
1950                 fmt.Sscanf(string(res),"%d %d",&rcode,&dsize)
1951                 fmt.Printf(Elapsed(Start)+"--In- S: %v",string(res[0:count]))
1952                 if 3 <= len(argv) {
1953                     fname = argv[2]
1954                     if strBegins(fname,"{") {
1955                         xin,xout,err := gsh.Popen(fname,"w")
1956                         if err {
1957                             }else{
1958                                 xin.Close()
1959                                 defer xout.Close()
1960                                 out = xout
1961                                 out_tobeclosed = xout
1962                                 pid = 0 // should be its pid
1963                             }
1964                         }else{
1965                             // should write to temporary file
1966                             // should suppress ^C on tty
1967                             xout,err := os.OpenFile(fname,os.O_CREATE|os.O_RDWR|os.O_TRUNC,0600)
1968                             if err != nil {
1969                                 fmt.Print("--En- %v\n",err)
1970                             }
1971                             out = xout
1972                             //fmt.Printf("--In-- %d > %s\n",out.Fd(),fname)
1973                         }
1974                     }
1975                     in,_ := serv.File()
1976                     fileRelay("RecvGET",in,out,dsize,bsize)
1977                     if 0 <= pid {
1978                         gsh.gshPA = savPA // recovery of Fd(), and more?
1979                         fmt.Printf(Elapsed(Start)+"--In- L: close Pipe > %v\n",fname)
1980                         out_tobeclosed.Close()
1981                         //syscall.Wait4(pid,nil,0,nil) //00
1982                     }
1983                 }
1984             }else
1985             if argv[0] == "PUT" {
1986                 remote,_ := serv.File()
1987                 var local *os.File = nil
1988                 var dsize int64 = 32*1024*1024
1989                 var bsize int = 64*1024
1990                 var ofile string = "-"
1991                 //fmt.Printf("--I-- Rex %v\n",argv)
1992                 if 1 < len(argv) {
1993                     fname := argv[1]
1994                     if strBegins(fname,"-z") {
1995                         fmt.Sscanf(fname[2:], "%d",&dsize)
1996                     }else
1997                     if strBegins(fname,"{") {
1998                         xin,xout,err := gsh.Popen(fname,"r")
1999                         if err {

```



```

2000     }else{
2001         xout.Close()
2002         defer xin.Close()
2003         //in = xin
2004         local = xin
2005         fmt.Printf("--In- [%d] < Upload output of %v\n",
2006             local.Fd(),fname)
2007         ofile = "-from."+fname
2008         dsize = MaxStreamSize
2009     }
2010 }else{
2011     xlocal,err := os.Open(fname)
2012     if err != nil {
2013         fmt.Printf("--En- (%s)\n",err)
2014         local = nil
2015     }else{
2016         local = xlocal
2017         fi,_ := local.Stat()
2018         dsize = fi.Size()
2019         defer local.Close()
2020         //fmt.Printf("--I-- Rex in(%v / %v)\n",ofile,dsize)
2021     }
2022     ofile = fname
2023     fmt.Printf(Elapsed(Start)+"--In- L: open(%v,r)=%v %v (%v)\n",
2024         fname,dsize,local,err)
2025 }
2026 }
2027 if 2 < len(argv) && argv[2] != "" {
2028     ofile = argv[2]
2029     //fmt.Printf("(%d)%v B.ofile=%v\n",len(argv),argv,ofile)
2030 }
2031 //fmt.Printf(Elapsed(Start)+"--I-- Rex out(%v)\n",ofile)
2032 fmt.Printf(Elapsed(Start)+"--In- PUT %v (%v)\n",dsize,bsize)
2033 req = fmt.Sprintf("PUT %v %v \r\n",dsize,ofile)
2034 if debug { fmt.Printf(Elapsed(Start)+"--In- C: %v",req) }
2035 fmt.Fprintf(serv,"%v",req)
2036 count,err = serv.Read(res)
2037 if debug { fmt.Printf(Elapsed(Start)+"--In- S: %v",string(res[0:count])) }
2038 fileRelay("SendPUT",local,remote,dsize,bsize)
2039 }else{
2040     req = fmt.Sprintf("%v\r\n",strings.Join(argv, " "))
2041     if debug { fmt.Printf(Elapsed(Start)+"--In- C: %v",req) }
2042     fmt.Fprintf(serv,"%v",req)
2043     //fmt.Printf("--In- sending RexRequest(%v)\n",len(req))
2044 }
2045 //fmt.Printf(Elapsed(Start)+"--In- waiting RexResponse...\n")
2046 count,err = serv.Read(res)
2047 ress := ""
2048 if count == 0 {
2049     ress = "(nil)\r\n"
2050 }else{
2051     ress = string(res[:count])
2052 }
2053 if err != nil {
2054     fmt.Printf(Elapsed(Start)+"--En- S: (%d,%v) %v",count,err,ress)
2055 }else{
2056     fmt.Printf(Elapsed(Start)+"--In- S: %v",ress)
2057 }
2058 serv.Close()
2059 //conn.Close()
2060
2061 var stat string
2062 var rcode int
2063 fmt.Sscanf(ress,"%d %s",&rcode,&stat)
2064 //fmt.Printf("--D-- Client: %v (%v)",rcode,stat)
2065 return rcode,ress
2066 }
2067
2068 // <a name="remote-sh">Remote Shell</a>
2069 // gcp file [...] { [host],[port:][dir] | dir } // -p | -no-p
2070 func (gsh*GshContext)FileCopy(argv []string){
2071     var host = ""
2072     var port = ""
2073     var upload = false
2074     var download = false
2075     var xargv = []string{"rex-gcp"}
2076     var srcv = []string{}
2077     var dstv = []string{}
2078     argv = argv[1:]
2079
2080     for _,v := range argv {
2081         /*
2082         if v[0] == '-' { // might be a pseudo file (generated date)
2083             continue
2084         }
2085         */
2086         obj := strings.Split(v,":")
2087         //fmt.Printf("%d %v %v\n",len(obj),v,obj)
2088         if 1 < len(obj) {
2089             host = obj[0]
2090             file := ""
2091             if 0 < len(host) {
2092                 gsh.LastServer.host = host
2093             }else{
2094                 host = gsh.LastServer.host
2095                 port = gsh.LastServer.port
2096             }
2097             if 2 < len(obj) {
2098                 port = obj[1]
2099                 if 0 < len(port) {
2100                     gsh.LastServer.port = port
2101                 }else{
2102                     port = gsh.LastServer.port
2103                 }
2104                 file = obj[2]
2105             }else{
2106                 file = obj[1]
2107             }
2108             if len(srcv) == 0 {
2109                 download = true
2110                 srcv = append(srcv,file)
2111                 continue
2112             }
2113             upload = true
2114             dstv = append(dstv,file)
2115             continue
2116         }
2117         /*
2118         idx := strings.Index(v,":")
2119         if 0 <= idx {
2120             remote = v[0:idx]
2121             if len(srcv) == 0 {
2122                 download = true
2123                 srcv = append(srcv,v[idx+1:])
2124                 continue

```

```

2125     }
2126     upload = true
2127     dstv = append(dstv,v[idx+1:])
2128     continue
2129     }
2130     */
2131     if download {
2132         dstv = append(dstv,v)
2133     }else{
2134         srcv = append(srcv,v)
2135     }
2136 }
2137 hostport := "@" + host + ":" + port
2138 if upload {
2139     if host != "" { xargv = append(xargv,hostport) }
2140     xargv = append(xargv,"PUT")
2141     xargv = append(xargv,srcv[0:]...)
2142     xargv = append(xargv,dstv[0:]...)
2143     //fmt.Printf("--I-- FileCopy PUT gsh://%s/%v < %v // %v\n",hostport,dstv,srcv,xargv)
2144     fmt.Printf("--I-- FileCopy PUT gsh://%s/%v < %v\n",hostport,dstv,srcv)
2145     gsh.RexecClient(xargv)
2146 }else{
2147     if download {
2148         if host != "" { xargv = append(xargv,hostport) }
2149         xargv = append(xargv,"GET")
2150         xargv = append(xargv,srcv[0:]...)
2151         xargv = append(xargv,dstv[0:]...)
2152         //fmt.Printf("--I-- FileCopy GET gsh://%v/%v > %v // %v\n",hostport,srcv,dstv,xargv)
2153         fmt.Printf("--I-- FileCopy GET gsh://%v/%v > %v\n",hostport,srcv,dstv)
2154         gsh.RexecClient(xargv)
2155     }else{
2156     }
2157 }
2158 }
2159 // target
2160 func (gsh*GshContext)Trelpath(rloc string)(string){
2161     cwd, _ := os.Getwd()
2162     os.Chdir(gsh.RWD)
2163     os.Chdir(rloc)
2164     twd, _ := os.Getwd()
2165     os.Chdir(cwd)
2166 }
2167 tpath := twd + "/" + rloc
2168 return tpath
2169 }
2170 // join to rremote GShell - [user@]host[:port] or cd host[:port]:path
2171 func (gsh*GshContext)Rjoin(argv[]string){
2172     if len(argv) <= 1 {
2173         fmt.Printf("--I-- current server = %v\n",gsh.RSERV)
2174         return
2175     }
2176     serv := argv[1]
2177     servv := strings.Split(serv,":")
2178     if 1 <= len(servv) {
2179         if servv[0] == "lo" {
2180             servv[0] = "localhost"
2181         }
2182     }
2183     switch len(servv) {
2184     case 1:
2185         //if strings.Index(serv,":") < 0 {
2186             serv = servv[0] + ":" + fmt.Sprintf("%d",GSH_PORT)
2187         //}
2188     case 2: // host:port
2189         serv = strings.Join(servv,":")
2190     }
2191     xargv := []string{"rex-join","@"+serv,"HELO"}
2192     rcode,stat := gsh.RexecClient(xargv)
2193     if (rcode / 100) == 2 {
2194         fmt.Printf("--I-- OK Joined (%v) %v\n",rcode,stat)
2195         gsh.RSERV = serv
2196     }else{
2197         fmt.Printf("--I-- NG, could not joined (%v) %v\n",rcode,stat)
2198     }
2199 }
2200 func (gsh*GshContext)Rexec(argv[]string){
2201     if len(argv) <= 1 {
2202         fmt.Printf("--I-- rexec command [ | {file || {command} ]\n",gsh.RSERV)
2203         return
2204     }
2205 }
2206 /*
2207 nargv := gshScanArg(strings.Join(argv," "),0)
2208 fmt.Printf("--D-- nargc=%d [%v]\n",len(nargv),nargv)
2209 if nargv[1][0] != '{' {
2210     nargv[1] = "{" + nargv[1] + "}"
2211     fmt.Printf("--D-- nargc=%d [%v]\n",len(nargv),nargv)
2212 }
2213 argv = nargv
2214 */
2215 nargv := []string{}
2216 nargv = append(nargv,"{"+strings.Join(argv[1:]," ")+"}")
2217 fmt.Printf("--D-- nargc=%d %v\n",len(nargv),nargv)
2218 argv = nargv
2219 }
2220 xargv := []string{"rex-exec","@"+gsh.RSERV,"GET"}
2221 xargv = append(xargv,argv...)
2222 xargv = append(xargv,"/dev/tty")
2223 rcode,stat := gsh.RexecClient(xargv)
2224 if (rcode / 100) == 2 {
2225     fmt.Printf("--I-- OK Rexec (%v) %v\n",rcode,stat)
2226 }else{
2227     fmt.Printf("--I-- NG Rexec (%v) %v\n",rcode,stat)
2228 }
2229 }
2230 func (gsh*GshContext)Rchdir(argv[]string){
2231     if len(argv) <= 1 {
2232         return
2233     }
2234     cwd, _ := os.Getwd()
2235     os.Chdir(gsh.RWD)
2236     os.Chdir(argv[1])
2237     twd, _ := os.Getwd()
2238     gsh.RWD = twd
2239     fmt.Printf("--I-- JWD=%v\n",twd)
2240     os.Chdir(cwd)
2241 }
2242 func (gsh*GshContext)Rpwd(argv[]string){
2243     fmt.Printf("%v\n",gsh.RWD)
2244 }
2245 func (gsh*GshContext)Rls(argv[]string){
2246     cwd, _ := os.Getwd()
2247     os.Chdir(gsh.RWD)
2248     argv[0] = "-ls"
2249     gsh.XFind(argv)

```

```

2250     os.Chdir(cwd)
2251 }
2252 func (gsh*GshContext)Rput(argv[]string){
2253     var local string = ""
2254     var remote string = ""
2255     if 1 < len(argv) {
2256         local = argv[1]
2257         remote = local // base name
2258     }
2259     if 2 < len(argv) {
2260         remote = argv[2]
2261     }
2262     fmt.Printf("--I-- jput from=%v to=%v\n",local,gsh.Trelpath(remote))
2263 }
2264 func (gsh*GshContext)Rget(argv[]string){
2265     var remote string = ""
2266     var local string = ""
2267     if 1 < len(argv) {
2268         remote = argv[1]
2269         local = remote // base name
2270     }
2271     if 2 < len(argv) {
2272         local = argv[2]
2273     }
2274     fmt.Printf("--I-- jget from=%v to=%v\n",gsh.Trelpath(remote),local)
2275 }
2276
2277 // <a name="network">network</a>
2278 // -s, -si, -so // bi-directional, source, sync (maybe socket)
2279 func (gshCtx*GshContext)sconnect(inTCP bool, argv []string) {
2280     gshPA := gshCtx.gshPA
2281     if len(argv) < 2 {
2282         fmt.Printf("Usage: -s [host]:[port[.udp]]\n")
2283         return
2284     }
2285     remote := argv[1]
2286     if remote == ":" { remote = "0.0.0.0:9999" }
2287
2288     if inTCP { // TCP
2289         dport, err := net.ResolveTCPAddr("tcp",remote);
2290         if err != nil {
2291             fmt.Printf("Address error: %s (%s)\n",remote,err)
2292             return
2293         }
2294         conn, err := net.DialTCP("tcp",nil,dport)
2295         if err != nil {
2296             fmt.Printf("Connection error: %s (%s)\n",remote,err)
2297             return
2298         }
2299         file, _ := conn.File();
2300         fd := file.Fd()
2301         fmt.Printf("Socket: connected to %s, socket[%d]\n",remote,fd)
2302
2303         savfd := gshPA.Files[1]
2304         gshPA.Files[1] = fd;
2305         gshCtx.gshelly(argv[2:])
2306         gshPA.Files[1] = savfd
2307         file.Close()
2308         conn.Close()
2309     }else{
2310         //dport, err := net.ResolveUDPAddr("udp4",remote);
2311         dport, err := net.ResolveUDPAddr("udp",remote);
2312         if err != nil {
2313             fmt.Printf("Address error: %s (%s)\n",remote,err)
2314             return
2315         }
2316         //conn, err := net.DialUDP("udp4",nil,dport)
2317         conn, err := net.DialUDP("udp",nil,dport)
2318         if err != nil {
2319             fmt.Printf("Connection error: %s (%s)\n",remote,err)
2320             return
2321         }
2322         file, _ := conn.File();
2323         fd := file.Fd()
2324
2325         ar := conn.RemoteAddr()
2326         //al := conn.LocalAddr()
2327         fmt.Printf("Socket: connected to %s [%s], socket[%d]\n",
2328             remote,ar.String(),fd)
2329
2330         savfd := gshPA.Files[1]
2331         gshPA.Files[1] = fd;
2332         gshCtx.gshelly(argv[2:])
2333         gshPA.Files[1] = savfd
2334         file.Close()
2335         conn.Close()
2336     }
2337 }
2338 func (gshCtx*GshContext)saccept(inTCP bool, argv []string) {
2339     gshPA := gshCtx.gshPA
2340     if len(argv) < 2 {
2341         fmt.Printf("Usage: -ac [host]:[port[.udp]]\n")
2342         return
2343     }
2344     local := argv[1]
2345     if local == ":" { local = "0.0.0.0:9999" }
2346     if inTCP { // TCP
2347         port, err := net.ResolveTCPAddr("tcp",local);
2348         if err != nil {
2349             fmt.Printf("Address error: %s (%s)\n",local,err)
2350             return
2351         }
2352         //fmt.Printf("Listen at %s...\n",local);
2353         sconn, err := net.ListenTCP("tcp", port)
2354         if err != nil {
2355             fmt.Printf("Listen error: %s (%s)\n",local,err)
2356             return
2357         }
2358         //fmt.Printf("Accepting at %s...\n",local);
2359         aconn, err := sconn.AcceptTCP()
2360         if err != nil {
2361             fmt.Printf("Accept error: %s (%s)\n",local,err)
2362             return
2363         }
2364         file, _ := aconn.File()
2365         fd := file.Fd()
2366         fmt.Printf("Accepted TCP at %s [%d]\n",local,fd)
2367
2368         savfd := gshPA.Files[0]
2369         gshPA.Files[0] = fd;
2370         gshCtx.gshelly(argv[2:])
2371         gshPA.Files[0] = savfd
2372
2373         sconn.Close();
2374         aconn.Close();

```

```

2375     file.Close();
2376 }else{
2377     //port, err := net.ResolveUDPAddr("udp4",local);
2378     port, err := net.ResolveUDPAddr("udp",local);
2379     if err != nil {
2380         fmt.Printf("Address error: %s (%s)\n",local,err)
2381         return
2382     }
2383     fmt.Printf("Listen UDP at %s...\n",local);
2384     //uconn, err := net.ListenUDP("udp4", port)
2385     uconn, err := net.ListenUDP("udp", port)
2386     if err != nil {
2387         fmt.Printf("Listen error: %s (%s)\n",local,err)
2388         return
2389     }
2390     file, _ := uconn.File()
2391     fd := file.Fd()
2392     ar := uconn.RemoteAddr()
2393     remote := ""
2394     if ar != nil { remote = ar.String() }
2395     if remote == "" { remote = "?" }
2396
2397     // not yet received
2398     //fmt.Printf("Accepted at %s [%d] <- %s\n",local,fd,"")
2399
2400     savfd := gshPA.Files[0]
2401     gshPA.Files[0] = fd;
2402     savenv := gshPA.Env
2403     gshPA.Env = append(savenv, "REMOTE_HOST="+remote)
2404     gshCtx.gshellv(argv[2:])
2405     gshPA.Env = savenv
2406     gshPA.Files[0] = savfd
2407
2408     uconn.Close();
2409     file.Close();
2410 }
2411 }
2412
2413 // empty line command
2414 func (gshCtx*GshContext)xPwd(argv[]string){
2415     // execute context command, pwd + date
2416     // context notation, representation scheme, to be resumed at re-login
2417     cwd, _ := os.Getwd()
2418     switch {
2419     case isin("-a",argv):
2420         gshCtx.ShowChdirHistory(argv)
2421     case isin("-ls",argv):
2422         showFileInfo(cwd,argv)
2423     default:
2424         fmt.Printf("%s\n",cwd)
2425     case isin("-v",argv): // obsolete empty command
2426         t := time.Now()
2427         date := t.Format(time.UnixDate)
2428         exe, _ := os.Executable()
2429         host, _ := os.Hostname()
2430         fmt.Printf("{PWD=\"%s\"}\n",cwd)
2431         fmt.Printf(" HOST=\"%s\" ",host)
2432         fmt.Printf(" DATE=\"%s\" ",date)
2433         fmt.Printf(" TIME=\"%s\" ",t.String())
2434         fmt.Printf(" PID=\"%d\" ",os.Getpid())
2435         fmt.Printf(" EXE=\"%s\" ",exe)
2436         fmt.Printf("}\n")
2437     }
2438 }
2439
2440 // <a name="history">History</a>
2441 // these should be browsed and edited by HTTP browser
2442 // show the time of command with -t and direcotry with -ls
2443 // openfile-history, sort by -a -m -c
2444 // sort by elapsed time by -t -s
2445 // search by "more" like interface
2446 // edit history
2447 // sort history, and wc or uniq
2448 // CPU and other resource consumptions
2449 // limit showing range (by time or so)
2450 // export / import history
2451 func (gshCtx *GshContext)xHistory(argv []string){
2452     atWorkDirX := -1
2453     if 1 < len(argv) && strBegins(argv[1],"@") {
2454         atWorkDirX,_ = strconv.Atoi(argv[1][1:])
2455     }
2456     //fmt.Printf("--D-- showHistory(%v)\n",argv)
2457     for i, v := range gshCtx.CommandHistory {
2458         // exclude commands not to be listed by default
2459         // internal commands may be suppressed by default
2460         if v.CmdLine == "" && !isin("-a",argv) {
2461             continue;
2462         }
2463         if 0 <= atWorkDirX {
2464             if v.WorkDirX != atWorkDirX {
2465                 continue
2466             }
2467         }
2468         if !isin("-n",argv){ // like "fc"
2469             fmt.Printf("!%-2d ",i)
2470         }
2471         if isin("-v",argv){
2472             fmt.Println(v) // should be with it date
2473         }else{
2474             if isin("-l",argv) || isin("-l0",argv) {
2475                 elps := v.EndAt.Sub(v.StartAt);
2476                 start := v.StartAt.Format(time.Stamp)
2477                 fmt.Printf("@%d ",v.WorkDirX)
2478                 fmt.Printf("[%v] %11v/t ",start,elps)
2479             }
2480             if isin("-l",argv) && !isin("-l0",argv){
2481                 fmt.Printf("%v",Rusagef("%t %u\t// %s",argv,v.Rusagev))
2482             }
2483             if isin("-at",argv) { // isin("-ls",argv){
2484                 dhi := v.WorkDirX // workdir history index
2485                 fmt.Printf("@%d %s\t",dhi,v.WorkDir)
2486                 // show the FileInfo of the output command??
2487             }
2488             fmt.Printf("%s",v.CmdLine)
2489             fmt.Printf("\n")
2490         }
2491     }
2492 }
2493 // !n - history index
2494 func searchHistory(gshCtx GshContext, gline string) (string, bool, bool){
2495     if gline[0] == '!' {
2496         hix, err := strconv.Atoi(gline[1:])
2497         if err != nil {
2498             fmt.Printf("--E-- (%s : range)\n",hix)
2499             return "", false, true

```

```

2500     }
2501     if hix < 0 || len(gshCtx.CommandHistory) <= hix {
2502         fmt.Printf("--E-- (%d : out of range)\n",hix)
2503         return "", false, true
2504     }
2505     return gshCtx.CommandHistory[hix].CmdLine, false, false
2506 }
2507 // search
2508 //for i, v := range gshCtx.CommandHistory {
2509 //}
2510 return gline, false, false
2511 }
2512 func (gsh*GshContext)cmdStringInHistory(hix int)(cmd string, ok bool){
2513     if 0 <= hix && hix < len(gsh.CommandHistory) {
2514         return gsh.CommandHistory[hix].CmdLine,true
2515     }
2516     return "",false
2517 }
2518
2519 // temporary adding to PATH environment
2520 // cd name -lib for LD_LIBRARY_PATH
2521 // chdir with directory history (date + full-path)
2522 // -s for sort option (by visit date or so)
2523 func (gsh*GshContext)ShowChdirHistory1(i int,v GChdirHistory, argv []string){
2524     fmt.Printf("!%d ",v.CmdIndex) // the first command at this WorkDir
2525     fmt.Printf("@%d ", i)
2526     fmt.Printf("[%v] ",v.MovedAt.Format(time.Stamp))
2527     showFileInfo(v.Dir,argv)
2528 }
2529 func (gsh*GshContext)ShowChdirHistory(argv []string){
2530     for i, v := range gsh.ChdirHistory {
2531         gsh.ShowChdirHistory1(i,v,argv)
2532     }
2533 }
2534 func skipOpts(argv[]string)(int){
2535     for i,v := range argv {
2536         if strBegins(v,"-") {
2537             }else{
2538                 return i
2539             }
2540     }
2541     return -1
2542 }
2543 func (gshCtx*GshContext)xChdir(argv []string){
2544     cdhist := gshCtx.ChdirHistory
2545     if isin("?",argv ) || isin("-t",argv) || isin("-a",argv) {
2546         gshCtx.ShowChdirHistory(argv)
2547         return
2548     }
2549     pwd, _ := os.Getwd()
2550     dir = ""
2551     if len(argv) <= 1 {
2552         dir = toFullPath("-")
2553     }else{
2554         i := skipOpts(argv[1:])
2555         if i < 0 {
2556             dir = toFullPath("-")
2557         }else{
2558             dir = argv[1+i]
2559         }
2560     }
2561     if strBegins(dir,"@") {
2562         if dir == "@0" { // obsolete
2563             dir = gshCtx.StartDir
2564         }else
2565         if dir == "@1" {
2566             index := len(cdhist) - 1
2567             if 0 < index { index -= 1 }
2568             dir = cdhist[index].Dir
2569         }else{
2570             index, err := strconv.Atoi(dir[1:])
2571             if err != nil {
2572                 fmt.Printf("--E-- xChdir(%v)\n",err)
2573                 dir = "?"
2574             }else
2575             if len(gshCtx.ChdirHistory) <= index {
2576                 fmt.Printf("--E-- xChdir(history range error)\n")
2577                 dir = "?"
2578             }else{
2579                 dir = cdhist[index].Dir
2580             }
2581         }
2582     }
2583     if dir != "?" {
2584         err := os.Chdir(dir)
2585         if err != nil {
2586             fmt.Printf("--E-- xChdir(%s)(%v)\n",argv[1],err)
2587         }else{
2588             cwd, _ := os.Getwd()
2589             if cwd != pwd {
2590                 hist1 := GChdirHistory { }
2591                 hist1.Dir = cwd
2592                 hist1.MovedAt = time.Now()
2593                 hist1.CmdIndex = len(gshCtx.CommandHistory)+1
2594                 gshCtx.ChdirHistory = append(cdhist,hist1)
2595                 if !isin("-s",argv){
2596                     //cwd, _ := os.Getwd()
2597                     //fmt.Printf("%s\n",cwd)
2598                     ix := len(gshCtx.ChdirHistory)-1
2599                     gshCtx.ShowChdirHistory1(ix,hist1,argv)
2600                 }
2601             }
2602         }
2603     }
2604     if isin("-ls",argv){
2605         cwd, _ := os.Getwd()
2606         showFileInfo(cwd,argv);
2607     }
2608 }
2609 func TimeValSub(tv1 *syscall.Timeval, tv2 *syscall.Timeval){
2610     *tv1 = syscall.NsecToTimeval(tv1.Nano() - tv2.Nano())
2611 }
2612 func RusageSubv(ru1, ru2 [2]syscall.Rusage){[2]syscall.Rusage){
2613     TimeValSub(&ru1[0].Utime,&ru2[0].Utime)
2614     TimeValSub(&ru1[0].Stime,&ru2[0].Stime)
2615     TimeValSub(&ru1[1].Utime,&ru2[1].Utime)
2616     TimeValSub(&ru1[1].Stime,&ru2[1].Stime)
2617     return ru1
2618 }
2619 func TimeValAdd(tv1 syscall.Timeval, tv2 syscall.Timeval)(syscall.Timeval){
2620     tvs := syscall.NsecToTimeval(tv1.Nano() + tv2.Nano())
2621     return tvs
2622 }
2623 /*
2624 func RusageAddv(ru1, ru2 [2]syscall.Rusage){[2]syscall.Rusage){

```

```

2625 TimeValAdd(ru1[0].Utime,ru2[0].Utime)
2626 TimeValAdd(ru1[0].Stime,ru2[0].Stime)
2627 TimeValAdd(ru1[1].Utime,ru2[1].Utime)
2628 TimeValAdd(ru1[1].Stime,ru2[1].Stime)
2629 return ru1
2630 }
2631 */
2632
2633 // <a name="rusage">Resource Usage</a>
2634 func sRusagef(fmtspec string, argv []string, ru [2]syscall.Rusage)(string){
2635 // ru[0] self , ru[1] children
2636 ut := TimeValAdd(ru[0].Utime,ru[1].Utime)
2637 st := TimeValAdd(ru[0].Stime,ru[1].Stime)
2638 uu := (ut.Sec*1000000 + int64(ut.Usec)) * 1000
2639 su := (st.Sec*1000000 + int64(st.Usec)) * 1000
2640 tu := uu + su
2641 ret := fmt.Sprintf("%v/sum", abftime(tu))
2642 ret += fmt.Sprintf(", %v/user", abftime(uu))
2643 ret += fmt.Sprintf(", %v/sys", abftime(su))
2644 return ret
2645 }
2646 func Rusagef(fmtspec string, argv []string, ru [2]syscall.Rusage)(string){
2647 ut := TimeValAdd(ru[0].Utime,ru[1].Utime)
2648 st := TimeValAdd(ru[0].Stime,ru[1].Stime)
2649 fmt.Printf("%d.%06ds/u ", ut.Sec,ut.Usec) //ru[1].Utime.Sec,ru[1].Utime.Usec)
2650 fmt.Printf("%d.%06ds/s ", st.Sec,st.Usec) //ru[1].Stime.Sec,ru[1].Stime.Usec)
2651 return ""
2652 }
2653 func Getrusagev()([2]syscall.Rusage){
2654 var ruv = [2]syscall.Rusage{}
2655 syscall.Getrusage(syscall.RUSAGE_SELF,&ruv[0])
2656 syscall.Getrusage(syscall.RUSAGE_CHILDREN,&ruv[1])
2657 return ruv
2658 }
2659 func showRusage(what string,argv []string, ru *syscall.Rusage){
2660 fmt.Printf("%s: ",what);
2661 fmt.Printf("Utr=%d.%06ds",ru.Utime.Sec,ru.Utime.Usec)
2662 fmt.Printf(" Sys=%d.%06ds",ru.Stime.Sec,ru.Stime.Usec)
2663 fmt.Printf(" Rss=%vB",ru.Maxrss)
2664 if isin("-l",argv) {
2665     fmt.Printf(" MinFlt=%v",ru.Minflt)
2666     fmt.Printf(" MajFlt=%v",ru.Majflt)
2667     fmt.Printf(" IxRSS=%vB",ru.Ixrss)
2668     fmt.Printf(" IdRSS=%vB",ru.Idrss)
2669     fmt.Printf(" Nswap=%vB",ru.Nswap)
2670     fmt.Printf(" Read=%v",ru.Inblock)
2671     fmt.Printf(" Write=%v",ru.Oublock)
2672 }
2673     fmt.Printf(" Snd=%v",ru.Msgsnd)
2674     fmt.Printf(" Rcv=%v",ru.Msgrcv)
2675 //if isin("-l",argv) {
2676     fmt.Printf(" Sig=%v",ru.Nsignals)
2677 //}
2678     fmt.Printf("\n");
2679 }
2680 func (gshCtx *GshContext)xTime(argv []string)(bool){
2681 if 2 <= len(argv){
2682     gshCtx.LastRusage = syscall.Rusage{}
2683     rusagev1 := Getrusagev()
2684     fin := gshCtx.gshellv(argv[1:])
2685     rusagev2 := Getrusagev()
2686     showRusage(argv[1],argv,&gshCtx.LastRusage)
2687     rusagev := RusageSubv(rusagev2,rusagev1)
2688     showRusage("self",argv,&rusagev[0])
2689     showRusage("chld",argv,&rusagev[1])
2690     return fin
2691 }else{
2692     rusage:= syscall.Rusage {}
2693     syscall.Getrusage(syscall.RUSAGE_SELF,&rusage)
2694     showRusage("self",argv, &rusage)
2695     syscall.Getrusage(syscall.RUSAGE_CHILDREN,&rusage)
2696     showRusage("chld",argv, &rusage)
2697     return false
2698 }
2699 }
2700 func (gshCtx *GshContext)xJobs(argv []string){
2701     fmt.Printf("%d Jobs\n",len(gshCtx.BackGroundJobs))
2702     for ji, pid := range gshCtx.BackGroundJobs {
2703         //wstat := syscall.WaitStatus {0}
2704         rusage := syscall.Rusage {}
2705         //wpid, err := syscall.Wait4(pid,&wstat,syscall.WNOHANG,&rusage);
2706         wpid, err := syscall.Wait4(pid,nil,syscall.WNOHANG,&rusage);
2707         if err != nil {
2708             fmt.Printf("--E-- %%%d [%d] (%v)\n",ji,pid,err)
2709         }else{
2710             fmt.Printf("%%d[%d] (%d)\n",ji,pid,wpid)
2711             showRusage("chld",argv,&rusage)
2712         }
2713     }
2714 }
2715 func (gsh*GshContext)inBackground(argv []string)(bool){
2716 if gsh.CmdTrace { fmt.Printf("--I-- inBackground(%v)\n",argv) }
2717 gsh.BackGround = true // set background option
2718 xfin := false
2719 xfin = gsh.gshellv(argv)
2720 gsh.BackGround = false
2721 return xfin
2722 }
2723 // -o file without command means just opening it and refer by #N
2724 // should be listed by "files" command
2725 func (gshCtx*GshContext)xOpen(argv []string){
2726     var pv = []int{-1,-1}
2727     err := syscall.Pipe(pv)
2728     fmt.Printf("--I-- pipe()=#%d,#%d(%v)\n",pv[0],pv[1],err)
2729 }
2730 func (gshCtx*GshContext)fromPipe(argv []string){
2731 }
2732 func (gshCtx*GshContext)xClose(argv []string){
2733 }
2734
2735 // <a name="redirect">redirect</a>
2736 func (gshCtx*GshContext)redirect(argv []string)(bool){
2737 if len(argv) < 2 {
2738     return false
2739 }
2740
2741 cmd := argv[0]
2742 fname := argv[1]
2743 var file *os.File = nil
2744
2745 fdix := 0
2746 mode := os.O_RDONLY
2747
2748 switch {
2749 case cmd == "-i" || cmd == "<":

```

```

2750     fdix = 0
2751     mode = os.O_RDONLY
2752     case cmd == "-o" || cmd == ">":
2753         fdix = 1
2754         mode = os.O_RDWR | os.O_CREATE
2755     case cmd == "-a" || cmd == ">>":
2756         fdix = 1
2757         mode = os.O_RDWR | os.O_CREATE | os.O_APPEND
2758     }
2759     if fname[0] == '#' {
2760         fd, err := strconv.Atoi(fname[1:])
2761         if err != nil {
2762             fmt.Printf("--E-- (%v)\n",err)
2763             return false
2764         }
2765         file = os.NewFile(uintptr(fd),"MaybePipe")
2766     }else{
2767         xfile, err := os.OpenFile(argv[1], mode, 0600)
2768         if err != nil {
2769             fmt.Printf("--E-- (%s)\n",err)
2770             return false
2771         }
2772         file = xfile
2773     }
2774     gshPA := gshCtx.gshPA
2775     savfd := gshPA.Files[fdix]
2776     gshPA.Files[fdix] = file.Fd()
2777     fmt.Printf("--I-- Opened [%d] %s\n",file.Fd(),argv[1])
2778     gshCtx.gshellv(argv[2:])
2779     gshPA.Files[fdix] = savfd
2780
2781     return false
2782 }
2783
2784 //fmt.Fprintf(res, "GShell Status: %q", html.EscapeString(req.URL.Path))
2785 func httpHandler(res http.ResponseWriter, req *http.Request){
2786     path := req.URL.Path
2787     fmt.Printf("--I-- Got HTTP Request(%s)\n",path)
2788     {
2789         gshCtxBuf, _ := setupGshContext()
2790         gshCtx := *gshCtxBuf
2791         fmt.Printf("--I-- %s\n",path[1:])
2792         gshCtx.tgshelll(path[1:])
2793     }
2794     fmt.Fprintf(res, "Hello(^-^)/\n%s\n",path)
2795 }
2796 func (gshCtx *GshContext) httpServer(argv []string){
2797     http.HandleFunc("/", httpHandler)
2798     accport := "localhost:9999"
2799     fmt.Printf("--I-- HTTP Server Start at [%s]\n",accport)
2800     http.ListenAndServe(accport,nil)
2801 }
2802 func (gshCtx *GshContext)xGo(argv []string){
2803     go gshCtx.gshellv(argv[1:]);
2804 }
2805 func (gshCtx *GshContext) xPs(argv []string){}
2806 }
2807
2808 // <a name="plugin">Plugin</a>
2809 // plugin [-ls [names]] to list plugins
2810 // Reference: <a href="https://golang.org/src/plugin/">plugin</a> source code
2811 func (gshCtx *GshContext) whichPlugin(name string,argv []string)(pi *PluginInfo){
2812     pi = nil
2813     for _,p := range gshCtx.PluginFuncs {
2814         if p.Name == name && pi == nil {
2815             pi = *p
2816         }
2817         if !isin("-s",argv){
2818             //fmt.Printf("%v %v ",i,p)
2819             if isin("-ls",argv){
2820                 showFileInfo(p.Path,argv)
2821             }else{
2822                 fmt.Printf("%s\n",p.Name)
2823             }
2824         }
2825     }
2826     return pi
2827 }
2828 func (gshCtx *GshContext) xPlugin(argv []string) (error) {
2829     if len(argv) == 0 || argv[0] == "-ls" {
2830         gshCtx.whichPlugin("",argv)
2831         return nil
2832     }
2833     name := argv[0]
2834     Pin := gshCtx.whichPlugin(name,[]string{"-s"})
2835     if Pin != nil {
2836         os.Args = argv // should be recovered?
2837         Pin.Addr.(func())()
2838         return nil
2839     }
2840     sofile := toFullPath(argv[0] + ".so") // or find it by which($PATH)
2841
2842     p, err := plugin.Open(sofile)
2843     if err != nil {
2844         fmt.Printf("--E-- plugin.Open(%s)(%v)\n",sofile,err)
2845         return err
2846     }
2847     fname := "Main"
2848     f, err := p.Lookup(fname)
2849     if( err != nil ){
2850         fmt.Printf("--E-- plugin.Lookup(%s)(%v)\n",fname,err)
2851         return err
2852     }
2853     pin := PluginInfo {p,f,name,sofile}
2854     gshCtx.PluginFuncs = append(gshCtx.PluginFuncs,pin)
2855     fmt.Printf("--I-- added (%d)\n",len(gshCtx.PluginFuncs))
2856
2857     //fmt.Printf("--I-- first call(%s:%s)%v\n",sofile,fname,argv)
2858     os.Args = argv
2859     f.(func())()
2860     return err
2861 }
2862 func (gshCtx*GshContext)Args(argv []string){
2863     for i,v := range os.Args {
2864         fmt.Printf("[%v] %v\n",i,v)
2865     }
2866 }
2867 func (gshCtx *GshContext) showVersion(argv []string){
2868     if isin("-l",argv) {
2869         fmt.Printf("%v/%v (%v)",NAME,VERSION,DATE);
2870     }else{
2871         fmt.Printf("%v",VERSION);
2872     }
2873     if isin("-a",argv) {
2874         fmt.Printf(" %s",AUTHOR)

```

```

2875 }
2876 if !isin("-n",argv) {
2877     fmt.Printf("\n")
2878 }
2879 }
2880
2881 // <a name="scanf">Scanf</a> // string decomposer
2882 // scanf [format] [input]
2883 func scanv(ssstr string)(strv[]string){
2884     strv = strings.Split(ssstr, " ")
2885     return strv
2886 }
2887 func scanUntil(src,end string)(rstr string,leng int){
2888     idx := strings.Index(src,end)
2889     if 0 <= idx {
2890         rstr = src[0:idx]
2891         return rstr,idx+leng(end)
2892     }
2893     return src,0
2894 }
2895
2896 // -bn -- display base-name part only // can be in some %fmt, for sed rewriting
2897 func (gsh*GshContext)printVal(fmts string, vstr string, optv[]string){
2898     //vint,err := strconv.Atoi(vstr)
2899     var ival int64 = 0
2900     n := 0
2901     err := error(nil)
2902     if strBegins(vstr, "-") {
2903         vx,_ := strconv.Atoi(vstr[1:])
2904         if vx < len(gsh.iValues) {
2905             vstr = gsh.iValues[vx]
2906         }else{
2907         }
2908     }
2909     // should use Eval()
2910     if strBegins(vstr,"0x") {
2911         n,err = fmt.Sscanf(vstr[2:], "%x", &ival)
2912     }else{
2913         n,err = fmt.Sscanf(vstr, "%d", &ival)
2914     }
2915     //fmt.Printf("--D-- n=%d err=(%v) (%s)=%v\n",n,err,vstr, ival)
2916     if n == 1 && err == nil {
2917         //fmt.Printf("--D-- formatn(%v) ival(%v)\n",fmts,ival)
2918         fmt.Printf("%"+fmts,ival)
2919     }else{
2920         if isin("-bn",optv){
2921             fmt.Printf("%"+fmts,filepath.Base(vstr))
2922         }else{
2923             fmt.Printf("%"+fmts,vstr)
2924         }
2925     }
2926 }
2927 func (gsh*GshContext)printfv(fmts,div string,argv[]string,optv[]string,list[]string){
2928     //fmt.Printf("%d",len(list))
2929     //curfmt := "v"
2930     outlen := 0
2931     curfmt := gsh.iFormat
2932
2933     if 0 < len(fmts) {
2934         for xi := 0; xi < len(fmts); xi++ {
2935             fch := fmts[xi]
2936             if fch == '%' {
2937                 if xi+1 < len(fmts) {
2938                     curfmt = string(fmts[xi+1])
2939                 }
2940                 gsh.iFormat = curfmt
2941                 xi += 1
2942                 if xi+1 < len(fmts) && fmts[xi+1] == '(' {
2943                     vals,leng := scanUntil(fmts[xi+2:],")")
2944                     //fmt.Printf("--D-- show fmt(%v) val(%v) next(%v)\n",curfmt,vals,leng)
2945                     gsh.printVal(curfmt,vals,optv)
2946                     xi += 2+leng-1
2947                     outlen += 1
2948                 }
2949                 continue
2950             }
2951             if fch == '-' {
2952                 hi,leng := scanInt(fmts[xi+1:])
2953                 if 0 < leng {
2954                     if hi < len(gsh.iValues) {
2955                         gsh.printVal(curfmt,gsh.iValues[hi],optv)
2956                         outlen += 1 // should be the real length
2957                     }else{
2958                         fmt.Printf("((out-range))")
2959                     }
2960                     xi += leng
2961                     continue;
2962                 }
2963             }
2964             fmt.Printf("%c",fch)
2965             outlen += 1
2966         }
2967     }else{
2968         //fmt.Printf("--D-- print (%s)\n")
2969         for i,v := range list {
2970             if 0 < i {
2971                 fmt.Printf(div)
2972             }
2973             gsh.printVal(curfmt,v,optv)
2974             outlen += 1
2975         }
2976     }
2977     if 0 < outlen {
2978         fmt.Printf("\n")
2979     }
2980 }
2981 func (gsh*GshContext)Scanv(argv[]string){
2982     //fmt.Printf("--D-- Scanv(%v)\n",argv)
2983     if len(argv) == 1 {
2984         return
2985     }
2986     argv = argv[1:]
2987     fmts := ""
2988     if strBegins(argv[0],"-F") {
2989         fmts = argv[0]
2990         gsh.iDelimiter = fmts
2991         argv = argv[1:]
2992     }
2993     input := strings.Join(argv, " ")
2994     if fmts == "" { // simple decomposition
2995         v := scanv(input)
2996         gsh.iValues = v
2997         //fmt.Printf("%v\n",strings.Join(v, ","))
2998     }else{
2999         v := make([]string,8)

```



```

3000     n,err := fmt.Sscanf(input,fmts,&v[0],&v[1],&v[2],&v[3])
3001     fmt.Printf("--D-- Sscanf ->(%v) n=%d err=(%v)\n",v,n,err)
3002     gsh.iValues = v
3003 }
3004 }
3005 func (gsh*GshContext)Printv(argv []string){
3006     if false { //@@@
3007         fmt.Printf("%v\n",strings.Join(argv[1:], " "))
3008         return
3009     }
3010     //fmt.Printf("--D-- Printv(%v)\n",argv)
3011     //fmt.Printf("%v\n",strings.Join(gsh.iValues,","))
3012     div := gsh.iDelimiter
3013     fmts := ""
3014     argv = argv[1:]
3015     if 0 < len(argv) {
3016         if strBegins(argv[0],"-F") {
3017             div = argv[0][2:]
3018             argv = argv[1:]
3019         }
3020     }
3021 }
3022 optv := []string{}
3023 for _,v := range argv {
3024     if strBegins(v,"-"){
3025         optv = append(optv,v)
3026         argv = argv[1:]
3027     }else{
3028         break;
3029     }
3030 }
3031 if 0 < len(argv) {
3032     fmts = strings.Join(argv, " ")
3033 }
3034 gsh.printf(fmts,div,argv,optv,gsh.iValues)
3035 }
3036 func (gsh*GshContext)Basename(argv []string){
3037     for i,v := range gsh.iValues {
3038         gsh.iValues[i] = filepath.Base(v)
3039     }
3040 }
3041 func (gsh*GshContext)Sortv(argv []string){
3042     sv := gsh.iValues
3043     sort.Slice(sv, func(i,j int) bool {
3044         return sv[i] < sv[j]
3045     })
3046 }
3047 func (gsh*GshContext)Shiftv(argv []string){
3048     vi := len(gsh.iValues)
3049     if 0 < vi {
3050         if isin("-r",argv) {
3051             top := gsh.iValues[0]
3052             gsh.iValues = append(gsh.iValues[1:],top)
3053         }else{
3054             gsh.iValues = gsh.iValues[1:]
3055         }
3056     }
3057 }
3058 }
3059 func (gsh*GshContext)Enq(argv []string){
3060 }
3061 func (gsh*GshContext)Deq(argv []string){
3062 }
3063 func (gsh*GshContext)Push(argv []string){
3064     gsh.iValStack = append(gsh.iValStack,argv[1:])
3065     fmt.Printf("depth=%d\n",len(gsh.iValStack))
3066 }
3067 func (gsh*GshContext)Dump(argv []string){
3068     for i,v := range gsh.iValStack {
3069         fmt.Printf("%d %v\n",i,v)
3070     }
3071 }
3072 func (gsh*GshContext)Pop(argv []string){
3073     depth := len(gsh.iValStack)
3074     if 0 < depth {
3075         v := gsh.iValStack[depth-1]
3076         if isin("-cat",argv){
3077             gsh.iValues = append(gsh.iValues,v...)
3078         }else{
3079             gsh.iValues = v
3080         }
3081         gsh.iValStack = gsh.iValStack[0:depth-1]
3082         fmt.Printf("depth=%d %s\n",len(gsh.iValStack),gsh.iValues)
3083     }else{
3084         fmt.Printf("depth=%d\n",depth)
3085     }
3086 }
3087 }
3088 // <a name="interpreter">Command Interpreter</a>
3089 func (gshCtx*GshContext)gshellv(argv []string) (fin bool) {
3090     fin = false
3091 }
3092 if gshCtx.CmdTrace { fmt.Fprintf(os.Stderr,"--I-- gshellv(%d)\n",len(argv)) }
3093 if len(argv) <= 0 {
3094     return false
3095 }
3096 xargv := []string{}
3097 for ai := 0; ai < len(argv); ai++ {
3098     xargv = append(xargv,subst(gshCtx,argv[ai],false))
3099 }
3100 argv = xargv
3101 if false {
3102     for ai := 0; ai < len(argv); ai++ {
3103         fmt.Printf("[%d] %s [%d]T\n",
3104             ai,argv[ai],len(argv[ai]),argv[ai])
3105     }
3106 }
3107 cmd := argv[0]
3108 if gshCtx.CmdTrace { fmt.Fprintf(os.Stderr,"--I-- gshellv(%d)%v\n",len(argv),argv) }
3109 switch { // https://tour.golang.org/flowcontrol/11
3110 case cmd == "":
3111     gshCtx.xPwd([]string{}); // empty command
3112 case cmd == "-x":
3113     gshCtx.CmdTrace = ! gshCtx.CmdTrace
3114 case cmd == "-xt":
3115     gshCtx.CmdTime = ! gshCtx.CmdTime
3116 case cmd == "-ot":
3117     gshCtx.sconnect(true, argv)
3118 case cmd == "-ou":
3119     gshCtx.sconnect(false, argv)
3120 case cmd == "-it":
3121     gshCtx.saccept(true, argv)
3122 case cmd == "-iu":
3123     gshCtx.saccept(false, argv)
3124 case cmd == "-i" || cmd == "<" || cmd == "-o" || cmd == ">" || cmd == "-a" || cmd == ">>" || cmd == "-s" || cmd == "><":

```

```

3125     gshCtx.redirect(argv)
3126 case cmd == "|":
3127     gshCtx.fromPipe(argv)
3128 case cmd == "args":
3129     gshCtx.Args(argv)
3130 case cmd == "bg" || cmd == "-bg":
3131     rfin := gshCtx.inBackground(argv[1:])
3132     return rfin
3133 case cmd == "-bn":
3134     gshCtx.BaseName(argv)
3135 case cmd == "call":
3136     _,_ = gshCtx.excommand(false,argv[1:])
3137 case cmd == "cd" || cmd == "chdir":
3138     gshCtx.xChdir(argv);
3139 case cmd == "-cksum":
3140     gshCtx.xFind(argv)
3141 case cmd == "-sum":
3142     gshCtx.xFind(argv)
3143 case cmd == "-sumtest":
3144     str := ""
3145     if 1 < len(argv) { str = argv[1] }
3146     crc := strCRC32(str,uint64(len(str)))
3147     fprintf(stderr,"%v %v\n",crc,len(str))
3148 case cmd == "close":
3149     gshCtx.xClose(argv)
3150 case cmd == "gcp":
3151     gshCtx.FileCopy(argv)
3152 case cmd == "dec" || cmd == "decode":
3153     gshCtx.Dec(argv)
3154 case cmd == "#define":
3155 case cmd == "dic" || cmd == "d":
3156     xDic(argv)
3157 case cmd == "dump":
3158     gshCtx.Dump(argv)
3159 case cmd == "echo" || cmd == "e":
3160     echo(argv,true)
3161 case cmd == "enc" || cmd == "encode":
3162     gshCtx.Enc(argv)
3163 case cmd == "env":
3164     env(argv)
3165 case cmd == "eval":
3166     xEval(argv[1:],true)
3167 case cmd == "ev" || cmd == "events":
3168     dumpEvents(argv)
3169 case cmd == "exec":
3170     _,_ = gshCtx.excommand(true,argv[1:])
3171     // should not return here
3172 case cmd == "exit" || cmd == "quit":
3173     // write Result code EXIT to 3>
3174     return true
3175 case cmd == "fds":
3176     // dump the attributes of fds (of other process)
3177 case cmd == "-find" || cmd == "fin" || cmd == "ufind" || cmd == "uf":
3178     gshCtx.xFind(argv[1:])
3179 case cmd == "fu":
3180     gshCtx.xFind(argv[1:])
3181 case cmd == "fork":
3182     // mainly for a server
3183 case cmd == "-gen":
3184     gshCtx.gen(argv)
3185 case cmd == "-go":
3186     gshCtx.xGo(argv)
3187 case cmd == "-grep":
3188     gshCtx.xFind(argv)
3189 case cmd == "gdeg":
3190     gshCtx.Deg(argv)
3191 case cmd == "genq":
3192     gshCtx.Enq(argv)
3193 case cmd == "gpop":
3194     gshCtx.Pop(argv)
3195 case cmd == "gpush":
3196     gshCtx.Push(argv)
3197 case cmd == "history" || cmd == "hi": // hi should be alias
3198     gshCtx.xHistory(argv)
3199 case cmd == "jobs":
3200     gshCtx.xJobs(argv)
3201 case cmd == "lisp" || cmd == "nlsp":
3202     gshCtx.SplitLine(argv)
3203 case cmd == "-ls":
3204     gshCtx.xFind(argv)
3205 case cmd == "nop":
3206     // do nothing
3207 case cmd == "pipe":
3208     gshCtx.xOpen(argv)
3209 case cmd == "plug" || cmd == "plugin" || cmd == "pin":
3210     gshCtx.xPlugin(argv[1:])
3211 case cmd == "print" || cmd == "-pr":
3212     // output internal slice // also sprintf should be
3213     gshCtx.Printf(argv)
3214 case cmd == "ps":
3215     gshCtx.xPs(argv)
3216 case cmd == "pstable":
3217     // to be gsh.title
3218 case cmd == "rexecl" || cmd == "rexd":
3219     gshCtx.RexecServer(argv)
3220 case cmd == "rexec" || cmd == "rex":
3221     gshCtx.RexecClient(argv)
3222 case cmd == "repeat" || cmd == "rep": // repeat cond command
3223     gshCtx.repeat(argv)
3224 case cmd == "replay":
3225     gshCtx.xReplay(argv)
3226 case cmd == "scan":
3227     // scan input (or so in fscanf) to internal slice (like Files or map)
3228     gshCtx.Scanv(argv)
3229 case cmd == "set":
3230     // set name ...
3231 case cmd == "serv":
3232     gshCtx.httpServer(argv)
3233 case cmd == "shift":
3234     gshCtx.Shiftv(argv)
3235 case cmd == "sleep":
3236     gshCtx.sleep(argv)
3237 case cmd == "-sort":
3238     gshCtx.Sortv(argv)
3239
3240 case cmd == "j" || cmd == "join":
3241     gshCtx.Rjoin(argv)
3242 case cmd == "a" || cmd == "alpa":
3243     gshCtx.Rexec(argv)
3244 case cmd == "jcd" || cmd == "jchdir":
3245     gshCtx.Rchdir(argv)
3246 case cmd == "jget":
3247     gshCtx.Rget(argv)
3248 case cmd == "jls":
3249     gshCtx.Rls(argv)

```

```

3250 case cmd == "jput":
3251     gshCtx.Rput(argv)
3252 case cmd == "jpwd":
3253     gshCtx.Rpwd(argv)
3254
3255 case cmd == "time":
3256     fin = gshCtx.xTime(argv)
3257 case cmd == "ungets":
3258     if 1 < len(argv) {
3259         ungets(argv[1]+"\\n")
3260     }else{
3261     }
3262 case cmd == "pwd":
3263     gshCtx.xPwd(argv);
3264 case cmd == "ver" || cmd == "-ver" || cmd == "version":
3265     gshCtx.showVersion(argv)
3266 case cmd == "where":
3267     // data file or so?
3268 case cmd == "which":
3269     which("PATH",argv);
3270 default:
3271     if gshCtx.whichPlugin(cmd,[jstring{"-s"}]) != nil {
3272         gshCtx.xPlugin(argv)
3273     }else{
3274         notfound_ := gshCtx.excommand(false,argv)
3275         if notfound {
3276             fmt.Printf("--E-- command not found (%v)\\n",cmd)
3277         }
3278     }
3279 }
3280 return fin
3281 }
3282
3283 func (gsh*GshContext)gshell(gline string) (rfin bool) {
3284     argv := strings.Split(string(gline)," ")
3285     fin := gsh.gshelly(argv)
3286     return fin
3287 }
3288 func (gsh*GshContext)tgshell(gline string)(xfin bool){
3289     start := time.Now()
3290     fin := gsh.gshell(gline)
3291     end := time.Now()
3292     elps := end.Sub(start);
3293     if gsh.CmdTime {
3294         fmt.Printf("--T-- " + time.Now().Format(time.Stamp) + " (%d.%09ds)\\n",
3295             elps/1000000000,elps%1000000000)
3296     }
3297     return fin
3298 }
3299 func Ttyid() (int) {
3300     fi, err := os.Stdin.Stat()
3301     if err != nil {
3302         return 0;
3303     }
3304     //fmt.Printf("Stdin: %v Dev=%d\\n",
3305     // fi.Mode(),fi.Mode()&os.ModeDevice)
3306     if (fi.Mode() & os.ModeDevice) != 0 {
3307         stat := syscall.Stat_t{};
3308         err := syscall.Fstat(0,&stat)
3309         if err != nil {
3310             //fmt.Printf("--I-- Stdin: (%v)\\n",err)
3311         }else{
3312             //fmt.Printf("--I-- Stdin: rdev=%d %d\\n",
3313             // stat.Rdev&0xFF,stat.Rdev);
3314             //fmt.Printf("--I-- Stdin: tty%d\\n",stat.Rdev&0xFF);
3315             return int(stat.Rdev & 0xFF)
3316         }
3317     }
3318     return 0
3319 }
3320 func (gshCtx *GshContext) ttyfile() string {
3321     //fmt.Printf("--I-- GSH_HOME=%s\\n",gshCtx.GshHomeDir)
3322     ttyfile := gshCtx.GshHomeDir + "/" + "gsh-tty" +
3323         fmt.Sprintf("%02d",gshCtx.TerminalId)
3324     //strconv.Itoa(gshCtx.TerminalId)
3325     //fmt.Printf("--I-- ttyfile=%s\\n",ttyfile)
3326     return ttyfile
3327 }
3328 func (gshCtx *GshContext) ttyline()(*os.File){
3329     file, err := os.OpenFile(gshCtx.ttyfile(),os.O_RDWR|os.O_CREATE|os.O_TRUNC,0600)
3330     if err != nil {
3331         fmt.Printf("--F-- cannot open %s (%s)\\n",gshCtx.ttyfile(),err)
3332         return file;
3333     }
3334     return file
3335 }
3336 func (gshCtx *GshContext)getline(hix int, skipping bool, prevline string) (string) {
3337     if( skipping ){
3338         reader := bufio.NewReaderSize(os.Stdin,LINESIZE)
3339         line, _, _ := reader.ReadLine()
3340         return string(line)
3341     }else
3342     if true {
3343         return xgetline(hix,prevline,gshCtx)
3344     }
3345     /*
3346     else
3347     if( with_exgetline && gshCtx.GetLine != "" ){
3348         //var xhix int64 = int64(hix); // cast
3349         newenv := os.Environ()
3350         newenv = append(newenv, "GSH_LINENO="+strconv.FormatInt(int64(hix),10) )
3351     }
3352     tty := gshCtx.ttyline()
3353     tty.WriteString(prevline)
3354     Pa := os.ProcAttr {
3355         "", // start dir
3356         newenv, //os.Environ(),
3357         []*os.File{os.Stdin,os.Stdout,os.Stderr,tty},
3358         nil,
3359     }
3360     //fmt.Printf("--I-- getline=%s // %s\\n",gsh_getlinev[0],gshCtx.GetLine)
3361     proc, err := os.StartProcess(gsh_getlinev[0],[jstring{"getline","getline"},&Pa)
3362     if err != nil {
3363         fmt.Printf("--F-- getline process error (%v)\\n",err)
3364         // for ; ; {
3365         return "exit (getline program failed)"
3366     }
3367     //stat, err := proc.Wait()
3368     proc.Wait()
3369     buff := make([]byte,LINESIZE)
3370     count, err := tty.Read(buff)
3371     //_, err = tty.Read(buff)
3372     //fmt.Printf("--D-- getline (%d)\\n",count)
3373     if err != nil {
3374         if !(count == 0) { // && err.String() == "EOF" } {

```

```

3375         fmt.Printf("--E-- getline error (%s)\n",err)
3376     }
3377 }else{
3378     //fmt.Printf("--I-- getline OK \"%s\"\n",buff)
3379 }
3380 tty.Close()
3381 gline := string(buff[0:count])
3382 return gline
3383 }else
3384 */
3385 {
3386     // if isatty {
3387     fmt.Printf("%d",hix)
3388     fmt.Print(PROMPT)
3389     // }
3390     reader := bufio.NewReaderSize(os.Stdin,LINESIZE)
3391     line, _, _ := reader.ReadLine()
3392     return string(line)
3393 }
3394 }
3395
3396 //== begin ===== getline
3397 /*
3398 * getline.c
3399 * 2020-0819 extracted from dog.c
3400 * getline.go
3401 * 2020-0822 ported to Go
3402 */
3403 /*
3404 package main // getline main
3405 import (
3406     "fmt" // <a href="https://golang.org/pkg/fmt/">fmt</a>
3407     "strings" // <a href="https://golang.org/pkg/strings/">strings</a>
3408     "os" // <a href="https://golang.org/pkg/os/">os</a>
3409     "syscall" // <a href="https://golang.org/pkg/syscall/">syscall</a>
3410     // "bytes" // <a href="https://golang.org/pkg/bytes/">bytes</a>
3411     // "os/exec" // <a href="https://golang.org/pkg/os/exec/">os/exec</a>
3412 )
3413 */
3414
3415 // C language compatibility functions
3416 var errno = 0
3417 var stdin *os.File = os.Stdin
3418 var stdout *os.File = os.Stdout
3419 var stderr *os.File = os.Stderr
3420 var EOF = -1
3421 var NULL = 0
3422 type FILE os.File
3423 type StrBuff []byte
3424 var NULL_FP *os.File = nil
3425 var NULLSP = 0
3426 //var LINESIZE = 1024
3427
3428 func system(cmdstr string)(int){
3429     PA := syscall.ProcAttr {
3430         "", // the starting directory
3431         os.Environ(),
3432         [uintptr(os.Stdin.Fd()),os.Stdout.Fd(),os.Stderr.Fd()],
3433         nil,
3434     }
3435     argv := strings.Split(cmdstr, " ")
3436     pid,err := syscall.ForkExec(argv[0],argv,&PA)
3437     if( err != nil ){
3438         fmt.Printf("--E-- syscall(%v) err(%v)\n",cmdstr,err)
3439     }
3440     syscall.Wait4(pid,nil,0,nil)
3441
3442     /*
3443     argv := strings.Split(cmdstr, " ")
3444     fmt.Fprintf(os.Stderr,"--I-- system(%v)\n",argv)
3445     //cmd := exec.Command(argv[0],...)
3446     cmd := exec.Command(argv[0],argv[1],argv[2])
3447     cmd.Stdin = strings.NewReader("output of system")
3448     var out bytes.Buffer
3449     cmd.Stdout = &out
3450     var serr bytes.Buffer
3451     cmd.Stderr = &serr
3452     err := cmd.Run()
3453     if err != nil {
3454         fmt.Fprintf(os.Stderr,"--E-- system(%v)err(%v)\n",argv,err)
3455         fmt.Printf("ERR:%s\n",serr.String())
3456     }else{
3457         fmt.Printf("%s",out.String())
3458     }
3459     */
3460     return 0
3461 }
3462 func atoi(str string)(ret int){
3463     ret,err := fmt.Sscanf(str,"%d",&ret)
3464     if err == nil {
3465         return ret
3466     }else{
3467         // should set errno
3468         return 0
3469     }
3470 }
3471 func getenv(name string)(string){
3472     val,got := os.LookupEnv(name)
3473     if got {
3474         return val
3475     }else{
3476         return "?"
3477     }
3478 }
3479 func strcpy(dst StrBuff, src string){
3480     var i int
3481     srcb := []byte(src)
3482     for i = 0; i < len(src) && srcb[i] != 0; i++ {
3483         dst[i] = srcb[i]
3484     }
3485     dst[i] = 0
3486 }
3487 func xstrcpy(dst StrBuff, src StrBuff){
3488     dst = src
3489 }
3490 func strcat(dst StrBuff, src StrBuff){
3491     dst = append(dst,src...)
3492 }
3493 func strdup(str StrBuff)(string){
3494     return string(str[0:strlen(str)])
3495 }
3496 func sstrlen(str string)(int){
3497     return len(str)
3498 }
3499 func strlen(str StrBuff)(int){

```

```

3500     var i int
3501     for i = 0; i < len(str) && str[i] != 0; i++ {
3502     }
3503     return i
3504 }
3505 func sizeof(data StrBuff)(int){
3506     return len(data)
3507 }
3508 func isatty(fd int)(ret int){
3509     return 1
3510 }
3511 }
3512 func fopen(file string,mode string)(fp*os.File){
3513     if mode == "r" {
3514         fp,err := os.Open(file)
3515         if( err != nil ){
3516             fmt.Printf("--E-- fopen(%s,%s)=(%v)\n",file,mode,err)
3517             return NULL_FP;
3518         }
3519         return fp;
3520     }else{
3521         fp,err := os.OpenFile(file,os.O_RDWR|os.O_CREATE|os.O_TRUNC,0600)
3522         if( err != nil ){
3523             return NULL_FP;
3524         }
3525         return fp;
3526     }
3527 }
3528 func fclose(fp*os.File){
3529     fp.Close()
3530 }
3531 func fflush(fp *os.File)(int){
3532     return 0
3533 }
3534 func fgetc(fp*os.File)(int){
3535     var buf [1]byte
3536     _,err := fp.Read(buf[0:1])
3537     if( err != nil ){
3538         return EOF;
3539     }else{
3540         return int(buf[0])
3541     }
3542 }
3543 func sfgets(str*string, size int, fp*os.File)(int){
3544     buf := make(StrBuff,size)
3545     var ch int
3546     var i int
3547     for i = 0; i < len(buf)-1; i++ {
3548         ch = fgetc(fp)
3549         //fprintf(stderr,"--fgets %d/%d %X\n",i,len(buf),ch)
3550         if( ch == EOF ){
3551             break;
3552         }
3553         buf[i] = byte(ch);
3554         if( ch == '\n' ){
3555             break;
3556         }
3557     }
3558     buf[i] = 0
3559     //fprintf(stderr,"--fgets %d/%d (%s)\n",i,len(buf),buf[0:i])
3560     return i
3561 }
3562 func fgets(buf StrBuff, size int, fp*os.File)(int){
3563     var ch int
3564     var i int
3565     for i = 0; i < len(buf)-1; i++ {
3566         ch = fgetc(fp)
3567         //fprintf(stderr,"--fgets %d/%d %X\n",i,len(buf),ch)
3568         if( ch == EOF ){
3569             break;
3570         }
3571         buf[i] = byte(ch);
3572         if( ch == '\n' ){
3573             break;
3574         }
3575     }
3576     buf[i] = 0
3577     //fprintf(stderr,"--fgets %d/%d (%s)\n",i,len(buf),buf[0:i])
3578     return i
3579 }
3580 func fputc(ch int , fp*os.File)(int){
3581     var buf [1]byte
3582     buf[0] = byte(ch)
3583     fp.Write(buf[0:1])
3584     return 0
3585 }
3586 func fputs(buf StrBuff, fp*os.File)(int){
3587     fp.Write(buf)
3588     return 0
3589 }
3590 func xfputss(str string, fp*os.File)(int){
3591     return fputs([]byte(str),fp)
3592 }
3593 func sscanf(str StrBuff,fmts string, params ...interface{})(int){
3594     fmt.Sscanf(string(str[0:strlen(str)]),fmts,params...)
3595     return 0
3596 }
3597 func fprintf(fp*os.File,fmts string, params ...interface{})(int){
3598     fmt.Fprintf(fp,fmts,params...)
3599     return 0
3600 }
3601 }
3602 // <a name="IME">Command Line IME</a>
3603 //----- MyIME
3604 var MyIMEVER = "MyIME/0.0.2";
3605 type RomKana struct {
3606     dic string // dictionary ID
3607     pat string // input pattern
3608     out string // output pattern
3609     hit int64 // count of hit and used
3610 }
3611 var dicents = 0
3612 var romkana [1024]RomKana
3613 var Romkan []RomKana
3614 }
3615 func isinDic(str string)(int){
3616     for i,v := range Romkan {
3617         if v.pat == str {
3618             return i
3619         }
3620     }
3621     return -1
3622 }
3623 const {
3624     DIC_COM_LOAD = "im"

```

```

3625     DIC_COM_DUMP = "s"
3626     DIC_COM_LIST = "ls"
3627     DIC_COM_ENA = "en"
3628     DIC_COM_DIS = "di"
3629 }
3630 func helpDic(argv []string){
3631     out := stderr
3632     cmd := ""
3633     if 0 < len(argv) { cmd = argv[0] }
3634     fprintf(out,"--- %v Usage\n",cmd)
3635     fprintf(out,"--- Commands\n")
3636     fprintf(out,"... %v %v [dicName] [dicURL ] -- Import dictionary\n",cmd,DIC_COM_LOAD)
3637     fprintf(out,"... %v %v [pattern] -- Search in dictionary\n",cmd,DIC_COM_DUMP)
3638     fprintf(out,"... %v %v [dicName] -- List dictionaries\n",cmd,DIC_COM_LIST)
3639     fprintf(out,"... %v %v [dicName] -- Disable dictionaries\n",cmd,DIC_COM_DIS)
3640     fprintf(out,"... %v %v [dicName] -- Enable dictionaries\n",cmd,DIC_COM_ENA)
3641     fprintf(out,"... Keys ... %v\n","ESC can be used for '\\')
3642     fprintf(out,"... \\c -- Reverse the case of the last character\n",)
3643     fprintf(out,"... \\i -- Replace input with translated text\n",)
3644     fprintf(out,"... \\j -- On/Off translation mode\n",)
3645     fprintf(out,"... \\l -- Force Lower Case\n",)
3646     fprintf(out,"... \\u -- Force Upper Case (software CapsLock)\n",)
3647     fprintf(out,"... \\v -- Show translation actions\n",)
3648     fprintf(out,"... \\x -- Replace the last input character with it Hexa-Decimal\n",)
3649 }
3650 func xDic(argv[]string){
3651     if len(argv) <= 1 {
3652         helpDic(argv)
3653         return
3654     }
3655     argv = argv[1:]
3656     var debug = false
3657     var info = false
3658     var silent = false
3659     var dump = false
3660     var builtin = false
3661     cmd := argv[0]
3662     argv = argv[1:]
3663     opt := ""
3664     arg := ""
3665
3666     if 0 < len(argv) {
3667         arg1 := argv[0]
3668         if arg1[0] == '-' {
3669             switch arg1 {
3670                 default: fmt.Printf("--Ed-- Unknown option(%v)\n",arg1)
3671                     return
3672                 case "-b": builtin = true
3673                 case "-d": debug = true
3674                 case "-s": silent = true
3675                 case "-v": info = true
3676             }
3677             opt = arg1
3678             argv = argv[1:]
3679         }
3680     }
3681
3682     dicName := ""
3683     dicURL := ""
3684     if 0 < len(argv) {
3685         arg = argv[0]
3686         dicName = arg
3687         argv = argv[1:]
3688     }
3689     if 0 < len(argv) {
3690         dicURL = argv[0]
3691         argv = argv[1:]
3692     }
3693     if false {
3694         fprintf(stderr,"--Dd-- com(%v) opt(%v) arg(%v)\n",cmd,opt,arg)
3695     }
3696     if cmd == DIC_COM_LOAD {
3697         //dicType := ""
3698         dicBody := ""
3699         if !builtin && dicName != "" && dicURL == "" {
3700             f,err := os.Open(dicName)
3701             if err == nil {
3702                 dicURL = dicName
3703             }else{
3704                 f,err = os.Open(dicName+".html")
3705                 if err == nil {
3706                     dicURL = dicName+".html"
3707                 }else{
3708                     f,err = os.Open("gshdic-"+dicName+".html")
3709                     if err == nil {
3710                         dicURL = "gshdic-"+dicName+".html"
3711                     }
3712                 }
3713             }
3714             if err == nil {
3715                 var buf = make([]byte,128*1024)
3716                 count,err := f.Read(buf)
3717                 f.Close()
3718                 if info {
3719                     fprintf(stderr,"--Id-- ReadDic(%v,%v)\n",count,err)
3720                 }
3721                 dicBody = string(buf[0:count])
3722             }
3723         }
3724         if dicBody == "" {
3725             switch arg {
3726                 default:
3727                     dicName = "WorldDic"
3728                     dicURL = WorldDic
3729                     if info {
3730                         fprintf(stderr,"--Id-- default dictionary \"%v\"\n",
3731                             dicName);
3732                     }
3733                 case "wnn":
3734                     dicName = "WnnDic"
3735                     dicURL = WnnDic
3736                 case "sumomo":
3737                     dicName = "SumomoDic"
3738                     dicURL = SumomoDic
3739                 case "sijimi":
3740                     dicName = "SijimiDic"
3741                     dicURL = SijimiDic
3742                 case "jkl":
3743                     dicName = "JKLJaDic"
3744                     dicURL = JA_JKLDic
3745             }
3746             if debug {
3747                 fprintf(stderr,"--Id-- %v URL=%v\n",dicName,dicURL);
3748             }
3749             dicv := strings.Split(dicURL,"")

```

```

3750     if debug {
3751         fprintf(stderr, "--Id-- %v encoded data...\n", dicName)
3752         fprintf(stderr, "Type: %v\n", dicv[0])
3753         fprintf(stderr, "Body: %v\n", dicv[1])
3754         fprintf(stderr, "\n")
3755     }
3756     body, _ := base64.StdEncoding.DecodeString(dicv[1])
3757     dicBody = string(body)
3758 }
3759 if info {
3760     fmt.Printf("--Id-- %v %v\n", dicName, dicURL)
3761     fmt.Printf("%s\n", dicBody)
3762 }
3763 if debug {
3764     fprintf(stderr, "--Id-- dicName %v text...\n", dicName)
3765     fprintf(stderr, "%v\n", string(dicBody))
3766 }
3767 envv := strings.Split(dicBody, "\n");
3768 if info {
3769     fprintf(stderr, "--Id-- %v scan...\n", dicName);
3770 }
3771 var added int = 0
3772 var dup int = 0
3773 for i, v := range envv {
3774     var pat string
3775     var out string
3776     fmt.Sscanf(v, "%s %s", &pat, &out)
3777     if len(pat) <= 0 {
3778     } else {
3779         if 0 <= isinDic(pat) {
3780             dup += 1
3781             continue
3782         }
3783         romkana[dicents] = RomKana{dicName, pat, out, 0}
3784         dicents += 1
3785         added += 1
3786         Romkan = append(Romkan, RomKana{dicName, pat, out, 0})
3787         if debug {
3788             fmt.Printf("[%3v]:[%2v]%-8v [%2v]%-8v\n",
3789                 i, len(pat), pat, len(out), out)
3790         }
3791     }
3792 }
3793 if !silent {
3794     url := dicURL
3795     if strBegins(url, "data:") {
3796         url = "builtin"
3797     }
3798     fprintf(stderr, "--Id-- %v scan... %v added, %v dup. / %v total (%v)\n",
3799         dicName, added, dup, len(Romkan), url);
3800 }
3801 // should sort by pattern length for complete match, for performance
3802 if debug {
3803     arg = "" // search pattern
3804     dump = true
3805 }
3806 }
3807 if cmd == DIC_COM_DUMP || dump {
3808     fprintf(stderr, "--Id-- %v dump... %v entries:\n", dicName, len(Romkan));
3809     var match = 0
3810     for i := 0; i < len(Romkan); i++ {
3811         dic := Romkan[i].dic
3812         pat := Romkan[i].pat
3813         out := Romkan[i].out
3814         if arg == "" || 0 <= strings.Index(pat, arg) || 0 <= strings.Index(out, arg) {
3815             fmt.Printf("\\\\%v\\t%v [%2v]%-8v [%2v]%-8v\n",
3816                 i, dic, len(pat), pat, len(out), out)
3817             match += 1
3818         }
3819     }
3820     fprintf(stderr, "--Id-- %v matched %v / %v entries:\n", arg, match, len(Romkan));
3821 }
3822 }
3823 func loadDefaultDic(dic int){
3824     if( 0 < len(Romkan) ){
3825         return
3826     }
3827     //fprintf(stderr, "\r\n")
3828     xDic([]string{"dic", DIC_COM_LOAD});
3829 }
3830 var info = false
3831 if info {
3832     fprintf(stderr, "--Id-- Conguraturations!! WorldDic is now activated.\r\n")
3833     fprintf(stderr, "--Id-- enter \"dic\" command for help.\r\n")
3834 }
3835 }
3836 func readDic()(int){
3837     /*
3838     var rk *os.File;
3839     var dic = "MyIME-dic.txt";
3840     //rk = fopen("romkana.txt", "r");
3841     //rk = fopen("JK-JA-morse-dic.txt", "r");
3842     rk = fopen(dic, "r");
3843     if( rk == NULL FP ){
3844         if( true ){
3845             fprintf(stderr, "--s-- Could not load %s\n", MyIMEVER, dic);
3846         }
3847         return -1;
3848     }
3849     if( true ){
3850         var di int;
3851         var line = make(StrBuff, 1024);
3852         var pat string
3853         var out string
3854         for di = 0; di < 1024; di++ {
3855             if( fgets(line, sizeof(line), rk) == NULLSP ){
3856                 break;
3857             }
3858             fmt.Sscanf(string(line[0:strlen(line)]), "%s %s", &pat, &out);
3859             //sscanf(line, "%s %[\r\n]", &pat, &out);
3860             romkana[di].pat = pat;
3861             romkana[di].out = out;
3862             //fprintf(stderr, "--Dd- %-10s %s\n", pat, out)
3863         }
3864         dicents += di
3865         if( false ){
3866             fprintf(stderr, "--s-- loaded romkana.txt [%d]\n", MyIMEVER, di);
3867             for di = 0; di < dicents; di++ {
3868                 fprintf(stderr,
3869                     "%s %s\n", romkana[di].pat, romkana[di].out);
3870             }
3871         }
3872     }
3873     fclose(rk);
3874 }

```

```

3875 //romkana[dictents].pat = "//ddump"
3876 //romkana[dictents].pat = "//ddump" // dump the dic. and clean the command input
3877 */
3878 return 0;
3879 }
3880 func matchlen(str1 string, pati string)(int){
3881 if strBegins(str1,pati) {
3882 return len(pati)
3883 }else{
3884 return 0
3885 }
3886 }
3887 func convs(src string)(string){
3888 var si int;
3889 var sx = len(src);
3890 var di int;
3891 var mi int;
3892 var dstb []byte
3893
3894 for si = 0; si < sx; { // search max. match from the position
3895 if strBegins(src[si:], "%x/") {
3896 // %x/integer/ // s/a/b/
3897 ix := strings.Index(src[si+3:], "/")
3898 if 0 < ix {
3899 var iv int = 0
3900 //fmt.Sscanf(src[si+3:si+3+ix], "%d", &iv)
3901 fmt.Sscanf(src[si+3:si+3+ix], "%v", &iv)
3902 sval := fmt.Sprintf("%x", iv)
3903 bval := []byte(sval)
3904 dstb = append(dstb, bval...)
3905 si = si+3+ix+1
3906 continue
3907 }
3908 }
3909 if strBegins(src[si:], "%d/") {
3910 // %d/integer/ // s/a/b/
3911 ix := strings.Index(src[si+3:], "/")
3912 if 0 < ix {
3913 var iv int = 0
3914 fmt.Sscanf(src[si+3:si+3+ix], "%v", &iv)
3915 sval := fmt.Sprintf("%d", iv)
3916 bval := []byte(sval)
3917 dstb = append(dstb, bval...)
3918 si = si+3+ix+1
3919 continue
3920 }
3921 }
3922 if strBegins(src[si:], "%t") {
3923 now := time.Now()
3924 if true {
3925 date := now.Format(time.Stamp)
3926 dstb = append(dstb, []byte(date)...)
3927 si = si+3
3928 }
3929 continue
3930 }
3931 var maxlen int = 0;
3932 var len int;
3933 mi = -1;
3934 for di = 0; di < dictents; di++ {
3935 len = matchlen(src[si:], romkana[di].pat);
3936 if( maxlen < len ){
3937 maxlen = len;
3938 mi = di;
3939 }
3940 }
3941 if( 0 < maxlen ){
3942 out := romkana[mi].out;
3943 dstb = append(dstb, []byte(out)...);
3944 si += maxlen;
3945 }else{
3946 dstb = append(dstb, src[si])
3947 si += 1;
3948 }
3949 }
3950 return string(dstb)
3951 }
3952 func trans(src string)(int){
3953 dst := convs(src);
3954 xfprintf(stderr, "%s", dst);
3955 return 0;
3956 }
3957
3958 //----- LINEEDIT
3959 // "?" at the top of the line means searching history
3960
3961 // should be compatilbe with Telnet
3962 const (
3963 EV_MODE = 255
3964 EV_IDLE = 254
3965 EV_TIMEOUT = 253
3966
3967 GO_UP = 252 // k
3968 GO_DOWN = 251 // j
3969 GO_RIGHT = 250 // l
3970 GO_LEFT = 249 // h
3971 DEL_RIGHT = 248 // x
3972 GO_TOPL = 'A'-0x40 // 0
3973 GO_ENDL = 'E'-0x40 // $
3974
3975 GO_TOPW = 239 // b
3976 GO_ENDW = 238 // e
3977 GO_NEXTW = 237 // w
3978
3979 GO_FORWCH = 229 // f
3980 GO_PAIRCH = 228 // %
3981
3982 GO_DEL = 219 // d
3983
3984 HI_SRCH_FW = 209 // /
3985 HI_SRCH_BK = 208 // ?
3986 HI_SRCH_RFW = 207 // n
3987 HI_SRCH_RBK = 206 // N
3988 )
3989
3990 // should return number of octets ready to be read immediately
3991 //fprintf(stderr, "\n--Select(%v %v)\n", err, r.Bits[0])
3992
3993
3994 var EventRecvFd = -1 // file descriptor
3995 var EventSendFd = -1
3996 const EventFdOffset = 1000000
3997 const NormalFdOffset = 100
3998
3999 func putEvent(event int, evarg int){

```



```

4000     if true {
4001         if EventRecvFd < 0 {
4002             var pv = [jint{-1,-1}]
4003             syscall.Pipe(pv)
4004             EventRecvFd = pv[0]
4005             EventSendFd = pv[1]
4006             //fmt.Printf("--De-- EventPipe created[%v,%v]\n",EventRecvFd,EventSendFd)
4007         }
4008     }else{
4009         if EventRecvFd < 0 {
4010             // the document differs from this spec
4011             // https://golang.org/src/syscall/syscall_unix.go?s=8096:8158#L340
4012             sv, err := syscall.Socketpair(syscall.AF_UNIX,syscall.SOCK_STREAM,0)
4013             EventRecvFd = sv[0]
4014             EventSendFd = sv[1]
4015             if err != nil {
4016                 fmt.Printf("--De-- EventSock created[%v,%v]($v)\n",
4017                     EventRecvFd,EventSendFd,err)
4018             }
4019         }
4020     }
4021     var buf = []byte{ byte(event)}
4022     n,err := syscall.Write(EventSendFd,buf)
4023     if err != nil {
4024         fmt.Printf("--De-- putEvent[%v]($3v)($v %v)\n",EventSendFd,event,n,err)
4025     }
4026 }
4027 func ungets(str string){
4028     for _,ch := range str {
4029         putEvent(int(ch),0)
4030     }
4031 }
4032 func (gsh*GshContext)xReplay(argv[]string){
4033     hix := 0
4034     tempo := 1.0
4035     xtempo := 1.0
4036     repeat := 1
4037
4038     for _,a := range argv { // tempo
4039         if strBegins(a,"x") {
4040             fmt.Sscanf(a[1:], "%f",&xtempo)
4041             tempo = 1 / xtempo
4042             //fprintf(stderr, "--Dr-- tempo=[%v]%v\n",a[2:],tempo);
4043         }else
4044         if strBegins(a,"r") { // repeat
4045             fmt.Sscanf(a[1:], "%v",&repeat)
4046         }else
4047         if strBegins(a,"!") {
4048             fmt.Sscanf(a[1:], "%d",&hix)
4049         }else{
4050             fmt.Sscanf(a, "%d",&hix)
4051         }
4052     }
4053     if hix == 0 || len(argv) <= 1 {
4054         hix = len(gsh.CommandHistory)-1
4055     }
4056     fmt.Printf("--Ir-- Replay(!%v x%v r%v)\n",hix,xtempo,repeat)
4057     //dumpEvents(hix)
4058     //gsh.xScanReplay(hix,false,repeat,tempo,argv)
4059     go gsh.xScanReplay(hix,true,repeat,tempo,argv)
4060 }
4061
4062 // <a href="https://golang.org/pkg/syscall/#FdSet">syscall.Select</a>
4063 // 2020-0827 GShell-0.2.3
4064 func FpollIn1(fp *os.File,usec int)(uintptr){
4065     nfd := 1
4066
4067     rdv := syscall.FdSet {}
4068     fd1 := fp.Fd()
4069     bank1 := fd1/32
4070     mask1 := int32(1 << fd1)
4071     rdv.Bits[bank1] = mask1
4072
4073     fd2 := -1
4074     bank2 := -1
4075     var mask2 int32 = 0
4076
4077     if 0 <= EventRecvFd {
4078         fd2 = EventRecvFd
4079         nfd = fd2 + 1
4080         bank2 = fd2/32
4081         mask2 = int32(1 << fd2)
4082         rdv.Bits[bank2] |= mask2
4083         //fmt.Printf("--De-- EventPoll mask added [%d][%v][%v]\n",fd2,bank2,mask2)
4084     }
4085
4086     tout := syscall.NsecToTimeval(int64(usec*1000))
4087     //n,err := syscall.Select(nfd,&rdv,nil,nil,&tout) // spec. mismatch
4088     err := syscall.Select(nfd,&rdv,nil,nil,&tout)
4089     if err != nil {
4090         //fmt.Printf("--De-- select() err($v)\n",err)
4091     }
4092     if err == nil {
4093         if 0 <= fd2 && (rdv.Bits[bank2] & mask2) != 0 {
4094             if false {
4095                 fmt.Printf("--De-- got Event\n")
4096             }
4097             return uintptr(EventFdOffset + fd2)
4098         }else
4099         if (rdv.Bits[bank1] & mask1) != 0 {
4100             return uintptr(NormalFdOffset + fd1)
4101         }else{
4102             return 1
4103         }
4104     }else{
4105         return 0
4106     }
4107 }
4108 func fgetoTimeout1(fp *os.File,usec int)(int){
4109     READ1:
4110     readyFd := FpollIn1(fp,usec)
4111     if readyFd < 100 {
4112         return EV_TIMEOUT
4113     }
4114
4115     var buf [1]byte
4116
4117     if EventFdOffset <= readyFd {
4118         fd := int(readyFd-EventFdOffset)
4119         _,err := syscall.Read(fd,buf[0:1])
4120         if( err != nil ){
4121             return EOF;
4122         }else{
4123             if buf[0] == EV_MODE {
4124                 recvEvent(fd)

```

```

4125         goto READ1
4126     }
4127     return int(buf[0])
4128 }
4129 }
4130
4131 _,err := fp.Read(buf[0:1])
4132 if( err != nil ){
4133     return EOF;
4134 }else{
4135     return int(buf[0])
4136 }
4137 }
4138
4139 func visibleChar(ch int)(string){
4140     switch {
4141     case '!' <= ch && ch <= '-':
4142         return string(ch)
4143     }
4144     switch ch {
4145     case ' ': return "\\s"
4146     case '\n': return "\\n"
4147     case '\r': return "\\r"
4148     case '\t': return "\\t"
4149     }
4150     switch ch {
4151     case 0x00: return "NUL"
4152     case 0x07: return "BEL"
4153     case 0x08: return "BS"
4154     case 0x0E: return "SO"
4155     case 0x0F: return "SI"
4156     case 0x1B: return "ESC"
4157     case 0x7F: return "DEL"
4158     }
4159     switch ch {
4160     case EV_IDLE: return fmt.Sprintf("IDLE")
4161     case EV_MODE: return fmt.Sprintf("MODE")
4162     }
4163     return fmt.Sprintf("%X",ch)
4164 }
4165 func recvEvent(fd int){
4166     var buf = make([]byte,1)
4167     _,_ = syscall.Read(fd,buf[0:1])
4168     if( buf[0] != 0 ){
4169         romkanmode = true
4170     }else{
4171         romkanmode = false
4172     }
4173 }
4174 func (gsh*GshContext)xScanReplay(hix int,replay bool,repeat int,tempo float64,argv[string]){
4175     var Start time.Time
4176     var events = []Event{}
4177     for _,e := range Events {
4178         if hix == 0 || e.CmdIndex == hix {
4179             events = append(events,e)
4180         }
4181     }
4182     elen := len(events)
4183     if 0 < elen {
4184         if events[elen-1].event == EV_IDLE {
4185             events = events[0:elen-1]
4186         }
4187     }
4188     for r := 0; r < repeat; r++ {
4189         for i,e := range events {
4190             nano := e.when.Nanosecond()
4191             micro := nano / 1000
4192             if Start.Second() == 0 {
4193                 Start = time.Now()
4194             }
4195             diff := time.Now().Sub(Start)
4196             if replay {
4197                 if e.event != EV_IDLE {
4198                     putEvent(e.event,0)
4199                     if e.event == EV_MODE { // event with arg
4200                         putEvent(int(e.evarg),0)
4201                     }
4202                 }
4203             }else{
4204                 fmt.Printf("%7.3fms %#-3v !%-3v [%v.%06d] %3v %02X %-4v %10.3fms\n",
4205                     float64(diff)/1000000.0,
4206                     i,
4207                     e.CmdIndex,
4208                     e.when.Format(time.Stamp),micro,
4209                     e.event,e.event,visibleChar(e.event),
4210                     float64(e.evarg)/1000000.0)
4211             }
4212             if e.event == EV_IDLE {
4213                 d := time.Duration(float64(time.Duration(e.evarg)) * tempo)
4214                 //nsleep(time.Duration(e.evarg))
4215                 nsleep(d)
4216             }
4217         }
4218     }
4219 }
4220 func dumpEvents(argv[string]){
4221     hix := 0
4222     if 1 < len(argv) {
4223         fmt.Sscanf(argv[1],"%d",&hix)
4224     }
4225     for i,e := range Events {
4226         nano := e.when.Nanosecond()
4227         micro := nano / 1000
4228         //if e.event != EV_TIMEOUT {
4229         if hix == 0 || e.CmdIndex == hix {
4230             fmt.Printf("%#-3v !%-3v [%v.%06d] %3v %02X %-4v %10.3fms\n",i,
4231                 e.CmdIndex,
4232                 e.when.Format(time.Stamp),micro,
4233                 e.event,e.event,visibleChar(e.event),float64(e.evarg)/1000000.0)
4234         }
4235         //}
4236     }
4237 }
4238 func fgetcTimeout(fp *os.File,usec int)(int){
4239     ch := fgetcTimeout1(fp,usec)
4240     if ch != EV_TIMEOUT {
4241         now := Time.Now()
4242         if 0 < len(Events) {
4243             last := Events[len(Events)-1]
4244             dura := int64(now.Sub(last.when))
4245             Events = append(Events,Event{last.when,EV_IDLE,dura,last.CmdIndex})
4246         }
4247         Events = append(Events,Event{time.Now(),ch,0,CmdIndex})
4248     }
4249     return ch

```

```

4250 }
4251
4252 var TtyMaxCol = 72 // to be obtained by ioctl?
4253 var EscTimeout = (100*1000)
4254 var (
4255     MODE_VicMode    bool    // vi compatible command mode
4256     MODE_ShowMode   bool    //
4257     romkanmode      bool    // shown translation mode, the mode to be retained
4258     MODE_Recursive  bool    // recursive translation
4259     MODE_CapsLock   bool    // software CapsLock
4260     MODE_LowerLock  bool    // force lower-case character lock
4261     MODE_ViInsert   int    // visible insert mode, should be like "I" icon in X Window
4262     MODE_ViTrace    bool    // output newline before translation
4263 )
4264 type IInput struct {
4265     lno      int
4266     lastlno int
4267     pch      []int // input queue
4268     prompt   string
4269     line     string
4270     right    string
4271     inJmode  bool
4272     pinJmode bool
4273     waitingMeta string // waiting meta character
4274     lastCmd   string
4275 }
4276 func (iin*IInput)Getc(timeoutUs int)(int){
4277     ch1 := EOF
4278     ch2 := EOF
4279     ch3 := EOF
4280     if( 0 < len(iin.pch) ){ // deQ
4281         ch1 = iin.pch[0]
4282         iin.pch = iin.pch[1:]
4283     }else{
4284         ch1 = fgetcTimeout(stdin,timeoutUs);
4285     }
4286     if( ch1 == 033 ){ // escape sequence
4287         ch2 = fgetcTimeout(stdin,EscTimeout);
4288         if( ch2 == EV_TIMEOUT ){
4289             }else{
4290                 ch3 = fgetcTimeout(stdin,EscTimeout);
4291                 if( ch3 == EV_TIMEOUT ){
4292                     iin.pch = append(iin.pch,ch2) // enQ
4293                 }else{
4294                     switch( ch2 ){
4295                         default:
4296                             iin.pch = append(iin.pch,ch2) // enQ
4297                             iin.pch = append(iin.pch,ch3) // enQ
4298                         case '|':
4299                             switch( ch3 ){
4300                                 case 'A': ch1 = GO_UP; // ^
4301                                 case 'B': ch1 = GO_DOWN; // v
4302                                 case 'C': ch1 = GO_RIGHT; // >
4303                                 case 'D': ch1 = GO_LEFT; // <
4304                                 case '3':
4305                                     ch4 := fgetcTimeout(stdin,EscTimeout);
4306                                     if( ch4 == '-' ){
4307                                         //fprintf(stderr, "x[%02X %02X %02X %02X]\n", ch1, ch2, ch3, ch4);
4308                                         ch1 = DEL_RIGHT
4309                                     }
4310                                 case '\\':
4311                                     //ch4 := fgetcTimeout(stdin,EscTimeout);
4312                                     //fprintf(stderr, "y[%02X %02X %02X %02X]\n", ch1, ch2, ch3, ch4);
4313                                     switch( ch3 ){
4314                                         case '-': ch1 = DEL_RIGHT
4315                                     }
4316                                 }
4317                             }
4318                         }
4319                 }
4320             }
4321         }
4322     }
4323     return ch1
4324 }
4325 func (inn*IInput)clearline(){
4326     var i int
4327     fprintf(stderr, "\r");
4328     // should be ANSI ESC sequence
4329     for i = 0; i < TtyMaxCol; i++ { // to the max. position in this input action
4330         fputc(' ',os.Stderr);
4331     }
4332     fprintf(stderr, "\r");
4333 }
4334 func (iin*IInput)Redraw(){
4335     redraw(iin, iin.lno, iin.line, iin.right)
4336 }
4337 func redraw(iin *IInput, lno int, line string, right string){
4338     inMeta := false
4339     showMode := ""
4340     showMeta := "" // visible Meta mode on the cursor position
4341     showLno := fmt.Sprintf("!&d! ", lno)
4342     InsertMark := "" // in visible insert mode
4343
4344     if MODE_VicMode {
4345     }else{
4346         if 0 < len(iin.right) {
4347             InsertMark = " "
4348         }
4349     }
4350     if( 0 < len(iin.waitingMeta) ){
4351         inMeta = true
4352         if iin.waitingMeta[0] != 033 {
4353             showMeta = iin.waitingMeta
4354         }
4355     }
4356     if( romkanmode ){
4357         //romkanmark = " *";
4358     }else{
4359         //romkanmark = "";
4360     }
4361     if MODE_ShowMode {
4362         romkan := "___"
4363         inmeta := "-"
4364         inveri := ""
4365         if MODE_CapsLock {
4366             inmeta = "A"
4367         }
4368         if MODE_LowerLock {
4369             inmeta = "a"
4370         }
4371         if MODE_ViTrace {
4372             inveri = "v"
4373         }
4374         if MODE_VicMode {
4375             inveri = ":"
4376         }
4377     }

```

```

4375     if romkanmode {
4376         romkan = "\343\201\202"
4377         if MODE_CapsLock {
4378             inmeta = "R"
4379         }else{
4380             inmeta = "r"
4381         }
4382     }
4383     if inMeta {
4384         inmeta = "\\"
4385     }
4386     showMode = "["+romkan+inmeta+inveri+"];";
4387 }
4388 Pre := "\r" + showMode + showLino
4389 Output := ""
4390 Left := ""
4391 Right := ""
4392 if romkanmode {
4393     Left = convs(line)
4394     Right = InsertMark+convs(right)
4395 }else{
4396     Left = line
4397     Right = InsertMark+right
4398 }
4399 Output = Pre+Left
4400 if MODE_ViTrace {
4401     Output += iin.LastCmd
4402 }
4403 Output += showMeta+Right
4404 for len(Output) < TtyMaxCol { // to the max. position that may be dirty
4405     Output += " "
4406     // should be ANSI ESC sequence
4407     // not necessary just after newline
4408 }
4409 Output += Pre+Left+showMeta // to set the cursor to the current input position
4410 fprintf(stderr,"%s",Output)
4411
4412 if MODE_ViTrace {
4413     if 0 < len(iin.LastCmd) {
4414         iin.LastCmd = ""
4415         fprintf(stderr,"\r\n")
4416     }
4417 }
4418 }
4419 // <a href="https://golang.org/pkg/unicode/utf8/">utf8</a>
4420 func delHeadChar(str string)(rline string,head string){
4421     _,clen := utf8.DecodeRune([]byte(str))
4422     head = string(str[0:clen])
4423     return str[clen:],head
4424 }
4425 func delTailChar(str string)(rline string, last string){
4426     var i = 0
4427     var clen = 0
4428     for {
4429         _,siz := utf8.DecodeRune([]byte(str)[i:])
4430         if siz <= 0 { break }
4431         clen = siz
4432         i += siz
4433     }
4434     last = str[len(str)-clen:]
4435     return str[0:len(str)-clen],last
4436 }
4437 }
4438 // 3> for output and history
4439 // 4> for keylog?
4440 // <a name="getline">Command Line Editor</a>
4441 func xgetline(lno int, prevline string, gsh*GshContext)(string){
4442     var iin IInput
4443     iin.lastlno = lno
4444     iin.lno = lno
4445
4446     CmdIndex = len(gsh.CommandHistory)
4447     if( isatty(0) == 0 ){
4448         if( sfgets(&iin.line,LINESIZE,stdin) == NULL ){
4449             iin.line = "exit\n";
4450         }else{
4451             }
4452         return iin.line
4453     }
4454     if( true ){
4455         //var pts string;
4456         //pts = ptsname(0);
4457         //pts = ttyname(0);
4458         //fprintf(stderr,"--pts[0] = %s\n",pts?pts:"?");
4459     }
4460     if( false ){
4461         fprintf(stderr,"! ");
4462         fflush(stderr);
4463         sfgets(&iin.line,LINESIZE,stdin);
4464         return iin.line
4465     }
4466     system("/bin/stty -echo -icanon");
4467     xline := iin.xgetline1(prevline,gsh)
4468     system("/bin/stty echo sane");
4469     return xline
4470 }
4471 func (iin*IInput)Translate(cmdch int){
4472     romkanmode = !romkanmode;
4473     if MODE_ViTrace {
4474         fprintf(stderr,"%v\r\n",string(cmdch));
4475     }else
4476     if( cmdch == 'J' ){
4477         fprintf(stderr,"J\r\n");
4478         iin.inJmode = true
4479     }
4480     iin.Redraw();
4481     loadDefaultDic(cmdch);
4482     iin.Redraw();
4483 }
4484 func (iin*IInput)Replace(cmdch int){
4485     iin.LastCmd = fmt.Sprintf("\%v",string(cmdch))
4486     iin.Redraw();
4487     loadDefaultDic(cmdch);
4488     dst := convs(iin.line+iin.right);
4489     iin.line = dst
4490     iin.right = ""
4491     if( cmdch == 'I' ){
4492         fprintf(stderr,"I\r\n");
4493         iin.inJmode = true
4494     }
4495     iin.Redraw();
4496 }
4497 // aa 12 alal
4498 func isAlpha(ch rune)(bool){
4499     if 'a' <= ch && ch <= 'z' || 'A' <= ch && ch <= 'Z' {

```

```

4500     return true
4501 }
4502 return false
4503 }
4504 func isAlnum(ch rune)(bool){
4505     if 'a' <= ch && ch <= 'z' || 'A' <= ch && ch <= 'Z' {
4506         return true
4507     }
4508     if '0' <= ch && ch <= '9' {
4509         return true
4510     }
4511     return false
4512 }
4513
4514 // 0.2.8 2020-0901 created
4515 // <a href="https://golang.org/pkg/unicode/utf8/#DecodeRuneInString">DecodeRuneInString</a>
4516 func (iin*Input)GotoTOPW(){
4517     str := iin.line
4518     i := len(str)
4519     if i <= 0 {
4520         return
4521     }
4522     //i0 := i
4523     i -= 1
4524     lastSize := 0
4525     var lastRune rune
4526     var found = -1
4527     for 0 < i { // skip preamble spaces
4528         lastRune, lastSize = utf8.DecodeRuneInString(str[i:])
4529         if !isAlnum(lastRune) { // character, type, or string to be searched
4530             i -= lastSize
4531             continue
4532         }
4533         break
4534     }
4535     for 0 < i {
4536         lastRune, lastSize = utf8.DecodeRuneInString(str[i:])
4537         if lastSize <= 0 { continue } // not the character top
4538         if !isAlnum(lastRune) { // character, type, or string to be searched
4539             found = i
4540             break
4541         }
4542         i -= lastSize
4543     }
4544     if found < 0 && i == 0 {
4545         found = 0
4546     }
4547     if 0 <= found {
4548         if isAlnum(lastRune) { // or non-kana character
4549             }else{ // when positioning to the top o the word
4550                 i += lastSize
4551             }
4552             iin.right = str[i:] + iin.right
4553             if 0 < i {
4554                 iin.line = str[0:i]
4555             }else{
4556                 iin.line = ""
4557             }
4558         }
4559         //fmt.Printf("\n(%d,%d,%d)[%s][%s]\n",i0,i,found,iin.line,iin.right)
4560         //fmt.Printf("") // set debug messae at the end of line
4561     }
4562 // 0.2.8 2020-0901 created
4563 func (iin*Input)GotoENDW(){
4564     str := iin.right
4565     if len(str) <= 0 {
4566         return
4567     }
4568     lastSize := 0
4569     var lastRune rune
4570     var lastW = 0
4571     i := 0
4572     inWord := false
4573
4574     lastRune, lastSize = utf8.DecodeRuneInString(str[0:])
4575     if isAlnum(lastRune) {
4576         r, z := utf8.DecodeRuneInString(str[lastSize:])
4577         if 0 < z && isAlnum(r) {
4578             inWord = true
4579         }
4580     }
4581     for i < len(str) {
4582         lastRune, lastSize = utf8.DecodeRuneInString(str[i:])
4583         if lastSize <= 0 { break } // broken data?
4584         if !isAlnum(lastRune) { // character, type, or string to be searched
4585             break
4586         }
4587         lastW = i // the last alnum if in alnum word
4588         i += lastSize
4589     }
4590     if inWord {
4591         goto DISP
4592     }
4593     for i < len(str) {
4594         lastRune, lastSize = utf8.DecodeRuneInString(str[i:])
4595         if lastSize <= 0 { break } // broken data?
4596         if isAlnum(lastRune) { // character, type, or string to be searched
4597             break
4598         }
4599         i += lastSize
4600     }
4601     for i < len(str) {
4602         lastRune, lastSize = utf8.DecodeRuneInString(str[i:])
4603         if lastSize <= 0 { break } // broken data?
4604         if !isAlnum(lastRune) { // character, type, or string to be searched
4605             break
4606         }
4607         lastW = i
4608         i += lastSize
4609     }
4610 DISP:
4611     if 0 < lastW {
4612         iin.line = iin.line + str[0:lastW]
4613         iin.right = str[lastW:]
4614     }
4615     //fmt.Printf("\n(%d)[%s][%s]\n",i,iin.line,iin.right)
4616     //fmt.Printf("") // set debug messae at the end of line
4617 }
4618 // 0.2.8 2020-0901 created
4619 func (iin*Input)GotoNEXTW(){
4620     str := iin.right
4621     if len(str) <= 0 {
4622         return
4623     }
4624     lastSize := 0

```

```

4625 var lastRune rune
4626 var found = -1
4627 i := 1
4628 for i < len(str) {
4629     lastRune, lastSize = utf8.DecodeRuneInString(str[i:])
4630     if lastSize <= 0 { break } // broken data?
4631     if !isAlnum(lastRune) { // character, type, or string to be searched
4632         found = i
4633         break
4634     }
4635     i += lastSize
4636 }
4637 if 0 < found {
4638     if isAlnum(lastRune) { // or non-kana character
4639     }else{ // when positioning to the top of the word
4640         found += lastSize
4641     }
4642     iin.line = iin.line + str[0:found]
4643     if 0 < found {
4644         iin.right = str[found:]
4645     }else{
4646         iin.right = ""
4647     }
4648 }
4649 //fmt.Printf("\n(%d)[%s][%s]\n", i, iin.line, iin.right)
4650 //fmt.Printf("") // set debug message at the end of line
4651 }
4652 // 0.2.8 2020-0902 created
4653 func (iin*Input)GotoPAIRCH(){
4654     str := iin.right
4655     if len(str) <= 0 {
4656         return
4657     }
4658     lastRune, lastSize := utf8.DecodeRuneInString(str[0:])
4659     if lastSize <= 0 {
4660         return
4661     }
4662     forw := false
4663     back := false
4664     pair := ""
4665     switch string(lastRune){
4666     case "{": pair = "}"; forw = true
4667     case "}": pair = "{"; back = true
4668     case "(": pair = ")"; forw = true
4669     case ")": pair = "("; back = true
4670     case "[": pair = "]"; forw = true
4671     case "]": pair = "["; back = true
4672     case "<": pair = ">"; forw = true
4673     case ">": pair = "<"; back = true
4674     case "\\": pair = "\\"; // context depended, can be f" or back-double quote
4675     case "'": pair = "'"; // context depended, can be f' or back-quote
4676     // case Japanese Kakkos
4677     }
4678     if forw {
4679         iin.SearchForward(pair)
4680     }
4681     if back {
4682         iin.SearchBackward(pair)
4683     }
4684 }
4685 // 0.2.8 2020-0902 created
4686 func (iin*Input)SearchForward(pat string)(bool){
4687     right := iin.right
4688     found := -1
4689     i := 0
4690     if strBegins(right, pat) {
4691         _z := utf8.DecodeRuneInString(right[i:])
4692         if 0 < z {
4693             i += z
4694         }
4695     }
4696     for i < len(right) {
4697         if strBegins(right[i:], pat) {
4698             found = i
4699             break
4700         }
4701         _z := utf8.DecodeRuneInString(right[i:])
4702         if z <= 0 { break }
4703         i += z
4704     }
4705     if 0 <= found {
4706         iin.line = iin.line + right[0:found]
4707         iin.right = iin.right[found:]
4708         return true
4709     }else{
4710         return false
4711     }
4712 }
4713 // 0.2.8 2020-0902 created
4714 func (iin*Input)SearchBackward(pat string)(bool){
4715     line := iin.line
4716     found := -1
4717     i := len(line)-1
4718     for i = i; 0 <= i; i-- {
4719         _z := utf8.DecodeRuneInString(line[i:])
4720         if z <= 0 {
4721             continue
4722         }
4723         //fprintf(stderr, "-- %v\n", pat, line[i:])
4724         if strBegins(line[i:], pat) {
4725             found = i
4726             break
4727         }
4728     }
4729     //fprintf(stderr, "--%d\n", found)
4730     if 0 <= found {
4731         iin.right = line[found:] + iin.right
4732         iin.line = line[0:found]
4733         return true
4734     }else{
4735         return false
4736     }
4737 }
4738 // 0.2.8 2020-0902 created
4739 // search from top, end, or current position
4740 func (gsh*GshContext)SearchHistory(pat string, forw bool)(bool, string){
4741     if forw {
4742         for _, v := range gsh.CommandHistory {
4743             if 0 <= strings.Index(v.CmdLine, pat) {
4744                 //fprintf(stderr, "\n--De-- found !%v [%v]\n", i, pat, v.CmdLine)
4745                 return true, v.CmdLine
4746             }
4747         }
4748     }else{
4749         hlen := len(gsh.CommandHistory)

```

```

4750     for i := hlen-1; 0 < i; i-- {
4751         v := gsh.CommandHistory[i]
4752         if 0 < strings.Index(v.CmdLine, pat) {
4753             //fprintf(stderr, "\n--De-- found !%v [%v]&v\n", i, pat, v.CmdLine)
4754             return true, v.CmdLine
4755         }
4756     }
4757 }
4758 //fprintf(stderr, "\n--De-- not-found(%v)\n", pat)
4759 return false, "(Not Found in History)"
4760 }
4761 // 0.2.8 2020-0902 created
4762 func (iin*IInput)GotoFORWSTR(pat string, gsh*GshContext){
4763     found := false
4764     if 0 < len(iin.right) {
4765         found = iin.SearchForward(pat)
4766     }
4767     if !found {
4768         found, line := gsh.SearchHistory(pat, true)
4769         if found {
4770             iin.line = line
4771             iin.right = ""
4772         }
4773     }
4774 }
4775 func (iin*IInput)GotoBACKSTR(pat string, gsh*GshContext){
4776     found := false
4777     if 0 < len(iin.line) {
4778         found = iin.SearchBackward(pat)
4779     }
4780     if !found {
4781         found, line := gsh.SearchHistory(pat, false)
4782         if found {
4783             iin.line = line
4784             iin.right = ""
4785         }
4786     }
4787 }
4788 func (iin*IInput)getString1(prompt string)(string){ // should be editable
4789     iin.clearline();
4790     fprintf(stderr, "\r%v", prompt)
4791     str := ""
4792     for {
4793         ch := iin.Getc(10*1000*1000)
4794         if ch == '\n' || ch == '\r' {
4795             break
4796         }
4797         sch := string(ch)
4798         str += sch
4799         fprintf(stderr, "%s", sch)
4800     }
4801     return str
4802 }
4803 }
4804 // search pattern must be an array and selectable with ^N/^P
4805 var SearchPat = ""
4806 var SearchForw = true
4807 }
4808 func (iin*IInput)xgetline1(prevline string, gsh*GshContext)(string){
4809     var ch int;
4810     MODE_ShowMode = false
4811     MODE_VicMode = false
4812     iin.Redraw();
4813     first := true
4814     for cix := 0; ; cix++ {
4815         iin.inJmode = iin.inJmode
4816         iin.inJmode = false
4817         ch = iin.Getc(1000*1000)
4818         if ch != EV_TIMEOUT && first {
4819             first = false
4820             mode := 0
4821             if romkanmode {
4822                 mode = 1
4823             }
4824             now := time.Now()
4825             Events = append(Events, Event{now, EV_MODE, int64(mode), CmdIndex})
4826         }
4827         if ch == 033 {
4828             MODE_ShowMode = true
4829             MODE_VicMode = !MODE_VicMode
4830             iin.Redraw();
4831             continue
4832         }
4833         if MODE_VicMode {
4834             switch ch {
4835                 case '0': ch = GO_TOPL
4836                 case '$': ch = GO_ENDL
4837                 case 'b': ch = GO_TOPW
4838                 case 'e': ch = GO_ENDW
4839                 case 'w': ch = GO_NEXTW
4840                 case '$': ch = GO_PAIRCH
4841                 case 'j': ch = GO_DOWN
4842                 case 'k': ch = GO_UP
4843                 case 'h': ch = GO_LEFT
4844                 case 'l': ch = GO_RIGHT
4845                 case 'x': ch = DEL_RIGHT
4846                 case 'a': MODE_VicMode = !MODE_VicMode
4847                     ch = GO_RIGHT
4848                 case 'i': MODE_VicMode = !MODE_VicMode
4849                     iin.Redraw();
4850                     continue
4851                 case '-':
4852                     right, head := delHeadChar(iin.right)
4853                     if len([]byte(head)) == 1 {
4854                         ch = int(head[0])
4855                         if( 'a' <= ch && ch <= 'z' ){
4856                             ch = ch + 'A'-'a'
4857                         }else
4858                         if( 'A' <= ch && ch <= 'Z' ){
4859                             ch = ch + 'a'-'A'
4860                         }
4861                     }
4862                     iin.right = string(ch) + right
4863                 }
4864             iin.Redraw();
4865             continue
4866         }
4867         case 'f': // GO_FORWCH
4868             iin.Redraw();
4869             ch = iin.Getc(3*1000*1000)
4870             if ch == EV_TIMEOUT {
4871                 iin.Redraw();

```

```

4875         continue
4876     }
4877     SearchPat = string(ch)
4878     SearchForw = true
4879     iin.GotoFORWSTR(SearchPat,gsh)
4880     iin.Redraw();
4881     continue
4882 case '/':
4883     SearchPat = iin.getstring1("/") // should be editable
4884     SearchForw = true
4885     iin.GotoFORWSTR(SearchPat,gsh)
4886     iin.Redraw();
4887     continue
4888 case '?':
4889     SearchPat = iin.getstring1("?") // should be editable
4890     SearchForw = false
4891     iin.GotoBACKSTR(SearchPat,gsh)
4892     iin.Redraw();
4893     continue
4894 case 'n':
4895     if SearchForw {
4896         iin.GotoFORWSTR(SearchPat,gsh)
4897     }else{
4898         iin.GotoBACKSTR(SearchPat,gsh)
4899     }
4900     iin.Redraw();
4901     continue
4902 case 'N':
4903     if !SearchForw {
4904         iin.GotoFORWSTR(SearchPat,gsh)
4905     }else{
4906         iin.GotoBACKSTR(SearchPat,gsh)
4907     }
4908     iin.Redraw();
4909     continue
4910     }
4911 }
4912 switch ch {
4913 case GO_TOPW:
4914     iin.GotoTOPW()
4915     iin.Redraw();
4916     continue
4917 case GO_ENDW:
4918     iin.GotoENDW()
4919     iin.Redraw();
4920     continue
4921 case GO_NEXTW:
4922     // To next space then
4923     iin.GotoNEXTW()
4924     iin.Redraw();
4925     continue
4926 case GO_PAIRCH:
4927     iin.GotoPAIRCH()
4928     iin.Redraw();
4929     continue
4930 }
4931
4932 //fprintf(stderr,"A[%02X]\n",ch);
4933 if( ch == '\\' || ch == 033 ){
4934     MODE_ShowMode = true
4935     metach := ch
4936     iin.waitingMeta = string(ch)
4937     iin.Redraw();
4938     // set cursor //fprintf(stderr,"???\b\b\b")
4939     ch = fgetcTimeout(stdin,2000*1000)
4940     // reset cursor
4941     iin.waitingMeta = ""
4942
4943     cmdch := ch
4944     if( ch == EV_TIMEOUT ){
4945         if metach == 033 {
4946             continue
4947         }
4948         ch = metach
4949     }else
4950     /*
4951     if( ch == 'm' || ch == 'M' ){
4952         mch := fgetcTimeout(stdin,1000*1000)
4953         if mch == 'r' {
4954             romkanmode = true
4955         }else{
4956             romkanmode = false
4957         }
4958         continue
4959     }else
4960     */
4961     if( ch == 'k' || ch == 'K' ){
4962         MODE_Recursive = !MODE_Recursive
4963         iin.Translate(cmdch);
4964         continue
4965     }else
4966     if( ch == 'j' || ch == 'J' ){
4967         iin.Translate(cmdch);
4968         continue
4969     }else
4970     if( ch == 'i' || ch == 'I' ){
4971         iin.Replace(cmdch);
4972         continue
4973     }else
4974     if( ch == 'l' || ch == 'L' ){
4975         MODE_LowerLock = !MODE_LowerLock
4976         MODE_CapsLock = false
4977         if MODE_ViTrace {
4978             fprintf(stderr,"%v\r\n",string(cmdch));
4979         }
4980         iin.Redraw();
4981         continue
4982     }else
4983     if( ch == 'u' || ch == 'U' ){
4984         MODE_CapsLock = !MODE_CapsLock
4985         MODE_LowerLock = false
4986         if MODE_ViTrace {
4987             fprintf(stderr,"%v\r\n",string(cmdch));
4988         }
4989         iin.Redraw();
4990         continue
4991     }else
4992     if( ch == 'v' || ch == 'V' ){
4993         MODE_ViTrace = !MODE_ViTrace
4994         if MODE_ViTrace {
4995             fprintf(stderr,"%v\r\n",string(cmdch));
4996         }
4997         iin.Redraw();
4998         continue
4999     }else

```



```

5000     if( ch == 'c' || ch == 'C' ){
5001         if 0 < len(iin.line) {
5002             xline,tail := delTailChar(iin.line)
5003             if len([]byte(tail)) == 1 {
5004                 ch = int(tail[0])
5005                 if( 'a' <= ch && ch <= 'z' ){
5006                     ch = ch + 'A'-'a'
5007                 }else
5008                 if( 'A' <= ch && ch <= 'z' ){
5009                     ch = ch + 'a'-'A'
5010                 }
5011                 iin.line = xline + string(ch)
5012             }
5013         }
5014         if MODE_ViTrace {
5015             fprintf(stderr,"%v\r\n",string(cmdch));
5016         }
5017         iin.Redraw();
5018         continue
5019     }else{
5020         iin.pch = append(iin.pch,ch) // push
5021         ch = '\\'
5022     }
5023 }
5024 switch( ch ){
5025 case 'P'-0x40: ch = GO_UP
5026 case 'N'-0x40: ch = GO_DOWN
5027 case 'B'-0x40: ch = GO_LEFT
5028 case 'F'-0x40: ch = GO_RIGHT
5029 }
5030 //fprintf(stderr,"B[%02X]\n",ch);
5031 switch( ch ){
5032 case 0:
5033     continue;
5034
5035 case '\t':
5036     iin.Replace('j');
5037     continue
5038 case 'X'-0x40:
5039     iin.Replace('j');
5040     continue
5041
5042 case EV_TIMEOUT:
5043     iin.Redraw();
5044     if iin.pinMode {
5045         fprintf(stderr,"\\J\r\n")
5046         iin.inJmode = true
5047     }
5048     continue
5049 case GO_UP:
5050     if iin.lno == 1 {
5051         continue
5052     }
5053     cmd,ok := gsh.cmdStringInHistory(iin.lno-1)
5054     if ok {
5055         iin.line = cmd
5056         iin.right = ""
5057         iin.lno = iin.lno - 1
5058     }
5059     iin.Redraw();
5060     continue
5061 case GO_DOWN:
5062     cmd,ok := gsh.cmdStringInHistory(iin.lno+1)
5063     if ok {
5064         iin.line = cmd
5065         iin.right = ""
5066         iin.lno = iin.lno + 1
5067     }else{
5068         iin.line = ""
5069         iin.right = ""
5070         if iin.lno == iin.lastlno-1 {
5071             iin.lno = iin.lno + 1
5072         }
5073     }
5074     iin.Redraw();
5075     continue
5076 case GO_LEFT:
5077     if 0 < len(iin.line) {
5078         xline,tail := delTailChar(iin.line)
5079         iin.line = xline
5080         iin.right = tail + iin.right
5081     }
5082     iin.Redraw();
5083     continue;
5084 case GO_RIGHT:
5085     if( 0 < len(iin.right) && iin.right[0] != 0 ){
5086         xright,head := delHeadChar(iin.right)
5087         iin.right = xright
5088         iin.line += head
5089     }
5090     iin.Redraw();
5091     continue;
5092 case EOF:
5093     goto EXIT;
5094 case 'R'-0x40: // replace
5095     dst := convs(iin.line+iin.right);
5096     iin.line = dst
5097     iin.right = ""
5098     iin.Redraw();
5099     continue;
5100 case 'T'-0x40: // just show the result
5101     readDic();
5102     romkanmode = !romkanmode;
5103     iin.Redraw();
5104     continue;
5105 case 'L'-0x40:
5106     iin.Redraw();
5107     continue
5108 case 'K'-0x40:
5109     iin.right = ""
5110     iin.Redraw();
5111     continue
5112 case 'E'-0x40:
5113     iin.line += iin.right
5114     iin.right = ""
5115     iin.Redraw();
5116     continue
5117 case 'A'-0x40:
5118     iin.right = iin.line + iin.right
5119     iin.line = ""
5120     iin.Redraw();
5121     continue
5122 case 'U'-0x40:
5123     iin.line = ""
5124     iin.right = ""

```

```

5125         iin.clearline();
5126         iin.Redraw();
5127         continue;
5128     case DEL_RIGHT:
5129         if( 0 < len(iin.right) ){
5130             iin.right,_ = delHeadChar(iin.right)
5131             iin.Redraw();
5132         }
5133         continue;
5134     case 0x7F: // BS? not DEL
5135         if( 0 < len(iin.line) ){
5136             iin.line,_ = delTailChar(iin.line)
5137             iin.Redraw();
5138         }
5139         /*
5140         else
5141             if( 0 < len(iin.right) ){
5142                 iin.right,_ = delHeadChar(iin.right)
5143                 iin.Redraw();
5144             }
5145             */
5146         continue;
5147     case 'H'-0x40:
5148         if( 0 < len(iin.line) ){
5149             iin.line,_ = delTailChar(iin.line)
5150             iin.Redraw();
5151         }
5152         continue;
5153     }
5154     if( ch == '\n' || ch == '\r' ){
5155         iin.line += iin.right;
5156         iin.right = ""
5157         iin.Redraw();
5158         fputc(ch,stderr);
5159         break;
5160     }
5161     if MODE_CapsLock {
5162         if 'a' <= ch && ch <= 'z' {
5163             ch = ch+'A'-'a'
5164         }
5165     }
5166     if MODE_LowerLock {
5167         if 'A' <= ch && ch <= 'Z' {
5168             ch = ch+'a'-'A'
5169         }
5170     }
5171     iin.line += string(ch);
5172     iin.Redraw();
5173 }
5174 EXIT:
5175     return iin.line + iin.right;
5176 }
5177
5178 func getline_main(){
5179     line := xgetline(0,"",nil)
5180     fprintf(stderr,"%s\n",line);
5181     /*
5182     dp = strpbrk(line,"\r\n");
5183     if( dp != NULL ){
5184         *dp = 0;
5185     }
5186
5187     if( 0 ){
5188         fprintf(stderr,"\n(%d)\n",int(strlen(line)));
5189     }
5190     if( lseek(3,0,0) == 0 ){
5191         if( romkanmode ){
5192             var buf [8*1024]byte;
5193             convs(line,buf);
5194             strcpy(line,buf);
5195         }
5196         write(3,line,strlen(line));
5197         ftruncate(3,lseek(3,0,SEEK_CUR));
5198         //fprintf(stderr,"outsize=%d\n",int)lseek(3,0,SEEK_END));
5199         lseek(3,0,SEEK_SET);
5200         close(3);
5201     }else{
5202         fprintf(stderr,"\r\ngotline: ");
5203         trans(line);
5204         //printf("%s\n",line);
5205         printf("\n");
5206     }
5207     */
5208 }
5209 //== end =====
5210
5211 //
5212 // $USERHOME/.gsh/
5213 // gsh-rc.txt, or gsh-configure.txt
5214 // gsh-history.txt
5215 // gsh-aliases.txt // should be conditional?
5216 //
5217 func (gshCtx *GshContext)gshSetupHomedir()(bool) {
5218     homedir,found := userHomeDir()
5219     if !found {
5220         fmt.Printf("--E-- You have no UserHomeDir\n")
5221         return true
5222     }
5223     gshhome := homedir + "/" + GSH_HOME
5224     _, err2 := os.Stat(gshhome)
5225     if err2 != nil {
5226         err3 := os.Mkdir(gshhome,0700)
5227         if err3 != nil {
5228             fmt.Printf("--E-- Could not Create %s (%s)\n",
5229                 gshhome,err3)
5230             return true
5231         }
5232         fmt.Printf("--I-- Created %s\n",gshhome)
5233     }
5234     gshCtx.GshHomeDir = gshhome
5235     return false
5236 }
5237 func setupGshContext()(GshContext,bool){
5238     gshPA := syscall.ProcAttr {
5239         "", // the staring directory
5240         os.Environ(), // environ[]
5241         []uintptr{os.Stdin.Fd(),os.Stdout.Fd(),os.Stderr.Fd()},
5242         nil, // OS specific
5243     }
5244     cwd,_ := os.Getwd()
5245     gshCtx := GshContext {
5246         cwd, // StartDir
5247         "", // GetLine
5248         []GchdirHistory { {cwd,time.Now(),0} }, // ChdirHistory
5249         gshPA,

```

```

5250     []GCommandHistory{}, //something for invokation?
5251     GCommandHistory{}, // CmdCurrent
5252     false,
5253     []int{},
5254     syscall.Rusage{},
5255     "", // GshHomeDir
5256     Ttyid(),
5257     false,
5258     false,
5259     []PluginInfo{},
5260     []string{},
5261     "",
5262     "v",
5263     ValueStack{},
5264     GServer{"", ""}, // LastServer
5265     "", // RSERV
5266     cwd, // RWD
5267     CheckSum{},
5268 }
5269 err := gshCtx.gshSetupHomedir()
5270 return gshCtx, err
5271 }
5272 func (gsh*GshContext)gshelllh(gline string)(bool){
5273     ghist := gsh.CmdCurrent
5274     ghist.WorkDir,_ = os.Getwd()
5275     ghist.WorkDirX = len(gsh.ChdirHistory)-1
5276     //fmt.Printf("--D--ChdirHistory(%#d)\n",len(gsh.ChdirHistory))
5277     ghist.StartAt = time.Now()
5278     rusagev1 := Getrusagev()
5279     gsh.CmdCurrent.FoundFile = []string{}
5280     fin := gsh.tgshelllh(gline)
5281     rusagev2 := Getrusagev()
5282     ghist.Rusagev = RusageSubv(rusagev2,rusagev1)
5283     ghist.EndAt = time.Now()
5284     ghist.CmdLine = gline
5285     ghist.FoundFile = gsh.CmdCurrent.FoundFile
5286
5287     /* record it but not show in list by default
5288     if len(gline) == 0 {
5289         continue
5290     }
5291     if gline == "hi" || gline == "history" { // don't record it
5292         continue
5293     }
5294     */
5295     gsh.CommandHistory = append(gsh.CommandHistory, ghist)
5296     return fin
5297 }
5298 // <a name="main">Main loop</a>
5299 func script(gshCtxGiven *GshContext) (_ GshContext) {
5300     gshCtxBuf,err0 := setupGshContext()
5301     if err0 {
5302         return gshCtxBuf;
5303     }
5304     gshCtx := &gshCtxBuf
5305
5306     //fmt.Printf("--I-- GSH_HOME=%s\n",gshCtx.GshHomeDir)
5307     //resmap()
5308
5309     /*
5310     if false {
5311         gsh_getlinev, with_exgetline :=
5312             which("PATH",[]string{"which","gsh-getline","-s"})
5313         if with_exgetline {
5314             gsh_getlinev[0] = toFullpath(gsh_getlinev[0])
5315             gshCtx.GetLine = toFullpath(gsh_getlinev[0])
5316         }else{
5317             fmt.Printf("--W-- No gsh-getline found. Using internal getline.\n");
5318         }
5319     }
5320     */
5321
5322     ghist0 := gshCtx.CmdCurrent // something special, or gshrc script, or permanent history
5323     gshCtx.CommandHistory = append(gshCtx.CommandHistory,ghist0)
5324
5325     prevline := ""
5326     skipping := false
5327     for hix := len(gshCtx.CommandHistory); ; {
5328         gline := gshCtx.getline(hix,skipping,prevline)
5329         if skipping {
5330             if strings.Index(gline,"fi") == 0 {
5331                 fmt.Printf("fi\n");
5332                 skipping = false;
5333             }else{
5334                 //fmt.Printf("%s\n",gline);
5335             }
5336             continue
5337         }
5338         if strings.Index(gline,"if") == 0 {
5339             //fmt.Printf("--D-- if start: %s\n",gline);
5340             skipping = true;
5341             continue
5342         }
5343         if false {
5344             os.Stdout.Write([]byte("gotline:"))
5345             os.Stdout.Write([]byte(gline))
5346             os.Stdout.Write([]byte("\n"))
5347         }
5348         gline = strsubst(gshCtx,gline,true)
5349         if false {
5350             fmt.Printf("fmt.Printf %%v - %v\n",gline)
5351             fmt.Printf("fmt.Printf %%s - %s\n",gline)
5352             fmt.Printf("fmt.Printf %%x - %x\n",gline)
5353             fmt.Printf("fmt.Printf %%U - %s\n",gline)
5354             fmt.Printf("Stoutt.Write -")
5355             os.Stdout.Write([]byte(gline))
5356             fmt.Printf("\n")
5357         }
5358         /*
5359         // should be cared in substitution ?
5360         if 0 < len(gline) && gline[0] == '|' {
5361             xgline, set, err := searchHistory(gshCtx,gline)
5362             if err {
5363                 continue
5364             }
5365             if set {
5366                 // set the line in command line editor
5367             }
5368             gline = xgline
5369         }
5370         */
5371         fin := gshCtx.gshelllh(gline)
5372         if fin {
5373             break;
5374         }

```



```

5500 "a2tqa2tsCe0BqApramtsCe0Bggpqa2prbAnjgasKa2tra2wJ44GsCmpqa2psCe0BrQpra2pg"+
5501 "banJga4Kamtra2wJ44GvCmpqa2tqbAnjgbiKampra2wJ44G1CmtsCe0BuApqa2tsCe0Buwpq"+
5502 "a2tqbAnjgbiKa2tga2psCe0BvwpqbAnjgoAKamtra2psCe0CgQpqa2tq2wJ44KCmtqamwJ"+
5503 "44KCmpraz2pgbAnjgoKampsCe0CiApra2tsCe0C1QpgamtsCe0CiQpqa2pqa2wJ44KLCmpg"+
5504 "amwJ44KCmtq2psCe0CjQpqa2psCe0CjwpramtramwJ44KQCmtqamrbanJgpEka2pqaamwJ"+
5505 "44KCmtq2prbAnjgpMka2pqa2psCe0DvApra2wJ44KbCmtramprbAnjgpwKa2pramtqbAnj"+
5506 "gIEK";
5507 //</span>
5508
5509 //</span>
5510 /*
5511 <details id="references"><summary>References</summary><div class="gsh-src">
5512 <p>
5513 <a href="https://golang.org">The Go Programming Language</a>
5514 <iframe src="https://golang.org" width="100%" height="300"></iframe>
5515
5516 <a href="https://developer.mozilla.org/ja/docs/Web">MDN web docs</a>
5517 <a href="https://developer.mozilla.org/ja/docs/Web/HTML/Element">HTML</a>
5518 CSS:
5519 <a href="https://developer.mozilla.org/en-US/docs/Web/CSS/CSS_Selectors">Selectors</a>
5520 <a href="https://developer.mozilla.org/en-US/docs/Web/CSS/background-repeat">repeat</a>
5521 HTTP
5522 JavaScript:
5523 .
5524 </p>
5525 </div></details>
5526 */
5527 /*
5528 <details id="html-src" onclick="frame_open();"><summary>Raw Source</summary><div>
5529
5530 <!-- h2>The full of this HTML including the Go code is here.</h2 -->
5531 <details id="gsh-whole-view"><summary>Whole file</summary>
5532 <a name="whole-src-view"></a>
5533 <span id="src-frame"></span><!-- a window to show source code -->
5534 </details>
5535
5536 <details id="gsh-style-frame" onclick="fill_CSSView()"><summary>CSS part</summary>
5537 <a name="style-src-view"></a>
5538 <span id="gsh-style-view"></span>
5539 </details>
5540
5541 <details id="gsh-script-frame" onclick="fill_JavaScriptView()"><summary>JavaScript part</summary>
5542 <a name="script-src-view"></a>
5543 <span id="gsh-script-view"></span>
5544 </details>
5545
5546 <details id="gsh-data-frame" onclick="fill_DataView()"><summary>Builtin data part</summary>
5547 <a name="gsh-data-frame"></a>
5548 <span id="gsh-data-view"></span>
5549 </details>
5550
5551 </div></details>
5552 */
5553 /*
5554 <div id="gsh-footer" style=""></div><!-- END-OF-VISIBLE-PART ----- -->
5555
5556
5557 <style id="gsh-style-def">
5558 //body {display:none;}
5559 .gsh-link{color:green;}
5560 #gsh {border-width:1;margin:0;padding:0;}
5561 #gsh {font-family:monospace,Courier New;color:#ddf;font-size:8px;}
5562 #gsh header{height:100px;}
5563 #xgsh header{height:100px;background-image:url(GShell-Logo00.png);}
5564 #gsh-menu{font-size:14pt;color:#f88;}
5565 #gsh-footer{height:100px;background-size:80px;background-repeat:no-repeat;}
5566 #gsh note{color:#000;font-size:10pt;}
5567 #gsh h2{color:#24a;font-family:Georgia;font-size:18pt;}
5568 #gsh h3{color:#24a;font-family:Georgia;font-size:16pt;}
5569 #gsh details{color:#888;background-color:#fff;font-family:monospace;}
5570 #gsh summary{font-size:16pt;color:#fff;background-color:#8af,height:30px;}
5571 #gsh pre{font-size:11pt;color:#223;background-color:#faffff;}
5572 #gsh a{color:#24a;}
5573 #gsh a[name]{color:#24a;font-size:16pt;}
5574 #gsh .gsh-src{white-space:pre;font-family:monospace,Courier New;font-size:11pt;}
5575 #gsh .gsh-src{background-color:#faffff;color:#223;}
5576 #gsh-src-src{spellcheck:false}
5577 #src-frame-textarea{white-space:pre;font-family:monospace,Courier New;font-size:11pt;}
5578 #src-frame-textarea{background-color:#faffff;color:#223;}
5579 .gsh-code {white-space:pre;font-family:monospace !import;}
5580 .gsh-code {color:#088;font-size:11pt; background-color:#eef;}
5581 .gsh-golang-data {display:none;}
5582 #gsh-winId {color:#000;font-size:14pt;}
5583
5584 .gsh-document {font-size:11pt;background-color:#fff;font-family:Georgia;}
5585 .gsh-document {color:#000;background-color:#fff !import;}
5586 .gsh-document > h2{color:#000;background-color:#fff !import;}
5587 .gsh-document details{color:#000;background-color:#fff;font-family:Georgia;}
5588 .gsh-document p{max-width:550pt;color:#000;background-color:#fff;font-family:Georgia;}
5589 .gsh-document address{width:500pt;color:#000;background-color:#fff;font-family:Georgia;}
5590
5591 @media print {
5592 #gsh pre{font-size:11pt !import;}
5593 }
5594 </style>
5595
5596 <!--
5597 // Logo image should be drawn by JavaScript from a meta-font.
5598 // CSS seems not follow line-splitted URL
5599 -->
5600 <script id="gsh-data">
5601 //GshLogo="QR-ITS-more.jp.png"
5602 GshLogo="data:image/png;base64,\
5603 iVBORw0KGooAAANSUHEUgAAAEAAAB/CAYAAdvs3f4AAAAAXNSR0IARs4c6QAAAHlWE1m\
5604 TU0AKgAAAqABAEaAAUAAAABAAAAPgEbaUAAAABAAAARgEoAAMAAAABAAIAAIIdpAAQAAAAB\
5605 AAAATgAAAAAAAABIAAAAAQAAAEgAAABAAQAAQADAAAAAQAABACqAgAEAAAAQAAAGGAWAE\
5606 AAAAQAAAH8AAAAAYx1BhgAAAA1wSfLzAAALEWAACMBAJcGAAAF3RJREFUEAhtnQuUFNWf\
5607 x+t7ukZ3iCggO/jY60sb8WgMzAvn7uG4+biSTR7YnXQdQPcKj2aNw1D2MS1RkeUAPnoCdu\
5608 4iUJx7jrIYZ5D0DGmF2VqIBEiSggCoIMMA+mu+vu//ZMD9U1daU6a2aUbv91GKR3vvdX6/q\
5609 fnXvdX8tBA8SIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAES\
5610 IAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAES\
5611 IAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAES\
5612 IAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAES\
5613 2eXs9H+ftKsDhXsC2qgdE7YusS+1qaalKfnY5YsokMHwEPTdK4MQFz5UEXlLbLYsAU15\
5614 npDiLKXEZC1FiRMS3JSUaq9ScqcU6i+2kK3StuOnY5reEKGJ7Qw7mOvKec2Toq0iZw0j\
5615 jbOVHcstMRB3USXEJ8hFu7DsdmFb2+XU4vWVWFxbBMeZU1AE/hcKogab66K6G01Nyh56PC\
5616 HxH2VVBKORqgh3qUeKi1YdaOFONJ56OkdI6w5BwomOqlyPziON9DLmXpF/60p2P/Piyov\
5617 N8mfm+NWJNgNj9kQToLVGSP+2p2Ri1lgn3j0V7YsoWmVzEuVPF1RKYdfoak2LRSB0q\
5618 zrWocOG6gEhvgRacj/dktj3g7dXXH4gKN6ARS0zPzYerqS6RAoZDQqfk79SKTRXHu/e+9FN\
5619 L66as88pU/PN1PNTLJKS73dPXSR20ur7iUwPcC8QhbNnCyHUIrlyyOTQVf55fvgBL7jX\
5620 +cNhjBj5gRyDlJHy39o84D40H2QtX8THaPeFuIOU+wLc+KnyhK5FGEVOWGAEXB83eXMoLY\
5621 rikbd9gHEP52vqrn014h89FUA6kYjYFbbQbnzLJg4Z7iesndHCwvUoeiVQob/5C9FY9DlUeO\
5622 +ZghUhnSgOgrmUwgrkI9RpjBD4Y6uQCQdD5TUOW63zD3MHesy14V49isbdKyxhGh1CpFR\
5623 UJ6toACF7F9Vf58NBfDHTOMBae74Ent+eWrrW+rLz/QTw60AdB7QUjps/OA7COoNBNCeMUZ\
5624 ttCu/coG28fLpKEL1PFV8JuRasEahbHvxaR1guoeBpYfUdO4+OfeBdyb8L4tZ9XeSXFAMoc\

```

```

5625 bgGgov0glzgg6W4fJ392xnHhdc+Wwf3JTjntZ2yClyJBjXNUT5KIkyck1sxXRdl6BmcevN\
5626 aJovy/VBacHevqEP46/zlnJjt9jx17VL5z15MtvapIQGlnHw5pQDqYNTQ1Z2b8nGcNG2ZV\
5627 qOoF3sdyVv0AZzday1dv6FJ35Cq1jzKz9hnr7e27zmp63THLJpK1cTpv1Htk/DJFv4Jw1\
5628 1ImhM5IKR9fz2gRRXw6/CvHQSPe+rIyRj3gEPTNahsHhLdS2Xh5Q5WCoFPpEdppccqm/8e\
5629 7/czoaBptag/m1k377UOVG0xybtdX/bx/Ptfa/i7rTku+cs0iCxUwzohx16wEV9H+ccVg\
5630 pd/Co042AK21P1vTK1L/sjYyE5PvHqr728NzvFuzvYD0Gy9GoopuuuhNLNc6Tx48YHLZgH\
5631 f/8hpXU/43rQg9xtg6Tcv1KDC3EmDQ9n3b1n1j19/P7ew+i0AQoGF+NI31aw82dwkFPUw\
5632 hracu6z6kckjZK8EUMxae71zuqWcu2nbi6fmln1j19/P7ew+i0AQoGF+NI31aw82dwkFPUw\
5633 WNW4EPy9jJxuvEdL/HXNzqTsvsdLzvsWHW19mu5vry/zX9F5e64v/LfmgEdIphDGLfM2UCW\
5634 gJiy2wORNFz3EciVwzYzCNJYtrNyhgAo8/RoJTAUMaieqOCJnRw5FPtW+frTwdh4S1Uw\
5635 bV1WwdfELRFR04qazRD7176/fzBjKLD5pBlz5W14wQ7tLkPncOPuW+frTwdh4S1Uw\
5636 10azYwDh9zEr2xODRqVQf5vXhOvYjRKAAM46pVT+RxaJVLjW7vY9+rCeUBmk168/rPQm\
5637 KcuZaldFN/y18qa5wC3dkIkhyvZuCYSVG/KhwvhWDRKAMDE8KX+HF12A9btzd172\
5638 2gnZOVzCDYmEhNy70oqXDXWIKAIQ7c0OZchyADWnerqN5VXtctJsdGp2OwtgmUJ7A+EH7\
5639 yhVugml1X7f7K1DwaRvUEN42FLuxNddVetAmL6eYCR26VbzawZpx8fMfmez3EM+mgso1k\
5640 d3/zNBGELXPUQWzKglYc5ew5/zBcy54aWogWfKEnwbqetwT4FUBVov32g68DLzDTMaJ\
5641 aupg7/bmXx+yw/egJGKOtKsy2d+gfbB9v0dvX5Bl2TOR+Hfjy0pP6UOXGOYNr/qrta3vB\
5642 Fgeua6vgz27vmbdV3r1dBw34GSFg910DC9h5XWknh9KaAhmyJ6dklpZmtD3cn71vtw5C\
5643 h/rzG1p7Wxp/VvuRDuc+wsq54ymr8zzKOgyRSPRA4IKoZGLi18b6ytagcEPmb9v/im09UATz\
5644 Jow6VnPCWkxHz+gNnpHsCjYja6crrsMyrGkiwF415UouliLiLRW7EmLXz3z2+/cfw1L1U2\
5645 Y72b6EazkfvoPctJil5QlnYLDrFrUzj/3pmkuG/YN9gaOgYMTf7neVx/6CHUghlluh/\
5646 F9Uvovg7G03q7zFLB8x+zw+8P6PW6f7xSxhInlayWdz2X1ULm/4uLmPwNoA5Gcd0L9\
5647 ZFaa6goxhzT66Q4LNRSDoj9xuvlcy+rFbcuJVanLkV0CefphUbICLRW1+9KP4vngHq6Fc2\
5648 NCqM5CsnKcXed+mtfBlWuxmdPboZqT/19422537CrczPQWhthG2zHraJ0/yb0kdkpnanZq\
5649 KxWF66/8Cb5AhcbzdpnhUjeC6YFowlgzEmtqNCDeKzTiXVuc3Lk4YvTJepuq5tgSFKkDA\
5650 ufu9MfWiG3qsnkt67+3*EXQWwzVeegSpvrZcm2afVSVy461+O4KvyVgicCugG2r2poyPvTeJ\
5651 02Um1zWzEO+EK60DftNXfw2U9x70/bqZct5z0Poio+vdpyDjcdxR34U9XcEhrloSktt3ug\
5652 AcwtKO09PFn+gWdS60DcFodrAxnoCfRXWUSO93pBXZV7vae+qvr506/20ALXgngLbrC\
5653 7HgRdveHz2W1MYVYqgm5zTTP5+7vo1RR/zJ1Oylx+8ohOzEb+CV/OTU5ic3NGfjks3OMZ\
5654 tFute1l+Y4yfCwkJzqzYb6HlqJebwqLXyo09/j8k/WW3S32qQPHv5AMtP1DFN2Op6\
5655 fz5yWf4HfMD+Buy4Nvu73yEFbOK65icot+zjP+8qf4Jkyi1TnGKTB/gST0MKKAC18jJPL\
5656 A4PCxYmPKotRjv84HpyOsws/BsqyT2RGZ6zr10gA9sBhEp46hsP2ratmOJegrugBWB2Pw\
5657 NYD1B40STMbmcms2E/GG2zvrF7Ue3qyW/7A7guEH6Ky19q3fp0QvQxtX4dz+Ueg+Lmy5V\
5658 bjjYto+b5L5ogp5Nz6nwbFhudaYgemZ4ap1z5dlbY3NQTc4F3RKYfOTKaUf9y0LW0u\
5659 sDMC/H290vGTmV1C+izhTua27rAebkb4+8h3P553qOoyu/WHjz1Z1Wbd7z2X1uV4f1qmQSV\
5660 2GML+6KmhovraWqne11yZ/gLLX+IBnCN2PQ7F9V5XQEN/qua+Hr3URAgG1MTRLg3bfPyEtP\
5661 m6450yCzcmzX9nQ2JAggbBymXSL9vzQsGfXUBjHpbXbz+vKueRRIotE/Bw8ogf/LIhZY\
5662 /9Tcnsh681t7DtgnQRE1EVT29eWTS5Jf71FSZov1YfTLvqUT0b62etccBRO1LheS68S7e\
5663 202deegmTW757ng7dKrV19rLztoMPBK73naAYrdZfm+5DzsymDymaHnClkvPOVHG5FRFS\
5664 wCY6RwU9DkxSMU9wQMaX+ePguLw8/dvEGULLPvsPbpXspOniQwagElsm9gNxtc0EO1vJ5\
5665 7BbbJAdhkmvd0/q/irW1bf44t5CNKQWaq7DsuJzH16Clz8bk+1u2u78FYWFKlQ4/qY2x\
5666 TyVjX8boyWm6zvc9/Ojwz7pUtV1Lp0NQ2UXL08PKODMuluvoOTDjlyxcrNWHEHjQw5yKrkP5\
5667 2JH14Lp3iCQXOyp6mS5fysKeilleOC95+WxOeJ3m5mcmj5e5b+lyBZYELXgJrMdnY/HtMK0S\
5668 PE7Md3PueUYz8WDovj5zXVf/xsFe+Lpz/WjQ09eIH94ZwqV562+CUHv11MtnJshfXorHfE\
5669 wKfg9FwLrTCRjWjw5+/ocSLZ0LzG52BvtGtwQpXRYEwcaRfrdb5C5bd/PysXbHakPWO\
5670 gZx9Y4L1U0ABBA4x5w8gSbH06++b0nwzjEXYAUvYi6Ece001I7SAZkx0qxmZB9ReavYvxx\
5671 2CMBjAdTRWwYkrIwy4myTH9zt3R93/8X1j0ESWetyy7GfJ1lodwAmhFEA2K6D1wteH6\
5672 H52HwWwLaLQHQOYzW76yZTls7rgu40YBjg4JBMJCayRhtYexX48/xCw+rus9L5ye50A+W\
5673 8v0wN2Zxaw7VADPzCEdPxpdsLx0dKefrWEM+yj47EAEA7yxzHjXm+1FzUL46ch7O0d6Qm\
5674 Wncf9BvXbs6z3hnxP1vm1KjJubTFKRBag1QCNIwubiPytyK1hWwZag8YKoeMcj19Y9Ly\
5675 PwK79U/55Bk75ESKchwhj79Y35xY7qu8YspvTbgSG+55hdj1n6Y56ErfyqV0LZxrbmWJ\
5676 Ywkg5S2p1IOK5dzjzgs+2LB1B4Z6/g+uosa6yuyROY1jzCucOG41lxVQ0Yep1wulXUL4\
5677 zD3GL6w1V43A35xePK1NLSuBb/34RcwB6JGXz6zfr1BBjbbJH7t1WbGDRVdb4iebqPbH\
5678 NQ31qgMHZ7EMHvRxn45r8FpQWRNdqfEV2gBlxEP16+rgdLV82CNvYBids2Jf6pWMPJ\
5679 Aw3rYbgm9qXmLmChjCnvUN5fKMRc2LbzJbK8mU55cm4x/2rLdJQzn1tKkyuou1pdeccF\
5680 qGp/ahfXooVi+JToEimZuJyn8F7QhMAMxdAaUeXK6cF075UUKygy50z33vW/20C7fb+scH\
5681 Ltnp1tH3YeW841pGt4JWAnu7Pn5xwqjxB4IMabC308rflZPCJfTe0Sf08BnadZSfWZqf\
5682 nmlJdITHGhN3eSRt+42M5KwctsxPMe35RjTvorP3mm49VMogfP80iD191X61dvbXmkjz\
5683 NfydX9m8Wimz1MLKZeSL/VzQSkDPZcdYcyte7lq/B4XKfKQaNeK3mL47z9fQL/gaT+/rE\
5684 qDTTXX0UWwKUMVfh9MYLzJvzpxu0fP00/pTedhod/1XXGzAwFuXp6G1Lz+eme2X91bo\
5685 OouU119F0bLAKGQhafa5NVPhxjK7X0LuOMRm+JAFefennaKzLRhZLYB5edUwK1/wD7\
5686 fd+JL72vEtDPEIqgWkZj6zEP/d5duzt+ZhhixFklnhs7umT011AjkyVScenpJ1W1AAACzAE\
5687 qD2Vsx/S+nLND0PelXVd/SkUr+JL579vshL75z+bvNS8Q2EuQ/0a31/FJZS/Vz30EGCB\
5688 ePtCYCROCRK3q6Vl0pof7XEvDAAvzGjOECZx56Cyemz7/CyuWar2IIN2x4NOC075/\
5689 4dyTRK3XuyfGJgmxt/xdpbt8uSR1711luoFJtQm3U17cKXfygWvFdvwpV9R9Aeh07FRV\
5690 hUL4693pww1Yn+FXOC+Cy0vRWXzyh/w3n7fiiibreUtSvURMitjpkWRWmPKkZmHdZFCiM\
5691 dm1f6g+em10/651MmCDD2YFE12dFycgJ38aRabQSPGX1sCGUCaKRDouysZauvcz6zAwTE\
5692 LLGqF1XjPjFYIthCkphr+cN+r76LoJLd3d451+sndV9Yr4v6CWg9+rXtX6G/areZLB4WX\
5693 tgzv7Wk4n+Z8f/FfzURiA3ky5ULmo9CE8N3HgLinI5ISERNy32hsXoRnTbMbvWmiP9T7o3\
5694 j0g8vnn35zecGfY1gCmlw2/fwicJojXytieoL10xvRGHMvYnZ1/IJL6Ww3j5y8j+711dy0U57\
5695 XLjJmM+X0FOgtRucgEUTDvIpfFenovWAE2KAeVrAG5T3tJBCQT+5rCIU+U1BzXP1PumpRV\
5696 4YzE2wP9x1fzv/oppuyDp9UNPih91/XXNOvNS5dGG88wms31CzfrkCQUTCZSHj+vm8Q\
5697 JV7XE3Xm6wqjL5rLVB668ToExtHjJ4Cdw24+uzFvsJrsT11RkFOoALtznPZf2D12QrQ\
5698 8Y588pdsboVhRLQD6exvrEO39y4gDQPk5Zmjjzy021LdV7y3zfl8qmsDmOFArTWFVC3i\
5699 N1NQGWk1jEavqOmRz78D2ZVeFmHcdFCU86nfbFBSzKF1fPMRHE6FO0S0Aotvm/d8Vv8km7D\
5700 C58YrseFULvslpXb79z64erdZNYuNLKileJdaUak7Joor315x+YA9CbQBDf/ck7JHDDb\
5701 E5eg69OKMH9pRjd6v3vgEvYbdQucus1VM9no/QaPP3K21ve8zWcmJk30kx+30RK0Kk1wN\
5702 blXaFhe29JqBL80f8Gkam6n5P9mdG5PmUikpmc22R7BHskjJp0kMctCt/KAM1s0JtXeJk\
5703 v7q/OzmZbn/Z5IoHT3+NpGzn2eyx7uiZ0JDM9xoyTcZBTOya+vndqW3URP1jyxwMdeOe1\
5704 zq4BzYggsLmpdhLIXKcmLWxskzBgwa940stveb+f7141iK3oi05Mkod+r9/I2Vx0P9E3\
5705 xp7XQYU8JTGmcat0+NeY/99v3bh+21bh03cnot1jdfCZnzkeapsDN/vjdg4ACn8b+W9p\
5706 9zduKz2Q3fev05lytqom03pz9Ec5shOY+FXFV150r6x5HkDFMGaadKQ3yA09dydfdj\
5707 ppf5kjq6grny13dfyKI5h14o0Kj1azehBj9NtWTFBAGv1uIawS2vTahFsB50dEprE\
5708 mR1fX0m8XmXnp/fby6av2f7y5SkWno2mPFSF3gCf3o4UGGSj/wI548wVlfbvVab720b\
5709 Xx/MwrgLF9zXPQMmX5CiAfjIhIyXjsh7BKKMfG8mLT+D3cdJF2qod1vnn3v3d60xwYf\
5710 koSvF0EpKzFegJWQ1d70c6dnp1h7i20z33h0LHWYU1rEhZ7ptxeV69XWH+3Jdsam6tO\
5711 IENSy1G5J8EajZNR0adga7TeVOR2LBSccVC8Z0u5Ue1JbSpkVqHecusjRkY1LW0VSSU1tmr\
5712 LaycExhPswTKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIK\
5713 QAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIK\
5714 QAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIK\
5715 QAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIK\
5716 QAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIK\
5717 QAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIKQAIK\
5718 m38w0ncAAAAASUVORK5CYII=";
5719
5720 GshIcon="data:image/png;base64,\
5721 iVORw0KGoAAAANSUHEUGAAAKWAAAB/CAYAAABymylZAAAAAXNSR0IARs4c6QAAAHlWElm\
5722 TUOARgAAAAGABEAaAAUAAAABAAAPAgEbaAAUAAAABAAAARgEoAAMAAAABAAATAAIpAAQAAAAB\
5723 AAAATgAAAAAAAABIAAAAAQAAABGAAAABAAGAAQADAAAAQAABACgAgEAAAAAQAAAKygAwAE\
5724 AAAAQAQAHA8AAAACt6tZAAAA1wSF1zAAALEwAAcMBAJcGAAADQRJREFUEAhTn09wFNu0d\
5725 x9/b21+zYCKCIk1lamW1j/jH6BckstFEFth1IqRwdstOoqEunnttW2nFY01Y1IatinZ0\
5726 amdAqY6jYIOX17kgglarVv74b3BAQPKbVAJj3e3r94WcJpe93csmcbj784kd/ve7723+3nF\
5727 ffv+nxA8SIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIA\
5728 SIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAESIAES\
5729 IeF5tEAHwEd81mP2wLTyTadyBmzrT+42pzRsrD3peQvPxmtrhgNYCn8fewHfUap+zyH\
5730 ZUASIAESIAESOKII+LPR9dzsk5ELVxdKBTz1hQpQkIEfLe+8Jan8AzkmYA/67BKX1ek+pmQ\
5731 hs7VveE6PyDz+oM6JmAxwz2nN6REVCS4SQXwh1L18XtFFcuWqH7AMRgIKQAIKQAIJAH/\
5732 Nbgem30981H0o58sa50440Umz+EzCEAE/FWHXfnjsofLD/YP80ZNUKRALVawLqEGG4C/BGSE\
5733 rgK0Amb/d3ucCJ1WJsYvNsIyOKAQ8FeVNmYJYR5F3cqmUmL6v/FwDD1QAV4S7EBPzYQ\
5734 65pV5cdd246QcHyZiLzEdt1K7M51Ayw2yWmXNDa8LcplJlWwoi01U1s3d05692zGp\
5735 2D8BHztDXp+28XK1cyGj9Fve6Eh5QVCinOVEqOKf1Ka7gpKvWbUnKnPoodS814tKywGP\
5736 e0Lc2e8+3+r1p162LEVYnPs6SQfapwSgmV0Kf8upDNKgzLsBawPFDureUtyYUePwH9e\
5737 fawMF19QQt4Ccz7YoroBVF9CrE/2gnEO/ElFa4DQdHalosCUT4rPjzSLGNJ56Z10QVrtE\
5738 rHxDxjvvnShmYsWPTq6UEZEGJES2Ewmpj4sk8J5VQA/zSeLUz5aemH2iRVkdhpAVH0\
5739 FR65zaZf851OgmVortLSeXG/otLBR9s+r5h8u0ihusYfz191fGLp2cNSyt1A2//w008aEK\
5740 IX87zhymPTktb3oc1bXa/DKX3bYpoeHh686jgQSEXcUgVXALY+CVNO508MMmi9BUOH+oH\
5741 zFN7phGbb3k0oJ1FO9zr7rGvN3d1QNRtg4570TSlhkYjsJ0uk6478h1PhRo614d4mmU7N\
5742 4t2xw1BFU11BE60Gw2+T9JpFNKn7wUbrmu5WgppJ7K13801ulcApeIwCLADauXgEoc1Ys4\
5743 1B7b03kBUET04panzx0+9yONN9ANsdFQmN4oxSnokzgn+f0CANUSNm3unJyA0vhz5uc6+\
5744 CGJp2DufdMGRf0n8Bez1JXDydcHa+vntqfD10QH1kcvCeJ9j5vJebVqEtoSfV1/ERXV9e\
5745 74raV8+EyC/v6wf7Xamno5Kqnr60Ylem/+GqTOA6dKXNTz8wCCamh8Mobur815bb166FC\
5746 RbHvm2bRm7h195Jv11hSpPwyen9SxhL6Jne71K1+UwQNK2hcmG5M6VzWuLU1Y1Te9TuxE+Ev\
5747 Sbn0gishHovWT/2W5q6VhWvNVT4r/QkuK2WP20giXhfsnYqgqYaz52btBav0/PdhIDX8Pw\
5748 1fhpLH6ftfbp7VC6fKUXFwHsOZYSjze1TK3TtJWR1jeer0Ht81rJCXhIuo9BNIxvfGqC\
5749 5w2uDRZKNx211qV08PLmXuoBcaZpaVgVJde1Z0+5Uopx3S11+3idYU2NxcnEDUvAJ2K0847e\

```

```

5750 GPe4dUaP7R/7A/WP77y76+A3c574a/FyENPbyb9YB/cvZPn3oYfirtv3PCjGPJ0FAKqAet3\
5751 7T4wc6jEgpkHy0eaEEDXFG7FWKKh72Wx453a+vBKsbw1a7r0hpRYM9SyoLQidvQtfd2/1\
5752 Tr/7DA8W5jK8WVTLKfLmS3csR741Lk+Y8t/zd1L0n0w1VcTe7wfdHK3+TazxSTJkLi2K6\
5753 C8zVlgGfHksRNeUfGQ9UBVok3OMFfZTUYA8prA0SRrnejKA0/hu0tNw+ccc5y9264nCLM\
5754 TyPH0lR+3pl9VWMIIdCpG6p1LTstAsnpJRCQ+BiH0q9KgnrXmH4drYnEzujfavzKbtINQRzX\
5755 eQdI6tyHZX6MCW21h9JseY9+0/wj2AjzQvHFPFKYtZogipvsrX70zKobW1viJ0eP8FN3\
5756 cSNW6Fsi3RtKH7ky7Ct+GEaoorst0dzVHGMI/O9rWtaHpuIszykF99UCZDBLz1LH0gT\
5757 2yDwtdL5VHH9Edrt1h1fOGMKMF/29W2qf7k7zDUuz1butncUDLmKYkR60L450y2RSIuy8\
5758 213vcxGbegYzDF3bH6gAT7f3yc0VzXndIotbx/86d1mVSB1tZPt55DmaCmHKwpmfma50nmfvm\
5759 vH9GEnbQ/DSrW0YsrRiQ34BEOx/gsvPD73Wk9owbtpBezP+JfTSogyoac6XR/ofj5Q-DY\
5760 Bnas4Zhs+2rDY5qZQAvdp5We1t/GQSM7Ym6HgmGEPJRC/j4aaU+7GfYl+L50KkKwC+3\
5761 AjzxKwCLD+BY307R86IHtuc8jclEpnNZZ5qZ4P8XK09H9p55283TmJN8zUPTN+OL/PC\
5762 k2P4UFahmsfn47H6RP12Vnwjzr5LufLwLBe0YF72KosQJyIzn2FL00acK46u68+BYyQ\
5763 TkKvweYgeupTgZ2fH6ghg26/jB8aPkoB59jzLh9L+O84E590SUQhk165Vwg6P3njy9W\
5764 85ziR5001+qabRR6Ts0+rzbMQxv2xr0csSSmQI/fcFY7LPdz21Jzr5Kk+C5dELh6ixYITwL\
5765 vL/nm4/cmbCw+XmNwee48EznelWaoF+EKYUroIldOPl3PawpZRGFplnIhtCOXyQ5CLqPQW\
5766 RCJ4fb1+LEu3VncC8bZ4Kvlzsz2fVnV56qj3yQv++Y0t29BUzWjrjgWZDI1oBJWxe18VIX\
5767 KEPL9fd5Bxp/2X66gXKM3dfCLatfd8adBN1u0UNh1AEwg6Bw93sevqjIHMULPw/b14a6npg\
5768 pkSWlw06EYmN+v3MLU6MwfbD3KvyWstXwj2zUcu04jSj+6WUyJBTllpSv1okE327S/NWx\
5769 Ng+21W6vtW1T14TY/bUnDxmS71u9baqa20YX5DbUx1z9BRpEvdRHHJ51k3m3z394Vgd5Yp\
5770 gZbnk1kQbbVhbtEhH61/0vu/ZgszaeFLR+NOBCXy90Xa7g7BbtQ6tbu/vOYIphU8xhZ4AR7\
5771 c1MaOu3Q4pYZWHWvCt1a17Ndi3bXo2P7v2p70cmEPEycw8L4Q6770Evh+zTzPNEd+mNfy/W2\
5772 9LRARH5E7/vQ5fI1w7StTREM44Au5+Q3T6aRsqdmq7Z+/GB47ui290Uw9JX4AnJ711IS\
5773 16Y+xi85fm6YcrRoxul4K1ysH6Be9110YHs791/4cxvbgH2jWb1j1XxexYQuZU0g5WDUq\
5774 Y6XmFg2XRCbeWTrTjP5NO7ZuP3v9IrmDnn4F5eSBkoH0tab6aStQot7/beUGSubPmhrC27B1\
5775 0YqH510JvclK0Y4fxKoz+kgw+oajdVesgVer9PehP+SrXwnkMNLm6VpOnUikIzm+PveQg\
5776 h4F8J1j9WOrt+64stf500WEZd2G5Cd/FZS/VXH3nagrQUL+4B2j8m8Ss/PmI9D3McBjwo\
5777 Rn3KXuzqzpsZkZU1cbOCRjMPhQ1abXm1gdsu1315d3JlR9ywoVm9Np1kTie/CQYIdwZV2\
5778 8/kpxgnKkvclbdveIDD0Usc+RxdmDipxnmTw78tYm6HGDc2f2gZnJ+8xzSRBvQ4zrhEw9\
5779 H926s8VJSOHFrzRII7AAPQwzKI7LspLurBj0Qpxybyb/8dmn2//1l/qgnago2AwgF/38/WEL\
5780 I4af+5Q5EXMARKAoI2CCP2xvJNV+LMZ78LkH3V27LWv2n9w4/+63gdKxJPLq7b1TADkwlP\
5781 nIHS+QSI+HiEWsrPuVengV20d6nf7K0tloP1dj/ikUsatCEBEiABEiABEiABEiABEiABE\
5782 EiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiAB\
5783 EiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiAB\
5784 EiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiAB\
5785 EiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiAB\
5786 EiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiABEiAB\
5787
5788 ITSmoreQR="data:image/png;base64,\
5789 iVBORw0KGgoAAANSUgEuHAAAGSAAABvAQMAADYCWwJAAAAB1BMVXV///9BaePhqDaJAAAB\
5790 hKElEQV4jdxTsa2EMawGYCMX7sICKVqjXVaCBe7CarASXda1LAWg54HwM5zEVS+mvSgS+ZBQ\
5791 8gc4B4Hyzw8szMSaUBHNM+KAd4QC8LDpDn8ogT4UpPGci2jI8IGF3eLWpWahWVWevce\
5792 UEHDxAb0X2AnjueYD0zNklQassPCKjcn4W3E1SfwqYk6jv/uAKPhg0ALShfhe8JtdkwdMwr\
5793 yMCSuPyWHAr19k0tKV2sb3sdw2RUCwq88g4RplA9s1JpV9cTPlNRD4XFkn8XaQCWt6Lzq\
5794 Z08dhw/4+U2Gzgl58gbqvmkfr1N6YX80qLD00m1CTWvzPERA8AL9vub0iFpSoL333fsVyrL\
5795 S9wiqDznhUI385vN783/gBuUs2eLgic8GAAAABJRU5ErkJggg=="\
5796
5797 </script>
5798
5799 <script id="gsh-script">
5800 //document.getElementById('gsh-faviconurl').href = GshIcon
5801 //document.getElementById('gsh-faviconurl').href = GshLogo
5802 document.getElementById('gsh-faviconurl').href = ITSmoreQR
5803
5804 // id of GShell HTML elemets
5805 var E_BANNER = "gsh-banner" // banner element in HTML
5806 var E_FOOTER = "gsh-footer" // footer element in HTML
5807 var E_GINDEX = "gsh-gindex" // index of Golang code of GShell
5808 var E_GOCODE = "gsh-gocode" // Golang code of GShell
5809 var E_TODO = "gsh-todo" // TODO of GShell
5810 var E_DICT = "gsh-dict" // Dictionary of GShell
5811
5812 function bannerElem(){ return document.getElementById(E_BANNER); }
5813 function bannerStyleFunc(){ return bannerElem().style; }
5814 var bannerStyle = bannerStyleFunc()
5815 bannerStyle.backgroundImage = "url( "+GshLogo+" )";
5816
5817 function footerElem(){ return document.getElementById(E_FOOTER); }
5818 function footerStyle(){ return footerElem().style; }
5819 footerElem().style.backgroundImage="url( "+ITSmoreQR+" )";
5820 //footerStyle().backgroundImage = "url( "+ITSmoreQR+" )";
5821
5822 function html_fold(e){
5823   if ( e.innerHTML == "Fold" ){
5824     e.innerHTML = "Unfold"
5825     document.getElementById('gsh-menu-exit').innerHTML=""
5826     document.getElementById('GshStatement').open=false
5827     document.getElementById('html-src').open=false
5828     document.getElementById(E_GINDEX).open=false
5829     document.getElementById(E_GOCODE).open=false
5830     document.getElementById(E_TODO).open=false
5831     document.getElementById('References').open=false
5832   }else{
5833     e.innerHTML = "Fold"
5834     document.getElementById('GshStatement').open=true
5835     document.getElementById(E_GINDEX).open=true
5836     document.getElementById(E_GOCODE).open=true
5837     document.getElementById(E_TODO).open=true
5838     document.getElementById('References').open=true
5839   }
5840 }
5841 function html_pure(e){
5842   if ( e.innerHTML == "Pure" ){
5843     document.getElementById('gsh').style.display=true
5844     //document.style.display = false
5845     e.innerHTML = "Unpure"
5846   }else{
5847     document.getElementById('gsh').style.display=false
5848     //document.style.display = true
5849     e.innerHTML = "Pure"
5850   }
5851 }
5852
5853 var bannerIsStopping = false
5854 //NOTE: .com/JSREF/prop_style_backgroundposition.asp
5855 function shiftBG(){
5856   bannerIsStopping = !bannerIsStopping
5857   bannerStyle.backgroundPosition = "0 0";
5858 }
5859 // status should be inherited on Window Fork(), so use the status in DOM
5860 function html_stop(e,toggle){
5861   if( toggle ){
5862     if( e.innerHTML == "Stop" ){
5863       bannerIsStopping = true
5864       e.innerHTML = "Start"
5865     }else{
5866       bannerIsStopping = false
5867       e.innerHTML = "Stop"
5868     }
5869   }else{
5870     // update JavaScript variable from DOM status
5871     if( e.innerHTML == "Stop" ){ // shown if it's running
5872       bannerIsStopping = false
5873     }else{
5874       bannerIsStopping = true

```



```

5875     }
5876   }
5877 }
5878 html_stop(document.getElementById('gsh-menu-stop'),false) // onInit.
5879 //html_stop(bannerElem(),false) // onInit.
5880
5881 //https://www.w3schools.com/jsref/met_win_setinterval.asp
5882 function shiftBanner(){
5883   var now = new Date().getTime();
5884   //console.log("now="+now%10)
5885   if( !bannerIsStopping ){
5886     bannerStyle.backgroundPosition = ((now/10)%100000)+" 0";
5887   }
5888 }
5889 setInterval(shiftBanner,10); // onInit.
5890
5891 // <a href="https://developer.mozilla.org/ja/docs/Web/API/Window/open">window.open()</a>
5892 // from embedded html to standalone page
5893 var MyChildren = 0
5894 function html_fork(){
5895   MyChildren += 1
5896   WinId = document.getElementById('gsh-WinId').innerHTML + "." + MyChildren;
5897   newwin = window.open("",WinId,"");
5898   src = document.getElementById("gsh");
5899   newwin.document.write("<"+<"+html>\n");
5900   newwin.document.write("<"+span id="gsh">");
5901   newwin.document.write(src.innerHTML);
5902   newwin.document.write("<"+span><"+html>\n"); // gsh span
5903   newwin.document.getElementById('gsh-menu-exit').innerHTML = "Close";
5904   newwin.document.getElementById('gsh-WinId').innerHTML = WinId;
5905   newwin.document.close();
5906   newwin.focus();
5907 }
5908 function html_close(){
5909   window.close()
5910 }
5911 function win_jump(win){
5912   //win = window.top;
5913   win = window.opener; // https://developer.mozilla.org/ja/docs/Web/API/window.opener
5914   if( win == null ){
5915     console.log("jump to window.opener("+win+") (Error)\n")
5916   }else{
5917     console.log("jump to window.opener("+win+")\n")
5918     win.focus();
5919   }
5920 }
5921
5922 // 0.2.9 2020-0902 created chekcsom of HTML
5923 CRC32UNIX = 0x04C11DB7 // Unix cksum
5924 function byteCRC32add(bigcrc,octstr,octlen){
5925   var crc = new Uint32Array(1)
5926   crc[0] = bigcrc
5927
5928   let oi = 0
5929   for( ; oi < octlen; oi++){
5930     var oct = new Uint8Array(1)
5931     oct[0] = octstr[oi]
5932     for( bi = 0; bi < 8; bi++){
5933       //console.log("--CRC32 "+crc[0]+" "+oct[0].toString(16)+" ["+oi+"."+bi+"]\n")
5934       ovf1 = crc[0] < 0 ? 1 : 0
5935       ovf2 = oct[0] < 0 ? 1 : 0
5936       ovf = ovf1 ^ ovf2
5937       oct[0] <<= 1
5938       crc[0] <<= 1
5939       if( ovf ){ crc[0] ^= CRC32UNIX }
5940     }
5941   }
5942   //console.log("--CRC32 byteAdd return crc="+crc[0]+","+oi+"/"+octlen+"\n")
5943   return crc[0];
5944 }
5945 function strCRC32add(bigcrc,stri,strlen){
5946   var crc = new Uint32Array(1)
5947   crc[0] = bigcrc
5948   var code = new Uint8Array(strlen);
5949   for( i = 0; i < strlen; i++){
5950     code[i] = stri.charCodeAtAt(i) // not charAt() !!!!
5951     //console.log("=== "+code[i].toString(16)+" <<== "+stri[i)+"\n")
5952   }
5953   crc[0] = byteCRC32add(crc,code,strlen)
5954   //console.log("--CRC32 strAdd return crc="+crc[0]+"\n")
5955   return crc[0]
5956 }
5957 function byteCRC32end(bigcrc,len){
5958   var crc = new Uint32Array(1)
5959   crc[0] = bigcrc
5960   var slen = new Uint8Array(4)
5961   let li = 0
5962   for( ; li < 4; ){
5963     slen[li] = len
5964     li += 1
5965     len >>= 8
5966     if( len == 0 ){
5967       break
5968     }
5969   }
5970   crc[0] = byteCRC32add(crc[0],slen,li)
5971   crc[0] ^= 0xFFFFFFFF
5972   return crc[0]
5973 }
5974 function strCRC32(stri,len){
5975   var crc = new Uint32Array(1)
5976   crc[0] = 0
5977   crc[0] = strCRC32add(0,stri,len)
5978   crc[0] = byteCRC32end(crc[0],len)
5979   //console.log("--CRC32 "+crc[0]+" "+len+"\n")
5980   return crc[0]
5981 }
5982 function html_cksum(){
5983   //alert("cksum="+strCRC32("",0))
5984   //alert("cksum="+strCRC32("0",1))
5985   //return
5986
5987   version = document.getElementById('gsh-version').innerHTML
5988   sfavico = document.getElementById('gsh-faviconurl').href;
5989   sbanner = document.getElementById('gsh-banner').style.backgroundImage;
5990   spositi = document.getElementById('gsh-banner').style.backgroundPosition;
5991   sfooter = document.getElementById('gsh-footer').style.backgroundImage;
5992   document.getElementById('gsh-faviconurl').href = "";
5993   document.getElementById('gsh-banner').style.backgroundImage = "";
5994   document.getElementById('gsh-banner').style.backgroundPosition = "";
5995   document.getElementById('gsh-footer').style.backgroundImage = ""
5996
5997   //html = document.getElementById("gsh").outerHTML;
5998   html = document.getElementById("gsh").innerHTML;
5999

```



```

6000     textarea = document.createElement("textarea")
6001     textarea.innerHTML = html
6002     // <a href="https://stackoverflow.com/questions/5796718/html-entity-decode">Thanks</a>
6003     text = textarea.value
6004     //textarea.destroy()
6005     text = ""
6006     + "</>" + "html>\n" // lost preamble text
6007     + "<+" + "span id=\"gsh\">" // lost preamble text
6008     + text
6009     + "<+" + "/span><+" + "/html>\n" // lost trail text
6010     ;
6011
6012     tlen = text.length
6013     console.log("length="+tlen+"\n"+text)
6014     alert("cksum : " + strCRC32(text,tlen) + " " + tlen + " " + version)
6015
6016     document.getElementById('gsh-faviconurl').href = sfavico;
6017     document.getElementById('gsh-banner').style.backgroundImage = sbanner;
6018     document.getElementById('gsh-banner').style.backgroundPosition = spositi;
6019     document.getElementById('gsh-banner').style.backgroundImage = sfavico;
6020 }
6021
6022 // source code viewr
6023 function frame_close(){
6024     srcframe = document.getElementById("src-frame");
6025     srcframe.innerHTML = "";
6026     //srcframe.style.cols = 1;
6027     srcframe.style.rows = 1;
6028     srcframe.style.height = 0;
6029     srcframe.style.display = false;
6030     src = document.getElementById("src-frame-textarea");
6031     src.innerHTML = ""
6032     //src.cols = 0
6033     src.rows = 0
6034     src.display = false
6035     //alert("--closed--")
6036 }
6037 //<!-- | <span onclick="html_view();">Source</span> -->
6038 //<!-- | <span onclick="frame_close();">SourceClose</span> -->
6039 //<!-- | <span>Download</span> -->
6040 function frame_open(){
6041     document.getElementById('gsh-faviconurl').href = "";
6042     oldsrc = document.getElementById("GENSRC");
6043     if (oldsrc != null){
6044         //alert("--I--(erasing old text)")
6045         oldsrc.innerHTML = "";
6046         return
6047     }else{
6048         //alert("--I--(no old text)")
6049     }
6050     banner = document.getElementById('gsh-banner').style.backgroundImage;
6051     footer = document.getElementById('gsh-footer').style.backgroundImage;
6052     document.getElementById('gsh-banner').style.backgroundImage = "";
6053     document.getElementById('gsh-banner').style.backgroundPosition = "";
6054     document.getElementById('gsh-footer').style.backgroundImage = "";
6055
6056     src = document.getElementById("gsh");
6057     srcframe = document.getElementById("src-frame");
6058     srcframe.innerHTML = ""
6059     + "<+" + "cite id=\"GENSRC\">\n"
6060     + "<+" + "style>\n"
6061     + "#GENSRC textarea{tab-size:4;}\n"
6062     + "#GENSRC textarea{-o-tab-size:4;}\n"
6063     + "#GENSRC textarea{-moz-tab-size:4;}\n"
6064     + "#GENSRC textarea{spellcheck:false;}\n"
6065     + "<+" + "style>\n"
6066     + "<+" + "textarea id=\"src-frame-textarea\" cols=100 rows=20 class=\"gsh-code\">"
6067     + "<+" + "html>\n" // lost preamble text
6068     + "<+" + "span id=\"gsh\">" // lost preamble text
6069     + src.innerHTML
6070     + "<+" + "/span><+" + "/html>\n" // lost trail text
6071     + "<+" + "textarea>\n"
6072     + "<+" + "cite><!-- GENSRC -->\n";
6073
6074     //srcframe.style.cols = 80;
6075     //srcframe.style.rows = 80;
6076
6077     document.getElementById('gsh-banner').style.backgroundImage = banner;
6078     document.getElementById('gsh-footer').style.backgroundImage = footer;
6079 }
6080 function fill_CSSView(){
6081     part = document.getElementById('gsh-style-def')
6082     view = document.getElementById('gsh-style-view')
6083     view.innerHTML = ""
6084     + "<+" + "textarea cols=100 rows=20 class=\"gsh-code\">"
6085     + part.innerHTML
6086     + "<+" + "/textarea>"
6087 }
6088 function fill_JavaScriptView(){
6089     jspart = document.getElementById('gsh-script')
6090     view = document.getElementById('gsh-script-view')
6091     view.innerHTML = ""
6092     + "<+" + "textarea cols=100 rows=20 class=\"gsh-code\">"
6093     + jspart.innerHTML
6094     + "<+" + "/textarea>"
6095 }
6096 function fill_DataView(){
6097     part = document.getElementById('gsh-data')
6098     view = document.getElementById('gsh-data-view')
6099     view.innerHTML = ""
6100     + "<+" + "textarea cols=100 rows=20 class=\"gsh-code\">"
6101     + part.innerHTML
6102     + "<+" + "/textarea>"
6103 }
6104 function jumpTo_StyleView(){
6105     jsview = document.getElementById('html-src')
6106     jsview.open = true
6107     jsview = document.getElementById('gsh-style-frame')
6108     jsview.open = true
6109     fill_CSSView()
6110 }
6111 function jumpTo_JavaScriptView(){
6112     jsview = document.getElementById('html-src')
6113     jsview.open = true
6114     jsview = document.getElementById('gsh-script-frame')
6115     jsview.open = true
6116     fill_JavaScriptView()
6117 }
6118 function jumpTo_DataView(){
6119     jsview = document.getElementById('html-src')
6120     jsview.open = true
6121     jsview = document.getElementById('gsh-data-frame')
6122     jsview.open = true
6123     fill_DataView()
6124 }

```

```

6125 function jumpto_WholeView(){
6126     jsview = document.getElementById('html-src')
6127     jsview.open = true
6128     jsview = document.getElementById('gsh-whole-view')
6129     jsview.open = true
6130     frame_open()
6131 }
6132 function html_view(){
6133     html_stop();
6134 }
6135 banner = document.getElementById('gsh-banner').style.backgroundImage;
6136 footer = document.getElementById('gsh-footer').style.backgroundImage;
6137 document.getElementById('gsh-banner').style.backgroundImage = "";
6138 document.getElementById('gsh-banner').style.backgroundPosition = "";
6139 document.getElementById('gsh-footer').style.backgroundImage = "";
6140
6141 //srcwin = window.open("", "CodeView2", "");
6142 srcwin = window.open("", "", "");
6143 srcwin.document.write("<span id='gsh'>\n");
6144
6145 src = document.getElementById("gsh");
6146 srcwin.document.write("<+style>\n");
6147 srcwin.document.write("textarea{tab-size:4;}\n");
6148 srcwin.document.write("textarea{-o-tab-size:4;}\n");
6149 srcwin.document.write("textarea{-moz-tab-size:4;}\n");
6150 srcwin.document.write("</style>\n");
6151 srcwin.document.write("<h2>\n");
6152 srcwin.document.write("<+span onclick='window.close();'>Close</span> | \n");
6153 //srcwin.document.write("<+span onclick='html_stop();'>Run</span>\n");
6154 srcwin.document.write("</h2>\n");
6155 srcwin.document.write("<textarea id='gsh-src-src' cols=100 rows=60>");
6156 srcwin.document.write("/<+html>\n");
6157 srcwin.document.write("<+span id='gsh'>");
6158 srcwin.document.write(src.innerHTML);
6159 srcwin.document.write("<+span><+html>\n");
6160 srcwin.document.write("</+textarea>\n");
6161
6162 document.getElementById('gsh-banner').style.backgroundImage = banner;
6163 document.getElementById('gsh-footer').style.backgroundImage = footer
6164
6165 sty = document.getElementById("gsh-style-def");
6166 srcwin.document.write("<+style>\n");
6167 srcwin.document.write(sty.innerHTML);
6168 srcwin.document.write("<+style>\n");
6169
6170 run = document.getElementById("gsh-script");
6171 srcwin.document.write("<+script>\n");
6172 srcwin.document.write(run.innerHTML);
6173 srcwin.document.write("<+script>\n");
6174
6175 srcwin.document.write("<+span><+html>\n"); // gsh span
6176 srcwin.document.close();
6177 srcwin.focus();
6178 }
6179 GSH = document.getElementById("gsh")
6180
6181 //GSH.onclick = "alert('Ouch!')"
6182 //GSH.css = "{background-color:#eef;}"
6183 //GSH.style = "background-color:#eef;"
6184 //GSH.style.display = false;
6185 //alert('Ouch0!')
6186 //GSH.style.display = true;
6187
6188 // 2020-0904 created, tentative
6189 document.addEventListener('keydown', jgshCommand);
6190 //GshStatement = document.getElementById("GshStatement") // unnecessary
6191 //GshFeatures = document.getElementById("GshFeatures") // unnecessary
6192 CurElement = GshFeatures
6193 function jgshCommand(e){
6194     console.log("JSGsh-Key: "+e.code+"(^-^)/")
6195     if (e.code == "KeyO" ){ // fold the element
6196         CurElement.open = false;
6197     }
6198     if (e.code == "KeyI" ){ // unfold the element
6199         CurElement.open = true;
6200     }
6201     if (e.code == "KeyJ" ){ // next element
6202         CurElement = GshFeatures
6203     }
6204     if (e.code == "KeyK" ){ // previous element
6205         CurElement = GshStatement
6206     }
6207 }
6208 </script>
6209
6210
6211 <!-- ##### WebCrypto ##### -->
6212 <details id="WebCrypto"><summary>WebCrypto</summary>
6213 Reference: <a href="https://mdn.github.io/dom-examples/web-crypto/encrypt-decrypt/index.html">
6214     https://mdn.github.io/dom-examples/web-crypto/encrypt-decrypt/index.html</a>
6215 <style id="web-crypto-demo-style.css">
6216 #WebCrypto { color:#080; font-size:9pt; }
6217 #rsa-oaep-message{ width:100% !important; height:24pt; color:#000 !important;
6218     border-width:2 !important; background-color:#eee !important; }
6219 #WebCrypto input{ width:50pt; background-color:#4a4; color:#fff; border-width:0; }
6220 </style>
6221
6222 <span id="web-crypto-demo.html">
6223 <section class="encrypt-decrypt rsa-oaep">
6224 <h3 class="encrypt-decrypt-heading">Web Crypto - RSA-OAEP</h3>
6225 <section class="encrypt-decrypt-controls">
6226 <p>
6227 <b>Plain text:</b><br>
6228 <input type="textarea" id="rsa-oaep-message" name="message"
6229     value="Hello, GShell!" style="color:#000;background-color:#fff;font-size:12pt;">
6230 </p>
6231 <p>
6232 <input class="encrypt-button" type="button" value="Encrypt"><br>
6233 <span class="ciphertext"><b>Cipher text:</b><br>
6234 <span class="ciphertext-value"></span></span>
6235 </p>
6236 <p>
6237 <input class="decrypt-button" type="button" value="Decrypt"><br>
6238 <span class="decrypted"><b>Decrypted text:</b><br>
6239 <span class="decrypted-value"></span></span>
6240 </p>
6241 <p>
6242 <input type="button" value="ShowKey" onclick="ShowKey()"><br>
6243 <span id="PublicKey">PublicKey...</span>
6244 </p>
6245 </section>
6246 </section>
6247 </span>
6248
6249 <script id="web-crypto-rsa-oaep.js">

```

```

6250 var RSAKeyPair = null;
6251 function ShowKey(){
6252     document.getElementById("PublicKey").innerHTML = RSAKeyPair.publicKey;
6253 }
6254 (( ) => {
6255     //Store the calculated ciphertext here, so we can decrypt the message later.
6256     let ciphertext;
6257
6258     //Fetch the contents of the "message" textbox, and encode it
6259     //in a form we can use for the encrypt operation.
6260     function getMessageEncoding() {
6261         const messageBox = document.querySelector("#rsa-oaep-message");
6262         let message = messageBox.value;
6263         let enc = new TextEncoder();
6264         return enc.encode(message);
6265     }
6266
6267     //Get the encoded message, encrypt it and display a representation
6268     //of the ciphertext in the "Ciphertext" element.
6269     async function encryptMessage(key) {
6270         let encoded = getMessageEncoding();
6271         ciphertext = await window.crypto.subtle.encrypt(
6272             {
6273                 name: "RSA-OAEP"
6274             },
6275             key,
6276             encoded
6277         );
6278
6279         //let xbuffer = new Uint8Array(ciphertext, 0, 5);
6280         let xbuffer = new Uint8Array(ciphertext, 0, ciphertext.byteLength);
6281         let b = new Uint8Array(ciphertext,0,ciphertext.byteLength);
6282         //document.write(""+b.length+"")
6283         //let b64 = btoa(b);
6284         let b64 = btoa(new Uint8Array(ciphertext,0,ciphertext.byteLength));
6285         const ciphertextValue = document.querySelector(".rsa-oaep .ciphertext-value");
6286         ciphertextValue.classList.add('fade-in');
6287         ciphertextValue.addEventListener('animationend', () => {
6288             ciphertextValue.classList.remove('fade-in');
6289         });
6290         ciphertextValue.textContent =
6291         ciphertext.byteLength
6292         + " bytes "
6293         + xbuffer
6294         //+ " "
6295         //+ b + " (" + b.length + ")"
6296         //+ b64 + " (" + b64.length + ")"
6297         ;
6298     }
6299
6300     //Fetch the ciphertext and decrypt it.
6301     //Write the decrypted message into the "Decrypted" box.
6302     async function decryptMessage(key) {
6303         let decrypted = await window.crypto.subtle.decrypt(
6304             {
6305                 name: "RSA-OAEP"
6306             },
6307             key,
6308             ciphertext
6309         );
6310
6311         let dec = new TextDecoder();
6312         const decryptedValue = document.querySelector(".rsa-oaep .decrypted-value");
6313         decryptedValue.classList.add('fade-in');
6314         decryptedValue.addEventListener('animationend', () => {
6315             decryptedValue.classList.remove('fade-in');
6316         });
6317         decryptedValue.textContent = dec.decode(decrypted);
6318     }
6319
6320     //Generate an encryption key pair, then set up event listeners
6321     //on the "Encrypt" and "Decrypt" buttons.
6322     window.crypto.subtle.generateKey(
6323         {
6324             name: "RSA-OAEP",
6325             // Consider using a 4096-bit key for systems that require long-term security
6326             modulusLength: 2048,
6327             publicExponent: new Uint8Array([1, 0, 1]),
6328             hash: "SHA-256",
6329         },
6330         true,
6331         ["encrypt", "decrypt"]
6332     ),then((keyPair) => {
6333         RSAKeyPair = keyPair
6334         const encryptButton = document.querySelector(".rsa-oaep .encrypt-button");
6335         //document.getElementById('PublicKey').innerHTML = crypto.subtle.exportKey(pkcs8,keyPair.publicKey)
6336         encryptButton.addEventListener("click", () => {
6337             encryptMessage(keyPair.publicKey);
6338         });
6339         const decryptButton = document.querySelector(".rsa-oaep .decrypt-button");
6340         decryptButton.addEventListener("click", () => {
6341             decryptMessage(keyPair.privateKey);
6342         });
6343     });
6344
6345     });
6346 }());
6347 </script>
6348 </details>
6349
6350 *///<br></span></html>
6351

```